

Project No : 2014-301

Design By : CD

Drawn By : TMK

Date	Description
5-6-14	PRELIMINARY DESIGN

These Drawings and Specifications, and all copies thereof are and shall remain the property and copyright of the Engineer. They shall be used only with respect to this Project and are not to be used on any other Project or Work without prior written permission from the Engineer.

CHECK SET
Not for
Construction
5-6-2014

Solar Array for
JENNINGS COUNTY
PUBLIC LIBRARY
2375 Indiana 3
North Vernon, Indiana

DC Side
Diagrams

PV4

SIGNAGE FOR DC DISCONNECT
@ ARRAYS 1 & 2

PHOTOVOLTAIC POWER SOURCE	
RATED MPP CURRENT	166A
RATED MPP VOLTAGE	385V
MAX SYSTEM VOLTAGE	600V
MAX CIRCUIT CURRENT	221A
WARNING: ELECTRICAL SHOCK HAZARD-LINE AND LOAD MAY BE ENERGIZED IN OPEN POSITION	

SIGNAGE FOR DC DISCONNECT
@ ARRAY 3

PHOTOVOLTAIC POWER SOURCE	
RATED MPP CURRENT	149A
RATED MPP VOLTAGE	437V
MAX SYSTEM VOLTAGE	600V
MAX CIRCUIT CURRENT	201A
WARNING: ELECTRICAL SHOCK HAZARD-LINE AND LOAD MAY BE ENERGIZED IN OPEN POSITION	

SIGNAGE FOR INVERTER OCPD
AND AC DISCONNECT
@ 250kW Inverter

SOLAR PV SYSTEM AC POINT OF CONNECTION	
AC OUTPUT CURRENT	xxxA
NOMINAL AC VOLTAGE	480V
THIS PANEL FED BY MULTIPLE SOURCES (UTILITY AND SOLAR)	

ARRAYS 1 & 2

PV MODULE RATINGS

MODULE MANUFACTURER	Yingli
MODULE MODEL NUMBER	YL245P-29b
MAX POWER-POINT CURRENT (Imp)	8.28 A
MAX POWER-POINT VOLTAGE (Vmp)	29.6 V
SHORT-CIRCUIT CURRENT (Isc)	8.83 A
OPEN-CIRCUIT VOLTAGE (Voc)	37.5 V
MAX SERIES FUSE (OCPD)	15A
MAXIMUM POWER (Pmax)	245 W
MAX SYSTEM VOLTAGE	1000 V
Voc TEMP COEFF	-0.32 %/°C

PV CIRCUIT DESIGN

NUMBER OF MODULES IN SOURCE CIRCUIT	13
NUMBER OF SOURCE CIRCUITS PER ARRAY	20
TOTAL NUMBER OF MODULES PER ARRAY	260
ARRAY VOLTAGE (VOC)	487.5 V
WIRE VOLT REQUIRED	600 V
OPEN CIRCUIT CURRENT (ISC)	176.6 AMP
OPEN CIRCUIT MAXIMUM CURRENT (Imax)	220.75 AMP
AMBIENT TEMPERATURE	32°C
TEMPERATURE INCREASE (0.5" - 3.5" ABOVE ROOF)	22°C
EFFECTIVE TEMPERATURE	54°C
CORRECTION FACTOR - TEMPERATURE	0.76
CORRECTION FACTOR - <4 CONDUCTORS	1.00
CALCULATION: 2014 NEC 690.8(B)(1) Imax x 125%	275.94 AMP
NEXT FUSE SIZE	300 AMP
CONDUCTOR AMPACITY @ 90°C	320 AMP
WIRE SIZE NEEDED (THWN-2)	300 kcmil
CALCULATION: 2014 NEC 690.8(B)(2) Imax x (1/0.76) =	290.46 AMP
NEXT FUSE SIZE	300 AMP
CONDUCTOR AMPACITY @ 90°C	320 AMP
WIRE SIZE NEEDED (THWN-2)	300 kcmil

ARRAY 3


PV MODULE RATINGS

MODULE MANUFACTURER	SunPower
MODULE MODEL NUMBER	5PR-435NE-WHT-D
MAX POWER-POINT CURRENT (Imp)	5.97 A
MAX POWER-POINT VOLTAGE (Vmp)	72.9 V
SHORT-CIRCUIT CURRENT (Isc)	6.43 A
OPEN-CIRCUIT VOLTAGE (Voc)	85.6 V
MAX SERIES FUSE (OCPD)	20A
MAXIMUM POWER (Pmax)	435 W
MAX SYSTEM VOLTAGE	1000 V
Voc TEMP COEFF	-0.38 %/°C

PV CIRCUIT DESIGN

NUMBER OF MODULES IN SOURCE CIRCUIT	6
NUMBER OF SOURCE CIRCUITS PER ARRAY	25
TOTAL NUMBER OF MODULES PER ARRAY	150
ARRAY VOLTAGE (VOC)	513.6 V
WIRE VOLT REQUIRED	600 V
OPEN CIRCUIT CURRENT (ISC)	160.75 AMP
OPEN CIRCUIT MAXIMUM CURRENT (Imax)	200.94 AMP
AMBIENT TEMPERATURE	32°C
TEMPERATURE INCREASE (0.5" - 3.5" ABOVE ROOF)	22°C
EFFECTIVE TEMPERATURE	54°C
CORRECTION FACTOR - TEMPERATURE	0.76
CORRECTION FACTOR - <4 CONDUCTORS	1.00
CALCULATION: 2014 NEC 690.8(B)(1) Imax x 125%	251.17 AMP
NEXT FUSE SIZE	300 AMP
CONDUCTOR AMPACITY @ 90°C	320 AMP
WIRE SIZE NEEDED (THWN-2)	300 kcmil
CALCULATION: 2014 NEC 690.8(B)(2) Imax x (1/0.76) =	264.39 AMP
NEXT FUSE SIZE	300 AMP
CONDUCTOR AMPACITY @ 90°C	320 AMP
WIRE SIZE NEEDED (THWN-2)	300 kcmil

NOTE:
EACH RACKING SYSTEM TO BE GROUNDED
WITH A CONTINUOUS GROUNDING SYSTEM
SUCH AS WEB CONNECTORS. RUN COPPER
GROUND WIRE BACK TO SYSTEM GROUND.



NOTE:
SEE AC ELECTRICAL DRAWINGS E1 AND E2
FOR AC SIDE DESIGN INFORMATION.