



#### Kirila Contractors, Inc.

INDUSTRIAL . COMMERCIAL

P.O. BOX 179 505 BEDFORD ROAD SE BROOKFIELD, OHIO 44403

E.O.E.
EQUIPMENT RENTALS

PHONE (330) 448-4055 FAX (330) 448-4054 15-908-TR-CVF

May 6, 2015

Ohio Public Utilities Commission Attn: Docketing Division 180 East Broad Street Columbus, OH 43215-3793

RE: Case # OH3225005703C

I would like to contest the above citation which was received by a driver of one of our trucks. We received the citation due to "Failing to secure cargo" properly.

In the citation, it states that the machine weighs 20,000 pounds. I have enclosed a picture of the label for the ROLL BAR, which states the roll bar is safe for a 20,000 pound machine to roll over. This is not the weight of the machine. I have also enclosed the cover page from the machine which we were hauling and the page which states the operating weights for the machine is only 17,545 pounds, not the 20,000 pounds that we were charged with. This machine was tied down properly for a machine UNDER 20,000 pounds. There was some confusion as to what was seen on the tag and what the machine actually weighs.

Please consider this appeal and dismiss the case. If you have any questions, please do not hesitate to call me.

Sincerely,

Robert J. Kirila Vice President

Enclosures

PUCO

MISMAY II PH 4: 2

ALE SMEEDING UNIONAL SERVICE S





#### OPERATOR'S MANUAL LOADER BACKHOE

580M, 580M TURBO 580 SUPER M, 580 SUPER M+ 590 SUPER M SERIES 2

6-87681 NA

Issued 03-2006

### 5/2 ₽4 **Front Tires**

Differential Lock On-the-go push-button activation	Torque Converter Ratio2.63	2/4WD19.5L x 24 (10-ply rating)	2/4WD17.5L x 24 (10-ply rating)	Rear Tires	4WD12 x 16.5 (8-ply rating)	2WD11L x 16.1 (10-ply rating)
xtivation	2.63	/ rating)	/ rating)		/ rating)	/ rating)

#### Rear axle

Service brakes: Individually applied, hydraulically actuated, maintenance-free,	Total reduction ratio 16.153	Planetary hub ratio	Differential ratio 2.333  Planetary hub ratio 6.923  Total reduction ratio 16.153  Service brakes: Individually applied, hydraulically actuated, maintenance-free,
Planetary hub ratio       6.923         Total reduction ratio       16.153	Planetary hub ratio 6.923		Differential ratio
Differential ratio       2.333         Planetary hub ratio       6.923         Total reduction ratio       16.153	Differential ratio	Differential ratio	neal axie

self-adjusting, inboard mounted, wet disc.

Parking brakes: Mechanically applied with electric activation sensors at each

## OPERATING WEIGHTS

#### **Lightest Configuration**

dipper, 17.5L x 24 rear tires, 11L x 16.1 front tires, single battery, standard cast purpose loader bucket, 24 in (610 mm) Universal backhoe bucket, standard Equipped with 2WD, ROPS canopy, non-suspension seat, 82 in (2.08 m) general

### **Heaviest Configuration**

x 24 rear tires, dual batteries, flip stabilizer pads and **no** operator 17 545 lb (7 958 Equipped with 4WD, ROPS cab, suspension seat, 82 in (2.08 m) 4 in 1 loader bucket, 24 in (610 mm Universal backhoe bucket, Extendahoe dipperstick, 19.5L



## LOADER BUCKETS

	cutting edge	*All weights include 47 kg (103 lbs) for holt on cutting edge	*All wigidate include /
0.96 (1.25)	0.82 (1.07)	Optional	2362 (93)
0.80 (1.04)	0.65 (.85)	4-in-1	2083 (82)
0.77 (1.01)	0.67 (.88)	Standard	2083 (82)
Capacities SAE Heaped m <sup>3</sup> (cu yd)	Capacities Struck m³ (cu yd)	Туре	Width mm (Inch)

# **BACKHOE BUCKETS - 580 SUPER**

Width mm (Inch) 305 (12)	Type Universal HD	Capacities Struck m3 (cu feet) 0.08 (3.00)
	Universal HD	0.08 (3.00)
457 (18)	Universal HD	0.12 (4.40)
610 (24)	Universal HD	0.17 (6.10)
762 (30)	Universal HD	 0.22 (7.90)
914 (36)	Universal HD	 0.27 (9.60)
610 (24)	H.D. Hi Capacity	0.20 (6.90)
762 (30)	H.D. Hi Capacity	0.24 (8.60)