

## LARGE FILING SEPARATOR SHEET

CASE NUMBER: 14-0253-GA-BTX FILE DATE: 04/12/19 SECTION: PART 1 OF Z FILED BY: DUKE ENERGY FILED ON BEHALF OF: DUKE ENERGY NUMBER OF PAGES: 151

# DESCRIPTION OF DOCUMENT: MULTIPLE EXHIBITS

This is to certify that the images appearing are an accurate and complete reproduction of a case file document delivered in the regular course of business. Technician \_\_\_\_\_\_ Date Processed \_\_\_\_\_\_12\_19\_\_\_

PUCO Case No. 16-0253-GA-BTX CITY-POD-01-005 CONF Attachment Page 34 of 87





FILE

# Western Route Constructability Review



**Duke Energy** 





#### 1.12 8.40 to 9.70, Downtown Reading

The route through downtown Reading had very few changes. From the bore across the railroad, turn south with the centerline in West St. to W. Pleasant St. There is a 230' segment between the ball park and the entrance to the school where the road would have to be closed for construction or put the centerline in the grassy area on the west side of the road.

Then the route turns east on W. Pleasant St. and then turns south on Market St. The centerline would have to be located on the west side of Market Street, between a 2" gas line and sewer line. The route continues east on E. Mechanic St. to cross the railroad. West of the railroad, the centerline would have to be on the north side of the road to avoid water and sewer. On the east side of the railroad it may be necessary to relocate part of a 2" gas line for the bore pit, if bored from the north east of the railroad. The east side of the railroad may have to close the street for bore and construction for 100', including an entrance to a drive thru beer store. If bored from the south, there is a small possibility of keeping one lane open.

The centerline continues on and goes south on E. 3rd St. There is a 2" gas line between the road and sidewalk on the east side. Along the east side of the street there are water and gas service lines crossing to houses on the west side all the way to the end of 3rd St at a cul-de-sac. The street is narrow, and conventional construction would restrict some access to the houses. However the street could be kept open. Residents currently use the street for parking. This would not be possible in area of construction. The centerline continues through open area south of 3rd St along east side of area. It is recommended to keep this location to accommodate any future development.



AV-INT-01-007

#### **REQUEST:**

Identify how the future upgrade, replacement, or improvement of the A-Line affects the need for the Pipeline.

#### **RESPONSE:**

Any future upgrade, replacement, or improvement of Line A will not affect the need for the Pipeline.

PERSON RESPONSIBLE: James Olberding





**Duke Energy Ohio** Case No. 16-253-GA-BTX **CITY Second Set Interrogatories** Date Received: June 5, 2017

#### **CITY-INT-02-009**

#### **REQUEST:**

On page 2-7 of the Application, you state that the Preferred Route (or Orange Route) would "best" allow for retirement of the propane-air facilities, while the Alternate Route "would also allow for retirement of the propane-air facilities."

- a. Why would the Preferred Route best allow for retirement of the propane-air facilities, as compared to the Alternate Route?
- b. Would Route 3 best allow for retirement of the propane-air facilities as compared to the Preferred Route?
- c. Would Route 3 best allow for retirement of the propane-air facilities as the received of the Alternate Route? c. Would Route 3 best allow for retirement of the propane-air facilities as compared to the Alternate Route?

information that is neither relevant to this proceeding nor likely to lead to the diservery of admissible evidence in this proceeding. Without waiving said objection, to the extent discoverable, and in the spirit of discovery,

- a. The preferred route would provide for better pressure distribution to the eastern parts of the Hamilton County system.
- b. No.
- c. Its effect on ability to retire propane-air facilities is similar.







Duke Energy Ohio Case No. 16-253-GA-BTX **AV Second Set Interrogatories** Date Received: July 24, 2017

AV-INT-02-007

#### **REQUEST:**

Does Duke intend that gas will flow through the A-Line in a northerly or southerly direction after an upgrade to the A-Line?

#### **RESPONSE:**

Objection. This Interrogatory is overly broad, and unduly burdensome, given that it seeks information that is neither relevant to this proceeding nor likely to lead to the discovery of admissible evidence in this proceeding. Objecting further, this Interrogatory is vague, ambiguous, and unduly burdensome. The question is susceptible to different interpretations and Duke Energy Ohio would have to engage in speculation or conjecture to ascertain the intended meaning of this request, as the term "upgrade" is not defined. Without waiving said objection, to the extent discoverable, in the spirit of discovery, and defining "upgrade" to refer to an increase in diameter and/or pressure, the existing Line A can flow in either direction (see response to AV-INT-02-006), based on customer demand and various system operations. Although specific plans have not been developed, the future operation of Line A would likely depend on customer demand, system operations, and engineering requirements.

#### **PERSON RESPONSIBLE:**

As to objection:	Legal
As to response:	Vince Andres

2019 APR 12 PH 2: 45

PUCO

ובכבועבם-מפנאבדואה הוא



CITY-INT-05-002

### **REQUEST:**

Please identify the peak hourly demand (in Mcfh) in 2016, 2017, and 2018.

#### **RESPONSE:**

2016 - 39038 2017 - 39382 2018 - 41984

PERSON RESPONSIBLE: Vince Andres / David Emerick / James Olberding



Duke Energy Ohio Case No. 16-253-GA-BTX AV First Set Production of Documents Date Received: May 18, 2017

#### **AV-POD-01-009 SUPPLEMENTAL**

#### **REQUEST:**

Produce all documents regarding the need for the Pipeline as it relates to Duke's plans to

upgrade, replace, or improve the A-Line.

#### **RESPONSE:**

Objection. This Interrogatory is overly broad, and unduly burdensome, given that it seeks information that is neither relevant to this proceeding nor likely to lead to the discovery of admissible evidence in this proceeding. Without waiving said objection, to the extent discoverable, and in the spirit of discovery, specific replacement/upgrade plans for Line A have not been developed. However, due to the number of gas customers who are served from Line A, the proposed line will support future upgrades of Line A by providing an alternate feed to customers and extending windows of time available for replacement activities.

#### PERSON RESPONSIBLE:

As to objection: Legal As to response: James Olberding



CITY-INT-05-006

#### **REQUEST:**

In response to STAFF-DR-18-002, Duke stated: "After the Central Corridor Pipeline is in

service and depending on the current system usage, we expect that the propane-air

peaking plants will continue to be operational for several years before decommissioning

as demand and system configurations are adjusted." Please identify and describe whether

Duke expects to continue making annual repairs to the equipment at the propane-air

peaking facilities (as referenced in Duke's response to NOPE-INT-03-029) during the

"several years before decommissioning."

**RESPONSE:** Objection. This Interrogatory causes Duke Energy Ohio to engage in impermissible speculation and guesswork as it has not been determined when the propane-air peaking plants will be decommissioned. Without waiving said objection, to the extent discoverable, and in the spirit of discovery, Duke Energy Ohio will make annual repairs as needed to keep the propane-air peaking plants safe, reliable and in compliance with regulatory requirements and industry best practices.

#### **PERSON RESPONSIBLE:**

As to objection: Legal As to response : Adam Long



CITY-INT-01-006

#### **REQUEST:**

What is the number of propane intolerant users and the number of total users on the Ohio system?

#### **RESPONSE:**

There are currently six propane intolerant customers in Ohio that are notified when the propane peaking plants are in operation. The total number of propane intolerant users is not known. There are over 400,000 users in southwest Ohio.



CITY-INT-05-008

#### **REQUEST:**

Please identify and describe the basis or bases for the contention, as most recently explained on page 28 of the Amended Staff Report, that Duke "found that the western options did not allow for retirement of the propane-air peaking plants."

**RESPONSE:** Objection. This Interrogatory seeks to elicit information that is of public record and thus is equally accessible to the requestor. Without waiving said objection, to the extent discoverable, and in the spirit of discovery, modeling of a 20" proposed western connection to the Duke high pressure distribution loop with propane/air peaking plants off line resulted in inadequate pressures during peak hour conditions in north eastern portions of the natural gas system.

#### PERSON RESPONSIBLE:

As to objection: Legal As to response: Vince Andres / David Emerick / James Olberding



CITY-INT-01-024

#### **REQUEST:**

Identify, describe, and explain Duke's definition of "excessive reliance" as used on p. 2-3 of the Amended Application.

**RESPONSE:** Excessive reliance refers to the current vunerability of the system due to the requirement to supply more than 50 percent of the system from one gate station during a peak day.



CITY-INT-05-014

#### **REQUEST:**

After the Project is constructed, please identify and describe the pipeline construction

projects that Duke plans to propose to further mitigate or eliminate the reliance on Foster

Station.

**RESPONSE:** Objection. This Interrogatory is overly broad and unduly burdensome, given that it seeks information that is unlimited as to time. Objecting further, this Interrogatory forces Duke Energy Ohio to engage in speculation and guesswork as to future events. Without waiving said objection, to the extent discoverable, and in the spirit of discovery, as noted in the 2017 Long-Term Forecast Report, projects are contemplated on lines CG04 and V000 that may have an effect on the balance of supply. Work on each of these lines would include replacement of sections of 20" pipe and ILI retrofits. Additional pipeline projects that may assist with system balance will be determined based on the approved scope of the Central Corridor Project, growth of system load, system integrity priorities, and other factors.

1

#### PERSON RESPONSIBLE:

As to objection: Legal As to response: Dave Emerick / Vince Andres



CITY-INT-01-035

#### **REQUEST:**

Identify whether the scoring criteria used in the RSS included consideration of a proposed route's ability to facilitate the retirement of the propane-air facilities described in the Amended Application on p. 2-7.

#### **RESPONSE:**

The scoring criteria in the RSS did not include explicit consideration of a proposed route's ability to facilitate the retirement of the propane-air facilities. However, the RSS in its entirety was scoped to meet the project needs in that all potential route candidates identified by the RSS met such needs at least to some degree. Qualitatively, there are advantages to specific route alternatives in best meeting the Project needs, as discussed in the answer to CITY-INT-01-034.

#### PERSON RESPONSIBLE:

David Emerick/Steve Lane/Mike Frank/James Nicholas



#### CITY-INT-01-036

#### **REQUEST:**

The following requests are based on Duke's statement on p. 1-5 of the RSS that "Line V will need to be upgraded in the near future irrespective of the Project."

- a. Identify, describe, and explain the need to upgrade Line V.
- b. Identify, describe, and explain the impact of upgrading Line V on the C314V project.
- c. Identify, describe, and explain the impact of the C314V project on the need to upgrade Line V.

#### **RESPONSE:**

- a. One of Duke Energy Ohio's long-term goals is to replace aging infrastructure; Line V was built in the 1950s.
- b. Upgrading Line V will have no impact on the C314V project.
- c. The C314V project has no impact on the need to upgrade Line V.



Duke Energy Ohio Case No. 16-253-GA-BTX CITY Fifth Set of Requests for Production Date Received: March 12, 2019

CITY-POD-05-003

#### **REQUEST:**

Please produce any engineering studies concerning whether or how the construction of

the Alternate or Preferred Routes may make it easier to undertake maintenance and

replacement work on the existing pipelines in the central corridor area.

**RESPONSE:** There are no such engineering studies.

PERSON RESPONSIBLE: Adam Long



Duke Energy Ohio Case No. 16-253-GA-BTX CITY Second Set Interrogatories Date Received: June 5, 2017

CITY-INT-02-007

#### **REQUEST:**

An evaluation of the boilers in the Kentucky facility completed in 2013 is referenced in response to STAFF-DR-01-001. Has a similar evaluation of the boilers been conducted for the propane peaking facility located in Ohio?

If so, please describe it.

#### **RESPONSE:**

A similar boiler evaluation has not been conducted for the peaking facility in Ohio.

#### **PERSON RESPONSIBLE:**

David Emerick



NOPE-INT-01-006

#### **REQUEST:**

Identify and describe any and all instances where customers in Ohio experienced supply vulnerability because of the failure of the propane-air plants or shut-in of the southern natural gas supply during periods of peak demand.

#### **RESPONSE:**

There have not been any instances when all of the propane-air peaking plants have failed or the southern natural gas supply was shut in during a peak day.



Duke Energy Ohio Case No. 16-253-GA-BTX CITY Second Set Interrogatories Date Received: June 5, 2017

#### **CITY-INT-02-008**

#### **REQUEST:**

Your response to STAFF-DR-12-001 states your expectation that the proposed 20-inch pipeline will reduce reliance on the Foster Station from 55 percent to 45 percent.

- a. Does this expectation assume the Preferred Route is used?
- b. What is the expectation with respect to the Alternate Route?

#### **RESPONSE:**

a. Yes

b. It is expected that use of the Alternate route would reduce reliance on Foster Station from 55 percent to approximately 50 percent.

#### **PERSON RESPONSIBLE:**

Vince Andres



#### **NOPE-INT-01-008**

#### **REQUEST:**

Please state the estimated cost of repairing and/or upgrading the propane-air plants that you claim need to be repaired or upgraded.

#### **RESPONSE:**

The estimated cost for upgrades at the propane air plants has not been identified in full. Storage options at the current locations are limited and may not be achievable based on current regulations.

**PERSON RESPONSIBLE:** James Olberding



#### **NOPE-INT-01-013**

#### **REQUEST:**

Describe all the ways in which construction of a pipeline in a high residential and high traffic area differ from construction of a pipeline in a more rural area.

#### **RESPONSE:**

- 1. Traffic Traffic control plan in place (flagging, work zone and signage, etc.)
- 2. Pipe Lay Pipeline is installed by "stove pipe" method usually 1-2 sticks of pipe at a time with a bell hole to weld pieces together. The workspace is generally smaller in higher traffic areas so a "train style" method (where several sticks of pipe are welded together on the edge of the trench and laid into the ground at once) cannot always be used. Spoils are hauled away and replaced with new soil/controlled density fill. In most instances, utilities/existing infrastructure are more common in high-traffic areas and that can lead to slower construction.
- 3. Hours of Operation Hours of operation are normally limited to daytime in residential areas.
- 4. Dust/Noise control Streets and sidewalks are swept to keep the dust minimized in higher traffic/residential areas. Noise control is put in place to limit impact of construction equipment noise.
- 5. End of Work day Trench is steel plated at the end of the day and all equipment is secured at a specific safe location so traffic can continue during non-working hours. In rural areas, trench may be left open and fenced off while equipment is left on site in some instances.

PERSON RESPONSIBLE: Bradley Seiter



Duke Energy Ohio Case No. 16-253-GA-BTX NOPE Third Set Data Requests Date Received: January 10, 2019

NOPE-INT-03-027

#### **REQUEST:**

State whether tariffs on imported steel will impact the costs of the proposed C314V

pipeline.

a. If the answer to this Interrogatory is in the affirmative, describe the

updated costs of the proposed C314V pipeline.

**RESPONSE:** Objection. This Interrogatory is overly broad and unduly burdensome, given that it seeks information that is neither relevant to this proceeding nor likely to lead to the discovery of admissible evidence in this proceeding. Without waiving said objection, to the extent discoverable, and in the spirit of discovery, the materials for the project have not yet been ordered and the cost impact of tariffs on imported steel is unknown at this time.

#### PERSON RESPONSIBLE:

As to objection: Legal As to response : James Olberding



NOPE-INT-01-014

#### **REQUEST:**

Identify and describe all widespread service outages in Ohio that have resulted because of the use of the propane-air plants referenced in the Application.

#### **RESPONSE:**

No widespread service outages have occurred in Ohio as a result of Duke Energy Ohio's use of the propane-air plants.



Duke Energy Ohio Case No. 16-253-GA-BTX NOPE Third Set Data Requests Date Received: January 10, 2019

NOPE-INT-03-029

#### **REQUEST:**

What installations, repairs, or upgrades have been made at the Riverside Peaking Plant in

the past 10 years?

a. What is the depreciation rate for the equipment involved in each

installation, repair, or upgrade?

**RESPONSE:** Objection. This Interrogatory is vague and ambiguous as to the term "Riverside Peaking Plant." The term is susceptible to different interpretations and Duke Energy Ohio would have to engage in speculation or conjecture to ascertain the intended meaning of this request. Objecting further, this Interrogatory is duplicative of NOPE-POD-01-006 and thus must be seen as intended to harass. Without waiving said objection, to the extent discoverable, and in the spirit of discovery, and assuming that "Riverside Peaking Plant" is the same as a "propane-air plant," annual repairs are made to the majority of the equipment. Piping sections are replaced as needed to meet integrity requirements. See the response to NOPE-POD-01-006.

a. Objection. This Interrogatory is vague and ambiguous as to the meaning of "depreciation rate." The term is susceptible to different interpretations and Duke Energy Ohio would have to engage in speculation or conjecture to ascertain the intended meaning of this request. Objecting further, to the extent that "depreciation rate" was intended to refer to depreciation for accounting and/or tax purposes, the Interrogatory seeks information that is of public record and thus equally accessible to NOPE and, further, is overly broad, unduly burdensome, and designed to elicit information that is both irrelevant and not reasonably calculated to lead to the discovery of admissible evidence.

#### **PERSON RESPONSIBLE:**

As to objection: Legal As to response : Adam Long



> NOPE-INT-01-026 SUPPLEMENTAL

#### **REQUEST:**

Identify the number of customers in the Natural Gas Curtailment program in the Cincinnati service area for the past 3 years. Please also provide:

- a. The estimated natural gas MCF usage of each customer in the curtailment program;
- b. Please state the total number of times these customers have been required to curtail their service and switch to over to alternative fuel for the past 3 years;
- c. Please state the MCF average usage shaved from each curtailment for each year over the past 3 years;
- d. What is the minimum amount of time a curtailment customer will be offline?
- e. What is the maximum amount of time a curtailment customer will be offline?
- f. Identify each time since 2014 that the curtailment program has been used to avoid a shortage of service gas;
- g. Identify the number of customers that have left the curtailment program over the last 3 years;
- h. Over the last 3 years, identify and describe what percentage of curtailment activity is used during peak demand period;

#### **RESPONSE:**

Currently there are 109 customers on Rate IT (Interruptible Transportation).

In December 2013, there were 133 customers on Rate IT.

In December 2014, there were 117 customers on Rate IT.

In December 2015, there were 114 customers on Rate IT.

In December 2016, there were 111 customers on Rate IT.

a. Individual customer usage information is confidential and will not be released by Duke Energy Ohio without customer authorization. The aggregate usage of the Rate IT customers was:

2016: 20,576,314 MCF 2015: 19,511,696 MCF 2014: 20,321,914 MCF

- b. IT customers have been curtailed five times in the last three calendar years (that is, between January 2014 and December 2016).
- c. 1/6/14 through 1/7/14: 88,000 MCF 1/24/14: 6,000 MCF 1/28/14: 36,000 MCF 1/08/15: 9,000 MCF 2/19/15: 42,000 MCF
- d. There is no minimum time length. Two hours was the shortest curtailment time for the past several years.
- e. There is no maximum time limit for curtailments.
- f. 1/6/14 through 1/7/14 with propane-air peaking plants on line.
  1/24/14 with propane-air peaking plants on line.
  1/28/14 with propane-air peaking plants on line.
  1/08/15 with propane-air peaking plants on line.
  2/19/15 with propane-air peaking plants on line.
- g. There has been a net decrease of 24 customers on Rate IT since January 2014. 27 customers are no longer on Rate IT, however, 3 customers have moved to Rate IT.
- h. 100%

#### PERSON RESPONSIBLE: Rick Colvin / Chris Blaut

#### SUPPLEMENTAL RESPONSE:

In December 2017, there were 111 customers on Rate IT. In December 2018, there were 109 customers on Rate IT.

a. Individual customer usage information is confidential and will not be released by Duke Energy Ohio without customer authorization. The aggregate usage of the Rate IT customers was:

2018: 20,632,025 MCF 2017: 20,518,356 MCF

- b. IT customers have been curtailed eleven times in the last five calendar years (that is, between January 2014 and January 2019).
- c. 12/27/17: 12,000 MCF 1/2/18: 21,000 MCF

1/3/18: 9,000 MCF 1/5/18: 9,000 MCF 1/21/19: 18,000 MCF 1/30/19 through 1/31/19: 105,000 MCF

- d. No supplementation necessary.
- e. No supplementation necessary.
- f. 12/27/17 with propane-air peaking plants on line.
  1/2/18 with propane-air peaking plants on line.
  1/3/18 with propane-air peaking plants on line.
  1/5/18 with propane-air peaking plants on line.
  1/21/19 with propane-air peaking plants on line.
  1/30/19 through 1/31/19 with propane-air peaking plants on line.
- g. No supplementation necessary.
- h. No supplementation necessary.

The propane peaking plants are aging and will eventually need to be retired. Without the propane peaking plants, we would need more gas curtailments.

PERSON RESPONSIBLE: Rick Colvin / Chris Blaut



Duke Energy Ohio Case No. 16-253-GA-BTX NOPE Third Set Data Requests Date Received: January 10, 2019

NOPE-INT-03-031

#### **REQUEST:**

What installations, repairs, or upgrades have been made at the Erlanger Peaking Plant in

the past 10 years?

a. What is the depreciation rate for the equipment involved in each

installation, repair, or upgrade?

**RESPONSE:** Objection. This Interrogatory is duplicative of NOPE-POD-01-006 and thus must be seen as intended to harass. Without waiving said objection, to the extent discoverable, and in the spirit of discovery, annual repairs are made to the majority of the equipment. Piping sections are replaced as needed to meet integrity requirements. See the response to NOPE-POD-01-006.

a. Objection. This Interrogatory is vague and ambiguous as to the meaning of "depreciation rate." The term is susceptible to different interpretations and Duke Energy Ohio would have to engage in speculation or conjecture to ascertain the intended meaning of this request. Objecting further, to the extent that "depreciation rate" was intended to refer to depreciation for accounting and/or tax purposes, the Interrogatory seeks information that is of public record and thus equally accessible to NOPE and, further, is overly broad, unduly burdensome, and designed to elicit information that is both irrelevant and not reasonably calculated to lead to the discovery of admissible evidence.

#### **PERSON RESPONSIBLE:**

As to objection:	Legal
As to response:	Adam Long



NOPE-INT-01-028

#### **REQUEST:**

State whether the 43,000 MCFH supply referenced on page 3-1 Application is to meet the needs of Ohio and Kentucky customers combined.

a. If the answer to this Interrogatory is in the affirmative, describe the daily peak hour flow supplied to Ohio only for the past 3 years.

#### **RESPONSE:**

Yes.

a. The highest hourly flow experienced to Ohio in the past three years was approximately 35,500 MCFH. This occurred on a day that was not a design day, when curtailments had not been exercised.

PERSON RESPONSIBLE: David Emerick / Vince Andres



#### NOPE-INT-01-033

#### **REQUEST:**

State whether propane intolerant users could be supplied from a portion of the system segregated from the propane-air plants.

- a. If you claim that propane intolerant users cannot be supplied from a segregated portion of the system, please explain why.
- b. Referring to your Figures 3-3 and 3-4 on p. 3-6 of the Application, please indicate the actual concentrations of propane in different parts of the system.

#### **RESPONSE:** Yes

- a. N/A
- b. Objection-question is not specific enough. Levels vary in red areas but are detectable

#### PERSON RESPONSIBLE: David Emerick / Vince Andres



NOPE-INT-01-035

#### **REQUEST:**

Describe the need that will no longer be met because of the change to a 20-inch pipeline as opposed to the original proposed 30-inch pipeline, as referenced on pages 3-4 and 3-5 of the Application.

**RESPONSE:** The need to balance supply will no longer be fully met.



Duke Energy Ohio Case No. 16-253-GA-BTX NOPE First Requests For Admission Date Received: May 26, 2017

NOPE-RFA-01-001

### **REQUEST:**

Admit that you can perform maintenance on existing lines in the central corridor without building the proposed pipeline.

**RESPONSE:** Admitted.



NOPE-INT-01-037

#### **REQUEST:**

State whether you considered alternative locations for the proposed pipeline in non-residential areas.

a. If you did consider locations in non-residential areas, identify and describe those locations.

#### **RESPONSE:**

Due to the nature of the study area, none of the routes considered avoided residential land uses completely. Other non-residential dominant land use types in the project area included commercial, industrial, institutional, wooded areas, and recreational outdoor spaces. These non-residential areas are identified and described in the Route Selection Study and Chapter 4906-5-04 of the Project's Amended Application.

PERSON RESPONSIBLE: Steve Lane



Duke Energy Ohio Case No. 16-253-GA-BTX NOPE First Requests For Admission Date Received: May 26, 2017

NOPE-RFA-01-004

#### **REQUEST:**

Admit that Lines A, EE, and V can be upgraded and/or replaced without the proposed line.

#### **RESPONSE:**

Admitted.



**NOPE-INT-01-038** 

#### **REQUEST:**

State whether the Application considered costs for decommissioning the propane-air plants.

a. Identify and describe the cost of decommissioning each propane-air plant.

**RESPONSE:** 

No.

PERSON RESPONSIBLE: James Olberding



Duke Energy Ohio Case No. 16-253-GA-BTX NOPE First Requests For Admission Date Received: May 26, 2017

NOPE-RFA-01-006

#### **REQUEST:**

Admit that the health and safety risks from accidents, including leaks, fires, and explosions, in densely populated areas are significantly greater than risks in rural areas.

#### **RESPONSE:**

Denied.

PERSON RESPONSIBLE: James Olberding


Duke Energy Ohio Case No. 16-253-GA-BTX NOPE Second Set Interrogatories Date Received: July 18, 2017

> NOPE-INT-02-022 SUPPLEMENTAL

# **REQUEST:**

Since January 2007, please identify all dates that met the criteria of an average of 0

degrees for a 24-hour period in Ohio and Kentucky.

a. Provide actual peak demand for each of those dates.

# **RESPONSE:**

January 6, 2014. a. Approximately 40,000 MCFH

PERSON RESPONSIBLE: Chuck Rust

## SUPPLEMENTAL RESPONSE:

February 19, 2015 a. Approximately 40,000 MCFH

PERSON RESPONSIBLE: Eric Emmerich



Duke Energy Ohio Case No. 16-253-GA-BTX NOPE First Requests For Admission Date Received: May 26, 2017

NOPE-RFA-01-008

# **REQUEST:**

Admit that the use of the propane-air plants referenced in the Application have not resulted in in any widespread service outages in Ohio.

**RESPONSE:** Admitted.

PERSON RESPONSIBLE: David Emerick



CITY-POD-01-020 Attachment

Duke Energy Ohio Case No. 16-253-GA-BTX Staff Second Set Data Requests Date Received: February 14, 2017

STAFF-DR-02-001

## **REQUEST:**

Table 7-4, on page 7-15 of the application, lists the total area of right-of-way for the Preferred Route at 44.6 acres, and lists 47.1 acres for the Alternate Route. Please explain why the Alternate Route is calculated to have a greater area of right-of-way despite being 5,441 feet shorter, as shown in Table 7-3.

### **RESPONSE:**

There was a transcription error in Table 7-4 in the preferred route ROW acreage column that went unnoticed during our QC review. The acreage value for "Pavement" has been corrected in the attached PDF, which results in a higher total ROW acreage (as expected for the preferred route). The percentages for each category were also affected slightly, so we have updated the narrative paragraphs to match.

The header in the attached PDF is stamped with 02/16/17. Please insert as updated pages.

See Staff-DR-02-001 Attachment.

PERSON RESPONSIBLE: Steve Lane

#### PUCO Case No. 16-0253-GA-BTX STAFF-DR-02-001 Attachment O 16-0253-GA-BTX Pate 1 of 4

ADDENDUM TO OPSB APPLICATION (02/16/17) OPSB CASE NO. 16-0253-GA-BTX Page 1 of 4

		Preferre	d Route			Alterna	te Route	
Land Use	CWA* Acres	CWA Percent	ROW Acres	ROW Percent	CWA Acres	CWA Percent	ROW Acres	ROW Percent
Delineated Pond	Q	0%	Q	0%	<u>Q.2</u>	<u>0.1%</u>	Q	975
Delineated Stream	<u>0.6</u>	0.6%	<u>0.1</u>	0.2%	0.5	0.48	0.2	0.4%
Delineated Wetland	1.5	1,2%	<u>0.2</u>	0.4%	1.4	1.1%	0.3	0.6%
Educational	2.8	2.0%	1.0	2.0%	2.4	1.9%	0.9	2.0%
Industrial/Commercial	<u>47.8</u>	35.1%	19.5	38.5%	48.3	38.3%	<u>19,6</u>	41.5%
lenoitutitani	Q.5	<u>0.3%</u>	<u>0.1</u>	9.2%	<b>Q.</b> Z	<u>0.6%</u>	0.1	0.3%
Parks and Recreation	<u>18.8</u>	13.5%	7.3	14.4%	<u>6,9</u>	<u>5.5%</u>	<u>2.9</u>	6.2%
Pavement <sup>a</sup>	<u>35.5</u>	<u>76.1%</u>	<u>13,4</u>	26.4%	35.4	28.1%	12.5	26.6%
Residential	<u>7.8</u>	5.6%	1.7	<u>3.3%</u>	<u>7,5</u>	<u>5.9%</u>	<u>2.5</u>	<u>5.4%</u>
Undefined	0.3	<u>0.2%</u>	<u>0.2</u>	0.4%	2.0	1.5%	<u>Q.4</u>	0.8%
Woodiots	<u>20.6</u>	15.1%	7.2	14.2%	20.8	16.5%	7.7	<u>16.2%</u>
Tatel	136.4	100%	<u>50.7</u>	100%	126.1	100%	47.1	100%

#### TABLE 7-4 Acreage and Percent of Land Uses Crossed by Route Alternatives

\* CWA = construction work area (80-foot wide construction area corridor).

<sup>b</sup>Pavement represents road ROW.

### FUCO Case No. 16-0253-GA-BTX STAFF-DR-02-001 Attachment

ADDENDUM TO OPSB APPLICATION (02/16/17) OPSB CASE NO. 16-0253-GA-BTX Page 2 of 4

	Route Alt	ernatives
	Preferred	Alternate
Length (in miles)	13.4 14.0	13.0
Features within 100 feet of Route Alternatives (centerline)		
Historic Structures (Ohio Historic Structures)	23	N/A.D
National Register of Historic Places	NAQ	N/A.0
Previously Identified Archaeological Sites	0	0
Residences	157,110	108 166
Other Sensitive Land Uses <sup>e</sup>	6 <u>5</u>	4 <u>10</u>
Features within 1,000 feet of Route Alternatives (centerline	)	
Historic Structures (Ohio Historic Structures)	42	12
National Register of Historic Places	N/A D	1
Previously identified Archaeological Sites	0	5
Residences	<del>2,749 3,149</del>	2,625 7.170
Other Sensitive Land Uses*	44_45	34 <u>38</u>
Structures within 200 feet of the Edge of Preliminary Permanent ROW (preliminary ROW is 30-feet wide)	673,641	694 <u>.655</u>

TABLE 7-5

Number of Land Use Features Near the Route Alternatives

\* Other sensitive land uses include algorts, parks/<u>recreation areas</u>, state forests, schools, hospitals, churches, and cemeteries.

Because the Project consists primarily of a buried pipeline, land uses within the CWA and ROW will generally remain unchanged. Most land use impacts are temporary and consist of surface disturbance during construction. Some permanent land use impacts will occur in selected areas because of vegetation clearing within the ROW and conversion of wooded or shrub habitat to herbaceous ground cover. However, in most cases property owners may continue to utilize most of the ROW area for general uses that will not affect the safe and reliable operation of the pipeline.

#### (a) Residential

<u>Preferred Route:</u> The Preferred Route centerline is located within 1,000 feet of 3,7493,150 residences and within 100 feet of 157-110 residences. As shown in Table 7-4, residential areas

#### PUCO Case No. 16-0253-GA-BTX STAFF-DR-02-001 Attachment ADDENDUM TO OPSB APPLICATION (02/16/17) OPSB CASE NO. 16-0253-GA-BTX Page 3 of 4

make up approximately 3.03.3 percent of the Preferred Route permanent ROW (30-foot width) acreage.

<u>Alternate Route</u>: The Alternate Route centerline is located within 1,000 feet of 2,6252,172 residences and within 100 feet of 198-166 residences. As shown in Table 7-4, residential areas make up approximately 5.35.4 percent of the Alternate Route permanent ROW acreage.

Although the Preferred Route is within 1,000 feet of more residences than the Alternate Route, the Preferred Route directly affects less residential land than the Alternate Route. Only <u>1,8712,188</u> linear feet of pipeline would be located on residential land under the Preferred Route scenarlo, compared to <u>3,516–3,658</u> linear feet of the Alternate Route located on residential land. This is largely because residential land use along the Alternate Route is in older, denser communities, leaving less options of avoiding direct impacts to residential properties.

#### (b) Industrial/Commercial

<u>Preferred Route</u>: Industrial or commercial land uses make up approximately 43-238.5 percent of the Preferred Route permanent ROW acreage. This represents the largest proportion of land use within the Preferred Route ROW. The Preferred Route centerline crosses 39,83328,493 feet (43-638.5 percent of the total length) of land classified as industrial or commercial.

<u>Alternate Route:</u> Industrial or commercial land uses make up approximately 44.741.5 percent of the Alternate Route permanent ROW acreage. The Alternate Route centerline crosses 31,33028,952 feet (45.642.3 percent of the total length) of land classified as industrial or commercial.

#### (c) Educational

<u>Preferred Route</u>: Educational land uses make up approximately <del>3.62.0</del> percent of the Preferred Route permanent ROW acreage

<u>Alternate Route:</u> Educational land uses make up approximately <u>1.92.0</u> percent of the Alternate Route permanent ROW acreage

#### PUCO Case No. 16-0253-GA-BTX STAFF-DR-02-001 Attachment ADDENDUM TO OPSB APPLICATION (02/16/17) OPSB CASE NO. 16-0253-GA-BTX Page 4 of 4

#### (d) Institutional

<u>Preferred Route:</u> Institutional land uses make up approximately 0.00.2 percent of the Preferred Route ROW acreage.

<u>Alternate Route:</u> Institutional land uses make up approximately 0-20.3 percent of the Alternate Route ROW acreage.

### (e) Parks and Recreation

<u>Preferred Route:</u> Parks and recreational land uses make up approximately 8-814.4 percent of the Preferred Route permanent ROW acreage.

<u>Alternate Route</u>: Parks and recreational land uses make up approximately 4.5<u>6.2</u> percent of the Alternate Route permanent ROW acreage.

#### (f) Pavement

<u>Preferred Route:</u> Paved areas (e.g., road ROW) make up approximately <u>27.926.4</u> percent of the Preferred Route permanent ROW acreage.

<u>Alternate Route:</u> Paved areas (e.g., road ROW) make up approximately <u>25.626.6</u> percent of the Alternate Route permanent ROW acreage.

### (g) Woodlots

<u>Preferred Route:</u> Woodlots make up approximately <u>11.814.2</u> percent of the Preferred Route permanent ROW acreage.

<u>Alternate Route:</u> Woodlots make up approximately <u>15.516.2</u> percent of the Alternate Route permanent ROW acreage.

(3) Impact on Identified Nearby Structures

### (a) Structures Within 200 Feet of Proposed Right-of-Way

There are <u>633-641</u> structures (residences, commercia) businesses, etc.) within 200 feet of the proposed permanent ROW (30-foot width of the Preferred Route). There are <u>656-655</u> structures within 200 feet of the proposed permanent ROW of Alternate Route. The individual structures and their distances from the proposed permanent ROW boundary are listed in Appendix 7-1



Duke Energy Ohio Case No. 16-253-GA-BTX Staff Fourteenth Set Data Requests Date Received: May 9, 2017

STAFF-DR-14-001

# **REQUEST:**

How will the selection of the Preferred Route impact future upgrades to Lines A, EE, and/or V versus the Alternate Route?

**RESPONSE:** Lines A, EE and V are being upgraded/replaced as part of the Duke Energy Ohio plans to replace aging infrastructure over the next 20 years. Selection of the Preferred or Alternate routes will have no effect on the decision to replace these lines.

PERSON RESPONSIBLE: James Olberding



Duke Energy Ohio Case No. 16-253-GA-BTX Staff Fourteenth Set Data Requests Date Received: May 9, 2017

STAFF-DR-14-002

# **REQUEST:**

Is there a timeline for upgrading these lines?

And if so please explain.

**RESPONSE:** Sections of Line A will be replaced over the next 20 years; Line EE is tentatively scheduled for sections to be replaced in 2018 and 2021; Line V is tentatively scheduled for replacement in 2022 or 2023. The timing for construction on these projects is subject to change depending on system priorities.

PERSON RESPONSIBLE: James Olberding



Duke Energy Ohio Case No. 16-253-GA-BTX Staff Eighteenth Set Data Requests Date Received: August 2, 2018

STAFF-DR-18-002

# **REQUEST:**

How many winter seasons does Duke Energy Ohio expect that it would continue to utilize the propane-air peaking plants?

### **RESPONSE:**

After the Central Corridor Pipeline is in service and depending on the current system usage, we expect that the propane-air peaking plants will continue to be operational for several years before decommissioning as demand and system configurations are adjusted.

# **PERSON RESPONSIBLE:**

James Olberding



Duke Energy Ohio Case No. 16-253-GA-BTX Staff Twentieth Set Data Requests Date Received: March 4, 2019

STAFF-DR-20-001

# **REQUEST:**

Provide a brief explanation about why the cost and tax estimates changed from the initial application to the supplemental information filing.

**RESPONSE:** When the initial filling occurred in 2016, the proposed routes were less than 30% designed. At the time of the supplemental application, the designs were further advanced, but were still in a preliminary state. The cost estimates for the original and supplemental filings were based on many assumptions and unknowns and had an accuracy of +30% to -20%. The cost spread was, therefore, approximately \$40 million on the high end and approximately \$20 million on the low end. At that level of design, the accuracy of an estimate varies greatly and should only be used as a rough estimate. Additionally, material, labor, and land costs have escalated over the last two years, further contributing to the increase in cost estimates.

PERSON RESPONSIBLE: James Olberding



1019 APR 12 PM

PUC

RECEIVED-DOCKETING DIV

# BEFORE

# THE OHIO POWER SITING BOARD

In the Matter of the Application of Duke	:	
Energy Ohio, Inc., for a Certificate of	:	
Environmental Compatibility and Public	:	Case No. 16-0253-GA-BTX
Need for the C314V Central Corridor Pipeline	:	
Extension Project	:	

# AFFIDAVIT OF MATT SPIDARE, PRINCIPAL ENGINEER, METROPOLITAN SEWER DISTRICT OF GREATER CINCINNATI, IN SUPPORT OF TESTIMONY BY THE CITY OF READING, OHIO

State of Ohio	)	
	)	SS:
County of Hamilton	)	

Affiant, being first sworn and cautioned, states as follows:

 $\mathbf{\tilde{v}}$ My name is Matt Spidare and I am employed as a Principal Engineer by the 1. £ Metropolitan Sewer District of Greater Cincinnati.

2. Attached is a true and accurate copy of the 90% design set for CSO 513 Partial Sewer Separation. This project is located in the City of Reading. This project is in compliance with the Global Consent Decree with the US EPA and the Ohio EPA.

7. I have personal knowledge of the matters to which I have sworn herein.

Matt Spidare, Principal Engineer

Sworn to and subscribed in my presence this  $\frac{4}{M'}$  day of  $\frac{AM'}{2019}$ .



JOSEPH C. NEFF Attorney at Law Notary Public, State of Ohio My Commission Has No Expiration Date. Section 147.03 O.R.C.

NOT

PRELIMINARY SUBJECT TO REVISION	TILI	Z	EECEIVED-DOCKETING DIV NUC 2019 APR 12 PM 2: 4002 4005 40	A CHEETOR OF SEMERS
	10142200	PARATIC MADIC	DESCRIMAN TPICL, INVERTS       TPICL, INVERTS       STANDARD CASTINGS FOR MANHOLES       STANDARD CASTINGS FOR MANHOLES       STANDARD CASTINGS FOR MANHOLE BASE       STANDARD CONCETE FRAME       STANDARD CASTINGS SINGLE OUTER NILET       STANDARD CASTINGS SINGLE OUTER NILET       STANDARD CASTINGS SINGLE OUTER NILET PLAN GLI       STANDARD CASTINGS SINGLE OUTER NILET       STANDARD CASTINGS FOR MANHOLES       STANDARD CASTINGS FOR MANHOLES       STANDARD CASTINGS FOR MANHOLES       STANDARD CASTINGS FOR MANHOLES       MH - 1.2       MH - 1.2       STANDARD CASTINGS FOR MANHOLES       STANDARD CASTINGS FOR MANHOLES       STANDARD CASTINGS FOR MANHOLES       STANDARD CASTINGS FOR MANHOLES       STANDARD CASTINGS FOR MANHOLE ON CONDITS 42" AND OVER TYPE       STANDARD CASTINGS FOR MANHOLES	
DISTRICT	NO	З С П		BRAD S. CLARK, P.E. STANTEC CONSULTING SERVICES INC.
ATER CINCINNA TON COUNTY	DUECT	SEWEF	And	NUTLINAR ROD WAT DO SEED B42-6500 SEED
THE METROPO OF GRE/ HAMII	ED PRC	ARTIAL		(III)
	PROPOS	SO 513 P	LES. APPLORTANCES SHALL BE CONSTRUCTED IN DISTRICT OF GRATER CHORMATI (KSDGC) MALL BE TYPE "D" CNCETY WHERE NOTED. THE FERCAGE WARHOLES. THE CONTRACTORS SHALL BE FORDERS TO ANHOLES. THE CONTRACTORS SHALL FERCAGE WARHOLES. THE CONTRACTORS SHALL FERCAGE WARHOLES. THE CONTRACTORS SHALL FERCAGE WARHOLES. THE CONTRACTORS SHALL FENCINES AND CONFERS. AND CONFERS. ALL MAYE FESUENT AND LEDBLE. JOINTS. ALL MAYE FESUENT AND LEDBLE. JOINTS. ALL MAYE FESUENT AND LEDBLE. JOINTS. S. FOUNDATIONES DRAVES. AND OTHER CLEAN BERER STSTENS ARE PROVIDED FOR CONTT NORS. AND CURFENT HANLING COUNTY MITENTIF PUBLIC FOR SHALL BE RADORTILED TONS AND CURFENT HANLING COUNTY WITENDE OF THE COUNTY AND CONTROL MINIMAR FERENCIALE REPORTS. ELS. FLO CONSTRUCT ALL REPORTS WILE ELS. FLO CONSTRUCT ALL REPORTS WILE ELS. CONSTRUCT ALL REPORTS WILE ELS. CONSTRUCT ALL REPORTS WILE ELS. FLO CONSTRUCT ALL REPORTS WILE ELS. MAYENDER OF THE SCOUNDLE MINIMARE AND CONSTRUCT ALL REPORTS BARE IN LES. FLO CONSTRUCT ALL REPORTS BARE IN MITENDE OF THE SCOUNDLE AND AND ALL BE INCLUDEN IN THE PREDOKAL ELS. THE RACK OF THE SCOUNDLE AND AND ALL BE INCLUDEN IN THE PREDOKAL ELS. THE RACK OF THE SCOUNDLE AND AND ALL BE INCLUDEN IN THE PREDOKAL ELS. THE RACK OF THE SCOUNDLE AND AND ALL BE INCLUDEN IN THE PREDOKAL ELS. THE RACK OF THE SCOUNDLE AND AND ALL BE INCLUDEN IN THE PREDOKAL ELS. THE RACK OF THE SCOUNDLE AND AND ALL BE INCLUDEN IN THE PREDOKAL ELS. THE RACK OF THE SCOUNDLE AND AND ALL BE INCLUDEN IN THE PREDOKAL ALL BE INCLUDEN IN THE REPORTS ALL BE INCLUDEN IN THE PREDOKAL ALL BE INCLUDEN IN THE REPORTS ALL BE INCLUDENT IN THE REPORTS ALL BE INCLUDENT IN THE REPORTS ALL BE INCLUDENT IN THE REPORTS AL	e
		Ü	ALL EXERL. ALL SEMES, MANOLES, AND EXERL. ALL SEMES, MANOLES, AND EXELIDIOS AND SECUL PROVISIONS FECTORIANS FRECSA INANOLES AND CORPOSACE WITH WEIRPOULDES, AND EXELIDIOS AND SECUL PROVISIONS ESULE CONTINUES. THE CONTRACTOR PROVID ESULE CONTINUES. THE CONTRACTOR PROVID ESULE AND AND AND AND AND AND AND MELE CONTRACTOR SIDE ESULE AND	Con accurate from the from one of units from structure where were re-example one con VAD DRAWING NAME D0407C DD1 CVR DW



TERIAL ALTERNATIVES, OPEN CUT INSTALLATION	TALLATION BEDDING DIAMETER/MAX COVER	5TM D2321 II 6".8".12".15"/ 14'	5TM D2321 II 18", 24"/ 14"	51W 02321 II 24",30",36",42",48",54",14"	5M D2321 II 18".24".30"/14"	5TM D2321 II 12".15".18"24".30"/14'	5TM 02321 II 30°.36°.42°48°/14'	C12 CLASS C ACC NO 49032 CLASS III 18: 24: 30'36'42'48'.54''76'										20									PHELIMINARY	SUBJECT TO REVISION	CS0 513	PARTIAL SEWER SEPARATION	GENERAL NOTES	CC. NO. X SHEET 3 OF 27
STANDARD GRAVITY SEWER PIPE MA	PIPE TYPE ALLOWABLE JOINTS INST	PVC SDR 35, ASTM D3034 FLEXHLE ELASTOMERIC AS SEALS, ASTM D3212 AS	PVC SOR 35. ASTM F679 FLEXBLE ELASTOMERIC AS SEALS. ASTM D3212 AS	'V'DON' PVC, ASTM F1803 FLEXBLE ELASTOMERIC AS	ULTRA-RIB' PVC. ASTM F794 FLEXBLE ELASTOMERIC AS	SANTITE HP POLYPROPYLENE FLEXBLE ELASTOMERIC AS HDPP ASTM F2736 SEALS, ASTM 03212 AS	SANTITE HP POLYPROPYLENE FLEXBLE ELASTOMERIC AS HDPP ASTM F2764 SEALS, ASTM 03212 AS	REINFORCED CONCRETE PIPE FLEXIBLE ELASTOMERIC ASTM (RCP), ASTM C76 0001 706.02 SEALS, ASTM C443 ASTM																					ED PROJECT NO. 10142200			Ā
C CONTACTED AT LLAST 48 HOURS (2	DPT IN SERVICE AT ALL TIMES	STRUCTOR ALL DAMAGES TO GAS FACULTES DUBNIC	DJUSTNENTS, WILL BE MADE BY DUKE ENERGY	LE ECCAVATIONS AS RECORDED TO 4 THE ZONE OF INPLUENCE (AS DETERMINED 204.)	ONSTRUCTION EQUIPMENT MAY CAUSE DUME ENERGYS GAS ENGINEEPING THE GAS FACUTIES FROM DAMAGE	D GAS FACUTIES UNTIL THE UTILITY HAS MAINTENANCE AND/OR ADJUSTMENTS	NG ANY DAMAGE TO DUME ENERGY GAS NGS AND MEAPPINGS ON STEEL GAS	T HAVE OCCURRED TO PLASTIC GAS EXPOSED OR INTERFERED WITH BY THE	OLED LOW STRENGTH MATERIAL WLL	BE APPROVED BY DURE EVERTY'S ENTYMIG ALL PERTNENT BLASTNG EDFERT PROR TO ANY		WY PRIOR TO EXCAVATION IN WORLTY E PLAN LOCATION SHOWN) OR WEDN	1002 (AT LEAST 48 HOLD VIEW NOT 100 VIEW VIEW VIEW VIEW VIEW VIEW VIEW VIEW	NORMATION, CALL 287-3523.	, P.O. BOX 960, CNCNEAATI, CHO	AACCS TO ELECTRIC FACUTIES DURING	L IMLS. The Edstrig Electric Facultes	LE INSTALLATION ARE EXPOSED OR TOR, PROTECTION BY THE CONTRACTOR DATING OR SURROUNDING THERMAL	DIRECT BURED CARLE SYSTEMS ARE CONTRACTOR SHALL PROTECT THE CONTRACTOR SHALL PROTECT THE	S TO PROVIDE PERMANENT MEASURES TO ALL BE BASED ON CONDITIONS TO BE	RHEAD ELECTRIC FACUTIES ARE EXPOSED AND SALL PROTECT THEM FROM	ACTOR INSUME THE INTERACT OF THE ADDITIONAL TAKE ADDITIONAL THE ADDITIONAL THE ADDITIONAL THE MERSURES TO RESTORE SUPPORT. THE MERSURES TO BE DETERMINED BY THE UTLUTY.	CCS REQUIRED ADAUSTALIDITS, DE BY DUAC DAERGY AT THE	CCTRIC FACUTES UNTIL THE COMPANY HAS UISTMENTS AND/OR MAINTENANCE THAT	NITES CONTRACTOR SHALL AMEDIATELY IN THE COMPANY OFFICIAL (381-2000) OF DAMAGED ELECTRIC FACUTIES UNTL STE				PROPOS		SCALE: HORIZ, NONE	
PROCESSING THE UTLATIC COMPANIES MUST BE PROCESSING THE UTLATIC COMPANIES MUST BE WORKING DAYS) PROP TO EXCAVATION BY C	CONSTRUCTION NOTES DAVE ENDIGY'S CAS FACUTES ARE TO BE X	<ol> <li>THE CONTRACTOR SHALL BE RESPONSIBLE FOR OR AS A RESULT OF THE CONTRACTOR'S CONS</li> </ol>	REQUIRING REPAIRS, RELOCATIONS AND/OR AL AT THE CONTRACTOR'S EXPENSE.	<ol> <li>THE CONTRACTOR SHALL SHEET AND SHORE A CONTRAUGULY SUPPORT CAS FACILITIES WHI BY THE NATURAL ANCLE OF REPOSE OF THE S</li> </ol>	<ul> <li>CROSSING BURED GAS FACUTES WITH HEAVY C DAMAGE TO THE CAS FACUTES CONTACT THE DEPARTMENT FOR DEFAILS ON HOW TO PROTECT</li> </ul>	5. THE CONTRACTOR SHALL NOT BACKFUL EXPOSE INSPECTED ITS FACUTES AND PERFORMED ANY DATA TALE OF CONTRACTOR SHALL NOT BACKFULLE TALE TALE OF CONTRACTOR SHALL NOT BACKFULL DEPOSE INSPECTED ITS FACUTES AND PERFORMED ANY DATA TALE OF CONTRACTOR SHALL NOT BACKFULL DEPOSE	INLEAD BY BE RECORDED. 6. THE CONTRACTOR IS RESPONSIBLE FOR PREVENT FACUTES THIS INCLUDES PROTECTION OF COAT	MANNS IT ALSO INCLUDES ANY DAMARCE WINGH MA MANNS, SUCH AS CRUPS OR DOUGES 7 MILLY LATE INCLUDES ANY DAMARCE AND 7 MILLY LATE INCLUDES ANY DESCRIPTION OF DESCRIPTION OF	HE CONTRACTOR'S EXPENSE IN FROM THE CONTRACTOR OF THE CONTRACTOR'S EXPENSE IN FOUND THE CONTRACTOR SERVICE IN THE CONTRACTOR OF TO THE CONTRACTOR OF THE CON	VERVICES ATTE MONTO O CAS FACURES MUST VERVICED OF EXAMINET OF CAS FACURES MUST LAS EXONOLOGING EXAMINET A BLASTING PLAN, ID INFORMATION, MUST BE SUBMITTED IN WORK WORK	ELECTRIC UTILITY NOTES DAME DADISY	<ol> <li>DANGER – CONTRACTOR SIALL CONTACT THE COMP. OF ELECTRIC UNDERCARCING FACULTES (APPROXIMATI WORKING NEAR ONEDREAD ELECTRIC FACULTES</li> </ol>	(A) FOR FILD INSPECTOR TO LOCATE UNDERGROUND EI UTLITES FROTECTION SERVICE" 1-800-362-2 UNDERGROUND FROTECTION INC." 1-800-752-	ADVANCE, LUCLUONS FROMEN, SATI, SATI, & (8) FOR ACOMPAAL UNCERCOUND ELECTRIC RECORD I	TO CENTRAL ACCOUNTING MARKETING SECTION	2 CONTRACTOR SMALL BE RESPONSIBLE FOR ALL DAY	<ul> <li>BLECTRIC FACURES TO BE KEPT IN SHAWKI, AT AL CONTRACTOR SHALL BE RESPONSIBLE FOR SUPPOR APTECTED BY THE PROPOSED CONSTRUCTION.</li> </ul>	<ul> <li>MAERE HIGH PRESUME ON FULLD PRE TYPE CAB OPHERMIC NUERFEED WITH BY THE CANTRAL MALL BE REQUIRED AGAINST DAMAGE TO THE O</li> </ul>	SAND ENVILOPE (II) WHEE CONCRETE ENCAGED CONDUT SYSTEMS OF EXPOSED OR OTHERWSE INTEREED WITH TH	SALL TAK RUCKAR APPROPRIAT STOLE SALL TAK RUCKAR APPROPRIAT STOL RESTORE SUPPORT THE METHODS USED SH DETERMINED BY THE UTILITY.	(C) MERE POLES OF ANCHORS THAT SUPPORT OVE OR OTHERWIS INTEREED WITH THE CONT	DAMAGE AND PROVIDE TRANSPORATY SUPPORATY SYSTEM AS SOON AS FASSBLE. THE CONTIN APPROPRIATE STEPS TO PROVIDE PERMANNEL	(0) ALL DAMAGE TO ELECTRIC FACUTIES AND SERV RELOCATIONS AND/OF REPAIRS WILL BE UN CONTRACTOR'S COST.	5 CONTRACTOR SHALL HOT BACKFILL ENPOSED ELL INSPECTUD ITS FACULTY OR PERCENAED ANY AD MAY BE REQUIRED.	NOTE SHOULD CONTRACTOR DAMAGE ELECTRIC FAC NOTEY TRE ELECTRIC STANDEL GEST, TREOLO CONTRACTOR SHALL XEEP CARTYONE CLARK COURANY FERSIONEL ARRIVE AT THE WORK				AN SEWER DISTRICT	25 CINCINNATI COUNTY, OHIO SUTTAS		DRAWING SEF ACC NO X
Dependence way, 1000 6551 Stratt, percentur, enu store aut. suttants zeness suut ec constructo ander he lesterino of he sones care researce and sones to tockwitch er	I APPROPRIATE UTULY COMPANIES SAULT DE NOTIERED AT LEAST 44 HOLPES PROPRING DECAMAGE DROIND FOR THE PARPOSE OF VERTILIA REPORTION. THE EXACT DECAMAGE DROIND FOR THE PARPOSE OF VERTILIA REPORTION. THE EXACT DECAMAGE DROIND FOR THE PARPOSE OF VERTILIAR REPORTION. THE EXACT DECAMAGE DROIND FOR THE PARPOSE OF VERTILIAR REPORTION. THE EXACT DECAMAGE DROIND FOR THE PARPOSE OF VERTILIAR REPORTION. THE EXACT DECAMAGE DROIND FOR THE PARPOSE OF VERTILIAR REPORTION. THE EXACT DECAMAGE DROIND FOR THE PARPOSE OF VERTILIAR REPORTION. THE EXACT DECAMAGE DROIND FOR THE PARPOSE OF VERTILIAR REPORTION. THE EXACT DECAMAGE DROIND FOR THE PARPOSE OF VERTILIAR REPORTION. THE EXACT DECAMAGE DROIND FOR THE PARPOSE OF VERTILIAR REPORTION. THE EXACT DECAMAGE DROIND FOR THE PARPOSE OF VERTILIAR REPORTION. THE EXACT DECAMAGE DROIND FOR THE PARPOSE OF VERTILIAR REPORTION. THE EXACT DECAMAGE DROIND FOR THE PARPOSE OF VERTILIAR REPORTION. THE EXACT DECAMAGE DROIND FOR THE PARPOSE OF VERTILIAR REPORTION. THE EXACT DECAMAGE DROIND FOR THE PARPOSE OF VERTILIAR REPORTION. THE EXACT DECAMAGE DROIND FOR THE PARPOSE OF VERTILIAR REPORTION. THE EXACT DECAMAGE DROIND FOR THE PARPOSE OF VERTILIAR REPORTION. THE EXACT DECAMAGE DROIND FOR THE PARPOSE OF VERTILIAR REPORTION FOR THE EXACT DECAMAGE DROIND FOR THE PARPOSE OF VERTILIAR REPORTION FOR THE EXACT DECAMAGE DROIND FOR THE PARPOSE OF VERTILIAR REPORTION FOR THE PARPOSE OF VERTILIAR REPORTION FOR THE EXACT DECAMAGE DROIND FOR THE PARPOSE OF VERTILIAR REPORTION FOR THE EXACT PARPOSE OF VERTILIAR REPORTION FOR THE EXACT PARPOSE OF VERTILIAR REPORTION FOR THE P	LOCATION OF UNDERFORMOND UTURES LOCATION OF UNDERFORMOND UTURES LOCATION OF UNDERFORMED SMULL MAY STANDARD LOS AND FRANCES 2. THE CONTRACTOR SMULL MAY STANDARD LOS AND FRANCES 3. THE CONTRACTOR SMULL MAY STANDARD FRANCTOR SMULL MAY STANDARD FRANCES 3. THE CONTRACTOR SMULL	ACC IN ORDER WEEK NOTED. THE FAME SHALL OF ON ANOINS, LONG A PLACE RELOCTIONS AND/OF AL THE TPP AUMNEEK STEMP REFORM 3/Y STEMLES STELL ONOL ANOINSS, LONG AL DOCUME TO EXTEMD THROUGH ANY GAUGE RNDS.	1. COMPLETOR LICENSE – ALL WORL OWER ON SAMETARY AND/OR COMBINED STARTS WHEN 3. THE CONTRACTOR AND MELL SECTION OF DECK. AND THE CONTRACTOR SAMEDA STARTS WHEN ALL AND CONTRACTOR SAMEDA STARTS AND ALL WARDOW STARTS THERE AND THE CONTRACTOR SAMEDA STARTS AND ALL AND CONTRACTOR AND ALL AND CONTRACTOR SAMEDA STARTS AND ALL AND CONTRACTOR AND CONTRACTOR SAMEDA STARTS AND ALL AND CONTRACTOR AND ALL AND ALL AND CONTRACTOR AND ALL AND CONTRACTOR AND ALL A	DE ARTINGET AND IRONGED. T RE ANALTER SERVE ANALONGED IN RAASS REEA, THE RAW ELFANTON DATA REEA VANADES CONSTRUCTED IN RAASS REEA, THE RIM ELFANTON DATA REEA VANADES CONSTRUCTED IN RAASS REEA, THE RIM ELFANTON DATA REEA VANADES CONSTRUCTED IN RAASS REEA, THE RIM ELFANTON DATA REEA VANADES CONSTRUCTED IN RAASS REEA, THE RIM ELFANTON DATA REEA VANADES CONSTRUCTED IN RAASS REEA, THE RIM ELFANTON DATA REEA VANADES CONSTRUCTED IN RAASS REEA, THE RIM ELFANTON DATA REEA VANADES CONSTRUCTED IN RAASS REEA, THE RIM ELFANTON DATA REEA VANADES CONSTRUCTED IN RAASS REEA, THE RIM ELFANTON DATA REEA VANADES CONSTRUCTED IN RAASS REEA, THE RIM ELFANTON DATA REEA VANADES CONSTRUCTED IN RAASS REEA, THE RIM ELFANTON DATA REEA VANADES CONSTRUCTED IN RAASS REEA, THE RIM ELFANTON DATA REEA VANADES CONSTRUCTED IN RAASS REEA, THE RIM ELFANTON DATA REEA VANADES CONSTRUCTED IN RAASS REEA, THE RIM REFERENCE TO THE RAAS REAVEN TO THE RAAVENT THE DATA REEA VANADES CONSTRUCTED IN RAASS REEA TO THE RAAVENT THE RAAVE	ANY PROVIDE A TRANSMENT AND A CAROUN SOFT. CONTRACTOR SHILL NOT BLOCKLIDE STALL NOT BLOCKLIDED ON THE CONTRACTOR SHILL NOT SHILL	TIGNED FOR LOOKAN ETING CANNOT RET ORGANIZATIONS SET INVENTION RE RECOMMENT TO FAML GARD ME UNANGLICKTONS AND RELATIVATIONS SAULT TO FAML GARD ME OPENINGS, SUCH AS FOR FORD FORM ALL UTTINGS SAULT EN PROJECTION RELATIVATION FOR AND RELATIVATIONS SAULT ET AN ENLIDES FOR FORMATION OF CONTRACTIVES FOR FORMATION RELATIVATION RELATIVATION FOR AND RELATIVATIONS SAULT ET AN ENLIDES FORMATION OF CONTRACTIVES FOR FORMATION OF CONTRACTIVES FOR FORMATION FOR AND RELATIVATION RELATIVATION FOR AND RELATIVATIVATION FOR AND RELATIVATIVATION FOR AND RELATIVATIVATIVATIVATIVATIVATIVATIVATIVATIV	In Findo the cert shut if have 10 spatty and 11 fit have 10 and 12 an	EXCOMMENT WITH CERT A VALUE TO ROCE WRITE FOR 19 PULL INCOMPLEX CONTRACT CONTRACT AND CONTRACT CONTRACT AND CONTRACT AN	CLOLATE THEA VELOCIATION OF ADDRESS IN THE OFFICIAN ALL MARKEN. THE ADDRESS INTE ADDRESS INTERVISE OF ADDRESS AND ADDRESS AND ADDRESS	I RELY WERT SERVICES AND REPORTED AND A DEVICE AND A DEVICE AND A DEVICE A DELOTED CONTROL OF A DEVICE A DEVICE AND A DEVICE A DEVICE A DEVICE AND A DEVICE A DEVICE A DEVICE AND A DEVICE A DEVICE A DEVICE A DEVICE AND A DEVICE A D	IN CONTRACT PROVING AN INCLUSION AND INCLUDENT INCLUDENT INCLUDENT IN AND INCLUDENT IN	TUDORARY DROBAL AND RELOARS PER SECTION OF 14 OS SALL EC (1) FOR FELD INSECTION TO LOCATE UNDERRORADE E (A) FOR FELD INSECTION TO CONCEL UNDERRORADE E (A) FOR FELD INSECTION AND LOCATE UNDERRORADE E (A) FOR FELD INSECTION FOR FELD INSECTION E (A) FOR FELD INSECTION AND LOCATE UNDERRORADE E (A) FOR FELD INSECTION E (A) FOR FE FOR FELD INSECTION E (A) FOR FELD I	1. All report The device Construction And industes Source and Annual Annual Instrument from Source Source and Annual Instrument of Inservice Mark (2017) and a minimum source source and annual source source and annual source source and annual annual source source and annual annual source source and annual source source annual annual source source annual annual source source annual source annual source source source annual source annual source source source annual source source annual source source source annual source source source annual source so	MARKEN FAMILIE DOER COMPONENT TO RESOLVE ANY UNDER CONTRACT MARKEN SCIENCE ANY UNDER TANADATI SALE E USD. MEDICINE MARKEN SCIENCE DOSOPED AUGES FROM TO WORK COMPONENT AUGUST FOR SCIENCE SCIENCE SCIENCE ACCOUNTS AUGUST FOR AUGUS	3. ALL WAR DONE ON STORMARTER ANALYSISCINE WOLF BE DONE BY A CONTRACTION 2. CONTRACTION SHALL DRIVEN AND ANALYSISCINE UNDER A DONE DATE OF ALL DRIVENCIAL STREPS ADAPTS PROPERLY LOTARIZED AND BOUND INFORMATION 2. CONTRACTION SHALL DRIVENCIAL STREPS ADAPTS PROPERLY LOTARIZED AND BOUND INFORMATION 2. CONTRACTION SHALL DRIVENCIAL STREPS ADAPTS PROPERLY LOTARIZED AND BOUND INFORMATION 2. CONTRACTION SHALL DRIVENCIAL STREPS ADAPTS PROPERLY LOTARIZED AND BOUND INFORMATION 2. CONTRACTION SHALL DRIVENCIAL STREPS ADAPTS PROPERLY LOTARIZED AND BOUND INFORMATION 2. CONTRACTION 2. CONTRACTION DRIVENCIAL STREPS ADAPTS PROPERLY LOTARIZED AND BOUND INFORMATION 2. CONTRACTION DRIVENCIAL STREPS ADAPTS PROPERLY LOTARIZED AND BOUND INFORMATION 2. CONTRACTION 2. CONTRACTION DRIVENCIAL STREPS ADAPTS PROPERLY LOTARIZED AND BOUND INFORMATION 2. CONTRACTION DRIVENCIAL STREPS ADAPTS PROPERLY LOTARIZED AND BOUND INFORMATION 2. CONTRACTION 2. CONTRACTION DRIVENCIAL STREPS ADAPTS PROPERLY PROPERLY DRIVENCIAL STREPS ADAPTS PROPERLY PROPERLY DRIVENCIAL STREPS ADAPTS PROPERLY	<ul> <li>NEAR THE CONNERTING OF MASS ON ALL STORMATTER INTRACTING. THE CONNERTING OF MASS ON ALL STORMATTER INTERCENTING. THE CONNERTING OF THE WASS ON OF THE OTHER STORMATTER INTER THE REPORTS CONSTRUCTION.</li> </ul>	put, and count TEASE (city) the streament available stream with use there are used and count TEASE (city) the streament available streament availab streament available streament avail	A start and a procer to enter the wood: To start that A cold hadres a weak and the start and a start that A cold hadres in a start and a start and a start and a start and a valuated start and a start and and and a start and a start and and a start and a start and and a start and a start and a start and a start and a start and a start and a start and a start and	PAUL CLUER ADDRESS AND REPAIRING TO THE CAREEN OF THE PRODUCTION ADDRESS ADDRE	NAFITAL F FARMALLY INCLUDE MARK AND	v. Kosti ruskos si-undi Freider Kuwiski owa k. ACCOBACK R. IZA KUWISKI S. ALLANIC S. ALLANIC S. AND KARA S. AND K. ALLANIC S. AND K. ALLANIC S. ALLANIC	исконски редикатов оббл они мискит 7 горпа не дочжко по тобликов. На са (1) ди дидиде то посте насител дие дин илите соязкова постепет водех или в макиа рожетер об в 10 ди дидиде то посте насител дие дин посте округова насически держители посте водете всего водете само со со со постелетов со со т	CODEST OF THE ANALY MUTER, METRIA THE REQUERENCE OF ALMAL, NO 44 OF CODEST SCAL RELEASE OF REAL AREA MAIN ALMALLERACE MUTERAL METRIC THE REQUERENCES OF 70201 OF THE COOT DAS MAIN THE REQUERENCES OF 70201 OF THE COOT DAS	AS FACUTY NOTES INTERVISE AND ADDRESS FACUTY NOTES AND CONTRICTS BANK CITERE MAY CITERE	C. D. BARTONE (20 APRIL) D. D. D. R. DOWN WAY STATE D. D. D	or concervance reprovinces to covery with statistican rescutations. Description cover under the process surface and securities week average- command or superstance and stacking	2 LON FOOLDINK OR LIVETLIN BECOM REARYINGY OF (15) 381-300 4 MET DR. SERVEZ BEE RELATED MY MANNIN DL. (-4), OL CONS	THE METROOLIAN SEMISE DISTRICT	Stantec HARLTRA CONTY, OHO MANUTAN AND AND AND AND AND AND AND AND AND A		FOR FASCUENT DRAWING SEF ACC NO X

	RTHING EASTING	4600.69 1420444.84	4587.75 1420461.27	4567.67 1420427.83	10.0269141 10.6000	4033.30 1421008.65	197.83 1420294.22	++22.51 1+20245.32	4192.85 1420114.55	+214.93 1+20210 75	4191.13 1420197.25	+165 45 1+20160.67	4061.45 1420608.75 4008.97 1420628.78	4071.60 1420637.06	3908.10 1420563.15	9909.76 1420606.95	1.20992.1 420992.14 1420992.14 1420924.1420904.14	1420574.76	199.14 1420198.12	109.42 1420436.82	4081.19 1420665.51	1420977.33	9919.35 1420597.22	605.28 1421465.92 547.00 1421460.75	545.39 1421485.90	5286.61 1421336.85	462.90 1420665.57	14201.99 1420717.50	940.94 1420569.67	675.25 1420533.42 837.67 1420572.51	1420363.39	584.40 1420434.09	491.66 1420400.03	1420369:31 1420369:53	412.66 1420266.47	178.27 1420139.45	892.09 1419973.76 842.38 1419957.03	5766.11 1419914.31	709.79 1419893.77						INARY	REVISION		ARATION		P TARIF
Citation of	DOT/MSD ACC. NO. NO	CB 11 45	49012 45	49012 45	21069	49017 45	\$	+301+ +5	43014 45	49012 45	49012 45	2	49012 45	49012 45	49012 45	49012 45	24 \$1055 57 51051	49005 45	120282 45	120282 45	120262 45	120282 45	120282 45	Cacroct	120282 454	120282 45	120282 45	120262 45	120282 454	120282 454	120282 45-	120282 454	120282 45	CB 1.1	120282 45-	120282 454	120282 450	120282 45	120282 451						RELIM	SUBJECT TO	100 E12	EWER SEP		NTES & ST
	STRUCTURE 0001/MSD ACC. NO. 0	CB 1.1	1064	1064	4901	49016		19061	49013	49011	1001		1001	11069	49011	1001	19041	+9037	1006+	49001	49001	1006+	49041	01000 C 1 00000	49001	49001	49001	49001	MH 1.2/49040	10001	MH 1.2/49040	1006	10064	C8 1.1	10064	49001	49001	49001	49004						۵.			PARTIAL SI		T CENI NO
	TYPE	CATCHBASIN (2-2)	ATCHBASH (SHOLE OUTER MLET)	ATCHBASN (SNOLE CUTTOR MLET)	ATCHBASH (SNOLE QUTTER MLET) EV PO (BRUDON BOTTOM)	CATCHEASA (COMB INLET)	C COMB. INLET (REWOOEL BOTTOM)	CATCHBASIN (COMB. INLET MH)	ATCHBASIN (DOUBLE OUTTER INLET)	ATOHBASA (SNOL OUTER MLT)	ATCH BASIN (SINCLE CUTTER INLET)	K. COMB INLET (REMODEL BOTTOM)	ATORIASIN (SNOLE OUTIDE INLT)	ATCHBASIN (SINCLE CUTTER INLET)	ATCHBASN (SNOLE CUTTER MLET)	ATCHBASIN (SINCLE CUTTER INLET)	CATCHBASIN (COMBINET MH)	* DA SAN SENER NH	4' DAA STU SCHER WH	4' DIA. STU SCHOR WH	4' DIA STU SCHER WH	4' DIA. STM SCHOR MH	4' DIA. STU SENER WH	EX WINGWALL (REMODEL)	S' DIA. STU SCHER WH	S' DIA STU SENDR WH	5' DIA STU SEMER UH	5' DIA. STU SENER WH	B' DIA. STU SEMER WH	S' DIA STU SCHOR UH	5' DIA STU SEMER MH	A' DIA. STU SCHOR WH	4' DIA STU SEMER UH	CATCHBASN (2-2)	5' DAL STU SENER MH	HIN BOW SENS IN STA	4' DIA. STM SEMER MH	HIN BOW 35 MIS VIO .+	+, DIV STN SEMICH MH								200	0		
	MANHOLE NO.	321	126	120	181	101	3	902	903 CA	1005 C	1006 CA	1007 Ex	1006	1010	1011 C	1012 CA	1013	4326011A	5	8	3 3	8	8	E 2	2	¥.	8 8	RB	68	R10	R12	R12A	R120	R120	814 814	RIS	817	618	R20								10142			D
	IC EASTING	1418222.49	1418390.43	7 1418381.39	1418430.50	1177 COLO 1	1412655.68	1418909.90	5 1419062.50	1419387.50	6 1419444,13	0 1419474.86	2 1419705.73	2 1419885.98	8 1419832.98	6 1419830.80	2 1419719.47	7 1418699.98	5 1419435.22	8 1419296.40	4 1419508.94	0 1419315.98	0 1419241.67	6 1419170.58	1419436.95																						IFCT NO			
	C. NO. NORTHIN	454827.3	454718.2	454696.1	454695.6	1 01000	1 20112	454508.5	454614.2	454466.3	454447.4	454474.2	454428.9	+54656.5	454528.4	454498.0	454531.0	454576.1	454428.4	454156.9	454824.6	454314.1	454185.8	454053.4	454784.7																						D PRO.	-		
	CASTING 0001/MSD AC		120282	120282	120252	CB0001	40001	120282	49007	120282	120282	120282	120262	120282	120282	C8 11	5 5	CB 175	C8 11	C8 11	C8 1.2	120282	120282	120282	120282																						ROPOSE			DRIZ. NONE
AVE. SIN	STRUCTURE T/MSD ACC. NO.	1.mH	WH 1 2/49040	*9001	WH 1 2/49040	12/40040	UH 1 2 / 45040	MH 12/49040	WH 1.2/49040	MH 12/49040	1006*	1006*	MH 1.2	49001	1006+	09.11	11 80	CR 1/2	08 11	08 1.1	C8 1.2	1006*	1006+	+3001	1006+																									SCALF- HC
1000	е 000	IT HEADWALL	SEMER WH	SCHOR WH	SEWER WH	SEWER MH	SUME AN	SCHER MH	STWCK MIH	SEWER MIH	SEWER NOT	SEWER MH	SEWER WH	SEMER NOT	SEMER MH	2N 2-2	N (RE-USE)	SN 2-4	N 2-2	W 2-2	2N 2-3 crues tot	SENCE NH	SENER WH	SEMER MH	SEMER WH																									
IC3I	E III	POH TINI .09	T DA STU	4' CIA. STU	T DIA STU	6 DA STU	0 00 ST	e' DA STU	e' DIA STU	T DIA. STU	S' DIA STU	S' DIA STU	6' DIA. STU	A' DIA STU	* DIA STU	CATCHBAS	EX CATCHBAS	CATCHBAS	CATCHBAS	CATCHBAS	CATCHBAS	AL DIA STU	4' DIA. STM	4. DIA. STM	AL DIA STU																						-			
	MANHOL NO.	-	5	4	•		5			=	21	1	*	2 2	2	150	8	16	324	330	6016	82	83	8																							TO DISTRICT	CINNATI 7, OHO	,	
	E VEHICLE IS WORK IS DONE	DR THE SAFETY OF	LET OF THE MICES OF AN	D. THE POLICE	NIRACION AND THE	HE START OF WORK						8	ED, NOTIFY THE	ICTION LISTED ON	ATH LEGIBLE DATES	VAL FROM THE CITY		THE CENERAL		OTES MUST BE	THE CITY OF	WORKS WILL	ONTACT																								THE NEWSDOW	OF CREATER C	OUTIONOLITIK DUCTO ATWAR OTWARD	CINCINNATI
OF THE PROVECT.	RED BY THE CITY WHEN	EDESTRIAN CONTROL. FO	AND PAY FOR THE SAFE	AARKED CAR AS NEEDED	EMPLOYED BY THE CON 7 THEIR ACTIONS	WING DAVE DRIDE TO TH						DUIRED BY THE ENGINEE	T PARKING ARE INSTALL	RE THE PARKING RESTRIC	ED TEMPOHARY SIGNS W	OBTAIN PRICE APPROV	OR NIGHTS.	ERE TO THE SAME MAIN SNERAL CONTRACTOR 1	ALL SUBCONTRACTORS	TENANCE OF TRAFFIC NO	IC OR PAVING NOTIFY T	THE CHIEF OF PUBLIC	LANE CLOSURES. THE CO		1	V2-1680 (DIRECT UNE): V3-3725 (MAIN OFFICE)																						tantec	487 LEBUNON ROAD WONNUT, 0460 45239	13) 842-8200
THE DURATION	WLL BE REQUI	INTERSECTIONS TRAFFIC AND P	BUC, PEDESTRI RRANCEMENTS	OFFICER AND A	ISIDERED TO BE	MALO ELLE MOR	CLOSURE	DISTRICT	ISES	S S S S S S S S S S S S S S S S S S S	NLS PERTY OWNERS	NTACTS AS REC	NS TO RESTRIC	4 HOURS BEFOR	ROPERLY WORD!	IS REQUIRED TO	I THE WEEKEND	ORS MUST ADH	ESPONSIBLE FOR	ON THESE MAIN	TO ANY CONDIN	PUBLIC WORKS	/OR PLANNED	S FOLLOWS	WORKS.	RTNEY: 513-84 513-73																						0	5	3
MAGED DURING	E USE OF A POI	HIN SIGNAUZED	E TRAVELING PU	F-DUTY POLICE	FICER(S) IS CON NTRACTOR IS RE	TEV THE FOLLO	D ANY STREET	LOCAL POUCE	LOCAL FIREHOU	LOCAL SCHOOL	LOCAL HOSPITA ABUTING PROF	ADDITIONAL CO	TEMPORARY SIG	CAL POLICE AVE	E SIGNS USE PE	E CONTRACTOR 1	R ANY WORK ON	ALE SUBCONTRACT	NTRACTOR IS RE	Y VARIANCE FRO	C WEEK DOIDD	ADING CHIEF OF	EA EVENTS AND	ORMAIION IS AS	T OF READING	DARRELL COU																								
INES DA	E H	# ¥	H	MES. OF	THS. OF CO	NOE	AN AN	10	•	•••	. NHEN	•	<u>ب</u>	NUE SIG	H N	N N	W FO	UN AL	SOL CO	AN	St St	RE	AR	RARY IN	55 z	NG		UNC	0č				MCES.				7F BE	VATED		DR TO CT NNS TO DPE	350	NG	FFIC USE		LE ON NTROL D TO NG OF	D BE		SCRIP TION:		
TRAFFIC AT ALL	T (MSD) AND THE CONSTRUCTION.	ABLE DRAWINGS	TRAFFIC CONTROL	G. CHANNELIZING	ACINGS, LANE WID	VE ALL MAINTEN	CONTROL DEVIC	IN PLACE PRIOR		OF THE EXISTIN	CALENDAR DAY.	31+00 AND STA		L BE MAINTAINED RIESENBERG AVE		ID CORMAN LANE	STA, AND RAINBO	TA TA COMPANY	M TRAFFIC CONTR		RK WITH THE LEA	CLOSURES AND	HICH NO WORK I	DETERMINED BY	WITH THE WORK	ALL TIMES DURI	TEMPORARY	FROM THE ABUTT	HED, AND HE SATISFACTION		IN ACCORDANCE CONSTRUCTION &	CINCINNATI	FIC CONTROL DE	ND INCIDENTALS.	CNI, SMALL DC	E LEFT OPEN DED BECAUSE OF	N TRENCHES SHA	IPMENT, OR EXCA	CLEAR ZONE	T ONE WEEK PRICHAT WOULD IMPA ACCEPTABLE MEA UCTION DUE TO ND UNDERCROUN	ANE CLOSURES	EVICES. CHANNELIZ	NY LANE TO TRA GRABBER CONES	APERS FOR LANE WE ONLY, SHORT	WLL BE AVAILAB NCY TRAFFIC CO HALL BE PROMDEL AT THE BEGINNI	OND TO POLICE VOTIFICATION, ANI CONTROL ISSUES	REVISIONS	8		
R MAINTAINING	SEWER DISTRICT	L INCLUDE SCAL	RIVEWAYS, ALL	NG AND WORDIN	RATES AND SPI	IST BOTH APPRO	PORARY TRAFFIC	EVICES MUST BE		IN EACH DIREC	DT TO EXCEED 1	R BETWEEN STA.		D AVENUE, AND		AHL TERRACE AN	WAY, BREEZY W	and the second	NUAL OF UNIFOR	IN THE REPLACE	E REQUIRED WO	ATION OF LANE	E PROJECT IN W	LEVEL OF UTUIZ	COMMENSURATE	CAL TRAFFIC AT	OPERTY OWNERS	ACCESS TO AND	VIRACTOR, TO TA		MCES SHALL BE DN (0007) 2016	E 2016 CITY OF	OF CINCINNATI	T, MATERIALS, A	TENS.	EMENT SHALL B	R REASON, OPE	WATERIALS, EOU	T PAVEMENT OR	INTERSECTION T INTERSECTION T TION ARRANGE DURING CONSTR OP DETECTORS A	USED FOR ALL L	FFIC CONTROL D	FOR CLOSING A MS OR 36 INCH	R CONES FOR TU	E PERSON MHO POND TO EMERGE SAID PERSON SH POUCE AGENCIES	E ABLE TO RESP ONE HOUR OF 1 PORARY TRAFFIC OTHICATION. THIS		ATE:		
ESPONSIBLE FO	METROPOLITAN METROPOLITAN DAYS PRIOR TO	FIC PLAN SHAL	ADWAYS AND D	JCNMENT, NOR	LUDING TAPER	Y AND MSD MU	N OF ANY TEM	TIC CONTROL DI	5	NE OF TRAFFIC	R A PERIOD NO	STORM SEWER		NE OF TWO-WI TREET, BERNARD		NTAINED ON G	IE, EAGLEVIEW		THE OHIO MAN	UP PEUESIKIAN	T PERFORM TH	IGTH AND DUR	CMENTS OF TH	REASONABLE ERMITTED. THE	ICES SHALL BE	T WAINTAIN LO	ANNER CAUSIN	E VEHICULAR A	ED BY THE CON		C CONTROL DE TRANSPORTATIC	OFICATIONS, THE	CMS, THE CITY	OR, EQUIPMEN	DUS CONTRACT	E EXISTING PAV	R FOR ANOTHE RECTION OF TH	T NOT STORE	EXISTING STREE	LL CONTACT TH GAHL TERRACE SIGNAL OPERA IAL OPERATION	TS SHALL BE L	EMPORARY TRA	ELIZING DEVICE 36 INCH DRUI	DINCH GRABBE DNES MAY BE L	LL IDENTIFY ON BASIS TO RESP MBER OF THE INTERESTED F	PILL B ONE HALF OF DIX ANY TEM		BY: D		
TRACTOR IS R	CONSTRUCTION PLAN TO THE	VANCE OF TRAF	INT OF ALL ROM	AND THEIR AL	PLACEMENT INC	ETC. THE CITY	FFIC PLANS AN	PORARY TRAFF	CONSTRUCTS	NED AT ALL TH	NT. EXCEPT FO	AM END OF THE		ES ON WEST ST	TIMES	SHALL BE MAI	E. CORMAN LAN		ORMANCE WITH	CTOR.	NTRACTOR SHAL	NENCE AND M	TION SHALL BE	ATED WITHIN A	CONTROL DEW SS.	VTRACTOR SHAL	UCTION IN A M	ARY TO PROVID	UENTLY REMOVE	GINEER.	PARTMENT OF	L SPECIFICATIC	MENT TO ODOT OK, AND THE C	L FOR ALL LAB	O IN THE VARIO	HT ADDITIONAL	ED AT THE DIS	TRACTOR SHAL	MTHIN THE	TRACTOR SHA IX NEAR THE TING TRAFFIC PROPER SIGN TED IMPACT TU	ARROW PANE	ANELS IN COM	NDARD CHANN ERLY WEIGHTED	ES 28 INCH CC	NTRACTOR SHA OUR PER DAY THE PHONE NU	COLECT. THIS PE T STAFF WITHIN C CORRECT AND ED WITHIN FOUR	NG : BSC	CMF	U.C.M	
8.	<u>o</u> ~ -	C 922 C	1.100	1000	14435				-	- 19		10. mm	100	32	-	· 2 •	(0)			<i>n</i> ₹	õ	55	ЦŲ	百六	ųω	ð	22	2.0	80	ž ·	ö۳	N N	98	Z		60	607	No.	N I	NESSE	NG	20	1 de	Harv	01.3	$\mathbf{u} \cup \mathbf{r} - \mathbf{r}$		-	in the second se	

ALE PROM RELAK RELAK











PLOTED BY CHIMER 2019 - 02:03 PW DATE MON 5: 2019 - 02:03 PW PATE L (MCAGARON-1/324/CIVE/173408407/CIVE/DRAWIGS/SHEET\_TEES/084037C\_003\_DTLA 101000-105-1010-1010



000	069	005	370	- 560	PREL IMINARY	SUBJECT TO REVISION	+50 11+00 11+50	-Vd-						PARTIAL SEWER SEPARATION READING ROAD	PLAN & PROFILE
4 TYPE "B", CLASS II BEDOING (P.V.C.)* 500.00' @ 0.20%				5vC ,+ x3		ES	10+00 10	City 2007724 +946	Crimer No. 200000 Crimer No. 2000000 Crimer No. 200000 Crimer No. 20000 Crimer No. 200000 Crimer No. 200000 Crimer No. 200000 Crimer No. 200000 Crimer No. 20000 Crimer No. 20000 Crimer No. 200000 Crimer No. 20000 Crimer No. 200000 Crimer No. 20000000 Crimer No. 200000 Crimer No. 2000000 Crimer No. 2000000 Crimer No. 200000 Crimer No. 200000 Crimer No. 200000 Crimer No. 2				= inter =	CT NO. 10142200	
PROP. 42" STM						*SEE SHEET 3 FOR PIPE ALTERNATIV	9+00 8+50	1 Vd.					PROFERES SERVICED PROFERES SERVICED D.C. SANTARY IN RELAY AND D.C. SANTA	PROPOSED PROJEC	SUME: 1-10
		<			илл = 266 53 50 52 882	HM 909 1A = 574 24 909 42"	00 립/AE 8+50	P/L =	* 1: 0: Mile + 33024005 (AATE-53:4 6) (AATE-53:4		EADING PID.		Gar 2000/244 (644	A SPARA PSTRICT A SPARA PSTRICT A SPARA PSTRICT A SPARA A SPARA PSTRICT A SPAR	2
5 (P.V.C.)•		Ex CROMO					7+50 8+	24 200724 844	7				STA = 8+20.24 5 A = 0.16'40' LT Δ = 0.16'40' LT ++++ πελακε π0	Provide the second seco	
ROP. 42° STM TYPE "B", CLASS II BEDDIN 450.00' @ 0.20%				131 ×1			6+50 7+00	04 0900000 00 000000 0000 0000000000000	11 000 - 0 AN 5 16 000 - 0 AN 5 16 000 - 0 AN 30 16 0000000 - 0 AN 30 16 0000000 - 0 AN 30 10 000000 - 0 AN 30 10 00000 - 0 AN 30 10 0 AN 30				Or SHOULD 4444	Oracoentrat.	
۵							6+00	√d						BY: DATE REVISIONS	
			+++	5* 9 . + X3			50		1	1 A		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	915 600	BSC .	



2" STM TYPE "B", CLASS II BEDDING (P.V.C.)	300.00' @ 0.20%	090	(1)		- 560	045	PRELIMINARY	SUBJECT TO REVISION	50 17+00 17+50	and manage the	Cher Carlos Carl	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$				сек Н #RR 16+2023	29 LT 64	CSO 513 PARTIAL SEWER SEPARATION	READING ROAD PLAN & PROFILE	NO. X SHEET 11 OF 27 (888)
PROP. 4	•				240 * x3 2 q * 5 x3	28.29	INA = 2 8 +20 53 ₩88	вор. мн 17 = 16 17 = 42"	16+00 alwara 16+		Control 60 400 400 400 400 400 400 400 400 400	<sup>α</sup>				ASP ML-553, 133012001 MR NV 12"=513.70 56 MV 12"=573.10 56 MV 10"=574.13 57 A. =	Δ = 0.4 9441 REACHO RD	. 10142200	Į	ACC.
•(3		- dw							15+50	PO 9444 READING RD EX C No. 42012005 EX C No. 42012005 M. R. N. 742-578 85 M. R. N. 742-578 85						EX CB No. 430012002 EX CB No. 430012002 ME 127 RCP Nov-573.16 SW 127 RCP Nov-573.16		OSED PROJECT NO	-20'	
TYPE "8", CLASS II BEDDING (P.V.	300.00' @ 0.20%	EX 0400						et 3 for pipe alternatives.	+50 15+00	32 READNO RD 9448 READNO	0 0 0 0 0				-Va	1 002000 1 001200 1 0000 1 00000 1 0000 1 0000 1 0000 1 0000 1 0000 1 0	4 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	PROF	SCALE: HORIZ, 1	×
PR0P. 42* STM								•SEE SHE	14+00 14	04 CHONES STATE	000 1 PA			OP. 42. STM		EX SO No. CON CONTRACTOR CONT	Vd	METROPOUTAN SEMER DISTRICT OF GREATER CINCINIATI HAMILTON COUNTY, OHIO		EASEMENT DRAWING SEE ACC. NO.
-	-		-	3	131 X3	£2,53	107 = 5 127 +20:22 #66	ROP. 42" 74. = 13 19. 42" 80P. 42"	almea 13+50		ROP. MH #R6 T.A. = 13+20.23					2004 BATE 575 36 2.42 2.42 2.42 00/0650165 SEDAVED B	DNG PD P1 REAR VA	™	11667 LEIMANON ROMD CINCINNUNT, DHO 4529 (513) 842-8200	FOR
S II BEDDING (P.V.C.).	20%								13+50 13+00	9468 READING RD 9464 READING RD	CONC 04 Th wir No. 43201004 M. Mark 43201004 F. M. Mark 4320010 Conc par 5.4 Mov 12-930.540 Conc par Conc par					EX COMP NO 43301 NE 12" RCP NUM5 5W 12" RCP NUM5	9401 KEYDING KD	Сеньшон	>	-
PROP. 42" STM TYPE "B", CLAS.	500.00' @ 0.2								12+00 1	Q4	/ d			w-PROP. 42" STM (X.4. WIN T W T (X.0.01 V) T W T (X.001 V)	0.000 000 000 000 000 000 000 000 000 0		Vd Vd 6462 EFrome an	DATE: REMSIONS DES		7C_001_READPP1.DWG
600		580			560	540	019	2	<sup>520</sup> 11+50	9474 READING	Cr Ci No. 433224004 CatTE=25510 NE ENV 24=57198 SW ENV 24=57200	1	-11 = AT		P/4		04 SPACE FOR SAL	IOUECT ENG: BSC SIGN BY: GUF AMM BY: CW	EUM. MEW. MAL REV. BY:	ACAD DRAWING NAME: 0940.

•

DOP. 36" STM TYPE "8", CLASS # BEDDING (P.V.C.)* CLASS # BEDDING OP. 36" STM TYPE "8", CLASS # BEDDING	301.00' @ 0.20%		0			(35) (25) (0 50	INA = 21 94 9653 197	HET 3 FOR PIPE ALTERNATIVES	0 21+50 22+00 22+50 23+00	PROP. 5GI #125	PACIFIC STATION OF CONTRACT STATION OF CONTRAC	ROPOSED PROJECT NO. 10142200 CSO 513
łd -		Ex GROUND	0	LEX SAN SCBN		(35) Ze 9 28 81	#810 8-25.22 104 = 52 104 = 52	ин - 2517, - 157 - 157, - 157 - 157, - 157 - 157, - 157 - 1	20+00 20+50 21+0	PROP. MH REIOA A = 101'59" LT A = 101'59" LT CONSTRUCTION TO THE TO THE ACTION TO THE TO THE ACTION TO THE ACTION TO THE ACTION A = 100'159" LT CONSTRUCTION TO THE ACTION A = 100'159" LT CONSTRUCTION A = 100'159" LT CONS	A A A 20016 ET (12 * 10 * 10 * 10 * 10 * 10 * 10 * 10 *	ROPOUTAN SOMER DISTRICT GREATER CHCHNATT
PROP. 36" SIM TYPE "8" CLASS II BEDDING (P.V.C.)*	75.00 @ 0.46%			3131	ā	(W2) 74 8 (34) 74 8 (2) 78 80 A11001 <u>5</u> 73 2	IIAN = 23 +25 WH #42 IIAN = 26 +20 52 +50 52 #83	ни дова 100- 34 100- 34 10	19+00 19+50		Control (10, 10, 10, 10, 10, 10, 10, 10, 10, 10,	20 129 34
900 PROP. 42" STM TYPE "B", CLASS II BEDOING (P.V.C.)*	300.00° @ 0.20%	200	500	are	990	540	PRELIMINARY	SUBJECT TO REVISION	13450 18+00 18+50		T = 1 = 1 = 1 = 1 = 1 = 1 = 1 = 1 = 1 =	ROALET BNG: BSC BY: DATE REMISCINS DESCRIPTION:

.



330.69' @ 0.12%	88		2 TE	095	- 500	PRELIMINARY	SUBJECT TO REVISION	28+50 29+00 29+50 29-50	SOUT		the second of th			+••+PROP. 30° STM * S		10 - 01 - 10 - 10 - 10 - 10 - 10 - 10 -	и/а	Δ Δ = 00.3410° RT (120) Δ = 90.3410° RT (122) Δ = 8827/46° LT (15)	CSO 513 DADTIAL SEWER SEPARATION	
2 44' @ 0.14%		<b>3</b>			(3S) 28 90 (3S) 200	100 = 274 100 = 574 100 = 574 100 = 574 100 = 574 100 = 574	bKOb 12. bKOb 20. 21V = 281 SW = 281 HW - 254 HW - 254 HW - 254 HW - 264 HW - 264 H	28+00	300 RELOWIG PD 9390 RELOWIG PD PERONUE	Land 100      Land 100	CONC MAX			STM SEE SHEET 25 *			EX 00 No 30 EX 00 No 30 EX 00 No 30 EX 000 No 20 EX 00 NO 20 EX 0	-1 (10 RE REMOND) 9359 REMOND RD	T NO. 10142200	
4			PROP 6. WATER MATER MATER MATER	10 x3 36 01)	25	≥25 = ^/NI	HM 9099 75 = .475 108 = .418 108 = .412 102 -9099	27+00 27+50			DICE WIX		*	EX 4" WIRL STATE OF COP. 30			PROP. MH VM15 TA 22+53.47 [Xuun Nu 4210004 17'47 RT (3007) 5'37'45' LT (18') [Xuun 12'-32184 RU 12'-32184 FROP. DGI #903 PROP. DGI #903	STA. = 800+2836 (REMOVE AND REPLACE) SEE DETAIL SHEET 7 SEE DETAIL SHEET 7	PROPOSED PROJEC	SOME: HORIZ, 1-20
225.13' @ 0.20%	Camara xa	10	CONC ENCASEMENT	EX 30, 6			*SEE SHEET 3 FOR PIPE ALTERNATIVES.	26+00 26+50	T T T T T T T T T T T T T T T T T T T	The matrice of the matrix of t	1	$= = - \underbrace{- \underbrace{- \underbrace{- \underbrace{- \underbrace{- \underbrace{- \underbrace{- \underbrace{- \underbrace{-$		- CONCRETE EXCAMENT (ThP.) READING RD.			$V_{\rm eff} = 0$ $\chi_{\rm eff} = 121000$ $\chi_{\rm eff} = 12000$ $\chi_{\rm eff} = 12000$ $\chi_{\rm eff} = 12000$ $\chi_{\rm eff} = 12000$ $\chi_{\rm eff} = 120000$ $\chi_{\rm eff} = 120000$ $\chi_{\rm eff} = 120000$ $\chi_{\rm eff} = 1200000$ $\chi_{\rm eff} = 1200000$ $\chi_{\rm eff} = 1200000$ $\chi_{\rm eff} = 12000000$ $\chi_{\rm eff} = 1200000000000000000000000000000000000$	NOTE: NOTE: SETTLENEL INSTAL AND WONTOR SETTLENEL MARKES AT 33.9 READING ROAD REFERENCE SPECIFICATION SECTION 31 09 00	THE METROPOLITAN SEMER DISTRICT OF GRATTER REVIEWATT HAMLITON COUNT, OHD	WITHOUTING WITHOUTING WITHOUTING
		•••			(3N) \$6 (3S) \$¥ (MN) \$1 (MS) 69	025 = 230 INA' = 234 INA' = 234 INA' = 23 P12# P12#	960Р. 36° 970Р. 36° 970Р. 30° 970Р. 30° 970Р. 30° 970Р. 36°	+00 25+50	9412 BELGADI RO 171 - 0015 - 0013 - 001	EX. 0. 160, 303 EX. W (REMOREL 16371304) W 12, 10, 10, 10, 10, 10, 10, 10, 10, 10, 10	ESA (TYP.) AN			SEE SHEET 25			V/d         V/d           13         V/d           001         0.46, 902           001         0.46, 902           001         0.46, 902           001         0.46, 902           100         0.46, 902           100         1.46           100         1.46	25) 254	Ctrutto	11677 LEANON ROLD CHORNANT, OHD 45239 (513) 842-6200
232.10' @ 0.32%								24+00 24+50 25+	Martin Product 1 (199	PROP. MH JR12C 51A, 252+2513 (2010) 302 A = 113377 L1 (2017) 304 17-5154 A = 813737 L1 (2017) 304 17-5154 A = 8127355 L1 (127)	20 EX CONC MUX #18 M/8 M/8	$c = = \frac{62^{10} \cdot 60^{10} \cdot 30^{10}}{10^1 \cdot 60^{10}} = = = = = = = = = = = = = = = = = = $	и на	****PROP. 36" STM	x x	EX CONC WALK	V 4 V4	C. (REMOVE AND REFLAC	DATE: REVISIONS DESCRIPTION:	
	590		570	560	550	540	530	23+50	PROP.	0 NOT DISTURB EX	8/W 8/W 8/W	53+20	*   * <b>*</b>			P =	- 1 1 	More PD	DECT ENG:: BSC BY:	NWN BY:CW





PLOTED BY: CMLHERS OVER MR: 2 '2018 - 0735 PM VALE R: 4 '2018 - 0735 PM

PROP. 17 SIM. TYPE B' 610 CLASS II EEDOING (P.V.C.) • 6.42' @ 2.027 600	590 EX GROUND 590 510 510	Bit Of State         Bit Of State<		CSO 513 EWER SEPARATION ROAD CEMETERY & PROFILE	SHEET 15 OF 27 6886
PROP 12 STM TYPE 9 610 611 CLASS II BEDDING (P.V.C.) • 1687 27 39 0 1687 600 600	570 530	30         30		12200 PARTIAL S READING	ACC. NO. X
600	590 590 590 - 590 590 - 590 590 - 590 590 - 590 590 - 590 590 - 590 590 - 590 590 - 510 -	BBUCH RM INFORM         Process RM INFORM	No.         No. <td>oposed project no. 1014</td> <td></td>	oposed project no. 1014	
510 12 514 TYPE "8", 510 510 510 510 510 510 510 510 510 510	500 510 510 510 510	402+50 402 - 100	DIVIDE CONTRACT OF	Rict PR	EE ACC. NO. X
E2° SIM THE "B", FRG BEDDING (P.V.C.) CLAS (53° 0.351%	Centrol	• В Выбор 15, INA = 281 28 (2)     • Выбор 15, INA = 281 28 (2)     • Выбор 15, INA = 281 28 (ИЕ)     • Выбор 15, INA = 401 48 35     • Выбор 74H Выбор     • Выбор 74H Выбор     • Стака = 233 22 (Е)	P6         P7	C C C C C C C C C C C C C C C C C C C	FOR EASEMENT DRAWING SE
BEDDING (P.V.C) PROP P. 0 2 002 16.33 0 83 2.762 83		(N) 54 L25 - NN [-6: 4094 (N) 54 L25 - NN [-6: 4094 02504 [D4 - 415 0316 [-6, 25] NN - 21 (-004 (M) 14 205 - NN [-2: 4004 (M) 14 205 - NN [-2: 4004 (M) 14 205 - NN [-2: 4004 04 - 4004 (M) 14 205 - NN [-2: 4004 04 - 4004 (M) 14 205 - NN [-2: 4004 04 - 4004 (M) 14 205 - NN [-2: 40	FROD         MHI #R12           FROD         FROD           FROD         FROD           A         BOS2 * 40°           B         BOS2 * 40°     <	00. Stante Stante Stante Stante Stante Stante Stante Stante	
PROP. 18" SIM. TYPE "B". CLASS II BEDONG (P.V.C.) 58.81	(3 4 4 0 4 5 4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	С 4 4 4 4 4 4 4 4 4 4 4 4 4	PROP. MH #R12A S1A = 400+89.43 A = 973'35'' L1 (12') A = 57'34'5' L1 (12') A = 57'34'5' L1 (12') A = 57'34'5' L1 (12') PROP. S01 #12' FIL = 400-27'30 PROP. S01 #12' PROP. S01 #12'	Yr DATE REVISIONS DESCRIPT	C 09407C 001 CEMETERYPP1.DWG
610	540	500	(REM PROP. CB (2-2) PROP. CB (2-2) (REMOVE AND REL (REMOVE AND REL (REDOVE AND REL (REDOVE) (	PROJECT ENC.: BSC B DESIGN BY: CMF DRAWN BY: CW PRELIM: REVIEW: FINAL REV. BY:	ACAD DRAWING NAME

And and Date ( States)

.









ыгошер ви: Сминевия очите на 2016 - 03/33 рм руне Г. Сирековонь/Туркуксинг/13408403/силг/рекмисс/жешт\_неви/0840300\_001\_См





6/011120 8// СМЦИВИЯ 201120 8// 2018 — 07/32 БМ 50114: 6//006/030/10/1/21//21/02/03/02/20/02/20/02



¥гошто ви силиения оите им 2 3016 – 07:35 № № ИГ С Кирековсик/1/24402440\_14/124408401/0.47/044760017#С



PLOTTED BY: CMTHERS DATE: More 5, 2019 - 03,25 PM PATH: E. \WORKCROUP/1724/ACT







.


КОЦЦЭ ВК СМИНЦЯ 071EF М№ 2508 - 0733 № 891EF (МОВИСОБ/1247/VCLI/E/12408402/СИГ/DBY1M02/2HEEL\_BEZ/08402/2001\_BEYDB



PRELIMINARY SUBJECT TO REVISION PRELIMINARY SUBJECT TO REVISION



ALTE, E, MORGROUP/124/VCTIV7/1340407/SML/DRAMMOS/SHETL\_FLEX/04407C\_001\_METRIPPEI DNG PLTE UM 5, 2019 - 012.03 PM PLTE D BT CARTER PLTE D BT CA

# FILE

#### BEFORE THE OHIO POWER SITING BOARD

)

)

)

In the Matter of the Application of Duke Energy Ohio, Inc., for a Certificate of Environmental Compatibility and Public Need for the C314V Central Corridor Pipeline Extension Project

Case No. 16-0253-GA-BTX

### DIRECT TESTIMONY OF JEAN-MICHEL GULDMANN ON BEHALF OF NOPE - NEIGHBORS OPPOSED TO PIPELINE EXTENSION, LLC

### CONFIDENTIAL VERSION

#### Q. Please state your name and business address.

My name is Jean-Michel Guldmann. My business address is 237 Knowlton Hall, Tro Ohio State University, 275 West Woodruff Avenue, Columbus, Ohio 43210.

#### Q. Please describe your education and job credentials.

I have a Master's Degree in Industrial and Systems Engineering, Ecole des Mines, Nancy, France (1970), specializing in operations research and industrial management. I also have a PhD in Urban and Regional Planning from the Israel Institute of Technology (1977), specializing in quantitative planning methods, urban economics, and environmental management. I have taught at The Ohio State University (OSU) from 1977 to 2012, rising from the rank of Assistant Professor to Full Professor. I have taught classes in regional planning, population and economic forecasting, statistical and optimization methods, as well as introductory and advanced classes in energy planning.

From 1978 to 1988, I served as a Senior Faculty Associate at the National Regulatory Research Institute at OSU, where I conducted several regulatory research projects related to natural gas distribution and funded by the Public Utilities Commission of Ohio (PUCO), the U.S. Department of Energy, and the National Association of Regulatory Utility Commissioners (NARUC). In the area of natural gas systems modeling, I have also served as consultant to the following organizations: U.S. National Bureau of Standards (1981-1982), the Information Science Division of Argonne National Laboratory (1987-2012), the Enron Corporation (1982), and the President's Commission on Critical Infrastructure Protection (1998). Since 2017, I have served as consultant to a California Energy Commission-funded project investigating the vulnerability of Northern California Natural Gas Energy System to climate change.

I have published 15 peer-reviewed articles on natural gas systems modeling, involving both econometric and optimization methods, including in flagship journals such as



2019 APR 12

PH

N

<u>Management Science</u>, <u>Operations Research</u>, <u>Resources and Energy</u>, and <u>European</u> <u>Journal of Operational Research</u>. I have also authored and co-authored 15 research reports on natural gas issues. For more details, please see my Curriculum Vitae, which is attached as Exhibit JMG-1.

#### Q. What are your professional certifications and credentials?

I am a member of the following organizations: American Economic Association, Regional Science Association, International Association for Energy Economics, and INFORMS (Operations Research/Management Science).

#### Q. On whose behalf are you providing expert testimony in this proceeding?

My testimony is on behalf of the following intervenors: Neighbors Opposed to Pipeline Extension ("NOPE"), the City of Cincinnati ("City"), and Hamilton County ("County").

#### Q. Have you testified as an expert witness before in any PUCO proceeding?

Yes. In 1979, I provided testimony to the PUCO regarding whether East Ohio Gas Company and Columbia Gas of Ohio should be allowed to resume natural gas hookups.

#### Q. Please describe the purposes of your testimony?

The purposes of my testimony are to (1) assess whether current and future market conditions support the C314V project, (2) assess whether the C314V project achieves the objectives stated by Duke Energy Ohio, Inc. ("DE-Ohio"), and (3) offer possible alternatives for network capacity expansion that would be much less disruptive and improve overall system reliability.

#### Q. What documents did you review in preparation for your testimony?

I have reviewed DE-Ohio's Application and Amended Application, information and documents produced by DE-Ohio in discovery, and other related reports and materials, and Staff's reports.

#### I. MARKET DEMAND ANALYSIS

#### Q. What aspects of market conditions are you focusing on?

I will first review recent trends in the residential, commercial-industrial, and electric generation markets for natural gas of DE-Ohio and Duke Energy Kentucky, Inc. ("DE-Kentucky") (collectively, "Duke Energy" or "DE"). Second, I will review forecasts of future markets, including the population of the Cincinnati Metropolitan Area ("CMA"), the power generation market, and the CNGV ("Compressed Natural Gas Vehicles") market. Third, I will review several estimates of market growth and peak deliveries

prepared by DE or other organizations on DE's behalf. Finally, I will assess whether all this information supports the need for the C314V project.

#### Q. What is your assessment of recent market trends?

All pipeline and distribution companies are required by the U.S. Energy Information Administration ("EIA") to file Form EIA 176 on an annual basis. This publiclyavailable data provides aggregate annual supplies and deliveries. Because of data consistency, this form is an ideal data source for analyzing multi-year patterns. The table in **Exhibit JMG-2** is a condensed form of the information for DE over the period 2010-2016 (the information about 2017 was not yet available). I provide data for DE-Ohio and DE-Kentucky, which are treated as separate companies for regulatory purposes. However, I focus below on both companies (i.e., DE), the sum of Ohio and Kentucky data. The discussion below is wholly based on the data in Exhibit JMG-2.

The total supply volume is the sum of the interstate pipeline deliveries (receipts at city gates) and supplemental gaseous fuels (primarily the output of the propane-air plants). The total supply has decreased from 94,305 mmcf ("Million cubic feet") in 2010 to 92,476 mmcf in 2016, or a decline of about -2%, or -0.33% per year). The peak supply in 2014 was due to a particularly cold year.

The number of residential consumers has grown from 467,083 in 2010 to 477,729 in 2016, at an overall rate of +2.28%, or +0.32% per year. The consumption per residential consumer has declined from 81.1 mmcf in 2010 to 67.6 mmcf in 2016, or -16.7% (-2.6% per year). This decline is consistent with other data, pointing to a weak/declining residential market.

The number of commercial consumers has declined from 44,232 in 2010 to 43,169 in 2016, at an overall rate of -2.4%, or -0.4% per year. The consumption per commercial consumer has declined from 663.5 mmcf in 2010 to 610 mmcf in 2016, or -8.06 % (-1.2% per year), pointing to a declining commercial market.

While the number of industrial consumers has steadily decreased from 1829 in 2010 to 1704 in 2016, the average consumption per industrial consumer has increased from 10,603 mmcf in 2010 to 13,406 mmcf in 2016, or an overall growth rate of +26.4%, or +3.4% per year. This suggests that smaller consumers have left the market and have been replaced by much larger consumers. As a result, the total industrial volume has grown from 19,393 mmcf in 2010 to 22,844 mmcf in 2016. It would be instructive to find out the consumptions and locations of the larger industrial consumers, as these may have serious implications for the need for network capacity expansion. Unfortunately, such data were not available to me.

The electric power market has grown from 19 mmcf in 2010 to 390 mmcf in 2016, and the corresponding number of consumers has grown from 1 to 2. While the growth has been strong, this is still a very small market as compared to the industrial market. As I

discuss below, any additional growth is unlikely to benefit from the Central Corridor Project ("Project" or "C314V").

In order to keep the above market changes in perspective, it is important to note the volume shares in 2016: Residential: 39.5%; Commercial: 32.2%; Industrial: 27.9%; Electric power: 0.4%. The shares in numbers of customers are: Residential: 91%; Commercial: 8%; Industrial: 0.3%.<sup>1</sup>

In summary, there has been a strong decline in the average gas usage per customer in the residential and commercial sectors due to energy conservation efforts, a decline in the number of commercial customers, and a very weak growth in the number of residential customers. These weaknesses have been, in part, compensated by the volume growth of the industrial and power markets. However, the whole market has been in decline, as indicated by the trend in total supply volume.

### Q. What is your assessment of future residential and commercial market trends?

Population is the primary driver of the residential and commercial markets, and also indirectly impacts the industrial and power markets. There are several available population forecasts for the CMA. There may be slight variations in the definition of the boundary of the area considered, and therefore direct comparisons across different population forecasts may not be useful. However, a meta-analysis of the forecasted growth rates is appropriate.

Consider first the forecasts over 2010-2040 prepared by the Ohio-Kentucky-Indiana ("OKI") Metropolitan Planning Organization ("MPO"), as presented in Table 1. These forecasts are inputs to the 2040 OKI Regional Transportation Plan.<sup>2</sup>

For the whole OKI Region, the population would grow by 219,257 people over 2010-2040, or an average annual growth rate of 0.35%. This annual rate is reduced to 0.32% over 2020-2040. While all the other counties experience some growth, both Hamilton and Campbell counties are expected to see their populations decline. Hamilton County, by far the largest county in terms of population in the OKI Region, represents the core of DE's service area.

<sup>&</sup>lt;sup>1</sup> See JMG-2.

<sup>&</sup>lt;sup>2</sup> See 2010 Census; 2020-2040 projections by the Ohio Development Services (2013 Edition), Kentucky State Data Center (2011 Edition) and Indiana Business Research Center (2012 Edition). See: <u>https://2040.oki.org/demographics/</u>

Table 1 OKI Population Forecasts

	2010	2020	2030	2040
Butler	368,130	390,110	410,960	430,360
Clermont	197,363	208,330	214,090	216,190
Hamilton	802,374	790,600	785,900	786,090
Warren	212,693	225,770	235,640	239,060
Boone	118,811	153,933	190,270	224,687
Campbell	90,336	91,642	90,731	88,012
Kenton	159,720	168,458	174,699	177,963
Dearborn	50,047	53,482	55,655	56,369
OKI Region	1,999,474	2,082,325	2,157,945	2,218,731

The Urban Institute (Washington, D.C) has a forecasting model that indicates that the Greater Cincinnati population will grow from 2,069,055 in 2010 to 2,252,872 in 2030, hence a growth of 8.88% or an annual average growth rate of 0.43%.<sup>3</sup>

Data from the American Community Survey ("ACS") of the U.S. Bureau of the Census point to the following historical data for the Cincinnati MSA:<sup>4</sup> 1990: 1,832,284 2000: 1,994,818 - Annual growth rate 1990-2000: 0.85% 2010: 2,114,686 - Annual growth rate 2000-2010: 0.58%

2016: 2,165,139 - Annual growth rate 2010-2016: 0.39%

The Open Data Network provides historical data and short-term forecasts (2017-2021):<sup>5</sup> 2010: 2,110,398 2013: 2,122,940 - Annual growth rate 2010-2013: 0.19% 2016: 2,146,410 - Annual growth rate 2013-2016: 0.36% 2020: 2,162,696 - Annual growth rate 2016-2020: 0.19% 2022: 2,166,677 - Annual growth rate 2020-2022: 0.09%

In summary, all the above forecasts are consistent with a weak population growth for the CMA. The annual population growth rate has declined over 2010-2016, and forecasts beyond 2020 point to annual growth rates ranging from +0.10% to +0.50%. Of particular concern is the expected population decline in Hamilton County, the core of DE's service

<sup>&</sup>lt;sup>3</sup> Mapping America's Future, Urban Institute, available at: <u>http://apps.urban.org/features/mapping-americas-futures/</u> (last accessed Mar. 26, 2019).

<sup>&</sup>lt;sup>4</sup> https://factfinder.census.gov/faces/tableservices/jsf/pages/productview.xhtml?src=bkmk

<sup>&</sup>lt;sup>5</sup> Cincinnati Metro Area Demographics, Open Data Network, available at: <u>https://www.opendatanetwork.com/entity/310M200US17140/Cincinnati\_Metro\_Area\_OH\_KY\_IN/demogr</u> <u>aphics.population.count?year=2017</u> (last accessed Mar. 26, 2019).

area, at the rate of -2.03% over 2010-2040, or -0.07% per year. These population forecasts could lead to declines in the numbers of residential and commercial gas customers. Conservation efforts, prodded by technological innovations, are likely to intensify, leading to further declines in residential and commercial gas deliveries.

I also note that the decreasing per-customer energy consumption is further confirmed nationwide by the U.S. Energy Information Administration in its State Energy Data System ("SEDS") information release of January 28, 2019, namely: "U.S. energy intensity, or energy consumption per unit of real gross domestic product (GDP), equaled 5.8 thousand Btu per chained 2009 dollar, a 2% decrease from 2015 and the lowest level since at least 1997, the earliest year for which SEDS has data".<sup>6</sup>

#### Q. What is your assessment of future electric power market trends?

This market would involve the conversion to natural gas of coal-fired power plants located along the Ohio River. DE has made the following peak-hour projections for three power plants:<sup>7</sup>

- Miami Fort: 2,000 mcfh (thousand cubic feet per hour)

- Stuart: 408 mcfh

- Zimmer: 2400 mcfh

However, The Dayton Power & Light Company ("DP&L") retired Stuart, due to economic and environmental challenges, and the plant ceased electricity generation in 2018.<sup>8</sup>

Miami Fort, located in Miami Township, Hamilton County, has 2 coal-fired units with total capacity of 1,020 MW, and 4 oil-fired facilities with total capacity of 56 MW.<sup>9</sup> The oldest unit, which has been retired, dates back to the late 1940s, and it is possible that retirement may be a more economical strategy. In any case, this plant is not close to the existing DE pipeline network system, and the construction of C314V would not help in this regard. However, the alternative western scenario (W-1), proposed by Lummus Consultants in their planning report to DE, would greatly facilitate this hookup. This scenario is extensively discussed further on in my testimony.

<sup>9</sup> U.S. Energy Information Administration, Form EIA-860, 2017 data, spreadsheet

3 1 Generator Y2017.xlsx, available at https://www.eia.gov/electricity/data/eia860/

<sup>&</sup>lt;sup>6</sup> https://www.eia.gov/state/seds/data.php?incfile=/state/seds/sep\_sum/html/rank\_use\_gdp.html&sid=US

<sup>&</sup>lt;sup>7</sup> Gas System Master Plan Study 2015-2035. Report prepared by Lummus Consultants International for Duke Energy Corporation. January 2015.

<sup>&</sup>lt;sup>8</sup> See In the Matter of the Application of The Dayton Power and Light Company to Establish a Standard Service Offer in the Form of an Electric Security Plan, Case No. 16-395-EL-SSO, Opinion and Order, p. 38 (Oct. 20, 2017). See also DPL Inc. Announces the Retirement of the J.M. Stuart and Killen Station Power Plants (May 31, 2018), available at https://www.businesswire.com/news/home/20180531005754/en/DPL-Announces-Retirement-J.M.-Stuart-Killen-Station.

Finally, Zimmer, located near Moscow, Ohio, was originally intended to be a nuclear power plant.<sup>10</sup> When it was nearly 97% completed, Zimmer was converted to coal burning, and was completed in 1991. It is possible that this plant could be better served directly by high-pressure interstate transmission pipelines.

Because the electric power generation market is in flux throughout the U.S. due to recent expansion of renewable technologies (e.g., wind, solar, etc.) in response to the impacts of climate change, it would be imprudent for local gas distribution companies to commit significant new network infrastructure to serve the power market, except in cases where there is a clear short-term payoff, such as serving the Miami Fort plant.

In any case, if new electric power generation units were to be connected to and served natural gas by DE's system, these new units would most likely be interruptible customers who would not add requirements at peak time. Therefore, such growth, if any, should not impact the peak-hour firm send-out.

# Q. What is your assessment of future compressed natural gas vehicle ("CNGV") market trends?

According to the Energy Information Administration,<sup>11</sup> less than 3% of U.S. natural gas consumption is for transportation: in 2017, 2.66% was for natural gas transmission and distribution, and 0.18% (or 48,658 mmcf) for the CNGV national market, with California the leading state with 22,096 mmcf or about 50% (other leading states being NY – 4,428 mmcf, TX – 4,486 mmcf, AZ - 2,861 mmcf). CNGV customers in Ohio consumed 993 mmcf in 2017. CNGV adoption in North America is much lower than on other continents. The major reasons for low adoption include, among others, inefficient mileage compared to gasoline-powered cars, significantly higher prices due to bulky storage tanks, and a paucity of fueling stations. Compressed natural gas ("CNG") is more feasible for centrally fueled/operated fleets with private refueling infrastructure.<sup>12</sup> In addition, this small market may be strongly impacted by the future competition of electric vehicles.

According to DE, a major hindrance to the expansion of this market within its service area is the mixing of propane gas with natural gas on peak days. However, CNGV fleet customers could easily adapt to this situation by expanding their on-site CNG storage capability to deal with this infrequent occurrence. As of April 20, 2017, DE had six propane-intolerant customers that are notified when the propane plants are in operation. These may include both industrial and CNGV customers. DE finds it difficult to project propane-intolerant market growth.<sup>13</sup>

<sup>&</sup>lt;sup>10</sup> See City of Cincinnati v. Pub. Util. Comm., 67 Ohio St.3d 523, 1993-Ohio-79, 620 N.E.2d 826.

<sup>&</sup>lt;sup>11</sup> https://www.eia.gov/dnav/ng/ng\_cons\_sum\_dcu\_nus\_a.htm

<sup>&</sup>lt;sup>12</sup> Transitions to Alternative Vehicles and Fuels. The National Academic Press, 2013, pp. 34, 35, 40, 63.

<sup>&</sup>lt;sup>13</sup> CITY-INT-01-005, CITY-INT-01-006, CITY-INT-01-007.

In addition, new CNGV fleet customers would most likely be interruptible customers, as their on-site storage capability would enable them to take advantage of interruptible tariffs. Therefore, the CNGV market growth, if any, would not add to the peak-hour firm send-out.

#### Q. Please summarize the market assessment DE is relying on to support its Project.

In its Amended Application, DE indicates that it supplies up to 43,000 mcfh (i.e., daily peak hour flow) to approximately 525,000 current customers in the combined Ohio and Kentucky service territories, including 91% residential customers using 50% by volume, 8% commercial customers using 20% by volume, and less than 1% industrial customers using about 10% by volume.<sup>14</sup> Based on the timing of the filing of the Amended Application, this data appears to be as of 2016 or earlier, though DE never explicitly states as much in the Amended Application.<sup>15</sup> The scenarios involving (1) the construction of C314V, and (2) the elimination of the propane-air plants, assume a peak hour flow of 45,500 mcfh. There is no information in the Amended Application that supports the increase of the peak hour flow from 43,000 mcfh to 45,500 mcfh (or +5.8%), nor any indication of the time horizon of the forecast. The Amended Staff Report of Investigation ("Staff Report") notes: "Staff has found that the proposed project fits into regional expansion plans. The Applicant has also identified several areas of its service territory where it anticipates growth. The proposed project could accommodate anticipated system growth of up to 45,000mcfh..."<sup>16</sup> However, aside from general statements regarding CNGV and power generation market expansions, neither the Amended Application nor the Staff Report provide any quantified and geographicallyspecific information.

If the increase of the peak-hour flow from 43,000 mcfh to 45,500 mcfh (or +5.8%) is assumed to take place over 10 years (2017-2027), this would translate into an annual growth rate of 0.56%, which is outside and above the range (0.10%-0.50%) that was derived from the earlier analyses of CMA population forecasts, and is not consistent with the forecast of a 0.07% rate of decline for the population of Hamilton County, the core of DE's service territories.

#### Q. Are there other documents that might clarify DE's market assessment?

Yes. As specifically identified below, certain documents filed with the PUCO refer to DE-Ohio's service territory while other documents pertain to both service territories of DE-Ohio and DE-Kentucky. The most relevant ones are reviewed below, with a focus on market and deliveries information.

<sup>&</sup>lt;sup>14</sup> Amended Application for a Certificate of Environmental Compatibility and Public Needs for the C314V Central Corridor Pipeline Extension Project ("Amended Application"), p. 3-1.

<sup>&</sup>lt;sup>15</sup> Compare Application, p. 3-1 (Sept. 2016) (approx. 525,000 customers, with percentages) to Amended Application, p. 3-1 (unchanged from 2016).

<sup>&</sup>lt;sup>16</sup> Amended Staff Report, p. 27.

### 1. Audit Reports<sup>17,18</sup>

Exeter Associates, Inc. (hereafter "Exeter") was commissioned by the PUCO to audit the purchasing practices and policies of DE-Ohio. I have reviewed both the 2015 and the 2019 Exeter audit reports, with a focus on DE-Ohio's model for forecasting peak-day demands. A design-day forecast is prepared annually by DE-Ohio's Load Forecasting Department.<sup>19</sup>

In the 2015 Exeter Report, Exeter notes that DE-Ohio relied on monthly historical data over 30 years to relate total send-out to weather variables such as current-day and priorday heating degree-days ("HDD") and average wind speed with an econometric model.<sup>20</sup> Monthly peak estimates would then be downscaled to peak-day send-out, and, ultimately, peak-hour send-out. Hourly demands vary with time of day and season of the year. Demand is lower at night and on weekends. Weather is a big factor, as gas consumption increases due to the use of space heating.<sup>21</sup> DE-Ohio uses the peak-day flow, and converts it to a peak-hour flow. For instance, on Jan. 6, 2014, the daily flow was 820,862 Dth, which, when using the 2014 natural gas content of 1.033 Btu/cf, yields a flow of 847,950 mcfd. This number, when divided by 24, yields an average hourly flow of 38,618 mcfh. The actual peak hour flow on that day was 42,358 mcfh, hence a peaking factor of 1.20 (i.e., ratio of peak over average hourly flows).<sup>22</sup> Using data on several cold days in 2014, DE found out that the peaking factor varied between 1.10 and 1.23, with an average of 1.15.23 This factor is then used to convert a forecasted maximum daily firm gas consumption to a forecasted peak-hour flow to be used in the Synergi model. The estimation of the peak-day flow is based on a forecast of peak-day temperature, which is then converted to HDD. The model was solved using a temperature of -14°F, corresponding to the 1% tail-end of the distribution of temperatures from 1947 to the present. Exeter highlighted the need to use only historical daily data to estimate a more accurate model that would enable a meaningful comparison of actual and projected peakday send-outs.24

In the 2019 Exeter Report, Exeter indicates that DE-Ohio has developed a new model based on a regression analysis of daily send-out and weather data beginning in 1995.<sup>25</sup>

<sup>&</sup>lt;sup>17</sup>Management and Performance Audit of Gas Purchasing Practices and Policies of Duke Energy Ohio. Report prepared by Exeter Associates, Inc. for the PUCO. December 2015 (2015 Exeter Report").

<sup>&</sup>lt;sup>18</sup> Management and Performance Audit of Gas Purchasing Practices and Policies of Duke Energy Ohio. Report prepared by Exeter Associates, Inc. for the PUCO. January 2019 ("2019 Exeter Report").

<sup>&</sup>lt;sup>19</sup> 2015 Exeter Report, p. 38.

<sup>&</sup>lt;sup>20</sup> 2015 Exeter Report, p. 38.

<sup>&</sup>lt;sup>21</sup> 2015 Exeter Report, p. 38.

<sup>&</sup>lt;sup>22</sup> 2015 Exeter Report, pp. 11, 41, 51.

<sup>&</sup>lt;sup>23</sup> Lummus Report, p. 48.

<sup>&</sup>lt;sup>24</sup> 2015 Exeter Report, pp. vii, 47.

<sup>&</sup>lt;sup>25</sup> 2019 Exeter Report, pp. 4-22.

HDD is now computed with a basis of 59°F (instead of 65°F), and the model includes, in addition to current-day and prior-day HDD, dummy variables for the day of the week and for holidays. A comparison of actual and projected firm peak-day demands is presented below (Table 11 in the 2019 Report), with units in decatherms ("Dth"):<sup>26</sup>

Date	Actual	Projected	Difference		
01-06-2017	593,051	632,747	39,696	(6.7%)	
01-05-2018	634,430	666,044	31,614	(5.0%)	

Exeter states that DE-Ohio has incorrectly used the model, which is statistically invalid, resulting in inflated forecasts.<sup>27</sup> However, this discovery comes too late as far as the C314V application is concerned. Indeed, it is likely that DE has also used the model incorrectly for estimating the peak-hour send-out for the DE-Ohio service territory. As a similar model is used for DE-Kentucky,<sup>28</sup> the over-forecasting most likely applies to the entire DE territory. If we assume an error of 6.0%, the 45,500 mcfh target send-out would be reduced to 42,924 mcfh, very close to the existing situation (i.e., 43,000 mcfh). This over-forecasting raises serious doubts about the validity of the 45,500 mcfh target.

The responsibility for DE design-day forecasts has been recently transferred to a newly created Pipeline Services Department, which has created a new model that uses data over the recent 5-year period, thus reflecting recent conservation efforts. Exeter deems this new model more appropriate, but believes usage data should be limited to the most recent three-year period.<sup>29</sup> In any case, this model was not available at the time Duke filed its Amended Application, and Duke has not updated its Amended Application to include a valid forecast.

#### 2. Lummus Consultants Planning Report

Lummus Consultants International ("Lummus") prepared a report to DE dated February 24, 2015, titled *The Gas System Master Plan Study 2015-2035* ("Lummus Report").<sup>30</sup> While its focus concerns various options for system expansion, the Lummus Report provides market information and forecasts to support DE's planning analyses. DE provided Lummus the historical data and projections, as well as other information, that formed the basis of the Lummus Report. Historical data on customers and deliveries point to limited customer growth and flat demand growth due primarily to energy efficiency programs, better home insulation, and more efficient natural gas appliances. These patterns are similar to those discussed earlier concerning Form EIA 176.

 $<sup>^{26}</sup>$  2019 Exeter Report, pp. 4-24 to 4-25. Note that 1 Dth =1 MMbtu (Million British Thermal Units). The heat content of natural gas delivered in DE-Ohio's territory = 1,076 Btu/cf. Hence, 1 DTH = 0.93 mmcf.

<sup>&</sup>lt;sup>27</sup> 2019 Exeter Report, pp. 4-25 to 4-26.

<sup>&</sup>lt;sup>28</sup> NOPE-POD-03-016 CONFIDENTIAL.

<sup>&</sup>lt;sup>29</sup> 2019 Exeter Report, pp. ES-4, 4-26.

<sup>&</sup>lt;sup>30</sup> CITY-POD-1-002 CONF Attachment 2, attached as Exhibit JMG-7.

Of greater interest are the seasonal gas load shape and peak flow data. Lummus reviewed the seasonality of DE's demand, which it considers consistent with the seasonality shape of other local distribution companies ("LDCs"), including large demand peaks in the winter heating season and much lower demand during the shoulder and summer months.<sup>31</sup> Figure 10 on page 19 of the Lummus Report depicts the actual load curve in 2014 and the projected load curves for various horizons (e.g., 2020, 2025, 2030, 2035). All the projected curves are nearly identical (superimposed).<sup>32</sup> I approximated, based on the figure's diagram, the January monthly loads for 2014 and 2035 in mcf. The difference is around 6,000,000 mcf (i.e., 19,333,333 mcf -13,333,333 mcf), or a decline of 31%. Lummus identifies this as the base case forecast, which means no market growth – i.e., the same, or lower, amount of send out in 2020, 2025, 2030 and 2035 as in 2014.

Lummus further reports peak-day and peak-hour flows, including actual data for 2014 and projections to 2035<sup>33</sup> in Table 11 (Duke Peak-Day Flow Projections) and Table 12 (Firm Gas Peaking Factors Table). Lummus reports that the actual peak-day flow in January 2014 was 956,726 mcfd, which historically represents the highest daily flow.<sup>34</sup> The table indicates a projected firm peak with a 1% exceedance in 2014 of 951,194 mcfd. In 2035, this 1% value is projected to be 957,119 mcfd.<sup>35</sup> I conclude that the 2014 DE system was able to satisfy a peak flow larger than the 1% target in 2014, and, therefore, would be very close to satisfy the 2035 1% daily flow target (a difference of 393 mcfd or 0.04% short). Next, in Table 13, the firm peak-hour gas flow at 1% exceedance was estimated to be 45,578 mcfh in 2014.<sup>36</sup> This corresponds to the 1% firm daily peak of 951,194 mcfd (Table 11), using a peaking factor of 1.15 (Table 12), with 45,578 =1.15\*(951,194/24). This would be less than the actual peak-hour flow experienced on Jan. 6, 2014, and would suggest that the existing 2014 system is able to satisfy a target of 45,500 mcfh, as used in the Amended Application. Further, the projection of the 1% flow to 2035 is 45,861 mcfh, or an increase of 283 mcfh, or +0.06 %. The projected peak-hour flows at 1% exceedance are quasi-constant over the period 2015-2035.37

While the load shape data suggest a decline of 31% in the peak January flow from 2014 to 2035, the peak-day and peak-hour projections suggest a close-to-constant level. The difference appears to reflect DE's assumptions of market growth from 2014 to 2035. This implicit growth assumption is not justified based on my earlier analysis of population forecasts. However, even if this growth assumption were to be accepted, the data suggest that the current DE system would be able to handle the corresponding hourly peak flow with 1% exceedance.

<sup>36</sup> Id., p. 49.

<sup>37</sup> Id.

<sup>&</sup>lt;sup>31</sup> Lummus Report, pp. 18-19.

<sup>&</sup>lt;sup>32</sup> Lummus Report, p. 19.

<sup>33</sup> Lummus Report, pp. 46-48.

<sup>34</sup> Id., p. 47.

<sup>&</sup>lt;sup>35</sup> Id.

# Q. Does the previous information support DE's claim of the need for C314V based on market demand and growth?

Future natural gas demand, whether expressed on an annual, monthly, peak-day, or peakhour basis, depends on the number and type of customers (residential, commercial, etc.), the average usage of gas per customer, customer sensitivity to weather (space heating), and expected future weather/temperatures. Projections of the peak-hour flow are particularly critical, because they determine the need for distribution network capacity expansion. The peak-hour flow represents the peak-hourly requirement of all firm customers, whether sales (i.e., buying their gas from DE) or transportation (i.e., buying their gas from third parties but using DE's network to transport the gas to their premises). Interruptible customers, who benefit from lower tariffs by agreeing to be curtailed at peak time, are not accounted for in peak flow projections. As I indicated earlier, this would likely be the case for new power generation and CNGV markets.

Based on the above considerations and the various data presented above, the peak-hour flow target used by DE in its Amended Application is grossly overestimated. First, the annual 0.56% growth rate it implies is not a reasonable population forecast for the CMA. Any growth in firm customers is very likely to be linked to population growth. Second, the 2019 Exeter Report raises serious doubts about the calculation of the peak flow and suggests an overestimation by about 6%. Third, the data and projections included in the Lummus Report suggest that the existing system may very well be able to handle short-and mid-term growth in the peak requirement.

I recommend that DE conduct a new comprehensive market and peak deliveries analysis, presenting clearly the data used and the estimated models. In doing so, DE should keep in mind that (1) the historical distributions of temperatures may not reflect future ones in light of climate change and warming, and (2) past conservation efforts may not reflect future efforts.

## II. THE C314V LINE WILL NOT ACHIEVE DE'S STATED OBJECTIVES FOR THE PROJECT.

#### Q. Could you provide an overview of the C314V line extension and DE's rationale?

First, I will first provide a description of the gas supply infrastructure that feeds into DE's system. Next, I will describe DE's system. Finally, I will describe the C314V extension (i.e., the Project).

#### Q. Please describe DE's gas supply infrastructure.

DE interconnects with five interstate pipelines: (1) to the north, Texas Gas Transmission ("TGT"), Texas Eastern Transmission ("TET"), ANR Pipeline, and Columbia Gas Transmission ("TCO"); (2) to the south, TCO (serving a very small and isolated market through the Brown County citygate station) and Kentucky-Ohio Transmission ("KOT"),

supplying gas through the Foster citygate station. KOT is a fully owned subsidiary of DE-Ohio and is supplied primarily by Columbia Gulf Transmission ("CGT") and TCO. These interconnections are illustrated on the system map presented in **Exhibit JMG-3**.<sup>38</sup> All these interstate pipelines link southern production areas to the major markets in the northern and northeastern U.S., but also access the Marcellus Shale in the Appalachian Basin. Several of these pipelines converge at the Lebanon supply hub.

There are 21 northern citygate stations, with supply from TGT, TET ANR, and TCO, and 2 southern citygate stations, with supply from CGT and TCO. In the north, TGT supplies gas at the following locations/stations: Harrison, Fernald, Venice, Liberty, Butler, Mason, and Route 63. The Liberty station serves exclusively the Woodsdale power plant. TET supplies gas at the following stations: Millville, Trenton, Dicks Creek Plant, Union Road, and Springboro. ANR supplies gas at the Springboro station. TCO supplies gas at the Springboro and Red Lion stations in the north. Note that Red Lion (about 3.5% of total send-out) supplies a small distribution system that is not interconnected with the rest of DE distribution system. In the south, TCO supplies the Brown County station, and CGT supplies the Foster station through KOT pipeline.<sup>39</sup>

#### Q. Please describe DE's network system.

In the following, DE refers to the whole gas transmission/distribution integrated network system serving the CMA. This system is subdivided, for regulatory purposes, into two subsystems: DE-Ohio and DE-Kentucky. These two systems interconnect at three stations located along the Ohio River: Anderson Ferry, Front & Rose, and Eastern Avenue (a.k.a. East Works and Cavern). Northern and southern supplies flow through these stations to DE-Kentucky and DE-Ohio, respectively.

DE does not use compression to deliver gas to its distribution system, and it does not own/operate underground natural gas storage facilities. Natural gas stored elsewhere is delivered to DE at the same citygates as other interstate supplies. DE has access to propane gas stored at two plants: Erlanger ("ERL") and East Works ("EW").<sup>40</sup>

DE system is made of (1) 700 miles of transmission and high-pressure pipelines with varying Maximum Allowed Operating Pressure ("MAOP") and diameter, and (2) low-pressure lateral and smaller-diameter distribution pipelines, all designed to bring natural gas to customers in the central core of Hamilton County. The focus here is on the first category of pipelines, which have all been constructed over the last 50 years. The system includes six Ohio River crossing stations: Anderson Ferry ("AF"), Front & Rose ("FR"), East Works ("EW"), California ("CA"), Bracken County ("BKC"), and Brown County ("BRC"). The system was built to distribute gas from the south to the north, initially from manufactured gas sites along the Ohio River. The backbone system includes: - Line A running north to south through central neighborhoods in Hamilton County;

<sup>&</sup>lt;sup>38</sup> See 2015 Exeter Report, p. 5.

<sup>&</sup>lt;sup>39</sup> 2015 Exeter Report, pp. 5-7.

<sup>&</sup>lt;sup>40</sup> *Id.*, pp. 7, 30.

- Line V (20") running east to west;

- Various Lines AM conveying gas from Foster to points in OH and KY.<sup>41</sup> Detailed characteristics of DE's existing and planned transmission lines are further described in **Exhibit JMG-4**.<sup>42</sup> The gas flow directions are as follows: (1) South-to-North is the predominant flow direction across the river; (2) North-to-South flow is only possible at AF, EW, and CA stations; (3) with the exception of gas flow northward from the Norwood and CA stations, all other flows in the northern area are generally southward on the peak day.

Line A, which is related to the C314V expansion, is further described here. It currently consists in a mixture of 18", 20", and 24" diameter pipes, with an overall length of 201,700 feet. It links Butler station (where it receives gas from ANR and TGT) in the north to Norwood station on Line V. The MAOP varies from 150 pounds per square inch ("psig') for the south section to 225 psig for the north section. Actual peak operating pressures have been very close to the MAOP, with average operating pressures for the past 5 years equal to 135 psig in the south and 200 psig in the north. Lateral pipelines that branch from Line A supply residential and industrial customers in the central area. Line A was constructed between 1950-1960, and will need to be upgraded or replaced. Any future replacement will likely be 20" pipes, which would provide additional capacity. Line A was constructed of carbon steel through open trench or bore installation methods. DE planned for the repair, replacement, upgrade, or improvement of two segments of Line A in 2018, at a cost of \$1.2 million, and in 2024 (cost unknown at this time).<sup>43</sup> In the summer, gas typically flows south through Line A.<sup>44</sup> At peak periods, gas generally flows north from Norwood and south from Butler.<sup>45</sup> The upgrades of Line A would increase diameter and/or pressure, so that gas could flow in either direction, based on customer demand and various systems operations.46

Historically, the flow balance over 2006-2014 has been 40% from the north and 60% from Foster.<sup>47</sup> In 2015, the ratio was 45%/55%.<sup>48</sup> Note that without the flow from Foster, DE cannot operate the propane-air ("P-A") peaking plants and blend its gas into the distribution system.<sup>49</sup> DE states that its current design peak demand is 43,000 mcfh, with the P-A plants able to serve up to 10% of the peak design load, i.e., 4,300 mcfh.<sup>50</sup>

<sup>45</sup> Id.

<sup>&</sup>lt;sup>41</sup> Amended Application, p. 2-3.

<sup>&</sup>lt;sup>42</sup> 2017 Long-Term Forecast Report for Gas Demand, Gas Supply, and Facility Projections, Case No. 17-1317-GA-FOR, Report submitted by DE-Ohio to the PUCO ("LTFR").

<sup>43</sup> LTFR, p. 5-14.

<sup>&</sup>lt;sup>44</sup> AV-INT-02-006.

<sup>&</sup>lt;sup>46</sup> AV-INT-02-007.

<sup>47</sup> NOPE-INT-02-007

<sup>48</sup> Id.

<sup>&</sup>lt;sup>49</sup> CITY-POD-01-017 CONFIDENTIAL.

<sup>&</sup>lt;sup>50</sup> NOPE-INT-02-011, NOPE-INT-02-014.

The peak-hour system capacity of the DE system is 45,000 mcfh, including the P-A plants.<sup>51</sup>

The two operational P-A plants overseen by DE are: 1) East Works ("EW") located in Ohio, and 2) Erlanger ("ERL") located in Kentucky. On the historical total peak send-out of 43,250 mcfh on January 6, 2014, the total output of these two plants was around 5,600 mcfh.<sup>52</sup>

# Q. What are the major characteristics of the C314V pipeline extension project?

DE served, on May 26, 2017 (or about 5 months after submitting its application), about 525,000 customers, 427,000 in Ohio and 98,000 in Kentucky.<sup>53</sup> In response to a data request, DE has indicated that it has 538,195 gas customers as of December 2018.<sup>54</sup> However, this information is not broken down by sectors, nor does it include delivery volumes, making it impossible to derive growth implications for the Project. DE has proposed to construct a pipeline (20" diameter, MAOP 500 psig, operating pressure 400 psig) linking the WW Feed station (which will become the Highpoint Park station, including the existing WW Feed and the new equipment for C314V) to the V Line.<sup>55</sup> The WW Feed is located at the intersection of Hamilton, Warren, and Butler counties.

The WW Feed station is the southern terminus of the line C314 pipeline (24" diameter, MAOP 670 psig). C314 receives gas at the Mason station from TGT at 670 psig, and was designed to assist with Line A deliveries as well as to support points to the east served by Line WW. Prior to the operation of C314, DE struggled to maintain pressures above 100 psig in Line A, thus increasing potential pressure drops for customers fed by Line A in the central core of the service area. DE argues that Line A has reached maximum capacity, and, without upgrades, is not capable of supplying additional gas on peak days at its current maximum pressure (i.e., 150 psig). Line A was built between 1940 and 1960, and does not meet current regulatory standards. In the current system, there is a notable pressure drop from 600 psig to 150 psig where C314 connects with WW Feed. This pressure reduction limits the capability of Line C314 to bring greater quantities of gas into the heart of the pipeline system from the north. DE claims that the extension of C314 into C314V has been part of DE's long-term plan for the system. DE claims C314V will bring increased volumes and pressures into the system from the north, eliminating some of the existing system constraints. The new station on Line V will further reduce pressure at the connection with Line V.

#### Q. What are DE's stated objectives for the C314V pipeline extension project?

<sup>&</sup>lt;sup>51</sup> NOPE-INT-02-019.

<sup>&</sup>lt;sup>52</sup> NOPE-INT-02-012.

<sup>&</sup>lt;sup>53</sup> NOPE-INT-01-027.

<sup>54</sup> Staff DR-19-003.

<sup>&</sup>lt;sup>55</sup> Amended Application, pp. 2-1 to 2-2.

DE has identified three goals for the C314V pipeline project:

(1) Retire the two operating P-A peaking plants (claimed by DE to have reached the end of their useful lives).

(2) Provide a better balanced system supply from north to south.

(3) Support inspection, replacement, and upgrading of aging infrastructure.<sup>56</sup>

#### Q. How did DE select the Central Corridor Project?

DE has used the proprietary Gas Synergi Version 4.7 model, originally developed by Stoner Associates, to model each conceived system expansion at peaking time, in order to determine the system's ability to fulfill long-range objectives. The Synergi model is widely used in the natural gas industry, and simulates both flows and pressures throughout the network. It accounts for demographics, regions of concentrated demand growth, and contemplated pipeline replacement or pressure changes. DE claims to have evaluated a wide variety of solutions to its system issues, including no action, replacement in place of the existing backbone (Line A from Line WW to Line V), and a variety of system improvements. However, no details were provided in the Amended Application on these replacements and improvements. In addition, DE's flow studies have shown that the propane-air mixture can travel extensively throughout the system.<sup>57</sup>

#### Q. What scenarios did DE test using the Synergi model?

The Amended Application indicates that the Synergi model was run for a design-day peak demand of 45,500 mcfh, with a 1% (0.01) probability of exceedance.<sup>58</sup> This value was based on load growth forecasts and peaking factors.<sup>59</sup> However, in its Amended Application, DE does not provide any information about these forecasts and factors, and one can only speculate as to the time horizon to which they apply. Three scenarios were tested:

1. P-A plants retired - C314V not constructed (Fig. 3.5)

According to the Synergi model, DE's current system cannot maintain sufficient pressure to serve all customers. Increasing flow from the northern gates is not possible without C314V and flow from Foster would be maximized. Approximately 50,000 customers would not be served.<sup>60</sup> However, this conclusion is contingent upon the validity of the 45,500 mcfh target, which I have demonstrated earlier is not valid.

2. P-A plants retired - C314V constructed - Foster flow maximized (Fig. 3.6)

<sup>&</sup>lt;sup>56</sup> Amended Application, p. 2-1. See Direct Testimony of Gary J. Hebbeler, pp. 8-14.

<sup>&</sup>lt;sup>57</sup> Amended Application, p. 3-6, Figs. 3.3 and 3.4.

<sup>58</sup> NOPE-INT-01-042.

<sup>59</sup> CITY-INT-01-022 CONFIDENTIAL.

<sup>&</sup>lt;sup>60</sup> Amended Application, pp. 3-6 to 3-7.

The system could serve all customers, with the following major peak supplies: Foster: 23,057 mcfh – maximized; Fernald: 4,200 mcfh; Mason:7,727 mcfh (including 4,600 mcfh to C314V); and Other northern gates: 10,516 mcfh. The Foster/northern gates flow ratio ("F/N") would then be: 51%/49%.<sup>61</sup>

#### 3. <u>P-A plants retired – C314V constructed – C314V flow maximized (Fig. 3.7)</u>

The system could serve all customers, with the following major peak supplies: Foster: 18,835 mcfh; Fernald: 4,900 mcfh; Mason: 11,736 mcfh (including 8,400 mcfh to C314V); and Other northern gates: 10,029 mcfh. The F/N would then be: 41%/59%.<sup>62</sup>

The above analyses indicate that Foster would supply natural gas in the range of 18,835 - 23,057 mcfh, with the balance supplied by the northern gates. Also noteworthy is the increase in flow from Fernald to 4,200-4,900 mcfh, thus including 1,800 mcfh to help replace the eliminated P-A flow.

#### Q. What other Synergi data does DE provide in the Amended Application?

In addition to the above three cases with a design-day peak demand of 45,500 mcfh, DE also mentions a Base Case System ("BCS") configuration, with a design-day peak demand of 43,000 mcfh, with the P-A plants in operation and interruptible customers curtailed.<sup>63</sup> Although DE does not expressly state it, BCS is clearly a depiction of the existing system in 2017. The results, which included a network map with flows at key city gates and a data table listing pressures at nodes, were provided under separate cover to Ohio Power Siting Board ("OPSB") Staff. In discovery, DE provided peak-hour flow data for the BCS.<sup>64</sup> The flow from Foster is 21,700 mcfh, and the sum of the flows from the 21 northern gates is 35,030 mcfh (including the flow from Fernald at 4,565 mcfh). In addition, the total flow from the P-A plants is 4,325 mcfh.

#### Q. Has Duke shown they need the C314V line if the P-A plants are retired?

Summing all the BCS flows above yields 62,412 mcfh, which is about 50% more that the design flow of 43,000 mcfh. This discrepancy might be due to the interruptible customer flows being supplied, or because all the 21 northern gates flows are not independent

<sup>&</sup>lt;sup>61</sup> *Id.*, pp. 3-8 to 3-9.

<sup>&</sup>lt;sup>62</sup> *Id.*, pp. 3-9 to 3-10.

<sup>&</sup>lt;sup>63</sup> *Id.*, p. 3-10.

<sup>&</sup>lt;sup>64</sup> NOPE-INT-01-039.

(which of course would negate the basic definition of city gate). In any case, the data +would suggest that the 43,000 mcfh demand could be supplied without the P-A plants.

#### Q. Are there other factors leading DE to select the C314V line?

A likely important factor for DE to select the Project is the connection to C314, taking advantage of its unused capacity. In answer to an interrogatory,<sup>65</sup> DE provides the following design-day peak flows in the Base Case System from C314 into:

- Line WW westward: 1,222 mcfh

- Line WW eastward: 1,774 mcfh

These values indicate a throughput of 2,996 mcfh over C314. With C314V installed and its flow maximized (see above), the total flow from Mason over C314 would be 11,736 mcfh, including 8,400 mcfh into C314V. Thus, the planned peak flows from C314 into Line WW would be 3,336 mcfh, just about 10% larger than in the Base Case. Assuming that 11,736 mcfh is close to the capacity of C314, then this capacity is probably only used currently at a 25% rate. So, if DE's goal is to maximize the use of C314 capacity, C314V is a rational choice. However, this goal was not stated as a basis of need in the Application, and is not consistent with other evaluation factors, as will be discussed further below.

#### Q. What routes did Duke select for the C314V Project?

DE indicates that 28 route variants of C314V were evaluated, with a scoring system reducing them to 3 primary routes.<sup>66</sup> It proposed two routes in its Amended application: (1) the Preferred Route ("PR"), ending at the Fairfax station on the V line, and (2) the Alternate Route ("AR"), ending at the Norwood station and also called the Green Route.<sup>67</sup> The project would involve expansions of the WW Feed and Norwood stations, or the construction of a new station at Fairfax (i.e., if the PR is selected). DE states that the PR would provide better pressure distribution in the eastern part of the Hamilton County system, both east and west on Line V.<sup>68</sup> It would also provide more pressure and flow towards the California station, providing the ability to more directly offset flows from Foster through the pipeline AM04.<sup>69</sup> As a result of the OPSB Staff recommendation that the AR route be selected,<sup>70</sup> DE has subsequently submitted to the OPSB a slightly modified version of the AR in April 2018, involving 7 adjustments to the original AR.<sup>71</sup> Land-use and other major characteristics of both routes in their final

<sup>71</sup> C314V Central Corridor Pipeline Extension Project – Supplemental Information. Report prepared by CH2M for Duke Energy. April 2018.

<sup>&</sup>lt;sup>65</sup> NOPE-INT-02-042.

<sup>&</sup>lt;sup>66</sup> Amended Application, p. 2-5.

<sup>67</sup> Id., pp. 2-5 to 2-8.

<sup>&</sup>lt;sup>68</sup> *Id.*, p. 2-7.

<sup>&</sup>lt;sup>69</sup> Id.

<sup>&</sup>lt;sup>70</sup> Staff Report of Investigation – Duke Energy Ohio C314V Central Corridor Pipeline Extension Project. Ohio Power Siting Board. May 2017.

forms are presented in **Exhibit JMG-5.** Note that the total capital costs (\$128.2 Million for AR and \$111.7 Million for PR) do not include the costs for decommissioning the P-A plants.

# Q. Will the C314V project achieve DE's stated goal of improving north to south flow across the system?

No. While the proposed pipeline would allow additional natural gas to be obtained from northern gates and moved southward through the system to serve customers, thus reducing the demand from Foster, this improvement would be minimal and would add minimal reliability. Under the "C314V flow maximized" scenario, the system would still rely on Foster for 41% of its supply at peak time.<sup>72</sup> An outage at Foster would still jeopardize much of DE's market. This is dramatically illustrated in Figure 3.7 of the Amended Application, where the geographical reach of the flow from Foster is delineated. DE's discovery responses<sup>73</sup> recognize that 1) "the proposed 20" pipeline is expected to reduce reliance from 55% to 45% from Foster" and 2) "the need to balance supply will no longer be fully met". In addition, DE recognizes that the Green or Alternate Route would reduce the reliance on Foster only from 55% to 50%.<sup>74</sup> As demonstrated below, there are other options that Lummus developed for DE that would nearly eliminate DE's reliance on Foster.

#### Q. Has Duke adequately shown the need to retire the PA plants?

No. The propane Duke uses is purchased, delivered by truck, and stored underground in mined rock caverns near the Ohio River. Descriptions of these facilities are available in the Lummus Report.<sup>75</sup> The Lummus Report indicates the following peak outputs: (1) EW: up to 1460 mcfh; (2) ERL: up to 2,250 mcfh.<sup>76</sup> These figures suggest that the P-A plants can inject up to 3,710 mcfh into the system at peak times.

The P-A plants were built in the early 60's. The retirements of the two plants figure prominently among the reasons for building C314V. However, when DE filled its original application with a 30" pipeline in 2016, the P-A plants did not appear to be the emergency now claimed by DE.

In the Amended Staff Report, the only apparent basis for the conclusion that the P-A plants have reached the end of their useful lives was from the 2015 Exeter Report, which states: "The Company's Dicks Creek Plant propane facility is no longer operational due to a geological failure at the Todhunter Propane Cavern. The Eastern Avenue and Erlanger Plant propane facilities are presently operational. However, the potential exists

<sup>72</sup> Amended Application, pp. 3-9 to 3-10

<sup>73</sup> STAFF-DR-12-001; NOPE-INT-01-035.

<sup>&</sup>lt;sup>74</sup> NOPE-INT-02-009

<sup>&</sup>lt;sup>75</sup> Lummus Report, pp. 79-83.

<sup>&</sup>lt;sup>76</sup> Lummus Report, pp. 51, 52.

for these facilities to also become unavailable. DE-Ohio should assess the potential for this to occur and evaluate and determine the Company's optimal interstate pipeline capacity portfolio if this were to occur."<sup>77</sup> However, the geological failure at Todhunter does not imply storage integrity issues at EW and ERL, and DE does not clarify the storage problems at EW and ERL.<sup>78</sup>

In addition, in response to Staff asking how many winter seasons does DE expect to continue using the P-A plants, DE replied: "After the Central Corridor Pipeline is in service and depending on the current system usage, we expect that the propane-air peaking plants will continue to be operational for several years before decommissioning as demand and system configurations are adjusted."<sup>79</sup> This reply certainly does not carry any sense of urgency regarding the retirement of the two plants, but is in contradiction with DE's statements that "the propane facilities are currently at the end of their useful lives" and that the ERL plant would be operable for another three to four years beyond 2013.<sup>80</sup> Further, DE has been active in carrying capital improvement projects over 2017-2018: \$4.84 million for EW and \$1.02 million for ERL.<sup>81</sup> This would confirm that DE plans to continue using the plants.

In any event, DE could replace these plants by new P-A plants with modern technology short periods (a few days per year) of extreme demand the necessary send-out increment, which would have to be otherwise secured, at additional cost, as a peak-day demand reservation from interstate pipelines. The numbers of days when the P-A plants were used in recent years are: 10 in 2015, 13 in 2016, 9 in 2017, and 13 in 2018, mostly in January, with a few additional days either in December or February.<sup>82</sup> The P-A problems of CNGV customers could be solved by increasing CNG storage capacity at customer sites. It is also likely that these customers would use lower interruptible tariffs. Alternatively, the plants could be replaced by a new LNG plant, or by increasing pipeline peaking service. The Lummus Report provides (a cost comparison of these options, assuming 85,000 Dthd of peaking capacity:<sup>83</sup>

Option	Investment (\$ Million)	Operation (\$ Million)			
P-A plants	15.1	9.1			
New LNG plant	146.3	16.8			
Pipeline peaking service	88.0	13.0			

The continued operation of the P-A plants is the most economical option. A new LNG plant would face siting issues (land area, proximity to population), and the only feasible

<sup>&</sup>lt;sup>77</sup> 2015 Exeter Report, p.48.

<sup>78</sup> CITY-INT-01-004 HIGHLY CONFIDENTIAL.

<sup>&</sup>lt;sup>79</sup> STAFF-DR-18-002.

<sup>&</sup>lt;sup>80</sup> STAFF-DR-01-001.

<sup>&</sup>lt;sup>81</sup> STAFF-DR-19-001 CONFIDENTIAL.

<sup>82</sup> STAFF-DR-19-004 SUPPLEMENTAL.

<sup>&</sup>lt;sup>83</sup> Lummus Report, p. 94, Table 21.

alternative would be increasing peaking services. As discussed earlier, it is clear that DE is planning to increase the peak flow from Fernald by 1,800 mcfh under both scenarios of "Foster flow maximized" and "C314V flow maximized". However, this incremental peak flow is independent of the construction of C314V, and does not require new investment on the line from Fernald. This suggests that there is unused capacity on this line, and this might be the case for other lines linked to the northern gates. Unfortunately, the dearth of data provided by DE does not allow for further analysis of this issue.

In summary, there is no current need in retiring the P-A plants. I recommend that DE further assess the costs of upgrading the two P-A plants with modern technology, as well as the feasibility of additional peaking service flows while using existing available capacity from the northern gates.

# Q. Is the C314V Project necessary to support inspection, replacement, and upgrading of aging infrastructure?

The C314V Project is not necessary to achieve this goal. DE intends, as it should, to conduct regular maintenance and upgrades on its existing lines. DE intends to replace sections of Line A over the next 20 years. Sections of Line EE were scheduled to be replaced in 2018 and 2021, i.e., before the scheduled start of C314V. Line V is scheduled for replacements in 2022 and 2023. While C314V could provide 1) alternative feeds to the south end of Line A via Line V, 2) an alternative feed to Line V when segments are disconnected, and/or 3) an alternate feed to Line V and the north section of Line EE when disconnected, DE admits<sup>84</sup> that lines A, EE, and V can be upgraded and/or replaced without operating C314V.

### III. DE APPEARS TO HAVE BETTER ALTERNATIVES TO THE C314V PROJECT THAT REQUIRE FURTHER CONSIDERATION.

#### Q. Do you think there are better alternatives to the C314V proposal?

Yes. First, as explained above, credible projections indicate that there will be limited growth of natural gas demand in DE service territory. With continued conservation efforts and the possible effects of climate change, notwithstanding the occasional polar vertex, it is likely that the current system, even without the P-A plants, could serve the peak-day demand for the foreseeable future. At the very least, market growth should be re-assessed.

Second, C314V does not achieve the goal of re-balancing the supply system from the south to the north, with Foster still supplying natural gas within the range 18,835 - 23,057 mcfh out of the hypothesized total peak demand of 45,500 mcfh (or 41% to 51% of the total supply). Therefore, C314V does not materially improve the reliability of the overall

<sup>&</sup>lt;sup>84</sup> NOPE-RFA-01-001.

system, and it leaves DE customers exposed to the consequences of a Foster supply interruption.

Third, even if capacity expansion is ultimately deemed necessary, there are better options that would reduce population exposure to a new line and improve overall reliability. In order to describe such options, it is necessary first to describe the expansion scenarios prepared and analyzed by Lummus.

#### Q. Please describe the expansion scenarios presented in the Lummus Report.

The Lummus Report emphasizes the need for capital expansion due to an ever-changing market and ever-aging system. Lummus evaluated several options for the purpose of decommissioning the P-A plants, which would require additional supplies of 3710 mcfh (i.e., the approximate peak output of the P-A plants: 54,000 mcfd or 2,250 mcfh for ERL, and 35,000 mcfd or 1,460 mcfh for EW).<sup>85</sup>

The supply of gas itself is not an issue, as third-party interstate transmission companies have the needed capacity and ready access to gas supplies throughout North America. Balancing solutions could be provided within the system by constructing new laterals, a satellite LNG peaking plant, compression facilities, and/or line looping. Lummus submitted each scenario to DE for testing with the Synergi simulation model.

All scenarios assume (1) a system-wide peak demand/send-out of 42,462 mcfh, and (2) no contributions from the P-A plants.<sup>86</sup> The selected peak demand has a probability of 1% of being exceeded.<sup>87</sup> All flows are computed/simulated by Synergi. In addition to a benchmark analysis (i.e., based on the current DE system), there are nine system expansion scenarios. Because of the critical nature of the Foster station, the peak send-outs are described, for each scenario, in terms of (1) the send-out through Foster, and (2) the aggregate send-outs through all the northern gates. There is a small separate send-out to 1,800 customers through the BRC station that is held constant (i.e., around 178 mcfh) in all scenarios, but is not further discussed in this analysis.

The benchmark flows are 25,511 mcfh through Foster and 16,951 mcfh through the northern gates, which constitutes a **60%/40%** F/N split, thus reflecting the vulnerability of the DE system to an interruption at Foster.<sup>88</sup> The foregoing flows reflect the current capability of the system. The gas from Foster serves the whole central loop and southern and eastern parts of the system, and partially extends northward through the A line and eastward through the SS line from the CA station.

### Scenario C-189

<sup>85</sup> Lummus Report, p. 51-52

<sup>&</sup>lt;sup>86</sup> Lummus Report, p. 61.

<sup>&</sup>lt;sup>87</sup> Lummus Report, p. 35.

<sup>&</sup>lt;sup>88</sup> Id.

<sup>&</sup>lt;sup>89</sup> Id., p. 62.

This scenario involves a 9.8 mile, 24" pipeline linking C314 at the WW Station to the V line east of Norwood. It bears some similarity with the Green Route (AR), which is characterized by a 20" diameter and 12.9 mile length. This line would allow an increase of the southward send-out at Mason to 10,663 mcfh (to be compared with 11,736 mcfh under the Amended Application scenario "C314V flow maximized"). The total northern gates send-out would be 22,622 mcfh, and the Foster send-out would be 19,662 mcfh (to be compared with 18,835 mcfh under the Amended Application scenario "C314V flow maximized"). This represents a **46.5%/53.5%** split between Foster and the northern gates (F/N).

Lummus estimated the cost to be in the range of \$52.181 to \$111.817 million.<sup>90</sup> These costs reflect capital costs and do not include external costs (e.g., safety). The capital cost of the Green Route (AR) was estimated at \$111.7 million (see Exhibit JMG-5), which is the upper bound of the Lummus range for C-1. This difference is most likely due to the length difference (i.e., 12.9 vs. 8.8 miles). However, a direct comparison is not warranted, as the Lummus line layout was approximate and did not account for the environmental and socio-economic constraints (unlike the C314V layout). On the positive side, C314V has a smaller pipe diameter (20" vs. 24"), thus possibly reducing safety risks.

#### Scenario C-291

This scenario is the extension of the C314V (Scenario C-1) line to the CA station, involving 18.7 miles of 36" pipe and 1.6 miles of 16" pipe for connection to the V line. The flow at Foster would be reduced to 0 mcfh, and all 42,284 mcfh would be supplied by the northern gates, including 29,187 mcfh through the Mason station. The F/N split is now **0%/100%**. Gas would flow from the northern gates southward through the whole DE system (except for the few customers served by the BRC station). Lummus estimated the cost to be in the range of \$106.078 to \$227.311 million.<sup>92</sup>

#### Scenario C-393

This scenario expands C-2 by adding a 9.9 miles lateral from Red Lion to Mason (36", 675 psig). As Red Lion is in the Lebanon Hub of several interstate pipelines, this line provides increased flexibility to the C-2 expansion. The send-out from Red Lion would then be 28,547 mcfh, the flow at Foster would be 0 mcfh, and all supplies would come through the northern gates, resulting in another F/N split of 0%/100%. Lummus estimated the cost to be in the range of \$149.163 to \$319.636 million.<sup>94</sup>

Scenario W-195

- <sup>92</sup> Id., p. 72.
- 93 Id., pp. 63-64.
- <sup>94</sup> *Id.*, p. 72.

95 Id., pp. 64-65.

<sup>&</sup>lt;sup>90</sup> *Id.*, p. 72.

<sup>91</sup> Id., pp. 62-63.

This western scenario involves a new lateral (18.1 miles, 32", 450 psig) from the Harrison station, supplied by TGT, to the AF station on the Ohio River. The send-out from Harrison would increase to 18,087 mcfh. The Foster send-out would be reduced to 9,134 mcfh, and the total northern gates send-out would be 33,148 mcfh. The F/N split would then be **21.6%/78.4%**. Lummus estimated the cost to be in the range of \$74.278 to \$159.16 million.<sup>96</sup>

#### Scenario W-297

This western scenario is a variation of Scenario W-1. The Harrison-AF lateral would include two parts: 1) 7.6 miles of 36" diameter pipeline, and 2) 10.5 miles of 32" diameter pipeline. In addition, there would be 3 miles of 16" diameter pipeline linking the lateral to the Miami Fort power plant, with the capacity of serving 5,000 mcfh. The send-out from Harrison would increase to 20,772 mcfh. The Foster send-out would be reduced to 6,628 mcfh, and the total northern gates send-out would be 35,654 mcfh. The F/N split would then be **15.67%/ 84.33%.** Lummus estimated the cost to be in the range \$81.349 to \$174.320 million.<sup>98</sup>

#### Scenario W-399

This western scenario involves 21.6 miles of 32" diameter lateral pipeline from the Fernald station to the AF station, but without service to the Miami Fort power plant. The total send-out from Fernald would be 18,087 mcfh. This scenario achieves the same F/N split as W-1 (i.e., **21.6%/ 78.4%)** and the same flows from the Foster and northern gates. It also has ROW acquisition and construction advantages over W-1. Lummus estimated the cost be in the range of \$136.436 to \$292.366 million.<sup>100</sup>

#### Scenario C-1 + W-1<sup>101</sup>

This scenario combines the earlier-reviewed scenarios C-1 and W-1. This combination reduces the send-out from Foster to 1254 mcfh. The send-out from Harrison would be 16,408 mcfh (down from 18,087 mcfh in W-1) while the send-out from Mason would be 10,750 mcfh. Both additional volumes would come from TGT, adding modest improvement in system flexibility. The total northern gates send-out would be 41,028 mcfh. The F/N split would then be **2.96%/ 97.04%.** Lummus estimated the cost to be in the range of \$126.459 to \$270.985 million.<sup>102</sup>

Scenario C-2 + W-2<sup>103</sup>

96 Id., p. 72.

<sup>98</sup> *Id.*, p. 72.

<sup>100</sup> Id., p. 72.

<sup>102</sup> Id., p. 72.

<sup>103</sup> Id., pp. 68-69.

<sup>97</sup> Id., pp. 65-66.

<sup>99</sup> Id., pp. 66-67.

<sup>&</sup>lt;sup>101</sup> Id., pp. 67-68.

This scenario combines the earlier-reviewed scenarios C-2 and W-2. This combination reduces the send-out from Foster to 0 mcfh. The send-out from Harrison would be 15,000 mcfh and the send-out from Mason would be 20,290 mcfh. Both additional volumes would come from TGT, adding modest improvement in system flexibility. The total northern gates send-out would be 42,284 mcfh. The F/N split would then be **0%/100%.** Lummus estimated the cost to be in the range of \$187.427 to \$401.631 million.<sup>104</sup>

#### Scenario E-1105

This scenario involves a 44 mile, 30" diameter pipeline directly linking Red Lion (on the Lebanon Hub) to the CA station. The multiple interconnections at the Lebanon Hub provides much system supply flexibility. The send-out from Red Lion would be 25,414 mcfh, and would be shared as follows at the CA station: 10,573 mcfh to the north of the central loop, and 14,842 mcfh to its southern part. The send-out from Foster would be 0 mcfh. The total northern gates send-out would be 42,284 mcfh. The F/N split would then be **0%/100%.** Lummus estimated the cost to be in the range \$128,629 to \$275,633 million.<sup>106</sup>

#### Q. How does Lummus evaluate these scenarios?

Lummus proposed an evaluation scheme of the nine scenarios it developed.<sup>107</sup> It also considered the "Do-Nothing" ("D-N") option. The criteria considered and their weights (summing up to 1) are as follows:<sup>108</sup>

1. Reliability (0.2):	The ability to reduce gas throughput at Foster
2. Cost (0.4):	Cost effectiveness
3. Constructability (0.1):	Difficulty to obtain easement rights or construct pipelines in the proposed corridor
4. Flexibility (0.05):	The ability to access multiple suppliers
5. New markets (0.05):	CNGV development due to the elimination of P-A plants
6. <u>Regional Growth</u> (0.1)	: Pipeline provides expansion of gas system to areas of new growth, power plant usage.
7. Pipeline upgrades (0.1)	): Regulatory risk, pipeline upgrades obviating the need for planned pipeline expansion, safety, ROW issues

Lummus assigned a score, ranging from 0 to 5, for each scenario regarding each criterion. A score of 5 indicates very strong preference, a score of 0 a very low one. The table below presents the scores, which are then weighted by the criteria weights to obtain a final favorability score for each scenario:<sup>109</sup>

- 106 Id., p. 72.
- 107 Id., p. 91.
- <sup>108</sup> Id.

<sup>&</sup>lt;sup>104</sup> Id., p. 72.

<sup>&</sup>lt;sup>105</sup> Id., pp. 69-70.

Criterion	C-1	C-2	C-3	W-1	W-2	W-3	C-1/W-1	E-1	C-2/W-2	D-N
1	1	5	5	3	3	3	4	5	5	0
2	4	2	1	3	3	1	2	2	0	5
3	4	3	3	3	3	2	3	1	2	5
4	1	1	5	2	2	2	2	5	2	0
5	5	5	5	5	5	5	5	5	5	0
6	1	3	3	3	4	2	3	4	5	0
7	3	4	4	3	3	3	5	2	5	0
Weighted	2.90	3.10	2.90	3.05	3.15	2.05	3.05	3.00	0 2.55	2.50

Lummus' top recommendation is W-2, followed by C-2. DE's choice (i.e., C-1 or PR) is poorly ranked regarding:

- reliability (ability to reduce gas throughput at Foster);

- flexibility (ability to access multiple suppliers); and

- regional growth (expansion of the gas system to areas of new growth, e.g., power plants).<sup>110</sup>

#### Q. Did Duke obtain other route evaluations?

There are more variants for C314V routing. TRC Pipeline Services ("TRC") analyzed 5 preliminary routes (i.e., 1, 3, 4, 5, 8) out of the 28 routes originally developed for DE by the consulting firm CH2M.<sup>111</sup> TRC also generated three additional routes: 1) TRC Western Route, 2) TRC I-71 Route, and 3) TRC Eastern Route.<sup>112</sup> All these routes link the WW Feed station to the V line between Elmwood Place and Fairfax.

Out of the 8 routes analyzed, TRC identified the following 3 top routes:

- Eastern Route, running east of I-71 through Kenwood, Madeira and terminating north of Lunken Airport, with a length of 15.62 miles;

- Western Route, running through Amberly and Golf Manor, and somewhat close to DE's Green Route (AR), with a length of 12.17 miles; and

- Route 8, which is very close to the Green Route, with a length of 12.2 miles.<sup>113</sup>

TRC used a proprietary routing and analysis tool (PPRO: Preliminary Pipeline Route Optimization) with extensive GIS data.<sup>114</sup> This tool can generate low-impact, preliminary pipeline routes based on construction, engineering, environmental, land, and

<sup>110</sup> Id.

112 Id.

<sup>113</sup> Id., pp. 10-14.

<sup>114</sup> Id., p. 6.

<sup>109</sup> Id.

<sup>&</sup>lt;sup>111</sup> Route Evaluation Report – Duke C314V. Report prepared by TRC Pipeline Services for Duke Energy. February 2016, p. 2 (CITY-POD-01-004 CONF attachment), attached as Exhibit JMG-8.

socio-economic factors. Preferred routes use road, pipeline, and powerline corridors, exclude federally-protected lands and cultural resources, and avoid populated areas, moderate slope, and forested wetlands. In order to account for the potential impact on residences within populated and congested areas, TRC used a Potential Impact Radius ("PIR") of 555.5 feet along each route segment and on both sides, using the formula:  $r = 0.69 (pd^2)^{0.5}$ , where p=MAOP=720 psig and d=nominal pipe diameter=30". Because TRC was analyzing DE's original proposal of a 30" pipeline, this PIR leads to a buffer of 1,111 feet in width.<sup>115</sup> The numbers of residences within this PIR and the lengths of the routes are as follows:

- Eastern Route: 650 residences, 15.62 miles

- Western Route: 1009 residences, 12.17 miles

- Route 8: 831 residences, 12.22 miles

TRC's preferred route is the Eastern Route, followed by the Western Route, and finally Route 8.<sup>116</sup> The preference for the Eastern Route is based on the constructability rating of the pipeline. It is higher than the rating of any of the other routes. While it is longer than the other two routes, it is deemed easier and quicker to construct, with less impact to congested and densely populated areas.<sup>117</sup>

The PIR would be 308.6 feet for the final specification of C314V (d=20", MAOP=500 psig). Note that while DE estimates the number of residences within two buffers of width 200 feet and 2,000 feet (see Exhibit JMG-5), it does not show how many residences are with the PIR of 308.6 feet for the PR and AR. DE may not have selected the Eastern Route because of its length of 15.62 miles. However, the TRC analysis and Lummus Report demonstrate that there are other available route options within and outside the Central Corridor with lower residential impact than the AR and PR routes selected by DE.

# Q. If network expansion is ultimately necessary, what are the better alternatives to the proposed C314V line?

The line W-1 (or its minor variant W-2) proposed by Lummus presents the best option by far, both in terms of population exposure and ability to provide a good north-south flow balance as described below. Moreover, DE has not fully explored options in and near the Central Corridor that might be less disruptive in view of its dense urban population. The Eastern Route delineated by TRC is but one example, while another example would be looping/upgrading lines WW and A, although these are not my preferred options as explained below.

#### Q. Could you describe the looping/upgrading alternative?

First, network capacity expansion may take different forms such as pipe replacements, pressure upgrades, line looping, compression, and/or new pipelines over new routes. DE

<sup>115</sup> Id., p. 9.

<sup>&</sup>lt;sup>116</sup> Id., pp. 10-15.

<sup>&</sup>lt;sup>117</sup> *Id.*, p. 11.

selected the last option. As an alternative, looping existing lines eliminates disruption of new population and activities.

In its Amended Application, DE presents two scenarios (A and B) as illustrated on Figures 3.6 and 3.7 respectively, wherein the P-A plants are retired and C314V is in operation. The peak design flow is 45,500 mcfh.

<u>Scenario A</u>: Foster = 23,047 mcfh; Fernald = 4,200 mcfh; Mason = 7,727 mcfh. Mason would send 4,600 mcfh through C314V, and the balance into Line A via Line WW west.

<u>Scenario B</u>: Foster = 18,835 mcfh; Fernald = 4,900 mcfh; Mason = 11.736 mcfh. Mason would send 8,600 mcfh through C314V, and the balance into Line A via Line WW west.

DE claims the difference between 45,500 and the sum of the above flows, in each scenario, is due to the other gate stations.<sup>118</sup> This difference is 6,000 mcfh for Scenario A, and 1,500 mcfh for Scenario B.

Combining the maximum supplies from both scenarios, excluding the flow into C314V, and reinstating the peak flows from the P-A plants, we obtain the following: Foster: 23,057 Fernald: 4,900 Mason: 11,736 – 8,600 (C314V) = 3,136 Other gates: 6,000 P-A plants: 4,325 ------Total: 41,418 mcfh

While the above flow is close to the design flow of 45,500 (which may be significantly overestimated), additional gas between 3,136 and 11,736 mcfh can be brought in from Mason. This could be done by upgrading/looping line WW west and Line A south of the interconnection with WW west. This additional gas could flow south to Norwood and feed the high-pressure loop, and north to customers linked to Line A. Alternatively, these customers could be fed from the north at the Butler station. This upgrading/looping option has not been explored by DE as an alternative to C314V. Using the same ROW, this option could be more economical and much less controversial. DE claims in its Amended Application that, "due to the current status of residential and commercial development around the existing pipelines extending from the north line V", there is not enough ROW width to replace Line A, extending from Line WW to Line V.<sup>119</sup> However, there is no supporting data for this claim. DE simply states that Line A has a variety of easement widths.<sup>120</sup> By using upgrading and looping, this alternative, which is located in the same area as C314V and makes use of gas brought in from Mason, would be much

<sup>&</sup>lt;sup>118</sup> STAFF-DR-08-005; STAFF-DR-08-006.

<sup>&</sup>lt;sup>119</sup> Amended Application, p. 4-3.

<sup>&</sup>lt;sup>120</sup> CITY-INT-01-019.

less disruptive to population and economic activities. However, this option would not improve the overall system reliability and over-dependence on Foster supplies.

#### Q. Could you describe the W-1 alternative?

As described earlier, the W-1 western scenario involves a new 18.1 mile line from the Harrison station, supplied by TGT, to the Anderson Ferry station on the Ohio River. This line would help reduce significantly the Foster send-out to 9,134 mcfh. The F/N gates split would then be **21.6%/78.4%**, which would be a great improvement over the split with C314V, thus ensuring increased reliability and less potential exposure to a supply interruption at Foster. This line would also increase potential access to other interstate suppliers. Finally, a variant of W-1, described as Scenario W-2, would allow serving the Miami Fort power plant through an additional lateral line of 3 miles. Such market growth would not be possible with C314V.

#### Q. Did the Amended Staff Report reference western options?

Yes. In the Amended Staff Report, the OPSB Staff states the following: "The Applicant considered three western options ....in the Gas System Master Plan. The Applicant found that the western options did not allow for retirement of the propane-air peaking plants or improve reliability in the central core area. Additionally, these western options did not allow pipeline inspection and replacement work to be conducted as needed in the central core area."<sup>121</sup>

#### Q. How do you respond to this statement in the Amended Staff Report?

There are several important considerations in response to this assertion.

First, <u>all</u> the scenarios considered and simulated by Lummus assume that the P-A plants are inoperable, and <u>all</u> are able to achieve the target peak-hour send-out of 42,462 mcfh. Thus, the W-1 and W-2 alternatives allow for retirement of the propane-air peaking plants.

Second, the W-1 scenario achieves a F/N split of 21.6%/78.4%, thus improving the reliability of the central core area by reducing the importance of the Foster supply.

Third, the Amended Application does not include any analysis of the western options.

Fourth, the target peak-hour flow in the Amended Application is 45,500 mcfh, which is in excess of 3,000 mcfh compared to the Lummus Report scenarios, likely providing the basis for the incorrect claim that P-A plants cannot be retired. However, to reach such a conclusion, the Synergi model would have to be run for the scenario W-1 under the 45,500 mcfh target. It is quite possible that an increased capacity for the new Harrison-Anderson Ferry line, as well as increased flows from other northern gates could provide

<sup>&</sup>lt;sup>121</sup> Amended Staff Report, p. 28.

for the 3,000 mcfh gap. It is not clear that any such new scenario has been simulated by Synergi.

Fifth, the problems related to inspection and replacement work in the central core area would have to be demonstrated through a new simulation of scenario W-1. DE admits that lines A, EE, and V can be upgraded and/or replaced without C314V.<sup>122</sup> While C314V could provide 1) alternative feeds to the south end of Line A via Line V, 2) an alternative feed to Line V when segments are disconnected, and 3) an alternate feed to Line V and the north section of Line EE when disconnected, it is not clear why, under Scenario W-1, additional gas injected into the loop at the Anderson Ferry station and flowing towards line V would not be able to provide the same support for maintenance/upgrade as new gas flowing from C314V into line V at Norwood or Fairfax.

Finally, as referenced earlier, both the need to retire the P-A plants and the need for a 45,500 mcfh target are doubtful. In sum, the W-1 scenario is fully viable in terms of satisfying possible increased gas needs and of strongly improving the reliability of the system.

#### Q. What analysis have you performed with respect to the W-1 route?

In addition to the above considerations, I have carried out a detailed geographical analysis of the W-1 line to assess its possible impacts on people and economic activities located close to the line. Detailed maps and data tables are available in **Exhibit JMG-6**. The possible layout is illustrated in Figure 1 of Exhibit JMG-6, linking Harrison Avenue to Anderson Ferry Road and crossing the Ohio River at Brower Road. This layout has first been set on a Google Earth image, and then analyzed with a Geographical Information System ("GIS"). As drawn, the line has a length of 16.8 miles, which is 1.3 miles shorter than the length reported by Lummus. Figure 2 presents the jurisdictional boundaries of nearby cities and municipalities. Figure 3 presents the boundaries of a line buffer 2000 ft. wide (i.e., 1000 ft. on each side of the line), together with the boundaries of the Census blocks crossed by the line and its 2000 ft. buffer. Identifying these Census blocks makes it possible to use data from the 2010 Population and Housing decennial Census, namely population, households, and housing units in each block. The population of each block appears on Figure 3. Two distinct analyses and comparisons with DE's estimates have been carried out: (1) population-residence, and (2) land uses.

#### **Population Analysis**

The goal of the population analysis is to estimate the total numbers of people, households, and housing units located within two buffers along the line: 200ft wide (Buffer A) and 2000 ft. wide (Buffer B). Buffer A cannot be graphically represented on the maps due to the map scale. However, it is of course fully represented within the GIS. Each block is then divided into two areas:  $A_1$  = area of the block within the buffer, and  $A_2$  = area of the block outside the buffer. The population-related variables are then

<sup>&</sup>lt;sup>122</sup> NOPE-RFA-01-001.

assigned to the buffer in proportion to the area of the buffer in the block. If  $P_T$  is the total block population, the population in the buffer,  $P_B$ , is estimated as:

$$P_{\rm B} = P_{\rm T} * [A_1/(A_1 + A_2)] \tag{1}$$

This area-proportional allocation is a standard approximation procedure in GIS when using different boundary systems. The results are presented in Table 1 of Exhibit JMG-6, where each block crossed by the line in Hamilton County (OH) and Boone County (KY) is identified, together with its area, population, number of households, and number of housing units. The table also shows the area of each block within the two buffers, and the resulting allocations of the population, households, and housing units. The estimated total population, households, and housing units are indicated at the bottom of the table:

Buffer A: population = 182; Households = 52; Housing units = 64Buffer B: population = 1706; Households = 479; Housing units = 598

A second method of allocation is based on the land cover composition derived from the 2011 U.S. National Land Cover Database ("NLCD"), as presented in Figure 4 of Exhibit JMG-6. Figure 5 of Exhibit JMG-6 expands Figure 4 by including block boundaries, and corresponding population. I have used the total developed area (sum of low-intensity, medium-intensity, and high-intensity developments) within a block as the allocation factor. Using such developed area allows for a more precise pinpointing of where people live. A<sub>1</sub> represents, for each block, the developed area within a buffer, and A<sub>2</sub> the developed area outside the buffer. Formula (1) is then applied, and the results are presented in Table 3 of Exhibit JMG-6. The estimated total population, households, and housing units are indicated at the bottom of the table:

Buffer A: population = 102; Households = 30; Housing units = 38Buffer B: population = 1460; Households = 407; Housing units = 512

A third method of allocation is based on the land-use composition derived from data from Hamilton County Auditor and OpenStreetMap for Boone County, as presented in Figure 6 of Exhibit JMG-6. Figure 7 of Exhibit JMG-6 expands Figure 6 by including block boundaries and corresponding population. The allocation method is similar to the one based on NLCD data, but uses exclusively residential areas. Formula (1) is then applied, and the results are presented in Table 5 of Exhibit JMG-6. The estimated total population, households, and housing units are indicated at the bottom of the table:

Buffer A: population = 121; Households = 35; Housing units = 44 Buffer B: population = 1509; Households = 420; Housing units = 532

The estimates obtained with the three methods have similar orders of magnitude. The third approach, based on residential land use, is probably the most accurate, and is used in the following comparison with DE impact estimates, as presented in **Exhibit JMG-5**. DE does not provide estimates of population and households. Therefore, I can only compare the above estimates with DE's numbers of residences within the two types of

buffer. In Buffer A (200 ft. wide), DE reports the number of residences at 115 in the preferred route (PR) and 182 in the alternate route (AR). These numbers must be compared with 44 housing units for the W-1 line or a reduction of 62% in the PR case and 76% in the AR case. In Buffer B (2000 ft. wide), DE reports the number of residences at 3153 in the preferred route and 2186 in the alternate route. These numbers must be compared with 532 housing units for the W-1 line or a reduction of 83% in the PR case and 76% in the AR case. I conclude that the population exposure to a new pipeline would be considerably lower in the case of Line W-1 compared to the C314V line. It should be further emphasized that the layout of the W-1 line could be improved to further reduce population exposure, but such detailed analysis was not feasible within the framework of the research for this testimony.

#### Land-use Analysis

Table 2 of Exhibit JMG-6 presents the land cover composition of the two buffers, as derived from the NLCD data (Figure 4), including both total areas and shares (%). Table 4 of Exhibit JMG-6 present similar data in the case of the land uses in Figure 6. The focus here is on Buffer B (2000 ft. wide), as DE reports land-use data only for this buffer corridor (see Exhibit JMG-5).

Table 2 indicates that the share of all developed land covers is around 6%, while forests represent 35.4%, cultivated land about 36.1%, open space about 6.9%, and water (Ohio River and other water bodies) about 15.5%. DE's data suggest that built areas (total minus woodlots and parks/recreation) represent around 70% of the C314V buffer for PR and 80% for AR.

Table 4 indicates that woodlots represent 19.3% of the W-1 buffer, to be compared with 14.1% for PR and 11.9% for AR. Commercial-industrial land uses represent 6.5% of the W-1 buffer, to be compared with 37.4% for PR and 40.2% for AR. Park/recreation represents 4.3% of the W-1 buffer, to be compared to 14.5% for PR and 6.8% for AR. It is not clear how to compare DE's paved areas with the data in Table 4.

Overall, the above comparisons indicate that the W-1 line would impact built land-uses and populations much less than the C314V line.

#### Q. Why is this difference in impact important?

Accidents regularly occur along pipelines, due to excavation or malfunctioning, and may result in explosions. The less people in the proximity of the pipeline, the safer. 20-year trend data on serious incident occurrences have been compiled by the Pipeline and Hazardous Materials Safety Administration ("PHMSA").<sup>123</sup> The data show that, over the period 1999-2018, there have been 775 serious pipeline incidents in the U.S., involving 305 fatalities and 1,273 injuries. As an example, on December 5 2017, an accident

<sup>123</sup> See https://www.phmsa.dot.gov/data-and-statistics/pipeline/pipeline-incident-20-year-trends

resulted from third party excavation at a depth of approximately 4 feet which ruptured a 20 inch high pressure natural pas pipeline, with two people killed.<sup>124</sup> This accident occurred in a rural area, hence the low number of casualties. Would it have happened in a high-density urban area, the results would have been catastrophic. In this respect, C314V is a risky project, and the W-1 scenario is a much safer option.

#### Q. What are the conclusions of your testimony?

Based on all the previous analyses, I recommend the following:

First, the C314V application should be denied by the OPSB, because 1) the project is not justified by market growth and related peak requirements; 2) the project does not materially improve the north-south balance and reliability of the system; 3) the need for retirement of the P-A plants is not clearly justified; and 4) the risks involved in operating the pipeline through a high-density populated area are not acceptable.

Second, DE must reassess its market and peak send-out forecasts by 1) re-analyzing longterm growth prospects in light of very recent trends and other information, such as energy conservation; and 2) revising its peak send-out estimation methodology and its use of temperature data in light of likely trends due to global warming.

Third, DE should conduct detailed socio-economic, land-use, and environmental impact analyses of either scenarios W-1 or W-2, as delineated in the Lummus report.

<sup>124</sup> See https://www.phmsa.dot.gov/safety-reports/pipeline-failure-investigation-reports
Curriculum Vitae of Jean-Michel Guldmann

## Curriculum Vitae

# JEAN-MICHEL GULDMANN

	Professor Emeritus and Academy Professor The Ohio State University
BUSINESS ADDRESS	City and Regional Planning Section Austin E. Knowlton School of Architecture 237 Knowlton Hall The Ohio State University (OSU) 275 West Woodruff Avenue, Columbus, Ohio 43210-1138, U.S.A. Phone: (614) 202-9989, Fax: (614) 292-7106 E-Mail: guldmann.1@osu.edu
EDUCATION	Master's Degree in Industrial and Systems Engineering, Ecole des Mines, Nancy, France, 1970 <u>Specialization</u> : Operations Research, Industrial Management.
	Ph.D. in Urban and Regional Planning, Technion - Israel Institute of Technology, 1977 <u>Specialization</u> : Quantitative Planning Methods, Urban Economics, Location Theory, Mathematical Models of Land Use, Transportation Systems, and Environmental Management.
ACADEMIC TEACHING	G POSITIONS
October 2018	Visiting Professor, Department of City and Regional Planning, Gazi University, Ankara, Turkey. Intensive course in Regional Economics and Decision Analysis, Thesis Workshop, and Seminar.
November 2013 – June 2016	Visiting Professor, College of Resources, Environment, and Tourism, Capital Normal University, Beijing, China. Seminars: Decision Analysis Methods; Optimization Methods and Applications.

July 2012 – Professor Emeritus of City and Regional Planning, The Ohio State University.

October 1987 - June 2012	Full Professor of City and Regional Planning, The Ohio State University
-	Graduate Courses Taught at OSU: Introduction to Quantitative Methods, Applications of Quantitative Methods, Urban Planning Data and Forecasting, Static Optimization, Dynamic Optimization, Decision Analysis, Introduction to Analysis of Energy Factors, Seminar on Mathematical Models of Energy Management and Planning, Regional Planning Studio, Outlines of Regional Planning.
October 1985 -	Berman Visiting Professor, Institute of Urban and Regional Studies, The Hebrew University of Jerusalem, Jerusalem, Israel
August 1986	Seminars on optimization methods and energy planning.
October 1982 - September 1987	Associate Professor of City and Regional Planning, The Ohio State University
October 1977 - September 1982	Assistant Professor of City and Regional Planning, The Ohio State University
May-June 1977	Adjunct Lecturer, Ecole Nationale Superieure des Mines de Paris, Paris, France. <u>Course</u> : Methodology for Air Pollution Control and Industrial Location in Urban Areas - graduate level (one quarter).
1975-1976	Adjunct Lecturer at the Louis Pasteur University, Strasbourg, France. <u>Courses:</u> The Environment in the Process of Urban and Regional Planning (undergraduate - two semesters) - Models of Environmental Management (graduate - one semester).
1972-1973	Teaching Assistant in the Program of Urban and Regional Planning, Technion-Israel Institute of Technology. <u>Courses</u> : Quantitative Methods (two semesters) and Mathematical Models of Urban Structure (one semester).
1969-1970	Teaching Assistant in Mathematics at the Department of Mathematics, University of Nancy, France, Undergraduate level (one semester).

# ACADEMIC ADMINISTRATIVE POSITION

October 1, 2005 -	Interim Director, Austin E. Knowlton School of Architecture,
August 31, 2007	The Ohio State University.

# ACADEMIC RESEARCH POSITIONS

1978-1988Senior Faculty Associate, The National Regulatory Research<br/>Institute, The Ohio State University. Regulatory modeling research

on various natural gas distribution issues.

November 1975 - January 1976	Research Associate, Center for Urban and Regional Studies, Technion – Israel Institute for Technology. Ford Foundation Research Grant: Economic Costs of Environmental Quality.
1974-1975	Research Associate, Louis Pasteur University, Strasbourg, France. Research project: Natural Resources and Regional Land Use Planning in Alsace.
1971-1973	Senior Research Assistant, Center for Urban and Regional Studies, Technion - Israel Institute of Technology.

# NON-ACADEMIC PROFESSIONAL POSITIONS

2017-2019	Consultant to California Energy Commission-funded project "Investigating Climate-Change-Induced Vulnerability of the California Northern Natural Gas Energy System and Identifying Resilience Options".
2017-2019	Consultant to Fair Shake Environmental Legal Services – Research and testimony related to Duke Energy's application for pipeline extension.
2007	Consultant to ACP – Visioning and Planning. Population forecasting for a large university town.
1998	Consultant to the President's Commission on Critical Infrastructure Protection (PCCIP). R&D planning for the U.S. natural gas infrastructure.
1995-1996	Consultant to the Centerior Energy Corporation, Cleveland, Ohio. Transmission lines projects evaluation.
1992	Consultant to the Enron Corporation, Houston, Texas. Spot and long-term natural gas pricing assessment.
1987-2012	Consultant to the Information Science Division, Argonne National Laboratory, Argonne, Illinois: (1) Analysis of the random factors in sulfur dioxide emissions and air quality; (2) Studies of natural gas delivery infrastructure; (3) Development of a GIS/MIS for the natural gas industry, (4) Study of natural gas hubs. (Works sponsored by NAPAP, U.S. Department of Energy, Joint Program Office for Special Technology Countermeasures.)
1981-1982	Consultant to the U.S. National Bureau of Standards, Washington, D.C. Development of the rate-making component of the <u>Gas Analysis</u> <u>Modeling System</u> .

1978	Consultant to Contract Research Corporation, Belmont, MA. Development and programming of a location-allocation model for the location of Small Business Administration agencies in the U.S.						
1976-1977	Senior Planner, Regional Planning Agency for Alsace (O.E.D.A.), Strasbourg, France. Principal investigator in the field of environmental management: design of a regional environmental data bank; development of water quality models for the evaluation of wastewater treatment strategies; evaluation of the impact on air quality of alternative industrial site developments; design of solid waste treatment strategies at the regional level; assessment of the impacts of different siting alternatives for nuclear power plants in the Rhine Valley.						
1976-1977	Consultant to the Commission of European Communities, Bruxelles, on the project: Ecological Mapping of the European Community.						
1976-1977	Consultant to the French Ministry of the Environment, Paris, for the preparation of a Handbook for the Design of Regional Environmental Planning Strategies.						
1972	Consultant to the Urban Renewal Authority, Ministry of Housing, Jerusalem, Israel. Data processing and analysis for a large-scale survey over two depressed neighborhoods in the City of Tiberias.						
1970-1971	Transportation Planning Engineer. Haifa Area Transportation Planning Agency, Haifa, Israel. Public transportation planning and urban network analysis.						
AWARDS							
1974	Sagorski Prize, for outstanding thesis in the Social Sciences, Technion - Israel Institute of Technology						
1979	Haifa Municipality Technology Prize, for the study "Centralized Air Pollution Treatment and the Optimal Location of Industries."						
1982	Engineering Research Award, College of Engineering, The Ohio State University.						
1985-86	Berman Visiting Professorship–The Hebrew University of Jerusalem.						
1986	Local Government Scientific Research Prize, for the book "Industrial Location and Air Quality Control: A Planning Approach" - 8th National Congress on Local Government and Administration, Ministry of the Interior, Ierusalem.						

1991	Ameritech Prize, Graduate School, Ohio State University.
2001	Lumley Research Award, College of Engineering The Ohio State University.
2014	Member, Emeritus Academy, The Ohio State University.

## **MEMBERSHIP IN PROFESSIONAL SOCIETIES**

American Economic Association Regional Science Association International Association for Energy Economics INFORMS (Operations Research/Management Science - full member)

## PRESENTATIONS IN CONFERENCES, CONGRESSES, AND SYMPOSIA

<u>Sixth Annual Conference of the British Section of the Regional Science Association</u>, London, England, August 1973. Presentation: A Model of Air Quality Impact on Industrial Land Use Allocation, (with D. Shefer).

<u>Fourteenth European Congress of the Regional Science Association</u>, Karlsruhe, West Germany, August 1974. Presentation: Indivisibilities, Economies of Scale and Air Quality Management, (with D. Shefer).

<u>Committee on Urban Economics, U.S.A. Annual Conference</u>, Santa Fe, New Mexico, March 1976. Presentation: Dynamic Planning of Industrial Location and Design of Central Regional Air Pollution Control Systems (with D. Shefer).

<u>Optimization Days</u>, Ecole Polytechnique, Montreal, May 1978. Presentation: Visual Impact and the Location of Activities: A Combinatorial Optimization Methodology.

<u>NARUC Biennial Regulatory Information Conference</u>, Columbus, Ohio, October 1978. Presentation: Regulatory Simulation Model (RSM) for Gas Distribution Utilities, (with D.Z. Czamanski).

<u>Twenty-fifth North American Meeting of the Regional Science Association</u>, Chicago, November 1978. Presentation: Evaluation of Natural Gas Allocation Policies in Consuming Regions with a Simulation Model, (with D.Z. Czamanski).

<u>Twenty-sixth North American Meeting of the Regional Science Association</u>, Los Angeles, November 1979. Presentation: Solar Energy and Access to Sunlight: An Optimization Model of Energy Supply and Land-Use Design.

<u>Canadian Regional Science Association Meeting</u>, Montreal, June 1980. Presentation: A Chance-Constrained Programming Model for Air Quality Control and Locational Decisions.

Twentieth Regional Science Association European Congress, Munich (W. Germany), August

1980. Presentation: Modeling the Interactions Between Geothermal Energy Use and Urban Structure

<u>V. Symposium Uber Operations Research</u>, Koln (W. Germany), August 1980. Presentation: Meteorological Variability and Air Quality Management: A Stochastic Optimization Approach.

<u>ORSA/TIMS Joint National Meeting</u>, Colorado Springs, November 1980. Presentation: The Optimal Location of Vegetated Buffer Zones in Urban Areas as a Means for Air Quality Management.

<u>Twelfth Annual Modeling and Simulation Conference</u>, Pittsburgh, May 1981. Presentation: Econometric Modeling of Electricity Distribution Capacity Costs and Implications for Marginal Cost Pricing.

<u>Twenty-eighth North American Meeting of the Regional Science Association</u>, Montreal, November 1981. Presentation: Impacts of Market Size and Mix, Population Density, and Climate on Gas Distribution Networks Investments in Urban Areas.

<u>ORSA/TIMS Joint National Meeting</u>, Detroit, MI April 1982. Presentation: A Marginal Cost Pricing Model for Gas Distribution Utilities.

<u>NARUC Biennial Regulatory Information Conference</u>, Columbus, Ohio, September 1982. Presentation: The Allocation of Gas Distribution Plant Costs Based on Marginal Costs by Customer Class, (with C. Aki and K. Lee).

<u>Twenty-ninth North American Meeting of the Regional Science Association</u>, Pittsburgh, PA November 1982. Presentation: Modeling the Structure of Electricity Distribution Costs in Urban Areas.

<u>Twenty-third European Congress of the Regional Science Association</u>, Poitiers (France), August 1983.

Presentation: A Structural Framework for the Design of Integrated Environmental and Land-Use Planning Optimization Models.

<u>Thirtieth North American Meeting of the Regional Science Association</u>, Chicago, November 1983. Presentation: The Dynamics of Utility Systems at the Urban Fringe.

<u>Fifteenth Annual Modeling and Simulation Conference</u>, Pittsburgh, PA April 1984. Presentation: A Chance-Constrained Dynamic Model of Air Quality Management.

<u>Twenty-fourth European Congress of the Regional Science Association</u>, Milan (Italy), August 1984. Presentation: Econometric Modeling of the Vintage Structure and Dynamics of Urban Gas and Electric Distribution Systems, (with Y.W. Lee).

<u>Colloque de l'Association de Science Regionale de Langue Francaise (ASRDLF)</u>, Lugano (Switzerland), September 1984. Presentation: Couts et Tarification d'un Service Public Urbain: le Cas de la Desserte Gaziere.

Thirty-third North American Meetings of the Regional Science Association, Columbus, Ohio,

November 1986. Presentation: Cross-Subsidizations in the Provision of Urban Utility Services.

<u>ORSA/TIMS Joint National Meeting</u>, Washington, D.C., April 1988. Presentation: Optimal Gas Contract Portfolio Selection Methodologies.

<u>Twenty-eighth European Congress of the Regional Science Association</u>, Stockholm (Sweden), August 1988. Presentation: Modeling the Cost Structure of Local Telephone Networks.

<u>Telecommunications Costing in a Dynamic Environment Conference</u>, San Diego, April 1989. Presentation: Disaggregate Capital and Operating Cost Functions for Local Exchange Companies. (Paper also presented at the CAST symposium <u>Alternative Methods for</u> <u>Telecommunications Regulation: Price Caps?</u>, The Ohio State University, June 1989).

<u>Eleventh Annual North American Conference of the International Association for Energy</u> <u>Economics</u>, Los Angeles, October 1989. Presentation: Optimal Capacity Expansion and Peak Load Pricing: A Case Study of the New England Gas Market (with D.A. Hanson).

<u>Symposia on Marginal Cost Techniques for Telephone Services</u>, Seattle, July 1990, and Columbus, August 1990. Presentations: (1) Disaggregate Capital and Operating Marginal Costs for Local Exchange Companies, and (2) Point-to-Point Marginal Costs for the Switched Network.

<u>Thirtieth European Congress of the Regional Science Association</u>, Istanbul (Turkey), August 1990. Presentation: Spatial Interaction Models of Sectoral Telecommunication Flows.

<u>Thirty-second European Congress of the Regional Science Association</u>, Louvain-la-Neuve (Belgium), August 1992. Presentation: Input-Output Modeling of Regional Telecommunication Flows.

<u>Thirty-fourth Annual Meeting of the Association of Collegiate Schools of Planning</u>, Columbus (Ohio), October 1992. Presentation: Assessing the Regional Economic Impacts of the Clean Air Act Amendments of 1990.

<u>1993 National Telecommunications Forecasting Conference</u>, Washington, D.C., June 1993. Presentation: Analysis of Intersectoral Business Telecommunications Demand: A Combined Input-Output/Gravity Model Approach.

<u>Thirty-fourth European Congress of the Regional Science Association</u>, Groningen (The Netherlands), August 1994. Presentation: Telecommunications, Information Exchange, and Spatial Interaction: Theoretical Framework and Empirical Results.

<u>Forty-first North American Meeting of the Regional Science Association International</u>, Niagara Falls (Canada), November 1994. Presentation: A Spatial Equilibrium Model for City Size, Urbanization Ratio and Rural Structure (with Fahui Wang).

Forty-second North American Meeting of the Regional Science Association International.

Cincinnati,

November 1995. Presentation: Simulating Urban Population and Employment Densities with a Garin-Lowry Model (with Fahui Wang).

<u>Thirty-sixth European Congress of the Regional Science Association</u>, Zurich (Switzerland), August 1996. Presentation: Urban Transportation Network Design, Traffic Allocation, and Air Quality Control: An Integrated Optimization Approach (with W.S. Kim).

<u>Forty-fourth North American Meeting of the Regional Science Association International</u>, Buffalo, New York, November 1995. Presentation: Hub-and-Spoke Network Design: A General Model and Numerical Results (with Guoqiang Shen).

<u>Thirty-eighth European Congress of the Regional Science Association</u>, Vienna (Austria), August 1998.

Presentation: Competing Destinations and Intervening Opportunities Interaction Models of Inter-City Telecommunication Flows.

<u>Fortieth European Congress of the Regional Science Association</u>, Barcelona (Spain), August 2000.

Presentation: Spatial Interaction Models of International Telecommunication Flows.

<u>Forty-first European Congress of the Regional Science Association</u>, Zagreb (Croatia), August 2001.

Presentation: Impacts of Telecommunication Infrastructure on Rural Development.

<u>Forty-second European Congress of the Regional Science Association</u>, Dortmund (Germany), August\_2002. Presentations: (1) International Water Resources Allocation and Conflicts - The Case of the Euphrates and the Tigris (with M. Kucukmehmetoglu), and (2) Spatial Interaction Modeling of Interregional Commodity Flows (with M. Celik).

<u>American Geophysical Union (AGU) Chapman Conference on Ecosystem Interactions with</u> <u>Land Use</u>, Santa Fe, New Mexico, June 14-18, 2003. Presentation: Development of the Optimal Land-Use Pattern with Minimal Non-point Source Pollution (with I. Yeo and S.I. Gordon).

<u>Fiftieth North American Meeting of the Regional Science Association International</u>, Philadelphia, Pennsylvania, November 2003. Presentation: Geography and the Cost of Network Infrastructure: The Case of Local Telephone Systems (with M. Cubukcu).

<u>American Geophysical Union (AGU) Annual Fall Meeting</u>, San Francisco, California, December 10-14, 2003. Presentation: Hierarchical Regression Approach to the Global Optimal Solution (with I. Yeo and S.I. Gordon).

<u>Forty-Sixth Annual Meeting of the Association of Collegiate Schools of Planning</u>, Portland (Oregon), October 2004. Presentation: Land Use Optimization for Nonpoint Source Water Pollution Control (with I. Yeo and S.I. Gordon).

<u>Forty-Fifth European Congress of the Regional Science Association</u>, Amsterdam (The Netherlands), August\_2005. Presentations: Multi-Objective Programming for the Allocation of Trans-Boundary Water Resources - The Case of the Euphrates and the Tigris (with M.

Kucukmehmetoglu).

<u>ASCE/EWRI Watershed Conference</u>, Williamsburg, VA, July 2005. Presentation: Multistage Hierarchical Optimization for Land Allocation to Control Nonpoint Source Water Pollution (with I. Yeo and S.I. Gordon).

<u>Mid-Continent Regional Science Association Conference</u>, Indianapolis, June 2006. Presentation: Estimating Suppressed Data in Regional Economic Databases: A Goal-Programming Approach (with S. Zhang).

<u>Forty-Seventh Annual Meeting of the Association of Collegiate Schools of Planning</u>, Fort Worth (Texas), November 2006. Presentation: Impacts of Urban Containment Policies (Urban Growth Boundaries, Urban Service Areas, and Greenbelt) on the Regional Economy (with M. Woo).

<u>Annual Meeting of the Association of American Geographers</u>, San Francisco, CA, April 2007. Presentation: Analysis of Urban Spatial Structure under Urban Containment Land Use Policies (with M. Woo).

<u>Forty-Eighth Annual Meeting of the Association of Collegiate Schools of Planning</u>, Milwaukee (Wisconsin), October 2007. Presentation: Urban Air Pollution, Traffic Volumes, and Road Congestion (with Y. Kim).

<u>American Geophysical Union Conference</u>, San Francisco (CA), December 2007. Presentation:

Is the Relationship Between Peak Runoff Discharge and Land-Use Patterns Convex? Numerical Experiment with the IHLUO Model (with I. Yeo).

Energy Systems Modeling Symposium, The Ohio State University, December 2007. Presentation:

Natural Gas Infrastructure Modeling: From Local Distribution to Trans-boundary Networks.

<u>Annual Meeting of the Association of American Geographers</u>, Boston, MA, April 2008. Presentation: Urban Vegetation: Is It Really Helpful for Air Pollution Mitigation? (with Y. Kim and Y.T. Leem).

<u>ACSP-AESOP 4th Joint Congress</u>, Chicago, IL, July 6-11, 2008.Presentation: No Driving for a Day per Week: Collective Actions for Urban Traffic Congestion (with Y. Kim).

<u>Seventh Annual CMAS Conference</u>, Chapel Hill, NC, October 2008. Presentation: Impacts of Traffic Volumes and Wind Directions on Air Pollution Concentrations in Seoul, Korea (with Y. Kim and H-M Ra).

<u>Forty-Eighth Annual Meeting of Western Regional Science Association</u>, Napa, California, February 2009. Presentation: Accessibility, Diversity, and Dynamics of Locations of Jobs and Population (with S. Zhang).

<u>Third World Conference of Spatial Econometrics</u>, Barcelona, July 8-10, 2009. Presentation: Modelling the Spatial Dependence of Shopping Center Trade Areas (with B. Ozuduru). <u>Thirty-Ninth Annual Meeting of the Urban Affairs Association: Contesting and Sustaining the</u> <u>City: Neighborhood, Region, or World</u>, Chicago, Illinois, March 2009. Presentation: Incorporating College Population into Cohort-Component Population Forecasting (with S. Zhang).

<u>UKC2009, Korean-American Scientists and Engineers Association (KSEA) Conference</u>, Raleigh, North Carolina, July 16-19, 2009. Presentation: Three-Dimensional City Model Based on Data Fusion for Virtual Environments (with B. Chun).

<u>Fiftieth Annual Meeting of the Association of Collegiate Schools of Planning</u>, Crystal City, Virginia, October 2009. Presentation: Reduced Traffic During The Weekend: Is It Good for Urban Air Quality? (with Y. Kim).

<u>Annual Meeting of the Association of American Geographers</u>, Washington, DC, April 2010. Presentation: Relationship Between High-rise Building Patterns and Land Values, using LiDAR, GIS, and Appraisal Data (with B. Chun).

<u>Fifty-First Annual Meeting of the Association of Collegiate Schools of Planning</u>, Minneapolis, Minnesota, October 2010. Presentation: Two- and Three-Dimensional Urban Core Determinants of the Urban Heat Island: A Statistical Approach (with B. Chun).

<u>Fifty-First Annual Meeting of the Association of Collegiate Schools of Planning</u>, Minneapolis, Minnesota, October 2010. Presentation: A Computable General Equilibrium Model of the City: Impacts of Locational Restrictions and Zoning (with C. Olwert).

<u>Fifty-Second Annual Meeting of the Association of Collegiate Schools of Planning</u>, Salt Lake City, Utah, October 2011. Presentation: Urban Core Determinants of the Urban Heat Island: Spatial Statistical Approach (with B. Chun).

<u>Ohio Transportation Engineering Conference (OTEC)</u>, Columbus, Ohio, October 2011. Presentation: Transportation Trends: How Do We Explain VMT? (with G. Akar).

<u>Transportation Research Board 91st Annual Meeting (TRB)</u>, Washington, D.C., January 2012.

Presentation: Another Look at VMT: Determinants of Vehicle Use in Two-Vehicle Households (with G. Akar).

<u>Fifty-Third Annual Meeting of the Association of Collegiate Schools of Planning</u>, Cincinnati, Ohio, November 2012. Presentation: A Spatial Panel Modeling Approach for the Assessment of Seismic Losses and Land-Use Planning (with C.-H. Wang).

<u>Transportation Research Board 92nd Annual Meeting (TRB)</u>, Washington, D.C., January 2013.

Presentation: Do your Neighbors Affect your Mode Choice: A Spatial Probit Model for Commuting to The Ohio State University (with C.-H. Wang and G. Akar).

<u>Fifty-Second Annual Meeting of the Western Regional Science Association (WRSA)</u>, Santa Barbara, California, February 2013. Presentation: Macro-Level Analysis of the Impacts of Urban Factors on Traffic Crashes: A Case Study of Central Ohio (with D. Lee and B. Von Rabenau). <u>Beijing Forum 2013</u>, Beijing, China, November 1-3, 2013. Invited presentation: Urban Heat Island Reduction through Urban Design and Planning Decisions: Combining Spatial Statistics and Simulation Models.

Sixtieth Annual North American Meeting of the Regional Science Association International (RSAI), Atlanta, Georgia, November 2013. Presentation: A Spatial Analysis of the Impact of Urban Environment Factors on Age-related Crashes in the Central Ohio Region (with D. Lee and B. Von Rabenau).

Sixtieth Annual North American Meeting of the Regional Science Association International (RSAI), Atlanta, Georgia, November 2013. Presentation: A land-use allocation optimization model to mitigate potential seismic losses (with C.-H. Wang).

Sixtieth Annual North American Meeting of the Regional Science Association International (RSAI), Atlanta, Georgia, November 2013. Presentation: Solar Energy Access and Complex Urban Cores Three-Dimensional Morphology: A Spatial Statistical Approach (with B. Chun).

<u>Fifty-Fourth Annual Meeting of the Association of Collegiate Schools of Planning (ACSP)</u>, Philadelphia, PA, October 2014. Presentation: Driver Demographics and Car Crashes: Implications for Urban Planning (with D. Lee and B. von Rabenau).

<u>Fifty-Fourth Annual Meeting of the Association of Collegiate Schools of Planning (ACSP)</u>, Philadelphia, PA, October 2014. Presentation: Statistical Modeling and Simulation of Parcel-Level Land Development Dynamics (with E. Tepe).

<u>INFORMS 2014 Annual Meeting</u>, San Francisco, November 2014. Presentation: Optimization of Roof and Ground Greening Strategies to Mitigate the Urban Heat Island (with B. Chun).

<u>INFORMS 2014 Annual Meeting</u>, San Francisco, November 2014. Presentation: A Chance-Constrained Optimization Model of Urban Land-Use Allocation under Seismic Hazard (with C.-H. Wang).

<u>Fourth Forum of Chinese Energy and Resources Economics and Management (CEREM)</u>, Xuzhou, China, July 2015. Invited keynote presentation: Optimization of Green Roof and Green Space Allocation to Mitigate the Urban Heat Island.

Fifty-Fifth Annual Meeting of the Association of Collegiate Schools of Planning (ACSP), Houston, TX, October 2015. Presentation: Impact of Driver Demographics, Built Environment, and Road Conditions on Crash Severity: A Logit Modeling Approach (with D. Lee and B. von Rabenau).

<u>Fifty-Fifth Annual Meeting of the Association of Collegiate Schools of Planning (ACSP)</u>, Houston, TX, October 2015. Presentation: Mitigation of the urban heat island with greening strategies: a nonlinear programming model (with B. Chun).

<u>Sixty-Second Annual North American Meeting of the Regional Science Association</u> <u>International</u> (RSAI), Portland, Oregon, November 2015. Presentation: Parcel-Level Land Development Dynamics: A Spatial and Temporal Autologistic Model (with E. Tepe).

<u>Fifty-Eighth Annual Meeting of the Association of Collegiate Schools of Planning (ACSP)</u>, Buffalo, NY, October 2018. Presentation: Interregional Virtual Water Trading: Implications for Regional Economic Development Under Climate Change (with M.G. Bhatia).

Fifty-Eighth Annual Meeting of the Association of Collegiate Schools of Planning (ACSP), Buffalo, NY, October 2018. Presentation: Characterizing Long-term Changes in Urban Green Infrastructure: A Comparative Study of the Columbus and Atlanta Metropolitan Areas (with Y. Park).

## **INVITED LECTURES**

Environmental Data Banks, Environmental Modeling, and Regional Planning: The Case of Alsace. Lectures given at the Seminar of Applied Ecology, organized by the Ecole Nationale du Genie Rural,

des Eaux et des Forets at Bandol, France (May 26, 1977; November 18, 1976; May 30, 1976).

Pollution Standards and Optimal Location of Activities in a Metropolitan Area: The Particular Case of Air Pollution. Lecture given at the Transportation Research Center, University of Montreal (Nov. 19, 1976).

Natural Resources and Regional Planning in Alsace. Lecture given at the Colloquium Architecture, Landscape and the Environment in Alsace, Institut Qualite Alsace (June 8, 1977), Strasbourg, France.

Technical and Environmental Problems of Using High-Sulfur Coal. Lecture given at the Department of City and Regional Planning, The Ohio State University, Columbus (April 12, 1977).

Where to Put the Collector: Land-Use and Planning Implications of Solar Energy. Lecture given at The Ohio State University Union, Solar Seminar Series (November 17, 1980).

Evaluation of Expansion and Pricing Policies for a Gas Distribution Utility -Simulation and Mathematical Programming Approaches. Lecture given at the Transportation Research Center, University of Montreal (December 17, 1980).

The Use of Mathematical Models in Environmental Quality Management and Land Use Planning. Lecture given at the Department of Geography, Tel-Aviv University (November 12, 1985).

Statistical Models for Urban Infrastructure Planning. Lecture given at the Department of Geography, Haifa University (January 23, 1986).

A Stochastic Approach to the Interactions between Meteorological Variability, Location of

Pollution Sources, and Air Quality Control. Lecture given at the Department of Geography, Ben Gurion University of the Negev (March 23, 1986).

Chance-Constrained Models for Air Quality Management. Lecture given in The Environmental Economics Seminar, Policy and Economic Analysis Group, Argonne National Laboratory (April 24, 1987).

Research on the Gas Industry - A Regulatory Perspective. Lecture given at the ANR Pipeline Company Annual CD-1 Meeting, Scottsdale, Arizona (May 14, 1987).

Natural Gas supply in the 1990s: Contracting, Reliability, and Pricing Issues. Lecture given at the Ohio Energy Strategy Forum, Public Utilities Commission of Ohio, Columbus, Ohio (January 13, 1992).

Uncertainty and Randomness in Environmental Planning Optimization Models. Lecture given at the ORSA Roundtable, Department of Industrial and Systems Engineering, The Ohio State University, Columbus, Ohio (February 3, 1992).

Modeling Inter-industry Telecommunications Flows: Spatial Equilibrium Framework and Empirical Estimates. Lecture given at the Geography Graduate Colloquium, Northern Illinois University, DeKalb, Illinois (April 1997).

Telecommunications and the Regional Economy. Lecture given at the Faculty Colloquium, Faculty of Architecture and Town Planning, Technion - Israel Institute of Technology, Haifa, Israel (December 20, 1999).

Telecommunications Flows in a Regional Economy: A Geographical Perspective. Lecture given at the Departmental Seminar, Department of Geography, The Hebrew University of Jerusalem, Jerusalem, Israel (December 22, 1999).

Statistical Models of Urban and Regional Air Quality: The cases of Ozone and Carbon Monoxide. Lecture given at the Departmental Seminar, Department of Geography, University of Haifa, Haifa, Israel (December 30, 1999).

Modeling Telecommunications Infrastructure and Usage in Rural Areas. Lecture given at the Center for Urban and Regional Analysis (CURA), The Ohio State University (January 18, 2002)

An Empirical Analysis of Shopping Center Locations in Ohio. Lecture given at the DAAP School of Planning Ph.D. Program Colloquium, University of Cincinnati (November 28, 2006).

Optimal Allocation of Stormwater Pollution Control Technologies in a Watershed. Lecture given at the School of Urban and Public Affairs, University of Louisville, Louisville, Kentucky (September 9, 2009).

Spatial Statistical Modeling of the Urban Heat Island in Urban Centers and Suburban Environments. Lecture given at: (1) College of Resources, Environment and Tourism, Capital Normal University, Beijing, China, July 2, 2013; (2) School of Management, Xi'an University of Architecture and Technology, Xi'an, China, July 9, 2013. Data Mining: Optimization Methods to Estimate Missing Data in Regional Economic Databases. Lecture given at the Institute of Geographic Sciences and Natural Resources Research, Chinese Academy of Sciences, Beijing, China, July 4, 2013.

Solar Energy Access and Urban Morphology in Complex Central Core Urban Areas. Lecture given at the Institute of GIS and Remote Sensing, Peking University, Beijing, China, July 8, 2013.

Urban Heat Island Mitigation through Urban Planning: Combining Spatial Regression and Simulation, Center for Urban and Regional Analysis (CURA), The Ohio State University, October 2, 2014.

Spatial Modeling of Earthquake Impacts and Damage Minimization through Land-Use Planning, College of Resources, Environment and Tourism, Capital Normal University, Beijing, China, October 10, 2014.

Optimal Allocation of Land Uses to Minimize Earthquake Damages: Application to Taichung, Taiwan. Lecture given at: (1) Institute of GIS and Remote Sensing, Peking University, and (2 Institute of Geographic Sciences and Natural Resources Research, Chinese Academy of Sciences, Beijing, China, October 2014.

Green Roofs and Green Spaces for the Mitigation of the Urban Heat Island in High-Density Cities. Department of City and Regional Planning, Faculty of Architecture, Middle East Technical University, Ankara, Turkey, October 8, 2015.

Quantitative Methods in Planning: (1) The Urban Heat Island and Green Spaces, and (2) Earthquake Mitigation and Land Use. Lecture given at: (1) Department of City and Regional Planning, Gazi University, Ankara, Turkey, October 9, 2015; (2) Department of City and Regional Planning, Dokuz Eylul University, Izmir, Turkey, October 12, 2015; and (3) Department of City and Regional Planning, Istanbul Technical University, Izmir, Turkey, October 14, 2015. Presentation at Gazi University available at: <u>https://www.youtube.com/watch?v=c4x[laP5Gbs</u>

Mitigation of the Urban Heat Island with Greening Strategies: An Optimization Model. Chinese Academy of Sciences, Institute of Geographic Sciences and Natural Resources Research, State Key Laboratory of Resources and Environmental Information Systems, Beijing, China, May 27, 2016.

Creating 3D City Models with Building Footprints and LiDAR Point Cloud Classification: A Machine Learning Approach. Department of City and Regional Planning, Gazi University, Ankara, Turkey, October 19, 2018.

Impacts of Greenery, Water, and Imperviousness on the Urban Heat Island in Beijing's Olympic Area: Spatial and Uncertainty Analyses. Department of City and Regional Planning, Gazi University, Ankara, Turkey, October 25, 2018.

#### PUBLICATIONS

#### А. Воок

Industrial Location and Air Quality Control: A Planning Approach. (Co-author: D. Shefer). John Wiley and Sons, New York, 1980.

## **B.** CHAPTERS IN BOOKS

- 1. Air Quality Control, Industrial Siting and Fuel Substitution: An Optimization Approach, in <u>Advances in Environmental Science and Technology</u>, Vol. 10, pp. 301-367, 1980, Wiley (with D. Shefer).
- Spatial Interaction Models of International Telecommunication Flows. In <u>Spatially</u> <u>Integrated Spatial Science: Examples in Best Practice</u>, M.F. Goodchild and D.G. Janelle (eds.), Oxford University Press, pp. 100-119, 2004

#### C. PEER-REVIEWED ARTICLES PUBLISHED/IN PRESS

- Mathematical Models of Industrial Plant Location and Pollution Abatement Strategies, <u>Environment</u> and Planning, Vol. 5, No. 5, 1973, pp. 577-588 (with D. Shefer).
- 2. A Model of Air Quality Impact on Industrial Land Use Allocation, <u>London Papers in</u> <u>Regional Science</u>, Vol. 5, 1975, pp. 66-83, Pion, London (with D. Shefer).
- 3. Beit-Shemesh as a Central Place, Its Sphere of Influence and Possible Means of Extending It, <u>Regional Studies</u>, Vol. 9, 1975, pp. 193-202 (with D. Shefer and H. Shear).
- 4. Stack Height as a Means for Air Quality Control: A Mathematical Programming Approach, <u>Journal of Environmental Management</u>, Vol. 4, No. 3, 1976, pp. 241-249 (with D. Shefer).
- 5. Optimal Plant Location and Air Quality Management Under Indivisibilities and Economies of Scale, <u>Socio-Economic Planning Sciences</u>, Vol. 11, No. 2, 1977, pp. 77-93 (with D. Shefer).
- 6. Centralized Air Pollution Treatment and the Optimal Location of Industries, <u>Environment</u> <u>and Planning A</u>, Vol. 9, No. 10, 1977, pp. 1121-1142 (with D. Shefer).
- Industrial Location, Air Pollution Control and Meteorological Variability: A Dynamic Optimization Approach, <u>Socio-Economic Planning Sciences</u>, Vol. 12, No. 4, 1978, pp. 197-214.
- Urban Land Use Allocation and Environmental Pollution Control: An Intertemporal Optimization Approach, <u>Socio-Economic Planning Sciences</u>, Vol. 13, No. 2, 1979, pp. 71-86.
- 9. Visual Impact and the Location of Activities: A Combinatorial Optimization Methodology,

Socio-Economic Planning Sciences, Vol. 13, No. 2, 1979, pp. 47-70.

- 10. The Analysis of New Gas Hook-ups in Ohio, <u>Bulletin of Business Research</u>, Vol. 54, No.3-4, March-April 1979 (with D.Z. Czamanski).
- 11. Solar Energy and Access to Sunlight: An Optimization Model of Energy Supply and Land-Use Design, <u>Environment and Planning A</u>, Vol. 12, 1980, pp. 765-786.
- 12. A Simulation Model of Market Expansion Policies for Natural Gas Distribution Utilities, <u>Energy</u>, Vol. 5, No. 10, 1980, pp. 1013-1043 (with D.Z. Czamanski).
- 13. A Mathematical Experiment in Landscape Planning, <u>Environment and Planning B</u>, Vol. 7, 1980, pp. 379-398.
- 14. Modeling the Interactions Between Geothermal Energy Use and Urban Structure, Energy, Vol. 6, 1981, pp. 351-368 (with B.D. Rosenthal).
- 15. A Chance-Constrained Programming Approach to Natural Gas Curtailment Decisions, <u>Resources and Energy</u>, Vol. 3, 1981, pp. 133-161.
- Supply, Storage, and Service Reliability Decisions by Natural Gas Distribution Utilities: A Chance-Constrained Approach, <u>Management Science</u>, Vol. 29, No. 8, 1983, pp. 884-906.
- 17. Modeling the Structure of Gas Distribution Costs in Urban Areas, <u>Regional Science and</u> <u>Urban Economics</u>, Vol. 13, No. 3, 1983, pp. 299-316.
- 18. Modeling the Location of Greenbelts as a Means for Air Quality Control, <u>Socio-Economic</u> <u>Planning Sciences</u>, Vol. 17, No. 4, 1983, pp. 217-224.
- 19. An Econometric Model of Electricity Distribution Systems in Urban Areas, <u>Environment</u> <u>and Planning A</u>, Vol. 16, 1984, pp. 793-806.
- 20. Une Taxonomie de Modeles Integres d'Amenagement et de Gestion de l'Environnement, <u>Revue d'Economie Regionale et Urbaine</u>, Vol. 6, 1984, pp. 321-346.
- 21. Extending Gas and Electric Lines at the Urban Fringe: A Statistical Analysis, <u>Journal of</u> <u>Environmental Systems</u>, Vol. 14(1), 1984, pp. 77-91.
- 22. A Further Note on the Structure of Gas Distribution Costs in Urban Areas, <u>Regional</u> <u>Science and Urban Economics</u>, Vol. 14, No. 4, 1984, pp. 583-588.
- A Disaggregate Econometric Analysis of Electricity Distribution Capital Costs, <u>Energy</u>, Vol. 10, No. 5, 1985, pp. 601-612.
- 24. Economies of Scale and Natural Monopoly in Urban Utilities: The Case of Gas Distribution, <u>Geographical Analysis</u>, Vol. 17, No. 4, 1985, pp. 302-317.
- 25. A Logit Analysis of Telecommunication Network Bypass Decisions, Socio-Economic

Planning Sciences, Vol. 19, No. 5, 1985, pp. 349-356 (with J. Racster and M.D. Wong).

- 26. A Structural Framework for the Design of Integrated Environmental and Land-Use Planning Optimization Models, <u>Mathematical Modelling</u>, Vol. 7, No. 1, 1986, pp. 61-81.
- 27. Interactions Between Weather Stochasticity and the Locations of Pollution Sources and Receptors in Air Quality Planning : A Chance-Constrained Approach, <u>Geographical Analysis</u>, Vol. 18, No. 3, 1986, pp. 198-214.
- A Marginal Cost Pricing Model for Gas Distribution Utilities, <u>Operations Research</u>, Vol. 34, No. 6, 1986, pp. 851-863.
- 29. Cost Reallocation as a State Regulatory Policy Option in Natural Gas Distribution Pricing, <u>Energy Systems and Policy</u>, Vol. 10, No. 4, 1987, pp. 373-404.
- 30. A Chance Constrained Dynamic Model of Air Quality Management, <u>Journal of Environmental Engineering ASCE</u>, Vol. 114, No. 5, 1988, pp. 1116-1135.
- Land Use, Market Mix, and the Allocation of the Investment Costs of Electricity Distribution Networks, <u>Socio-Economic Planning Sciences</u>, Vol. 22, No. 5, 1988, pp. 201-212.
- 32. Capacity Cost Allocation in the Provision of Urban Public Services: The Case of Gas Distribution, <u>Growth and Change</u>, Vol. 20, No. 2, 1989, pp. 1-18.
- 33. Economies of Scale and Density in Local Telephone Networks, <u>Regional Science and</u> <u>Urban Economics</u>, Vol. 20, No. 4, 1990, pp. 521-535.
- 34. Natural Gas Market Expansion and Delivery Infrastructure Costs: The Case of New England (with D.A. Hanson), <u>Resources and Energy</u>, Vol. 13, No. 1, 1991, pp. 57-94.
- 35. Modeling Residential and Business Telecommunications Flows: A Regional Point-to-Point Approach, <u>Geographical Analysis</u>, Vol. 24, No. 2, 1992, pp. 121-141.
- 36. Input-Output Analysis of Regional Telecommunications Flows, <u>Information Economics</u> <u>and Policy</u>, Vol. 5, No. 4, 1993, pp. 311-329.
- 37. Cross-Subsidization in the Telephone Industry: Empirical Evidence from the Pre-Divestiture Era, <u>Socio-Economic Planning Sciences</u>, Vol. 28, No. 2, 1994, pp. 101-112.
- Reliability Pricing of Electric Power Service: A Stochastic Production Cost Simulation Approach (with Y. Hegazy), <u>Energy-The International Journal</u>, Vol. 21, No. 2, 1996, pp. 87-97.
- 39. Simulating Urban Population Density with a Gravity-Based Model, <u>Socio-Economic</u> <u>Planning Sciences</u>, Vol. 30, No. 4, 1996, pp. 245-256 (with F. Wang).
- 40. A Spatial Equilibrium Model for City Size, Urbanization Ratio and Rural Structure, <u>Environment and Planning A</u>, Vol. 29, 1997, pp. 929-941 (with F. Wang).

- 41. Intersectoral Point-to-Point Telecommunication Flows: Theoretical Framework and Empirical Results, <u>Regional Science and Urban Economics</u>, Vol. 28, No. 5, 1998, pp. 585-610.
- 42. Population and Employment Density Functions Revisited: A Spatial Interaction Approach, <u>Papers in Regional Science</u>, Vol. 77, No. 2, 1998, pp. 19-41 (with F. Wang).
- 43. Optimizing The Natural Gas Supply Mix of Local Distribution Utilities, <u>The European</u> <u>Journal of Operational Research</u>, Vol. 112, 1999, pp. 598-612 (with F. Wang).
- 44. Competing Destinations and Intervening Opportunities Interaction Models of Inter-City Telecommunication Flows, <u>Papers in Regional Science</u>, Vol. 78, 1999, pp. 179-194.
- 45. Modeling Air Quality in Urban Areas: A Cell-Based Statistical Approach, <u>Geographical</u> <u>Analysis</u>, Vol. 33, No. 2, 2001, pp. 156-180 (with H.Y. Kim).
- 46. GIS in Coal Transportation Modeling: Case Study of Ohio, <u>Geographic Information</u> <u>Sciences</u>, Vol. 7, No. 1, 2001, pp.24-34 (with H. Tu).
- 47. International Water Resources Allocation and Conflicts The Case of the Euphrates and the Tigris, <u>Environment and Planning A</u>, Vol. 36, No. 5, 2004, pp. 783-802 (with M. Kucukmehmetoglu).
- Optimizing Patterns of Land Use to Reduce Peak Runoff Flow and Non-point Source Pollution with an Integrated Hydrological and Land-Use Model, <u>Earth Interactions</u>, Vol. 8, No. 6, 2004, pp. 1-20 (with I.-Y. Yeo and S.I. Gordon).
- 49. Vehicle Characteristics and Emissions: Logit and Regression Analyses of I/M Data from Massachusetts, Maryland, and Illinois, <u>Transportation Research Part D</u>, Vol. 11, No. 1, 2006, pp. 59-76 (with M. Beydoun).
- 50. Spatial Interaction Modeling of Interregional Commodity Flows, <u>Socio-Economic</u> <u>Planning Sciences</u>, Vol. 41, No. 2, 2007, pp. 147-162 (with M. Celik).
- 51. Land-Use Optimization for Nonpoint Source Water Pollution Control, <u>Environment and</u> <u>Planning B</u>, Vol. 33, No. 6, 2006, pp. 903-921 (with I. Yeo).
- 52. A Hierarchical Optimization Approach to Watershed Land-Use Planning, <u>Water</u> <u>Resources Research</u> Vol. 43, WO9420, doi:10.1029/2005WR004731, 2007 (with I. Yeo and S.I. Gordon).
- 53. Estimating Suppressed Data in Regional Economic Databases: A Goal-Programming Approach, <u>European Journal of Operational Research</u> Vol. 192, No. 2, 2009, pp. 521-537 (with S. Zhang).
- 54. Geography and the Cost of Network Infrastructure: The Case of Local Telephone Systems, <u>Annals of Regional Science</u>, Vol. 42, No. 4, 2008, pp. 821-842 (with M. Cubukcu).

- 55. Multi-Objective Allocation of Trans-Boundary Water Resources: The Case of the Euphrates and Tigris, <u>Journal of Water Resources Planning and Management</u>, Vol. 136, No. 1, 2010, pp. 95-105 (with M. Kucukmehmetoglu).
- Accessibility, Diversity, Environmental Quality and the Dynamics of Intra-Urban Population and Employment Location, <u>Growth and Change</u>, Vol. 41, No. 1, 2010, pp. 85-114 (with S. Zhang).
- Global Spatial Optimization with Hydrological Systems Simulation: Application to Land-Use Allocation and Peak Runoff Minimization, <u>Hydrological and Earth System Sciences</u>, Vol. 14, 2010, pp. 325-338 (with I. Yeo).
- 58. Impacts of Urban Containment Policies on the Spatial Structure of Metropolitan Areas, <u>Urban Studies</u>, Vol. 48, No. 16, 2011, pp. 3511-3536 (with M. Woo).
- 59. Impact of Traffic Flows and Wind Directions on Air Pollution Concentrations in Seoul, Korea, <u>Atmospheric Environment</u>, Vol. 45, 2011, pp. 2803-2810 (with Y. Kim).
- 60. A Computable General Equilibrium Model of the City: Impacts of Technology, Zoning, and Trade, <u>Environment and Planning A</u>, Vol. 44, No. 1, 2012, pp. 237-253 (with C. Olwert).
- 61. Impact of Multi-Dimensional Isovists on Commercial Real Estate Values in the CBD Area Using GIS, <u>Seoul Studies</u>, Vol. 9, 2011, pp. 17-32 (with B. Chun and W. Seo).
- 62. Landscape Ecology, Land-Use Structure, and Population Density: Case Study of the Columbus Metropolitan Area, <u>Landscape and Urban Planning</u>, Vol. 105, 2012, pp.74-85 (with J. Lu).
- 63. Two- and Three-Dimensional Urban Core Determinants of the Urban Heat Island: A Statistical Approach, <u>Journal of Environmental Science and Engineering</u>, Vol. B1, No. 3, 2012, pp. 363-378 (with B. Chun).
- 64. Costs of Abandoned Coal Mine Reclamation and Associated Recreation Benefits in Ohio, <u>Journal of Environmental Management</u>, Vol. 100, 2012, pp. 52-58. (with S. Mishra, F. Hitzhusen, B. Sohngen)
- 65. Another Look at VMT: Determinants of Vehicle Use in Two-Vehicle Households, <u>Transportation Research Record – Journal of the Transportation Research Board</u>, Vol. 2322, 2012, pp. 110-118 (with G. Akar).
- 66. Spatial Analysis of the Urban Heat Island Using a 3-D City Model, <u>Journal of the Korea Spatial Information System Society</u>, Vol. 20 (4), 2012, pp. 1-16 (with B. Chun).
- 67. Analytical Strategies for Estimating Suppressed and Missing Data in Large Regional and Local Employment, Population, and Transportation Databases, <u>WIREs Data Mining and Knowledge Discovery</u>, Vol. 3, 2013, pp. 280-289.

- A Regression-Constrained Optimization Approach to Estimating Suppressed Information Using Time-Series Data: Application to County Business Patterns 1999-2006, <u>International Regional Science Review</u>, Vol. 38(2), 2015, pp. 119-150 (with S. Zhang).
- 69. Land-Use Planning and the Urban Heat Island, <u>Environment and Planning B</u>, Vol. 41, 2014, pp. 1077-1099 (with J-P. Kim).
- 70. The Urban Heat Island in High-Density Central Cities: A Multi-Scale Spatial Statistical Analysis, <u>Landscape and Urban Planning</u>, Vol. 125, 2014, pp. 76-88 (with B. Chun).
- 71. Urban Containment Policies and Urban Growth, <u>International Journal of Urban Sciences</u>, Vol. 18(3), 2014, pp. 309-326 (with M. Woo).
- 72. Retail Location and Urban Resilience: Towards a New Framework of Retail Policy, <u>S.A.P.I. E.N.S.</u>, Vol. 6 (1), 2014, pp. 1-12 (with B. Ozuduru).
- Employment Distribution and Land-Use Structure in the Columbus Metropolitan Area, <u>Journal of Urban Planning and Development – ASCE</u>, published online: September 26, 2014, DOI: 10.1061/(ASCE)UP.1943-5444.0000234. (with J. Lu).
- 74. Do Your Neighbors Affect Your Bicycling Choice? A Spatial Probit Model for Bicycling to The Ohio State University, <u>Journal of Transport Geography</u> Vol. 42, 2015, pp. 122-130 (with C.-H. Wang and G. Akar).
- 75. Land-Use Regression Panel Models of NO<sub>2</sub> Concentrations in Seoul, Korea, <u>Atmospheric</u> <u>Environment</u>, Vol. 107, 2015, pp. 364-373 (with Y. Kim).
- 76. A Land-Use Allocation Optimization Model to Mitigate Potential Seismic Losses, <u>Environment and Planning B.</u> Vol. 42, 2015, pp. 730-753 (with C.-H. Wang).
- 77. A Spatial Panel Approach to the Statistical Assessment of Seismic Impacts and Economic Damages: Case Study of Taichung, Taiwan, <u>Computers, Environment and Urban</u> <u>Systems</u>, Vol. 57, 2016, pp. 178-188 (with C.-H. Wang).
- Geography and the Capital Costs of Urban Energy Infrastructure: The Case of Electricity and Natural Gas, <u>METU Journal of the Faculty of Architecture</u>, Vol. 33(1), 2016, pp. 61-86 (with M.A. Senyel).
- 79. Spatial and Temporal Modeling of Parcel-Level Land Dynamics, <u>Computers,</u> <u>Environment and Urban Systems</u>, Vol. 64, 2017, pp. 204-214 (with E. Tepe).
- Interactions Between the Built and Socio-Economic Environment and Driver Demographics: Spatial Econometric Models of Car Crashes in the Columbus Metropolitan Area, <u>International Journal of Urban Sciences</u>, Vol. 22(1), 2018, pp. 17-37 (with D. Lee and B. von Rabenau).
- 81. Spatial Regression Models of Park and Land-Use Impacts on the Urban Heat Island in Central Beijing, <u>Science of the Total Environment</u>, Vol. 626, 2018, pp. 1136-1147 (with Z. Dai and Y. Hu).

- 82. Joint Costs in Electricity and Natural Gas Distribution Infrastructures: The Role of Urban Factors, <u>Urban Science</u>, 2, 35, 2018 (with M.A. Senyel).
- 83. Impacts of Greening on the Urban Heat Island: Seasonal Variations and Mitigation Strategies, <u>Computers, Environment and Urban Systems</u>, Vol. 71, 2018, pp. 165-176 (with B. Chun).
- 84. Spatio-Temporal Multinomial Autologistic Modeling of Land-Use Change: A Parcel-Level Approach, <u>Environment and Planning B: Urban Analytics and City Science</u>, Online July 6, 2018, DOI: 10.11.77/2399808318786511 (with E. Tepe).
- Influence of Trees on the Outdoor Thermal Environment in Subtropical Areas: An Experimental Study in Guangzhou, China, <u>Sustainable Cities and Society</u>, Vol. 42, 2018, pp. 482-497 (with S. Zheng, Z. Liu, and L. Zhao).
- Thermal Impacts of Greenery, Water, and Impervious Structures in Beijing's Olympic Area: A Spatial Regression Approach, <u>Ecological Indicators</u>, Vol. 97, 2019, pp. 77-88 (with Z. Dai and Y. Hu).
- 87. Creating 3D City Models with Building Footprints and LiDAR Point Cloud Classification: A Machine Learning Approach, <u>Computers, Environment and Urban Systems</u>, Vol. 75, 2019, pp. 76-89 (with Y. Park).

### D. WORKING PAPERS UNDER REVIEW OR REVISION

- 1. Modeling of Shade Creation and Radiation Modification by Four Tree Species in Hot and Humid Areas: Case Study of Guangzhou, China (with S. Zheng, Z. Liu, L. Zhao, J. Wang).
- 2. The Sky View Factor and Urban Morphology: A Spatial Regression Approach (with B. Chun).
- 3. Interregional Virtual Water Trading: Implications for Regional Economic Development under Climate Change (with M. Bhatia).
- 4. Chinese Urban Energy Consumption Structure and its Determinants: A Dynamic Shift-Share Analysis (with Z. Li and Z. Hu).
- 5. Optimal Allocation of Stormwater Pollution Control Technologies in a Watershed (with W-B Chen and S.I. Gordon).
- 6. County-Level Empirical Analysis of Shopping Center Locations in Ohio (with B. Ozuduru).
- 7 Urban Transportation Network Design, Traffic Allocation, and Air Quality Control: An Integrated Optimization Approach (with W.S. Kim and S. Zhang).
- 8. Spatial Analysis of Telecommunication Flows: Literature Review and Conceptual

Framework.

9. Modeling Telecommunications Infrastructure and Usage Decisions in Rural Areas.

### **E.** CONFERENCE PROCEEDINGS

Regulatory Simulation Model (RSM) for Gas Distribution Utilities, <u>Proceedings of the First</u> <u>NARUC Biennial Regulatory Conference</u>, 1978, pp. D3-D14 (with D.Z. Czamanski).

Meteorological Variability and Air Quality Management: A Stochastic Optimization Approach, <u>Methods in Operations Research</u>, Vol. 41, 1981, pp. 153-156, Oelgeschlager, Gunn and Hain Publishers, Cambridge, MA.

Econometric Modeling of Electricity Distribution Capacity Costs and Implications for Marginal Cost Pricing, <u>Modeling and Simulation</u>, Vol. 12, 1981, pp. 893-897.

The Allocation of Gas Distribution Plant Costs Based on Marginal Costs by Customer Class, <u>Proceedings of the Third NARUC Biennial Regulatory Conference</u>, 1982, pp. 476-488 (with C. Aki and K. Lee).

A Chance-Contrained Dynamic Model of Air Quality Management, <u>Modeling and Simulation</u>, 1984, Vol. 15, pp. 495-499.

Disaggregate Capital and Operating Cost Functions for Local Exchange Companies, <u>Proceedings of the Bellcore-Bell Canada Conference on Telecommunications Costing</u>, 1989, pp. 717-749.

Multistage (Top-Down) Optimization Approach To Watershed Conservation to Control Nonpoint Source Water Pollution. <u>Proceeding of Watershed Management Conference 2005</u>, the Environmental & Water Resources Institute of the American Society of Civil Engineers, 2005 (with I. Yeo and S.I. Gordon).

#### F. BOOK REVIEWS

Review of "Energy Development in the Western United States - Impact on Rural Areas" by S.H. Murdock and F.L. Leistritz, and "Energy Conservation and Public Policy" edited by J.C. Sawhill. <u>Environment and Planning A</u>, Vol. 8, 1982, pp. 408-410.

Review of "Geothermal Energy Development: Problems and Prospects in the Imperial Valley of California" by E.W. Butler and J.B. Pick. <u>Environment and Planning A</u>, Vol. 16, 1984, pp. 558-559.

Review of "Energy, Planning and Urban Form" by S. Owens. <u>Geographical Analysis</u>, October 1988, pp. 348-350.

#### G. RESEARCH REPORTS

Forecasting the Demand for Employment, Capital and Land of the Industries in the Haifa Region with a Regional Input-Output Model, May 1974, pp. 120 (in Hebrew, summary in English). Center for Urban and Regional Studies, Technion - Israel Institute of Technology (with D. Shefer, Y. Frishman, H. Shalev).

Economic Costs of Environmental Qualities: The Optimal Spatial Configuration of Industrial Plants in a Growing Urban Region, June 1976. Final Report to the Ford Foundation, Center for Urban and Regional Studies, Technion - Israel Institute of Technology (with D. Shefer).

Methodologies d'Integration des Ressources Naturelles dans les Decisions d'Amenagement du Territoire. Final Report to the French Ministry of the Environment, November 1975, pp. 150 (in French), Louis Pasteur University, Strasbourg, France.

Evaluation d'Impacts sur l'Environnement et Analyse Economique: Trois Applications Regionales. Final Report to the French Ministry of the Environment, October 1975, pp. 175 (in French), Louis Pasteur University, Strasbourg, France.

Atlas de l'Environnement-Alsace, September 1975, pp. 50 (Set of 25 commented maps on various aspects of regional environmental quality and problems). Louis Pasteur University, Strasbourg, France.

The Allocation of Increasing Gas Supplies in Ohio. Three-volume report to the Public Utilities Commission of Ohio, October 1978 (with D.Z. Czamanski).

Optimal Policies of Gas Purchases and Storage Operations and Expansion. The National Regulatory Research Institute (NRRI), April 1979.

Optimal Gas Curtailment Policies. NRRI, May 1979.

Extension of the Regulatory Simulation Model: RSM User's Manual. NRRI, March 1979 (with R.E. Kurth, D.Z. Czamanski, and E. Snijders).

Budget Billing Plans for Electric and Gas Utilities: An Analysis and Some Recommendations for Change. NRRI, January 1980 (with K.A. McDermott).

Marginal Cost Pricing for Gas Distribution Utilities: Preliminary Analyses and Models. NRRI, Report No. 80-12, November 1980.

Marginal Cost Pricing for Gas Distribution Utilities: Further Analyses and Models. NRRI, Report No. 81-9, December 1981 (with W. Pollard and R.A. Tybout).

A Marginal Cost Pricing Model for Gas Distribution Utilities. NRRI, Occasional Paper No. 5, December 1982.

State Regulatory Options for Dealing with Natural Gas Wellhead Price Deregulation. NRRI, Report No. 83-7, August 1983 (with others).

Model Documentation of the Gas Analysis Modeling System - Appendices A and B. Energy Information Administration, U.S. Department of Energy, Report DOE/EIA-0450, Volume 2,

#### August 1984.

The Bypass Issue: An Emerging Form of Competition in the Telephone Industry. NRRI, Report No. 84-17, December 1984 (with J. Racster and M. Wong).

Natural Gas Rate Design and Transportation Policy Under Deregulation and Market Uncertainty. NRRI, December 1985 (with J.S. Henderson).

Natural Gas Producer - Distributor Contracts: State Regulatory Issues. NRRI, January 1988 (with J.S. Henderson and A. Desai).

Penetration of Gas Delivery Systems in the United States: A State-Level Data Analysis. Argonne National Laboratory, Report ANL/EAIS/TM-9, 85 pages, February 1990.

Natural Gas Market Expansion and Delivery Infrastructure Costs: Case Study of New England. Argonne National Laboratory, Report ANL/EAIS/TM-21, 283 pages, June 1990.

Issues Report on the Oil and Gas Infrastructures. President's Commission on Critical Infrastructure Protection. Prepared by the Energy Team (J.M. Guldmann member), August 1997.

Natural Gas Hubs: History, Geography, and Functions. Argonne National Laboratory, Infrastructure Assurance Center, 100 pages, July 2001.

#### **RESEARCH GRANTS**

Public Utilities Commission of Ohio for the study: Allocation of Increasing Gas Supplies in Ohio. \$56,0000. January 1, 1978 - October 31, 1978. Co-principal Investigator (CO-PI).

Public Utilities Commission of Ohio for the preparation of testimonies on the case of Columbia Gas of Ohio request to hook-up new customers. \$14,000. November 15, 1978 - March 31, 1979. (CO-PI).

U.S. Department of Energy for the study: Regulatory Simulation Model for Gas Distribution Systems. \$37,000. October 1, 1978 - April 30, 1979. (CO-PI).

U.S. Department of Energy for the study: Budget Billing Plans for Electric and Gas Utilities. \$15,000. April 1, 1979 - September 30, 1979. (CO-PI).

U.S. Department of Energy for the study: Gas Capacity Cost Study. \$40,000. December 1, 1979 - November 15, 1980. Principal Investigator (PI).

Program for Energy Research, Education, and Public Service, The Ohio State University, for the study: Probabilistic Optimization Models for the Dynamic Control of Air Pollution Generated by High-Sulfur Coal Burning Facilities. \$4,615. July 1, 1980 - March 31, 1981. (PI).

U.S. Department of Energy for the study: Gas Marginal Cost Applications. \$104,553.

November 15, 1980 - February 28, 1982. (PI).

National Association of Regulatory Utility Commissioners (NARUC) for the study: State Regulatory Options for Dealing with Natural Gas Wellhead Price Deregulation. \$119,000. October 1, 1982 - August 31, 1983. (Research Associate).

National Association of Regulatory Utility Commissioners for the study: Analysis of Bypass in Telecommunications. \$ 140,000. October 1, 1983 - December 31, 1984. (Research Associate).

National Association of Regulatory Utility Commissioners (NARUC) for the study: Gas Rate Design under Gas Deregulation: \$ 120,000. October 1, 1984 - December 31, 1985. (Research Associate).

National Science Foundation for the study: The Cost Structure and Investment Dynamics of Gas and Electricity Distribution Systems in Urban Areas. \$ 31,000. March 15, 1985-March 15, 1987. (PI).

Office of Research and Graduate Studies, OSU. Small grant of \$ 667 for obtaining data from the Federal Energy Regulatory Commission. May 1985.

National Association of Regulatory Utility Commissioners (NARUC) for the study: Regulatory Treatment of Direct Gas Purchases. \$ 150,000. October 1, 1986 - December 31, 1987. (Research Associate).

National Association of Regulatory Utility Commissioners (NARUC) for the study: A Feasibility Study of a Point-to-Point Marginal Cost Model for Local Telephone Service. \$ 28,000. January 1, 1988 - September 30, 1988. (PI).

Ameritech Foundation for the study: Economies of Scale and Productivity Growth in Local Telephone Systems: A Cost Function Approach. \$ 21,658. July 1988 - June 1989. (PI)

Ohio Board of Regents - Urban Affairs and Urban Assistance Program, for the study: Modeling Inter-Industry Telecommunication Flows: New Tools for Regional Analysis and Development Policy.

\$19,902. April 1, 1990 - June 30, 1991. (PI)

Ohio Board of Regents - Urban Affairs and Urban Assistance Program, for the study: Assessing the Economic Impacts of the Clean Air Act Amendments of 1990 on the State of Ohio. \$ 19,744. April 8, 1992 - June 30, 1993. (PI)

Ameritech Foundation for the study: Modeling Telecommunication Demand in the Business Sector: A Disaggregate Production Function Approach. \$ 18,000. July 1992 - June 1993.

Argonne National Laboratory, for the study: Natural Gas Database Development. \$ 28,217. April - June 1993.

Ohio Board of Regents - Urban Affairs and Urban Assistance Program, for the study: Urban Structure and Dynamics in Ohio: Population and Employment Density Functions Revisited. \$ 20,000. July 1994 - June 1995. (PI)

Ohio Board of Regents - Urban Affairs and Urban Assistance Program, for the study: Central Place Structure and Scale Economies in the Ohio System of Cities. \$ 20,450. July 1995 - June 1996. (PI)

Ameritech Foundation for the study: Modeling The Interactions between International Telecommunications and Trade Flows. \$ 14,139. October 1996 - September 1997.

Ohio Board of Regents - Urban Affairs and Urban Assistance Program, for the study: Commuting Flows and the Hierarchy of Employment Centers in Ohio's Metropolitan Areas. \$ 20,000. July 1997 - June 1998. (PI)

National Science Foundation for the study: Telecommunications Demand and Impacts in the Regional Economy. \$ 85,514. July 15, 1998 - June 30, 2000.

Ohio Board of Regents - Urban Affairs and Urban Assistance Program, for the study: Using Geographical Information Systems to Estimate Models of Urban and Regional Air Quality. \$ 20,000. July 1999 - June 2000. (PI)

Ameritech Foundation for the study: Telecommunications Infrastructure, Business Location, and Local Economic Development. \$21,098. October 2000 - September 2001.

SBC Faculty Research Grant for the study: Internet Broadband Service Demand Analysis: Qualitative Choice Models of Household and Firm Behavior. (with E. Malecki), \$28,681. July 2003- June 2004.

Emeritus Academy Small Grant for the study: Long-Term Microclimatic Changes in the Columbus Metropolitan Area, \$2,400. December 2017-November 2018.

#### DOCTORAL STUDENTS SUPERVISION – DISSERTATIONS COMPLETED

- 1. Sadoun, Balqies I., 1992. A Modeling Methodology for Energy-Conserving Site Design.
- 2. Hegazy, Youssef, 1993. Reliability-based Pricing of Electricity Service.
- 3. Kim, WoonSoo, 1995. Combined Transportation Network Optimization and Spatial Allocation of Pollution Emissions.
- 4. Wang, Fahui, 1995. Spatial Equilibrium Models of Systems of Cities with Interurban Transportation Costs.
- 5. Shen, Yung-Tang, 1996. Studies in Fuel Supply and Air Quality Planning by Electric Utilities.
- 6. Shen, Guoqiang, 1998. Hub Location and Network Design: Model Formulation and Numerical Analyses.
- 7. Kim, Hag-Yeol, 1999. GIS-Based Statistical Models of Urban and Regional Air Quality: The Cases of Ozone and Carbon Monoxide.

- 8. Celik, H. Murat, 2001. Spatial Interaction Modeling of Interregional Commodity Flows.
- 9. Kucuknehmetoglu, Mehmet, 2002. Water Resources Allocation and Conflicts: The Case of the Euphrates and the Tigris.
- 10. Cubukcu, Mert K., 2003. Geography and the Cost of Network Infrastructure: The Case of Local Telephone Systems.
- 11. Shen, Kang-Ping, 2003. Airshed-Based Statistical Modeling of the Spatial Distribution of Air Pollution: The Case of Sulfur Dioxide.
- 12. Kim, Tae-Kyung, 2004. Dynamic Analysis of Sulfur Dioxide Monthly Emissions in U.S. Power Plants.
- 13. Beydoun, Mustapha, 2004. Vehicular Characteristics and Urban Air Pollution: Socio-Economic and Environmental Policy Issues.
- 14. Yeo, In-Young, 2005. Multistage Hierarchical Optimization for Land Allocation to Control Nonpoint Source Water Pollution. (Co-adviser: S.I. Gordon).
- 15. Sucahyono, Hadi, 2006. Neighborhood Impacts on Suburban Housing Values. (Coadviser: B. von Rabenau).
- 16. Ozuduru, Burcu, 2006. An Empirical Analysis of Shopping Center Locations in Ohio.
- 17. Chen, Wei-Bin, 2006. Optimal Allocation of Stormwater Pollution Control Technologies in a Watershed. (Co-adviser: S.I. Gordon).
- 18. Woo, Myungje, 2007. Impacts of Urban Containment Policies on Urban Growth and Structure.
- 19. Zhang, Sumei, 2008. Metropolitan Dynamics of Accessibility, Diversity, and Locations of Population and Activities.
- 20. Lu, Jia, 2008. Land-Use Structure and Population and Employment Densities: Empirical Analysis of the Columbus (Ohio) Metropolitan Area.
- 21. Kim, Jun-Pill, 2009. Land-Use Planning and the Urban Heat Island Effect.
- 22. Kim, Youngkook, 2010. Impacts of Transportation, Land Uses, and Meteorology on Urban Air Quality.
- 23. Olwert, Craig T., 2010. A Computable General Equilibrium Model of the City with Optimization of its Transportation Network: Impacts of Changes in Technology, Preferences and Policy.
- 24. Lee, David Jung-Hwi, 2010. Optimal Regional Allocation of Population and Employment: Application of a Spatial Interaction Commuting Model.

- 25. Chun, BumSeok, 2011. Three-Dimensional City Determinants of the Urban Heat Island: A Statistical Approach.
- Wang, Chih-Hao, 2013. Land-Use Allocation and Earthquake Damage Mitigation: A Combined Spatial Statistics and Optimization Approach.
- 27. Senyel, Muzeyyen Anil, 2013. Geography and the Costs of Urban Energy Infrastructure: The Case of Electricity and Natural Gas Capital Investments.
- 28. Lee, Dongkwan, 2015. Driver Demographics, Built Environment, and Car Crashes: Implications for Urban Planning (Co-adviser: B. von Rabenau).
- 29. Guliani, Manraj, 2015. Interregional Commodity and Virtual Water Trade: Impact of Changing Climate and Water Supply.
- 30. Tepe, Emre, 2016. Statistical Modeling and Simulation of Land Development Dynamics.

# Data from EIA Form 176

#### Volumes and Consumers - Duke Energy - 2010-2016 Source: Form EIA 176

Intern 2010 2011 2012 2013 2014 2015 2014 2015 2014 2015 2014 2015 2014 2015 2014 2015 2014 2015 2014 2015 2014 2015 2014 2015 2014 2015 <	ltom		2010	2011	2012	2012	2014	2015	2010
Receipts at Citygate Volume KY 19826073 21606614 19605514 2162978 22435927 20489042 2225733   Total Supply Volume KY 19831543 21614743 19606201 22192242 22487842 20539795 2236076   Residential Consumers KY 6531587 6043620 520077 6483744 6447088 59899   Commercial Consumers KY 4615627 4393883 3977527 4589505 5027511 4403981 417852   Commercial Sales Consumers KY 7429 7371 7389 7343 7448 7467 7493   Commercial Sales Consumers KY 2380062 2396479 2458337 2629720 2704500 2761188 2831353   Industrial Volume KY 2380062 2396479 2458337 2629720 2704500 2761188 2831354   Industrial Volume OH 64575916 60297252 68772542 73969827 64639383 60530744   Residential Consumers OH			2010	2011	2012	2013	2014	2015	2016
Total Supply Volume KY 19831543 21614743 19606201 22192242 22487842 20539795 2236076   Residential Consumers KY 6531587 6043620 5230077 6433794 6647088 5945448 541058   Residential Consumers KY 8615627 439883 3975727 4589505 5027511 4403891 137825   Commercial Consumers KY 7429 7371 7349 7343 7448 7467 7493   Commercial Sales Consumers KY 7429 7371 7339 7343 7448 7467 7493   Commercial Sales Volume KY 238062 2396479 2458337 2629720 2704050 275118 831355   Industrial Volume OH 68597481 62758916 60297252 68772542 73969827 64639383 60530744   Total Supply Volume OH 74473349 71436182 68257742 73969827 64639383 60530744   Total Supply Volume OH <t< td=""><td>Receipts at Citygate Volume</td><td>кү</td><td>19826073</td><td>21606614</td><td>19605514</td><td>22162978</td><td>22435927</td><td>20489042</td><td>22295737</td></t<>	Receipts at Citygate Volume	кү	19826073	21606614	19605514	22162978	22435927	20489042	22295737
Residential Volume KY 6531587 6043620 5230077 6483794 6647088 5945448 541058   Residential Consumers KY 87260 87316 87883 88282 88731 89195 89999   Commercial Volume KY 4615627 4393883 3977527 4589505 5027511 4403981 417852   Commercial Sales Consumers KY 7489 7427 7448 7408 7512 7536   Commercial Sales Consumers KY 7429 7371 7389 7433 7448 7467 7499   Commercial Sales Volume KY 2380062 2396479 2458337 2529720 2704500 2761188 283135   Industrial Consumers KY 2258 260 259 259 259 250 259 250 210 11490   Residential Consumers OH 7447349 7146182 2827919 7631460 81571814 711490   Residential Consumers OH 3132	Total Supply Volume	ку	19831543	21614743	19606201	22192242	22487842	20539795	22360766
Residential Consumers KY 87260 87316 87883 88282 88731 89195 8999   Commercial Volume KY 4615627 4393883 3977527 4589505 5027511 4403981 417852   Commercial Sales Consumers KY 7489 7427 7448 7408 7512 7531 756   Commercial Sales Volume KY 7429 7341 303471 2919794 3462828 3876357 3347311 304651   Industrial Consumers KY 2380062 2396479 2458337 2629720 2704500 2761188 283135   Industrial Consumers KY 2380062 2396479 2458337 2629720 2704500 2761188 283135   Industrial Consumers CH 68597481 62758916 60297252 68772542 73969827 64639383 6053074   Total Supply Volume CH 3132756 29262577 25780303 31467942 3283445 29093625 26893703   Commercial Vo	Residential Volume	KY	6531587	6043620	5230077	6483794	6847088	5945448	5410586
Commercial Volume KY 4615627 4393883 3977527 4589505 5027511 4403981 417852   Commercial Consumers KY 7489 7427 7448 7408 7512 7531 7560   Commercial Sales Consumers KY 7429 7371 7389 7343 7448 7467 749   Commercial Sales Volume KY 3570316 3303471 2919794 3462828 3876357 3347311 304551   Industrial Volume KY 2380062 2396479 245837 252970 2704500 2761188 283135   Industrial Volume OH 68597481 62758916 60297252 68772542 73969827 64639383 6053074   Receipts at Citygate Volume OH 74473349 71446182 62758916 61029722 75780309 31467942 3283441 2903625 2689390   Residential Consumers OH 379823 379527 380689 381605 384208 385647 387732	Residential Consumers	KY	87260	87316	87883	88282	88731	89195	89990
Commercial Consumers KY 7489 7427 7448 7408 7512 7531 7563   Commercial Sales Consumers KY 7429 7371 7389 7343 7448 7467 7499   Commercial Sales Volume KY 3303471 2919794 4462828 3876357 3347311 3046511   Industrial Volume KY 2380062 2396479 2458337 2629720 2704500 2761188 2831352   Industrial Consumers KY 2380062 2396479 2458337 2659 259 259 260 255   Receipts at Citygate Volume OH 668597481 62758916 60297252 68772542 7396827 64639383 60530741   Total Supply Volume OH 31332756 25265277 25783039 31467942 3283445 29093622 2689390   Residential Consumers OH 379823 379527 380689 381605 384208 385647 387733   Commercial Consumers OH	Commercial Volume	кү	4615627	4393883	3977527	4589505	5027511	4403981	4178528
Commercial Sales Consumers KY 7429 7371 7389 7343 7448 7467 7499   Commercial Sales Volume KY 3570316 3303471 2919794 3462828 3876357 3347311 304651   Industrial Consumers KY 2380062 2396479 2458337 2629720 2704500 2761188 2831355   Industrial Consumers KY 2280062 2396479 2458337 2629720 2704500 2761188 2831355   Industrial Consumers CH 68597481 62758916 60297252 68772542 73969827 64639383 6053074   Total Supply Volume OH 74473349 71436182 68257919 76819460 81571814 71856896 7011490   Residential Consumers OH 373923 37927 380693 381605 384208 385647 387733   Commercial Consumers OH 136731 1554 1517 1493 1479 1454 1444   Electric Power Volume	Commercial Consumers	KY	7489	7427	7448	7408	7512	7531	7564
Commercial Sales Volume KY 3570316 3303471 2919794 3462828 3876357 3347311 304651   Industrial Volume KY 2380062 2396479 2458337 2629720 2704500 2761188 2831350   Industrial Consumers KY 258 260 259 259 259 260 259   Receipts at Citygate Volume OH 68597481 62758916 681772542 73969827 64639383 60530744   Total Supply Volume OH 74473349 71436182 68257919 76819460 81571814 71856896 7011490   Residential Consumers OH 31332756 29262577 25780309 31467942 3283445 29093625 2689390   Commercial Volume OH 31332756 29262577 25780309 31467942 3283445 29093625 2689300 2061513 205651737 22676383 215310 205076 2053492 24293455 25651737 2267638 215100 2001681 104941 2011	Commercial Sales Consumers	KY	7429	7371	7389	7343	7448	7467	7498
Industrial Volume KY 2380062 2396479 2458337 2629720 2704500 2761188 283135   Industrial Consumers KY 258 260 259 259 259 260 255   Receipts at Citygate Volume OH 68597481 6275816 60297252 68772542 73969827 64639383 60530744   Total Supply Volume OH 74473349 71436182 68257919 76813460 8157181 71856896 70114900   Residential Volume OH 31332756 52262577 25651737 22676383 22153102   Commercial Volume OH 36743 36384 36120 35994 35979 35768 35600   Industrial Volume OH 1701381 17351460 1818748 1649617 20211619 19643190 2001268   Industrial Volume OH 1571 1554 1517 1493 1479 1454 14444   Electric Power Volume OH 18778 283521 33	Commercial Sales Volume	KY	3570316	3303471	2919794	3462828	3876357	3347311	3046517
Industrial Consumers KY 258 260 259 259 259 260 255   Receipts at Citygate Volume OH 68597481 62758916 60297252 68772542 73969827 64639383 60530744   Total Supply Volume OH 74473349 71436182 68257919 76819460 81571814 71856895 7011490   Residential Volume OH 3132756 29262577 2578039 31467942 2833445 29093625 26893900   Residential Consumers OH 3473373 23500276 22053492 24293455 22656373 2267633 22153102   Commercial Volume OH 17013381 17351460 18187428 19649617 20211619 19643190 20012682   Industrial Consumers OH 1571 1554 1517 1493 1479 1454 14444   Electric Power Volume OH 188778 28942 33821 144299 424774 576311 390344   Electric Power Transport Consume	Industrial Volume	ку	2380062	2396479	2458337	2629720	2704500	2761188	2831350
Receipts at Citygate Volume OH 68597481 62758916 60297252 68772542 73969827 64639383 60530744   Total Supply Volume OH 74473349 71436182 68257919 76819460 81571814 71856896 7011490   Residential Volume OH 31332756 29262577 25780309 31467942 32833445 29093625 26893900   Residential Consumers OH 379823 379527 380689 381605 384208 385647 387733   Commercial Consumers OH 24733773 23500276 22053492 24293455 2265737 22676383 2215310   Industrial Volume OH 17013381 17351460 18187428 19649617 20211619 19643100 2001268:   Industrial Consumers OH 1571 1554 1517 1493 1479 1454 1444   Electric Power Volume OH 18978 28942 33821 144299 424774 576311 3990342   Total Sup	Industrial Consumers	KY	258	260	259	259	259	260	258
Receipts at Citygate Volume OH 68597481 62758916 60297252 68772542 73969827 64639383 60530744   Total Supply Volume OH 74473349 71436182 68257919 76819460 81571814 71856896 7011490   Residential Volume OH 31332756 29262577 25780309 31467942 32833445 29093625 2689390   Residential Consumers OH 379823 379527 380689 381605 384208 385647 387732   Commercial Volume OH 24733773 23500276 22053492 24293455 25651737 22676383 215310   Commercial Consumers OH 13703181 17351460 1817428 19649617 20211619 19643109 20012682   Industrial Consumers OH 18978 28942 33821 144299 424774 576311 3903442   Electric Power Volume DE 94304892 93050925 87864120 99011702 104059656 92396691 9247567									
Total Supply Volume OH 74473349 71436182 68257919 76819460 81571814 71856896 7011490   Residential Volume OH 31332756 29262577 25780309 31467942 32833445 29093625 26893900   Residential Consumers OH 379823 379527 380689 381605 384208 385647 387732   Commercial Volume OH 24733773 23500276 22053492 24293455 25651737 22676383 2215310   Commercial Consumers OH 36743 36384 36120 35994 35979 35768 35600   Industrial Volume OH 17013381 17351460 18187428 19649617 20211619 19643190 2001268   Industrial Consumers OH 18771 1554 1517 14939 14479 14444   Electric Power Volume OH 18978 28942 33821 144299 424774 576311 390344   Electric Power Volume DE	Receipts at Citygate Volume	он	68597481	62758916	60297252	68772542	73969827	64639383	60530748
Residential Volume OH 31332756 29262577 25780309 31467942 32833445 29093625 26893900   Residential Consumers OH 379823 379527 380689 381605 384208 385647 387733   Commercial Volume OH 24733773 23500276 22053492 24293455 25651737 22676383 215310   Commercial Consumers OH 36743 36384 36120 35994 35979 35768 35600   Industrial Volume OH 17013381 17351460 18187428 19649617 20211619 19643190 2001268   Industrial Consumers OH 1571 1554 1517 1493 1479 1454 14449   Electric Power Volume OH 1 1 2	Total Supply Volume	он	74473349	71436182	68257919	76819460	81571814	71856896	70114904
Residential Consumers OH 379823 379527 380689 381605 384208 385647 387733   Commercial Volume OH 24733773 23500276 22053492 24293455 25651737 22676383 2215310   Commercial Consumers OH 36743 36384 36120 35994 35979 35768 35600   Industrial Volume OH 17013381 17351460 18187428 19649617 20211619 19643190 2001268   Industrial Consumers OH 1571 1554 1517 1493 1479 1454 1444   Electric Power Volume OH 18978 28942 33821 144299 424774 576311 390344   Electric Power Transport Consumers OH 1 1 1 2	Residential Volume	он	31332756	29262577	25780309	31467942	32833445	29093625	26893900
Commercial Volume OH 24733773 23500276 22053492 24293455 25651737 22676383 2215310   Commercial Consumers OH 36743 36384 36120 35994 35979 35768 35600   Industrial Volume OH 17013381 17351460 18187428 19649617 20211619 19643190 20012683   Industrial Consumers OH 1571 1554 1517 1493 1479 1454 1444   Electric Power Volume OH 18978 28942 33821 144299 424774 576311 390344   Electric Power Transport Consumers OH 1 1 1 2	Residential Consumers	он	379823	379527	380689	381605	384208	385647	387739
Commercial Consumers OH 36743 36384 36120 35994 35979 35768 35600   Industrial Volume OH 17013381 17351460 18187428 19649617 20211619 19643190 2001268   Industrial Consumers OH 1571 1554 1517 1493 1479 1454 1444   Electric Power Volume OH 18978 28942 33821 144299 424774 576311 39034   Electric Power Volume OH 1 1 1 2	Commercial Volume	он	24733773	23500276	22053492	24293455	25651737	22676383	22153102
Industrial Volume OH 17013381 17351460 18187428 19649617 20211619 19643190 2001268   Industrial Consumers OH 1571 1554 1517 1493 1479 1454 1444   Electric Power Volume OH 18978 28942 33821 144299 424774 576311 39034   Electric Power Transport Consumers OH 1 1 2	Commercial Consumers	он	36743	36384	36120	35994	35979	35768	35605
Industrial Consumers OH 1571 1554 1517 1493 1479 1454 1444   Electric Power Volume OH 18978 28942 33821 144299 424774 576311 39034   Electric Power Volume OH 1 1 1 2	Industrial Volume	он	17013381	17351460	18187428	19649617	20211619	19643190	20012682
Electric Power Volume OH 18978 28942 33821 144299 424774 576311 39034   Electric Power Transport Consumers OH 1 1 1 2 <td< td=""><td>Industrial Consumers</td><td>он</td><td>1571</td><td>1554</td><td>1517</td><td>1493</td><td>1479</td><td>1454</td><td>1446</td></td<>	Industrial Consumers	он	1571	1554	1517	1493	1479	1454	1446
Electric Power Transport Consumers OH 1 1 1 2 2 2   Receipt at City Gate Volume DE 88423554 84365530 79902766 90935520 96405754 85128425 8282648   Total Supply Volume DE 94304892 93050925 87864120 99011702 104059656 92396691 92475670   Residential Volumes DE 37864343 35306197 31010386 37951736 39680533 35039073 32304480   Residential Consumers DE 467083 466843 468572 469887 472939 474842 477729   Residential Volume per Consumer DE 81.1 75.6 66.2 80.8 83.9 73.8 67.4   Commercial Volume DE 29349400 27894159 26031019 28882960 30679248 27080364 26331630   Commercial Volume per Consumer DE 44232 43811 43568 43402 43491 43299 43169   Commercial Volume per Consumer	Electric Power Volume	он	18978	28942	33821	144299	424774	576311	390340
Image: Network Image:	Electric Power Transport Consumers	он	1	1	1	2	2	2	2
Receipt at City Gate Volume DE 88423554 84365530 79902766 90935520 96405754 85128425 8282648   Total Supply Volume DE 94304892 93050925 87864120 99011702 104059656 92396691 92475677   Residential Volumes DE 37864343 35306197 31010386 37951736 39680533 35039073 3230448   Residential Consumers DE 467083 466843 468572 469887 472939 474842 477729   Residential Volume per Consumer DE 81.1 75.6 66.2 80.8 83.9 73.8 67.0   Commercial Volume DE 29349400 27894159 26031019 28882960 30679248 2780364 26331630   Commercial Volume per Consumer DE 44232 43811 43568 43402 43491 43299 43169   Commercial Volume per Consumer DE 1663.5 636.7 597.5 665.5 705.4 625.4 610   Indu									
Total Supply Volume DE 94304892 93050925 87864120 99011702 104059656 92396691 92475670   Residential Volumes DE 37864343 35306197 31010386 37951736 39680533 35039073 3230448   Residential Consumers DE 467083 466843 468572 469887 472939 474842 477722   Residential Volume per Consumer DE 81.1 75.6 66.2 80.8 83.9 73.8 67.0   Commercial Volume DE 29349400 27894159 26031019 28882960 30679248 27080364 26331630   Commercial Volume per Consumer DE 44232 43811 43568 43402 43491 43299 43169   Commercial Volume per Consumer DE 19393443 19747939 20645765 22279337 22916119 22404378 22844037   Industrial Volume DE 19393443 19747939 20645765 22279337 22916119 22404378 22844037	Receipt at City Gate Volume	DE	88423554	84365530	79902766	90935520	96405754	85128425	82826485
Residential Volumes DE 37864343 35306197 31010386 37951736 39680533 35039073 3230448   Residential Consumers DE 467083 466843 468572 469887 472939 474842 477722   Residential Consumers DE 81.1 75.6 66.2 80.8 83.9 73.8 67.0   Commercial Volume DE 29349400 27894159 26031019 28882960 30679248 27080364 26331630   Commercial Consumers DE 44232 43811 43568 43402 43491 43299 43169   Commercial Volume per Consumer DE 663.5 636.7 597.5 665.5 705.4 625.4 610   Industrial Volume DE 19393443 19747939 20645765 22279337 22916119 22404378 22844037   Industrial Consumers DE 1829 1814 1776 1752 1738 1714 1704   Industrial Volume per Consumer DE	Total Supply Volume	DE	94304892	93050925	87864120	99011702	104059656	92396691	92475670
Residential Consumers DE 467083 466843 468572 469887 472939 474842 477722   Residential Volume per Consumer DE 81.1 75.6 66.2 80.8 83.9 73.8 67.0   Commercial Volume DE 29349400 27894159 26031019 28882960 30679248 27080364 26331633   Commercial Consumers DE 44232 43811 43568 43402 43491 43299 43163   Commercial Volume per Consumer DE 663.5 636.7 597.5 665.5 705.4 625.4 610   Industrial Volume DE 19393443 19747939 20645765 22279337 22916119 22404378 22844032   Industrial Consumers DE 1829 1814 1776 1752 1738 1714 1704   Industrial Volume per Consumer DE 10603.3 10886.41 11624.87 12716.52 13185.34 13071.4 13406.12   Electric Power Volume DE	Residential Volumes	DE	37864343	35306197	31010386	37951736	39680533	35039073	32304486
Residential Volume per Consumer DE 81.1 75.6 66.2 80.8 83.9 73.8 67.0   Commercial Volume DE 29349400 27894159 26031019 28882960 30679248 27080364 26331633   Commercial Consumers DE 44232 43811 43568 43402 43491 43299 43163   Commercial Volume per Consumer DE 663.5 636.7 597.5 665.5 705.4 625.4 610   Industrial Volume DE 19393443 19747939 20645765 22279337 22916119 22404378 22844032   Industrial Consumers DE 1829 1814 1776 1752 1738 1714 1704   Industrial Volume per Consumer DE 10603.3 10886.41 11624.87 12716.52 13185.34 13071.4 13406.12   Electric Power Volume DE 18978 28942 33821 142499 424774 57631 390344	Residential Consumers	DE	467083	466843	468572	469887	472939	474842	477729
Commercial Volume DE 29349400 27894159 26031019 28882960 30679248 27080364 26331630   Commercial Consumers DE 44232 43811 43568 43402 43491 43299 43161   Commercial Consumers DE 663.5 636.7 597.5 665.5 705.4 625.4 6101   Industrial Volume DE 19393443 19747939 20645765 22279337 22916119 22404378 22844032   Industrial Consumers DE 1829 1814 1776 1752 1738 1714 1704   Industrial Volume per Consumer DE 10603.3 10886.41 11624.87 12716.52 13185.34 13071.4 13406.12   Electric Power Volume DE 18978 28942 33821 144299 424774 57631 390344	Residential Volume per Consumer	DE	81.1	75.6	66.2	80.8	83.9	73.8	67.6
Commercial Consumers DE 44232 43811 43568 43402 43491 43299 43166   Commercial Volume per Consumer DE 663.5 636.7 597.5 665.5 705.4 625.4 610   Industrial Volume DE 19393443 19747939 20645765 22279337 22916119 22404378 22844033   Industrial Consumers DE 1829 1814 1776 1752 1738 1714 1704   Industrial Volume per Consumer DE 10603.3 10886.41 11624.87 12716.52 13185.34 13071.4 13406.12   Electric Power Volume DE 18978 28942 33821 14299 424774 576311 390344	Commercial Volume	DE	29349400	27894159	26031019	28882960	30679248	27080364	26331630
Commercial Volume per Consumer DE 663.5 636.7 597.5 665.5 705.4 625.4 611   Industrial Volume DE 19393443 19747939 20645765 22279337 22916119 22404378 22840378   Industrial Consumers DE 1829 1814 1776 1752 1738 1714 1700   Industrial Volume per Consumer DE 10603.3 10886.41 11624.87 12716.52 13185.34 13071.4 13406.12   Electric Power Volume DE 18978 28942 33821 144299 424774 576311 390344	Commercial Consumers	DE	44232	43811	43568	43402	43491	43299	43169
Industrial Volume DE 19393443 19747939 20645765 22279337 22916119 22404378 2284033   Industrial Consumers DE 1829 1814 1776 1752 1738 1714 1700   Industrial Volume per Consumer DE 10603.3 10886.41 11624.87 12716.52 13185.34 13071.4 13406.12   Electric Power Volume DE 18978 28942 33821 14229 424774 576311 390344	Commercial Volume per Consumer	DE	663.5	636.7	597.5	665.5	705.4	625.4	610
Industrial Consumers DE 1829 1814 1776 1752 1738 1714 1700   Industrial Volume per Consumer DE 10603.3 10886.41 11624.87 12716.52 13185.34 13071.4 13406.12   Electric Power Volume DE 18978 28942 33821 144299 424774 576311 390344	Industrial Volume	DE	19393443	19747939	20645765	22279337	22916119	22404378	22844032
Industrial Volume per Consumer DE 10603.3 10886.41 11624.87 12716.52 13185.34 13071.4 13406.12   Electric Power Volume DE 18978 28942 33821 144299 424774 576311 390344	Industrial Consumers	DE	1829	1814	1776	1752	1738	1714	1704
Electric Power Volume DE 18978 28942 33821 144299 424774 576311 390344   Electric Power Volume DE 1 1 2 2 2 2	Industrial Volume per Consumer	DE	10603.3	10886.41	11624.87	12716.52	13185.34	13071.4	13406.12
	Electric Power Volume	DE	18978	28942	33821	144299	424774	576311	390340
	Electric Power Consumers	DE	1	1	1	2	2	2	2
Electric Power Volume per Consumer DE 18978 28942 33821 72150 212387 288156 19517(	Electric Power Volume per Consumer	DE	18978	28942	33821	72150	212387	288156	195170
Total Delivery Volume DE 86626164 82977237 77720991 89258332 93700674 85100126 81870488	Total Delivery Volume	DE	86626164	82977237	77720991	89258332	93700674	85100126	81870488
Volume Losses Whole Company DE 7678728 10073688 10143129 9753370 10358982 7296565 10605183	Volume Losses Whole Company	DE	7678728	10073688	10143129	9753370	10358982	7296565	10605182
Rate of loss % DE 8.1 10.8 11.5 9.9 10.0 7.9 11.5	Rate of loss %	DE	8.1	10.8	11.5	9.9	10.0	7.9	11.5

Volume: mcf; Consumers: #; Volume losses = Total supply volume – Total delivery volume

Rate of loss = (Volume Loss/Total supply volume)\*100





Source: 2015 Exeter Report, p. 5.

Transmission Lines in DE Network

Existing transmission lines [Doc 44]

- Line A: Centerville Sta. No. 9 to Norwood Sta. No. 36; 20"; 225psi, 150 psi;

112,872+88,236 feet length;

- Line D: California Sta. No. 7 to East Works Sta.; 24"; 200, 388, 175 psi; length = 23,766 feet;

- Line V: Line D to Norwood; 20"; 200, 175 psi; 45,116 feet;

- Line AA: Anderson Ferry Sta. to North Bend Road Sta.; 20-24"; 175 psi;86,588 feet;

- Line EE: California Sta. to Line V: 24"; 200 psi; 25,481 feet;

- Line CG07: Butler Sta. to Dicks Creek Sta.; 10, 12, 16"; 400, 438, 800 psi; 25,443 feet;

- Line LP2: Dicks Creek Sta. to Line A: 20"; 225, 438, 800 psi; 1,524 feet;

- Line LP5: Dicks Creek Sta. to AK Steel Back-up Sta.: 8, 12"; 538 psi; 4,371 feet;

- Line C210: Princeton Road to Woodsdale Plant: 16, 24"; 670, 500 psi; 24,359 feet;

- Line CG04: Line AA to Livingston Road: 20"; 175 psi; 20, 754 feet;

- Line C314: Mason Rd. Sta (@Texas Gas) to F/L WW on Fields Ertel Rd.; 24"; 670 psi; 56,303 feet;

- Line C338: Ohio River to Bethel Sta. #760: 12"; 535 psi; 86,967 feet;

- Line C340: Sta. #759 (Bracken Co., KY) to F/L C338 on Ohio shore; 12"; 535 psi; 3,699 feet;

- Line C251: STA 137 Minton Rd. to Miami Western Dr.; 8"; 360 psi; 38,387 feet;

- Line CG63: LP02 Tap to Sta 311 & 181: "; 438 psi; 582 feet.

#### Planned transmission lines [Doc 44]

- Existing Line C314 to Lebanon Hub (Warren Co.):48,000 feet; 24"; 720 psi; loop current pipeline to increase capacity for system load growth and provide greater operational alternatives; timing: 2023;

- Existing Line C338 at Bethel to Blanchester (Clermont Co.): 12"; 650 psi; 132,000 feet; loop current pipeline to increase capacity for system for future industrial growth; timing: 2024;

- Replacements for D000b, A000b, EE00, CG07b;

- Several retrofits.

Land and Population Impacts of the Preferred (PR) and Alternative (AR) Routes for C314V

Variable	<u>PR</u>	AR
Length (miles)	13.9	12.9
# properties crossed by the construction ROW	723	471
Proposed construction ROW (acres)	135	125
Land uses within 2000 feet corridor (%)		
Industrial and commercial	37.4	40.2
Paved areas	27.5	36.8
Parks & recreation	14.5	6.8
Woodlots	14.1	11.9
Number of land-use features within 100 feet		
Historic Structures	31	4
Residences	115	182
Number of land-use features within 1000 feet		
Historic Structures	230	116
Residences	3153	2186
Pipeline length in feet (%) crossing land uses		
Residences	2581 (3.5%)	82
(0.1%)		
Parks & recreation	10,808 (15.7%)	4,582
(6.7%)		
Industrial and commercial 41.6%)	27,557 (37.4%)	28,365
<u>Capital costs (\$ Million)</u>	128.2	111.7
I otal	128.2	111./
Land & land rights	26.8	19.6
Structures & improvements	5.2	0.9
Pipes	87.2	82.4
Nik equipment	8.7	8./
KOw clearing	0.3	0.1
Property tax revenues (\$ Million)	3.3	2.9





FIGURE 1. Location of the Proposed Gas Line (Length: 27,020m = 16.79 mile) – Scenario W-1



FIGURE 2. Locations of Nearby Cities and Municipalities – Scenario W-1



FIGURE 3. Population (2010) per Census Block Surrounding the Proposed Gas Line – Scenario W-1



FIGURE 4. Land Cover Compositions Along the Proposed Gas Line (Source: US National Land Cover Database 2011)


## FIGURE 5. Census Block Population (2010) and Land Cover Compositions Along the Proposed Gas Line

Note: Those blocks with no residing population are excluded.



FIGURE 6. Land Use Compositions Along the Proposed Gas Line (Source: Hamilton County Auditor Data 2018, OpenStreetMap Land Use Data)



FIGURE 7. Census Block Population (2010) and Land Use Compositions Along the Proposed Gas Line Note: Those blocks with no residing population are exclude

		-	_	_	_	_	_	_	_	_	-	_	_	_	_	_	_	_	_				_		_
rea	House	1.00	1.68	6.00	2.98	0.95	7.61	41.53	1.64	0.92	0.87	24.98	1.93	123.24	21.28	1.74	0.44	3.20	17.05	2.10	0.15	24.65	0.00	2.58	8.30
t Buffer A n width)	Family	0.00	0.84	4.00	2.98	0.72	6.34	28.30	0.98	0.62	0.58	18.88	1.45	103.31	15.09	1.74	0.44	3.20	15.40	1.35	0.12	20.61	0.00	1.99	7.14
in 1,000 f (2,000 ft i	Pop	1.00	2.52	16.00	6.96	2.40	20.71	95.76	3.94	1.54	2.62	67.73	3.86	391.48	54.44	7.40	1.33	10.24	57.43	4.75	0.40	75.29	0.09	6.83	27.22
With	Area	0.002	0.150	0.016	0.035	0.064	0.077	0.086	0.263	0.240	0.287	0.439	0.585	0.444	0.803	0.793	1.001	1.298	0.042	0.027	0.004	0.027	0.001	0.121	0.009
ea	House	0.03	0.02	1.54	0.43	0.09	0.63	4.32	0.07	0.09	0.09	2.64	0.21	18.99	2.11	0.21	0.05	0.33	1		1	1	ı	1	1
Buffer Ar width)	Family	0.00	0.01	1.03	0.43	0.07	0.53	2.94	0.04	0.06	0.06	2.00	0.16	15.92	1.49	0.21	0.05	0.33	•	-	•	•	•		
hin 100 ft (200 ft ir	Pop	0.03	0.03	4.11	1.00	0.24	1.72	9.96	0.17	0.16	0.26	7.16	0.42	60.33	5.39	0.89	0.15	1.06	•	•	,	1	•		
Wit	Area	0.000	0.002	0.004	0.005	0.006	0.006	0.009	0.012	0.024	0.028	0.046	0.064	0.068	0.080	0.095	0.117	0.134	•	-	1		1	1	1
Housing		+	2	9	3	62	18	157	5	3	3	45	4	136	86	4	1	5	155	177	70	55	8	57	43
House-	shini	0	٢	4	ю	47	15	107	3	2	2	34	3	114	61	4	-	5	140	114	58	46	5	44	37
Population		1	3	16	7	157	49	362	12	5	6	122	8	432	220	17	3	16	522	401	187	168	158	151	141
Area	( 1111)	0.002	0.179	0.016	0.035	4.209	0.181	0.327	0.802	0.780	0.987	0.791	1.212	0.490	3.246	1.821	2.266	2.028	0.378	2.287	1.997	0.059	2.037	2.667	0 047
Census Block	0	390610261015005	390610261015031	390610261015018	390610261015017	390610204032031	390610204015015	390610261015001	390610261021016	390610204032020	390610262002026	390610204032024	390610261021031	390610261015019	390610204032022	390610262002021	390610261021006	390610261021030	390610261015027	390610261023001	390610204032034	390610261015021	390610261022020	390610262002001	390610261015026
County													Hamilton	County	5										

Table 1. Estimated Population Sizes and Housing Units Within Two Buffer Areas of the Proposed Gas Line (100 ft and 1,000 ft, Area-Proportional Fractions)

uffer Area idth)	mily House	0.00 22.00	.15 2.54	.82 1.16	.21 0.25	.97 5.97	.49 0.57	.75 7.91	20 0.20	.00 0.01	.86 0.86	0.02 0.02	.00 2.00	00 2.00	.00 1.00	.07 1.42	.00 22.00	.00 12.00	.94 1.32	.73 9.13	0.53 12.03	9.01 57.22	.45 0.60	2.55 84.62	.64 2.64	.00 4.00	1.25 43.76	a course of the second se
1,000 ft Bu	op Fa	3.99 20	.00 2	.74 0.	.60 0.	1.86 4.	.47 0.	3.45 4.	.0 66.	.02 0.	.58 0.	.07 0.	.00	.00 2	.00	.65 1.	3.00 9.	5.00 11	.77 0.	5.47 6.	3.59 10	5.85 49	.66 0	9.89 72	.03 2	.00 3.	1.79 34	
Within 1 (2,	Area F	0.026 8:	0.004 8	0.010 2	0.000	0.006 24	0.093 1	0.007 13	0.015 0	0.003 0	0.006 2	0.010 0	0.010 4	0.012 4	0.002 2	0.238 3	0.214 38	0.036 3!	0.325 3	0.348 29	0.341 3:	0.371 16	0.606 1	0.855 25	1.097 7	1.003 8	1.874 10	
g	House	-		-	-		-			-				-		0.00	1.66 (	5.62 (	0.13 0	1.20 0	1.63 (	8.44 (	0.06	7.06 0	0.30	0.52	5.86	
Buffer Are width)	Family	,	,	•	•			•	,		,		3			0.00	0.68	5.15	0.09	0.88	1.43	7.23	0.04	6.05	0.30	0.39	4.59	
hin 100 ft (200 ft ir	Pop	,		•		1				1	1		,		,	0.00	2.87	16.39	0.37	3.34	4.55	24.45	0.16	21.67	0.79	1.03	13.64	
With	Area		,	,	1	,	,	,		,	1	ı			,	0.000	0.016	0.017	0.032	0.046	0.046	0.055	0.060	0.071	0.124	0.130	0.251	
Housing		22	26	17	14	9	7	10	2	4	2	-	2	2	-	16	22	12	7	19	24	237	4	589	3	4	46	r
House-	SDIOI	20	22	12	12	5	9	9	2	+	2	-	-	2	-	12	ი	1	5	14	21	203	e	505	e	e	36	
Population		84	82	40	34	25	18	17	10	8	9	4	4	4	2	41	38	35	20	53	67	687	11	1809	ø	80	107	
Area		0.026	0.039	0.143	0.027	0.006	1.141	0.009	0.148	0.969	0.014	0.550	0.010	0.012	0.002	2.668	0.214	0.036	1.723	0.724	0.680	1.536	4.025	5.952	1.248	1.003	1.970	
Census Block	0	390610261015020	390610261015022	390610260011039	390610261015023	390610261015015	390610261021010	390610261015030	390610261015010	390610204032039	390610261015013	390610262002027	390610261015008	390610261015006	390610261015007	210150704012015	210150703112002	210150704012017	210150704011004	210150703112003	210150704012030	210150704012003	210150704012027	210150704012005	210150704011001	210150704012001	210150704012009	0101010101010
County																						Boone	County	Z				

County	Census Block	Area	Population	House-	Housing	Wit	hin 100 ft (200 ft ii	: Buffer Ar n width)	ea	With	in 1,000 (2,000 ft	ft Buffer A in width)	rea
	₽	(		Shipi		Area	Pop	Family	House	Area	Pop	Family	House
	210150703112013	0.367	10	з	4	•	•	•	1	0.015	0.42	0.13	0.17
	210150703112011	0.054	7	2	2					0.021	2.77	0.79	0.79
	Total	55.76	6,448	1,782	2,229	1.55	182	52	64	14.46	1,706	479	598

Source: US Decennial Census 2010 Note: Those blocks with no residing population are excluded.

Table 2. Land Cover Compositions (2011) Within Two Buffer Areas of the Proposed Gas Line

Rank	Land Cover	Within 100 ft (200 ft ir	Buffer Area า width)	Within 1,000 f (2,000 ft	t Buffer Area in width)
		Area (km²)	%	Area (km²)	%
-	Forest	0.60	36.4%	5.74	34.2%
2	Cultivated Crops	0.49	29.9%	4.41	26.3%
З	Cultivated Pasture	0.19	11.2%	1.64	9.8%
4	Open Space	0.14	8.2%	1.16	6.9%
5	Water	0.13	7.9%	2.60	15.5%
9	Developed: Low intensity	0.05	3.0%	0.65	3.9%
7	Developed: Medium intensity	0.03	2.0%	0.30	1.8%
8	Evergreen Forest	0.02	0.9%	0.20	1.2%
6	Developed: High intensity	0.01	0.5%	0.06	0.3%
	Total	1.65	100%	16.76	100%

Source: US Geological Survey (USGS) US National Land Cover Database 2011