Legal Department

December 29, 2010

Chairman Alan Schriber Ohio Power Siting Board Public Utilities Commission of Ohio 180 East Broad Street Columbus, OH 43215-3793

 Re:
 In the Matter of Columbus Board of Education)

 and Columbus Southern Power
)

 Company for Approval of a
)

 Case No. 10-1870-EL-EEC

 Special Arrangement Agreement
)

 with a Mercantile Customer
)

Dear Chairman Schriber,

Attached please find the Joint Application of Columbus Southern Power (CSP) and mercantile customer **Columbus Board of Education** for approval of a Special Arrangement of the commitment of energy efficiency/peak demand reduction (EE/PDR) resources toward compliance with the statutory benchmarks.

Amended Substitute Senate Bill 221 sets forth in R.C. 4928.66 EE/PDR benchmarks that electric distribution utilities shall be required to meet or exceed. The statute allows utilities to include EE/PDR resources committed by mercantile customers for integration into the utilities programs to be counted toward compliance with a utility's EE/PDR benchmarks. The statute also enables the Commission to approve special arrangements for mercantile customers that commit EE/PDR resources to be counted toward compliance with EE/PDR benchmarks.

The Commission's Order in Case No. 10-834-EL-EEC, established a streamlined process to expedite review of these special arrangements by developing a sample application process for parties to follow for consideration of such programs implemented during the prior three calendar years. Attached is CSP's version of that application and accompanying affidavit. Any confidential information referenced in the Joint Application has been filed in Commission Docket 10-1799-EL-EEC, under a request for protective treatment. CSP respectfully requests that the Commission treat the two cases as associated dockets.

Cordially,

<u>/s/ Matthew J. Satterwhite</u> Matthew J. Satterwhite, Senior Counsel

Attachments

Matthew J. Satterwhite Senior Counsel – Regulatory Services (614) 716-1915 (P) (614) 716-2014 (F) mjsatterwhite@aep.com



Case No.: 10-1870-**EL-EEC**

Rule 4901:1-39-05(F), Ohio Administrative Code (O.A.C.), permits a mercantile customer to file, either individually or jointly with an electric utility, an application to commit the customer's existing demand reduction, demand response, and energy efficiency programs for integration with the electric utility's programs. The following application form is to be used by mercantile customers, either individually or jointly with their electric utility, to apply for commitment of such programs implemented during the prior three calendar years.

Completed applications requesting the cash rebate reasonable arrangement option (Option 1) in lieu of an exemption from the rider will be automatically approved on the sixty-first calendar day after filing, unless the Commission, or an attorney examiner, suspends or denies the application prior to that time. Completed applications requesting the exemption from the electric utilities' energy efficiency rider option (Option 2) will not qualify for the 60-day automatic approval.

Complete a separate application for each customer program. Projects undertaken by a customer as a single program at a single location or at various locations within the same service territory should be submitted together as a single program filing, when possible. Check all boxes that are applicable to your program. For each box checked, be sure to complete all subparts of the question, and provide all requested additional information. Submittal of incomplete applications may result in a suspension of the automatic approval process or denial of the application.

If you consider some of the items requested in the application to be confidential or trade secret information, please file a copy of the application under seal, along with a motion for protective order pertaining to the material you believe to be confidential. Please also file a copy of the application in the public docket, with the information you believe to be confidential redacted.

Section 1: Company Information

Name: COLUMBUS BOARD OF EDUCATION

Principal address: 889 East 17th Avenue, Columbus, OH 43211

Address of facility for which this energy efficiency program applies: 791 Griggs Ct, Columbus, Oh 43223-2305

Name and telephone number for responses to questions:

Dan Spence, Columbus Board Of Education, (614) 365-5188

Electricity use by our company (at least one must apply to your company – check the box or boxes that apply):

We use more than seven hundred thousand kilowatt hours per year at our facility. (Please attach documentation.)

See <u>Confidential and Proprietary Attachment 4 – Calculation of Rider</u> <u>Exemption and UCT</u> which provides the facility consumption for the last three years, benchmark kWh, and the last 12 months usage.

We are part of a national account involving multiple facilities in one or more states. (Please attach documentation.) When checked, see <u>Attachment 6 – Supporting Documentation for a listing of the customer's</u> <u>name and service addresses of other accounts in the AEP Ohio service</u> <u>territory.</u>

Section 2: Application Information

- A) We are filing this application (choose which applies):
 - Individually, on our own.
 - Jointly with our electric utility.
- B) Our electric utility is: Columbus Southern Power Company

The application to participate in the electric utility energy efficiency program is "Confidential and Proprietary Attachment 3 – Self Direct Program Project Completed Application."

- C) We are offering to commit (choose which applies):
 - Energy savings from our energy efficiency program. (Complete Sections 3, 5, 6, and 7.)
 - Demand reduction from our demand response/demand reduction program. (Complete Sections 4, 5, 6, and 7.)
 - Both the energy savings and the demand reduction from our energy efficiency program. (Complete all sections of the Application.)

Section 3: Energy Efficiency Programs

A) Our energy efficiency program involves (choose whichever applies):

Early replacement of fully functioning equipment with new equipment. (Provide the date on which you replaced your fully functioning equipment, and the date on which you would have replaced your equipment if you had not replaced it early. Please include a brief explanation for how you determined this future replacement date (or, if not known, please explain why this is not known)).

- Installation of new equipment to replace equipment that needed to be replaced. We installed our new equipment on the following date(s):
- Installation of new equipment for new construction or facility expansion. We installed our new equipment on the following date(s): 12/14/2006
- B) Energy savings achieved/to be achieved by your energy efficiency program:
 - a) If you checked the box indicating that your project involves the early replacement of fully functioning equipment replaced with new equipment, then calculate the annual savings [(kWh used by the original equipment) (kWh used by new equipment) = (kWh per year saved)]. Please attach your calculations and record the results below:

Annual savings: kWh

b) If you checked the box indicating that you installed new equipment to replace equipment that needed to be replaced, then calculate the annual savings [(kWh used by less efficient new equipment) – (kWh used by the higher efficiency new equipment) = (kWh per year saved)]. Please attach your calculations and record the results below:

Annual savings: kWh

Please describe the less efficient new equipment that you rejected in favor of the more efficient new equipment.

c) If you checked the box indicating that your project involves equipment for new construction or facility expansion, then calculate the annual savings [(kWh used by less efficient new equipment) – (kWh used by higher efficiency new equipment) = (kWh per year saved)]. Please attach your calculations and record the results below:

Unit Quantity (watts) = Existing (watts x units) – Installed (watts x units)

kWh Reduction (Annual Savings) = Unit Quantity x (Deemed kWh/Unit)

Annual savings: 10,349 kWh

See <u>Confidential and Proprietary Attachment 5 – Self Direct Program</u> <u>Project Calculation</u> for annual energy savings calculations and <u>Attachment</u> <u>8 – Prescriptive Protocols</u> for the work papers that provide all methodologies, protocols, and practices used in this application for prescriptive measures, as needed.

Please describe the less efficient new equipment that you rejected in favor of the more efficient new equipment.

The less efficient new equipment is the minimum required by Ohio State code or Federal Standard whichever is more stringent. For those measures where no code applies the baseline equipment is assumed to be the least efficient equipment available in the marketplace or standard practice, whichever results in the most conservative annual savings. Any information available describing the less efficient new equipment option is provided in <u>Attachment 8 – Prescriptive Protocols</u> for the work papers that provide all methodologies, protocols, and practices used in this application for prescriptive measures.

Section 4: Demand Reduction/Demand Response Programs

- A) Our program involves (choose which applies):
 - Coincident peak-demand savings from our energy efficiency program.

Actual peak-demand reduction. (Attach a description and documentation of the peak-demand reduction.)

- Potential peak-demand reduction (choose which applies):
 - Choose one or more of the following that applies:

Our peak-demand reduction program meets the requirements to be counted as a capacity resource under a tariff of a regional transmission organization (RTO) approved by the Federal Energy Regulatory Commission.

Our peak-demand reduction program meets the requirements to be counted as a capacity resource under a program that is equivalent to an RTO program, which has been approved by the Public Utilities Commission of Ohio.

B) What is the date your peak demand reduction program was initiated?

The coincident peak-demand savings are permanent installations that reduce demand through energy efficiency and were installed on the date specified in Section 3 A above.

C) What is the peak demand reduction achieved or capable of being achieved (show calculations through which this was determined):

Unit Quantity (watts) = Existing (watts x units) – Installed (watts x units)

KW Demand Reduction = Unit Quantity (watts) x (Deemed KW/Unit (watts))

1.9 kW

See <u>Confidential and Proprietary Attachment 5 – Self Direct Program Project</u> <u>Calculation</u> for peak demand reduction calculation, and <u>Attachment 8 –</u> <u>Prescriptive Protocols</u> for the work papers that provide all methodologies, protocols, and practices used in this application for prescriptive measures, as needed.

Section 5: Request for Cash Rebate Reasonable Arrangement (Option 1) or Exemption from Rider (Option 2)

Under this section, check the box that applies and fill in all blanks relating to that choice.

Note: If Option 2 is selected, the application will not qualify for the 60-day automatic approval. All applications, however, will be considered on a timely basis by the Commission.

- A) We are applying for:
 - Option 1: A cash rebate reasonable arrangement.

OR

- Option 2: An exemption from the cost recovery mechanism implemented by the electric utility.
- B) The value of the option that we are seeking is:
 - Option 1: A cash rebate reasonable arrangement, which is the lesser of (show both amounts):
 - A cash rebate, based on avoided generation cost, of \$_____. (Attach documentation showing the methodology used to determine the cash rebate value and calculations showing how this payment amount was determined.)
 - OR
 - A cash rebate valued at no more than 50% of the total project cost, which is equal to \$ 631.80. (Attach documentation and calculations showing how this payment amount was determined.)

See <u>Confidential and Proprietary Attachment 5 – Self Direct</u> <u>Program Project Calculation</u> for incentive calculations for this mercantile program.

Option 2: An exemption from payment of the electric utility's energy efficiency/peak demand reduction rider.

An exemption from payment of the electric utility's energy efficiency/peak demand reduction rider for ______ months (not to exceed 24 months). (Attach calculations showing how this time period was determined.)

OR

Ongoing exemption from payment of the electric utility's energy efficiency/peak demand reduction rider for an initial period of 24 months because this program is part of an ongoing efficiency program that is practiced by our organization. (Attach documentation that establishes your organization's ongoing efficiency program. In order to continue the exemption beyond the initial 24 month period your organization will need to provide a future application establishing additional energy savings and the continuance of the organization's energy efficiency program.)

Section 6: Cost Effectiveness

The program is cost effective because it has a benefit/cost ratio greater than 1 using the (choose which applies):

- Total Resource Cost (TRC) Test. The calculated TRC value is: _____ (Continue to Subsection 1, then skip Subsection 2)
- Utility Cost Test (UCT) . The calculated UCT value is: 6.6 (Skip to Subsection 2.)

Subsection 1: TRC Test Used (please fill in all blanks).

The TRC value of the program is calculated by dividing the value of our avoided supply costs (capacity and energy) by the sum of our program costs and our electric utility's administrative costs to implement the program.

Our avoided supply costs were _____.

Our program costs were _____.

The utility's administrative costs were _____.

Subsection 2: UCT Used (please fill in all blanks).

We calculated the UCT value of our program by dividing the value of our avoided supply costs (capacity and energy) by the costs to our electric utility (including administrative costs and incentives paid or rider exemption costs) to obtain our commitment.

Our avoided supply costs were \$ 4,551.04

The utility's administrative costs were \$ 62.09

The utility's incentive costs/rebate costs were \$ 631.80.

Section 7: Additional Information

Please attach the following supporting documentation to this application:

• Narrative description of your program including, but not limited to, make, model, and year of any installed and replaced equipment.

See <u>Attachment 1 - Self Direct Project Overview and Commitment</u> for a description of the project. See <u>Attachment 6 - Supporting Documentation</u>, for the specifications of the replacement equipment <u>Attachment 8 - Prescriptive</u> <u>Protocols</u> for the work papers that provide all methodologies, protocols, and practices used in this application for prescriptive measures, as needed. Due to the length of time since the equipment replacement, the make, model and year of the replaced equipment is not available.

- A copy of the formal declaration or agreement that commits your program to the electric utility, including:
 - 1) any confidentiality requirements associated with the agreement;

See <u>Attachment 2 – Self Direct Program Project Blank Application</u> including Rules and Requirements. All confidentially requirements are pursuant to the Retrospective Projects/Rules and Requirements that are part of the signed application which is provided as Confidential and <u>Proprietary Attachment 3 – Self Direct Program Project Completed</u> <u>Application.</u>)

2) a description of any consequences of noncompliance with the terms of the commitment;

See <u>Attachment 2 – Self Direct Program Project Blank Application</u> including Rules and Requirements. All consequences of noncompliance are pursuant to the Retrospective Projects/Rules and Requirements that are part of the signed application which is provided as <u>Confidential and</u> <u>Proprietary Attachment 3 – Self Direct Program Project Completed</u> <u>Application</u>.

3) a description of coordination requirements between you and the electric utility with regard to peak demand reduction;

None required because the resources committed are permanent installations that reduce demand through increased efficiency during the Company's peak summer demand period generally defined as May through September and do not require specific coordination and communication to provide demand reduction capabilities to the Company. 4) permission by you to the electric utility and Commission staff and consultants to measure and verify energy savings and/or peak-demand reductions resulting from your program; and,

See <u>Attachment 2 – Self Direct Program Blank Application</u> including Rules and Requirements granting such permission pursuant to the Retrospective Projects/Rules and Requirements that are part of the signed application which is provided as <u>Confidential and Proprietary Attachment 3 – Self</u> <u>Direct Program Project Completed Application</u>.

5) a commitment by you to provide an annual report on your energy savings and electric utility peak-demand reductions achieved.

See <u>Attachment 1 - Self Direct Project Overview and Commitment</u> for the commitment to comply with any information and compliance reporting requirements imposed by rule or as part of the approval of this arrangement by the Public Utilities Commission of Ohio.

• A description of all methodologies, protocols, and practices used or proposed to be used in measuring and verifying program results. Additionally, identify and explain all deviations from any program measurement and verification guidelines that may be published by the Commission.

The Company applies the same methodologies, protocols, and practices to Self Direct Program retrospective projects that are screened and submitted for approval as it does to prospective projects submitted through its Prescriptive and Custom Programs. The Commission has not published a technical reference manual for use by the Company so deviations can not be identified. The project submitted is a prescriptive project and energy savings are determined as described in <u>Confidential and Proprietary Attachment 5 - Self Direct Program Project Calculation</u>, and <u>Attachment 8 - Prescriptive Protocols</u> for the work papers that provide all methodologies, protocols, and practices used in this application for prescriptive measures, as needed.



Application to Commit Energy Efficiency/Peak Demand Reduction Programs (Mercantile Customers Only)

Case No.: 10-1870-EL-EEC

State of ________:

IEFENEY ROE Affiant, being duly sworn according to law, deposes and says that:

1. I am the duly authorized representative of:

KEMA Services, Inc agent of Columbus Southern Power

- 2. I have personally examined all the information contained in the foregoing application, including any exhibits and attachments. Based upon my examination and inquiry of those persons immediately responsible for obtaining the information contained in the application, I believe that the information is true, accurate and complete.
- 3. I am aware of fines and penalties which may be imposed under Ohio Revised Code Sections 2921.11, 2921.31, 4903.02, 4903.03, and 4903.99 for submitting false information.

- ENERLY EXERCIENCY ENGINEY Signature of Affiant & Title

Sworn and subscribed before me this 27 day of NETEMBER, 200 Month/Year

Signature of official administering oath

HAULDOUN, OUTRUCH Manager

My commission expires on 01-03-11



ANGIE DOAN Notary Public, State of Ohio My Commission Expires 01-03-11



Attachment 1 Solf Direct Project Overview & Commitment Page 1 of 1

Self Direct Project Overview & Commitment

The Public Utility Commission of Ohio (PUCO) will soon review your application for participation in AEP Ohio's Energy Efficiency/Peak Demand Response program. Based on your submitted project, please select by initialing one of the two options below, sign and fax to 877-607-0740.

Customer Name	COLUMBUS BOARD OF EDUCATION	V	
Project Number	AEP-10-01078		
Customer Premise Address	791 GRIGGS CT. COLUMBUS, OH 43223-2305		
Customer Mailing Address	889 East 17th Avenue, Columbus, OH 43211		
Date Received	12/31/2009		
Project Installation Date	12/14/2006		
Annual kWh Reduction	10.349		
Total Project Cost	\$2,276.75	10 ST. 10	
Unadjusted Energy Efficiency Credit (EEC) Calculation	\$842.40		
Simple Payback (vrs)	2.3		
Utility Cost Test (UCT)	6.6		
	Please Choo	se One Option Below and Initial	
Option 1 - Self Direct EEC: 75%	\$631.80	Initial S	
Option 2 - EE/PDR Rider Exemption	5 Months (After PUCO Approval)	Initials	

Note: This is a one time selection. By selecting Option 1, the customer will receive payment in the amount stated above. Selection of Option 2: EE/PDR rider exemption, will result in the customer not being eligible to participate in any other energy efficiency programs offered by AEP Ohio during the period of exemption. In addition, the term of Option 2: EE/PDR rider exemption is subject to ongoing review for compliance and could be changed by the PUCO.

If Option 1 has been selected, will the Energy Efficiency Funds selected help you move forward with other energy efficiency projects?

____ NO

Project Overview:

The Self Direct (Prescriptive) project that the above has completed and applied is as follows. New Construction of Sullivant Elementary School resulted in a reduction of 2.106kW below baseline. Allowed lighting power is 59,998 W and the used lighting power is 57,892 W.

The documentation that was included with the application proved that the energy measures applied for were purchased and installed.

By signing this document, the Mercantile customer affirms its intention to commit and integrate the above listed energy efficiency resources into the utility's peak demand reduction, demand response, and energy efficiency programs. By signing, the Mercantile customer also agrees to serve as a joint applicant in any filings necessary to secure approval of this arrangement by the Public Utilities Commission of Ohio, and comply with any information and compliance reporting requirements imposed by rule or as part of that approval.

Columbus Southern Power Company

By: Title: Manage 12/27/1 Date:

COLUMBUS BOARD OF EDUCATION Βv Title: 2010 17 Date:

Attachment 2 - Self Direct Program Project Application Blank including Rules and Requirements Page 1 of 5

AEP OHIO° A unit of American Electric Power

Self-Direct Program Project Application

Application Instructions

- Complete the application form for each installation account number.
- Complete the Self-Direct Program spreadsheet, which is in Excel format, fully describing each
 measure replaced and installed along with project costs, existing and new equipment
 inventories/operation descriptions, baseline and new usage measurements or detailed
 calculations, total energy and demand savings, and other specified information. It shall be
 the customer's responsibility to provide all necessary documentation, calculations, and energy
 impact and summer peak demand saving verification in order to justify the project for
 incentives.
- Complete the Self-Direct Program project description and include all required documentation including detailed customer-approved invoices, proof of purchase, receipts, technical specifications, studies/proposals, etc.
- NOTE: Sending inadequate invoice documentation, incomplete/incorrect forms, or backup information, including detailed energy and summer peak demand calculations, will delay review of the application. Contact AEP Ohio if you require additional assistance in completing the application.
- Submit all information to AEP Ohio. All completed submissions become the property of AEP Ohio. Make a copy of all documents for your records.

FORM SUBMITTAL: Please note all Rules and Requirements. Return the signed, completed form and all required detailed documentation to:

> Mail: AEP Ohio 6031 East Main Street, Suite 190 Columbus, OH 43213 Fax: 877-607-0740 Email: gridsmartohio@kema.com Questions: Call 877-607-0739

Visit **gridsmartohio.com** for more information on the Self-Direct Program and other energy efficiency incentive programs offered by AEP Ohio.

Attachment 2 - Self Direct Program Project Application Blank including Rules and Requirements Page 2 of 5

Final Application



Self-Direct Program Project Application

> Project ID provided by AEP Ohio PROJECT ID:

THIS INCENTIVE APPLICATION FORM IS VALID THROUGH DECEMBER 31, 2009.

Pre-approval Application

SECTION 1: SELF-DIRECT CUSTOMER INFOR	MATIO	N						
Company Name					Contract Date	of Acce	ptance	
Mailing Address								
City				State	•		Zip Code	•
Contact Name (print)			Phone			Fax		
Contact E-mail*								
Building Type: Office School/College Warehouse Light industry	Retail/S □ Heav	ervice vy Industr	□ Restaura y □ Gov	nt (ernmei	□ Hotel/Motel nt/Municipal □	⊡ Meo Other_	dical 🗆	Grocery
By signing here, I acknowledge the information on this ap Rules and Requirements of this application and I have the	oplicatior e authori	n is accura ty to exec	ite and com ute on beha	plete. I If of m	: confirm I have r y company / con	read, ag poration	ree with a ì.	nd understand the
Customer Signature	-					Date		
* By providing your e-mail address, you are granting AEP	Ohio pe	rmission t	o send furth	er e-m	ails regarding ou	ir progra	ams and s	ervices
SECTION 2: COMPLETION AND PAYMENT INF	FORMA	TION						
Attention to				Total I \$	Incentive Amount	t Reque	sted	
Taxpayer ID # of Recipient (if not a Corporation or Tax E	xempt)			Total I \$	Project Cost		Total Inc \$	cremental Cost
Corporation (Inc, LLC, PC, etc.) Other (Individual, Partnership – may receive 1099)		Tax Exem	pt	Total /	Annual kWh Clain	med	kW Dem	and Reduction Claimed
SECTION 3: JOB SITE INFORMATION (where ex	quipmen	t was inst	alled)					
Job Site Name					Project Contact N	Name		
Job Site Address (physical location)					Project Contact 1	Telepho	ne	
City	State	Zip Code	e		Project Contact E	Email		
Job Site AEP Ohio Account Number (primary account) Job Site Premise Number								
SECTION 4: CONTRACTOR INFORMATION (equipment or service provider/ installer)								
Contractor Name								
Contractor Street Address			Ci	ty			State	Zip Code

			•			
Contractor Contact Name		Contact Telephone		Contact	t Email	
SECTION 5: CUSTOMER ELECTION (CHOOSE ONE OPTION AND COMPLETE ASSOCIATED INFORMATION)						
Option #1	Incentive Payment		Incentive Calculation:	\$		
Option #2	Exemption From EE/PDR R	lider	# of Months Exempte AFP Ohio)	d:	months (ca	alculation provided by

Attachment 2 - Self Direct Program Project Application Blank including Rules and Requirements

Self-Direct Program Retrospective Projects / Rules and Requirements

Columbus Southern Power Company and Ohio Power Company are collectively known as AEP Ohio ("AEP Ohio"). AEP Ohio provides energy-efficiency incentives for the purchase and installation of qualifying cost-effective equipment in the customer's facility (the customer's "Commitment of Resources") under the Rules and Requirements provided in this incentive application and subject to regulatory approvals.

Customer Qualifications

The Self-Direct Program (the "Program") applies to customers served at AEP Ohio's retail electric rates who meet the minimum energy usage requirements of 700,000 kWh per year or who are part of a national account involving multiple facilities in one or more states. This application defines the Date of Acceptance.

Terms and Conditions

- THIS INCENTIVE APPLICATION FORM IS VALID FOR SUBMITTAL BY SELF-DIRECT CUSTOMERS UNTIL DECEMBER 31, 2009. AEP Ohio incentive programs may be changed or cancelled at any time without notice. The Customer and its contractor are solely responsible for contacting AEP Ohio to ask whether or not the program is still in effect and to verify program parameters.
- Customer agrees to commit all energy and demand resources identified in this application to AEP Ohio's energy and demand target / benchmarks as identified in Senate Bill 221.
- Incentive payments are available while program funding lasts.
- To ensure maximum program participation, AEP Ohio reserves the right to limit funding on a per project basis.
- Pre-approval by AEP Ohio is required.
- Incentive items must be installed on the AEP Ohio electric account listed on the application.
- The incentive payment shall be:
 - 75% of the calculated incentive under the Business Lighting or Custom Program, whichever is applicable to this project.
- In lieu of a one-time incentive payment, the customer may elect to seek an exemption
 from the Energy Efficiency / Peak Demand Reduction (EE/PDR) Rider for the associated
 electric account(s) for a defined period of time as stated on this Application. For this
 exemption, and as defined in the table below, the incentive payment amount is
 compared to the estimated net present value (NPV) of the customer's estimated EE/PDR
 rider obligation, as calculated by AEP Ohio. If exemption is elected, the customer is not
 eligible for other programs offered by AEP Ohio during the period of exemption. Unless
 additional resources are committed, the customer will, after the specified number of
 months on this Application, be subject to the EE/PDR Rider.
- If an incentive is elected, the customer remains in the EE/PDR rider for the period of time that an exemption would have been in effect and may also participate in other AEP Ohio programs.
- All equipment must be new; used or rebuilt equipment is <u>not</u> eligible for an incentive.
- Eligible measures must produce <u>verifiable</u> and <u>persistent</u> energy and/or demand reduction, for a period of no less than five (5) years from the date of installation, through an increase in efficiency or through the use of load-shifting technologies. Measurement and verification may be required.
- Ineligible measures:
 - Rely solely on changes in customer behavior and require no capital investment, or merely terminate existing processes, facilities and/or operations.
 - Are required by state or federal law, building or other codes, or are standard industry practices.
 - 3. Involve fuel switching, plug loads, or generate electricity.
 - 4. Are easily reverted / removed or are installed entirely for reasons other than
 - improving energy efficiency.
 - 5. Include other conditions to be determined by AEP Ohio.
- Projects submitted for retrospective claims must be installed and operating between January 1, 2006 and the Date of Acceptance into the Self-Direct Program. Incentive levels, as shown in the table below, are based on the calendar year of installation / operation. Customer shall provide proof of equipment installation / operation start-up.
- All applications are subject to AEP Ohio, its contractor(s) / agent(s), and the Public Utility Commission of Ohio (PUCO) review and approval prior to any incentives paid or exemption from the EE/PDR Rider under this program.

OPTION #1 - ONE-TIME INCENTIVE PAYMENT				
Incentive Levels (for retrospective projects completed since January 1, 2006)	75% of the calculated incentive payment under the current Business Lighting or Custom Programs, whichever is applicable.			
Min / Max payback w/o incentive applied	1 year Min / 7 Year Max			

- Customer is allowed and encouraged to consider using all or a portion of the incentive payment, as received from AEP Ohio under this program, to help fund other customer-initiated energy efficiency and demand reduction projects in the future. Future projects can also qualify for incentives under the Business Lighting or Custom program.
- A signed final application with documentation verifying installation of the project including, but not limited to, equipment, invoices, approvals, and other related information must be submitted to AEP Ohio prior to application approval.
- The summer peak period is defined as weekday peak-demand hours (7:00 AM to 9:00 PM, May through September).
- Customers are encouraged to submit projects that warrant special treatment (i.e., non-typical projects) to be considered on a case-by-case basis by AEP Ohio.
- AEP Ohio reserves the right to randomly inspect customer facility(ies) for installation
 of materials listed on this incentive application and will need access to survey the
 installed project. Customer understands and agrees that Program installations may
 also be subject to inspections by the PUCO or their designee, and photographs of
 installation may be required. All documentation and verification is subject to strict
 confidentiality.
- If the inspection finds that customer did not comply with program rules and requirements, any incentive received under this Program must be returned to AEP Ohio including interest. Exemption from the rider will be voided as well. In addition, AEP Ohio reserves the right to withhold payment or exemption for projects that do not meet reasonable industry standards as determined by AEP Ohio.
- AEP Ohio reserves the right to refuse payment and participation if the customer or contractor violates program rules and procedures. AEP Ohio is not liable for incentives promised to customers as a result of program misrepresentation.
- The customer understands and agrees that all other terms and conditions, as specified in the application, including all attachments and exhibits attached to this application, which will serve as a contract for the customer's commitment of energy and demand resources to AEP Ohio, shall apply.
- AEP Ohio reserves the right to request additional backup information, supporting detail, calculations, manufacturer specification sheets or any other information prior to any incentive payment.
- Equipment could have been installed in retrofit, replacement, or new construction applications and must meet reasonable industry standards. All equipment / measures must meet minimum cost effectiveness requirements as defined or determined by AEP Ohio. Customer must also provide evidence of measure life.
- AEP Ohio will issue any approved incentives in the form of checks.
- Customer can not apply for incentives for future projects and elect after the fact to apply for exemption under this program.
- All documentation and verification is subject to strict confidentiality.
- · All completed submissions become the property of AEP Ohio.

Disclaimers

AEP Ohio:

- Does not endorse any particular manufacturer, product or system design by offering these incentives.
- Will not be responsible for any tax liability imposed on the customer as a result of the
 payment of incentives. AEP Ohio will report incentives greater than \$as income on
 IRS form 1099. Such incentives shall be taxable unless Customer 600 meets
 acceptable tax exemption criteria. Customers are encouraged to consult with their
 tax advisors about the taxability of any incentive payments.
- Does not expressly or implicitly warrant the performance of installed equipment (contact your contractor for detailed equipment warranties).
- Is not responsible for the proper disposal/recycling of any waste generated as a result of this project.
- Is not liable for any damage caused by the operation or malfunction of the installed equipment.
- Does not guarantee that a specific level of energy or cost savings will result from the implementation of energy conservation measures or the use of products funded under this program.

OPTION #2 - EXEMPTION FROM EE / PDR RIDER

Exemption from the EE/PDR rider is determined by comparing the value of the one-time incentive payment with the estimated net present value (NPV) of the EE/PDR rider payments, as calculated by AEP Ohio, for the customer's associated electric account. This NPV is defined as the customer's financial contribution to AEP Ohio's efforts to reach EE/PDR targets. Exemption term will be rounded to the nearest month.

Attachment 2 - Self Direct Program Project Application Blank including Rules and Requirements Page 4 of 5

Self-Direct Program

Retrospective Project Description: Project of	

Project Descriptive Name	Project In-service Date
Affected Electric Account Number(s)	

Claimed Project Baseline (AEP Ohio will make the final determination of applicable baseline):

Retrofit (the project was an elective retrofit and the equipment was still operable)

Replacement (the project was a replacement of equipment at or near the end of its useful life)

___ New (the project was an addition of new equipment in an existing facility or new construction)

Describe the project including detail of energy savings equipment. Attach additional sheets if needed.

Describe the removed equipment and operating strategy. Attach additional sheets if needed.

Describe the installed equipment and operating strategy. Attach additional sheets if needed.

Describe your calculation method for energy savings. Attach additional sheets if needed.

In addition to electrical energy and/or demand reduction, other benefits of proposed project include:

Conserves other utilities (gas, water, etc.)	Meets environmental regulations
Improves process flow	Reduces labor
Improves product quality	Saves energy
Increases production capacity	Uses fewer raw materials
Other	

Project Technical Specifications

between 7 a.m. to 9 p.m. on a weekday from May 1 through September 30.

Attachment 2 - Self Direct Program Project Application Blank including Rules and Requirements Page 5 of 5

(This sheet provides an example of required data collection. The Self-Direct spreadsheet provides additional guidance and streamlines the process for collecting, documenting and reporting this information to AEP Ohio, and it follows the format of this sheet. Please provide as much detail as possible on the Self-Direct spreadsheet to expedite review and processing of the requested incentive).

Please complete the Self-Direct spreadsheet for each measure installed and provide supporting documentation including engineering or equipment supplier studies, customer-approved invoices, purchase orders, detailed calculations of baseline and energy and peak summer demand savings. A detailed proposal and complete package will expedite review of application. This information is required by AEP Ohio and/or its consultants for project analysis.

	EQUIPMENT REMOVED OR LOWER EFFICIENCY OPTION	INSTALLED EQUIPMENT OR HIGHER EFFICIENCY OPTION	
Equipment type			
Manufacturer of equipment			
Model number(s)			
Date of Removal / In-Service Date			
Age of equipment at removal			
Estimated remaining useful life at time of removal or installation			
Efficiency rating			
Nameplate data: kW, tons, HP, watts, etc.			
Quantity			
Annual operating hours			
Annual energy savings (kWh)			
Summer peak reduction (kW)*			
Annual electric bill savings (\$)			
COST BREAKOUT			
Equipment			
Engineering			
Installation			
Other (explain)			
TOTAL PROJECT COST			
Incremental Cost = Installed Option Total Cost – Removed Equipment or Lower Efficiency Option Total Cost			
* Determination of peak demand reduction (kW) from non-HVAC equipment: For non-HVAC measures, calculate the average kW reduction over the period from 7 a.m. to 9 p.m., weekdays, from May 1 through September 30. The preferred calculation method will estimate hourly kW demands over the peak demand period, and average the results. However, if measures do not vary significantly during those hours, a less rigorous estimation process may be applied if approved in advance by the program.			
* Determination of neak demand reduction (kV	V) within HVAC systems: Calculate the maximu	m HVAC neak demand reduction that occurs	

Project #AEP-10-1078 Docket #CSP-10-1870

Customer Name	Somico Addrocc	City	Zin
			21µ 42215 1720
		COLUMBUS	43215-1720
		COLUMBUS	43207-3712
		GAHANNA	43230-1469
		COLUMBUS	43229-4476
COLUMBUS BOARD OF EDUCATION	546 JACK GIBBS BLVD BLDG 75	COLUMBUS	43215-1720
COLUMBUS BOARD OF EDUCATION	5535 SANDALWOOD BLVD	COLUMBUS	43229-4476
COLUMBUS BOARD OF EDUCATION	935 NORTHRIDGE RD	COLUMBUS	43224-2654
COLUMBUS BOARD OF EDUCATION	417 S WEYANT AVE REAR S	COLUMBUS	43213-2279
COLUMBUS BOARD OF EDUCATION	6655 SHARON WOODS BLVD	COLUMBUS	43229-7019
COLUMBUS BOARD OF EDUCATION	1590 ALPINE DR	COLUMBUS	43229-2120
COLUMBUS BOARD OF EDUCATION	546 JACK GIBBS BLVD APT 110	COLUMBUS	43215-1720
COLUMBUS BOARD OF EDUCATION	3392 SCOTTWOOD RD	COLUMBUS	43227-3564
COLUMBUS BOARD OF EDUCATION	5535 SANDALWOOD BLVD TRLR	COLUMBUS	43229-4476
COLUMBUS BOARD OF EDUCATION	529 E WEISHEIMER RD	COLUMBUS	43214-2238
COLUMBUS BOARD OF EDUCATION	908 BRICKER BLVD	COLUMBUS	43221-1642
COLUMBUS BOARD OF EDUCATION	3770 SHATTUCK AVE TRLR C	COLUMBUS	43220-4179
COLUMBUS BOARD OF EDUCATION	2155 FENTON ST	COLUMBUS	43224-2314
COLUMBUS BOARD OF EDUCATION	5151 KARL RD	COLUMBUS	43229-4431
COLUMBUS BOARD OF EDUCATION	1415 OAK ST	COLUMBUS	43205-2080
COLUMBUS BOARD OF EDUCATION	2521 FAIRWOOD AVE	COLUMBUS	43207-2712
COLUMBUS BOARD OF EDUCATION	288 REEB AVE	COLUMBUS	43207-1936
COLUMBUS BOARD OF EDUCATION	680 JACK GIBBS BLVD	COLUMBUS	43215-1708
COLUMBUS BOARD OF EDUCATION	6286 AMBLESIDE DR	COLUMBUS	43229-1984
COLUMBUS BOARD OF EDUCATION	104 W HUBBARD AVE UNIT A	COLUMBUS	43215-6415
COLUMBUS BOARD OF EDUCATION	4776 WINTERSET DR	COLUMBUS	43220-3139
COLUMBUS BOARD OF EDUCATION	2360 GARNET PL	COLUMBUS	43232-3905
COLUMBUS BOARD OF EDUCATION	791 GRIGGS AVE	COLUMBUS	43223-2305
COLUMBUS BOARD OF EDUCATION	873 WALCUTT AVE	COLUMBUS	43219-2668
COLUMBUS BOARD OF EDUCATION	546 JACK GIBBS BLVD BLDG 85	COLUMBUS	43215-1720
COLUMBUS BOARD OF EDUCATION	1590 ALPINE DR	COLUMBUS	43229-2120
COLUMBUS BOARD OF EDUCATION	519 TREVITT ST	COLUMBUS	43203-1100
COLUMBUS BOARD OF EDUCATION	2950 PARSONS AVE	COLUMBUS	43207-3742
COLUMBUS BOARD OF EDUCATION	1919 NORTHCLIFE DR REAR		43229-5332
COLUMBUS BOARD OF EDUCATION	1590 ALPINE DR	COLUMBUS	43229-2120
COLUMBUS BOARD OF EDUCATION	889 F 17TH AVE REAR	COLUMBUS	43211-2492
	2575 BRIGGS RD	COLUMBUS	43223-3110
COLUMBUS BOARD OF EDUCATION	2989 RFIS AVE	COLUMBUS	43224-3939
	3770 SHATTUCK AVE SIDE	COLUMBUS	43224 3333
	5220 AVALON AVE TRLR NEW	COLUMBUS	43220 4175
		COLUMBUS	43229 4735
	3245 OAK SPRING ST	COLUMBUS	43229-3214
		COLUMBUS	43219-3007
		COLUMBUS	43228-3144
			43211-2017
		COLUMBUS	43213-1720
			43212-2204
			43220-4173
			43223-4431
			43233-7306
	5600 E LIVINGSTON AVE BLDG SCHOOL	COLUMBUS	43232-2924
		COLUMBUS	43202-1453
	330 E DOMINION BLVD		43214-2212
		COLUMBUS	43229-5133
		COLUMBUS	43229-4131
		COLUMBUS	43206-2942
	3774 EAKIN KD		43228-3008
	1091 KING AVE		43212-2204
	530 CLEVELAND AVE	COLUMBUS	43215-1737
COLUMBUS BOARD OF EDUCATION	737 E HUDSON ST	COLUMBUS	43211-1034

COLUMBUS BOARD OF EDUCATION	3400 KOHR BLVD	COLUMBUS	43224-3051
COLUMBUS BOARD OF EDUCATION	3450 MEDWAY AVE	COLUMBUS	43213-1631
COLUMBUS BOARD OF EDUCATION	2655 SCOTTWOOD RD	COLUMBUS	43209-3130
COLUMBUS BOARD OF EDUCATION	1711 PENWORTH DR	COLUMBUS	43229-5214
COLUMBUS BOARD OF EDUCATION	2541 LINDBERGH DR TRLR OLD	COLUMBUS	43223-3124
COLUMBUS BOARD OF EDUCATION	2345 W MOUND ST	COLUMBUS	43204-2901
COLUMBUS BOARD OF EDUCATION	3392 SCOTTWOOD RD	COLUMBUS	43227-3564
COLUMBUS BOARD OF EDUCATION	1718 E COOKE RD	COLUMBUS	43224-5213
COLUMBUS BOARD OF EDUCATION	2200 WINSLOW DR	COLUMBUS	43207-2270
COLUMBUS BOARD OF EDUCATION	104 W HUBBARD AVE UNIT B	COLUMBUS	43215
COLUMBUS BOARD OF EDUCATION	NEWBLDG	COLUMBUS	43219
COLUMBUS BOARD OF EDUCATION	1560 MOLER RD	COLUMBUS	43207-1601
COLUMBUS BOARD OF EDUCATION	448 E LIVINGSTON AVE	COLUMBUS	43215-5530
COLUMBUS BOARD OF EDUCATION	1444 SHADY LANE RD	COLUMBUS	43227-2110
COLUMBUS BOARD OF EDUCATION	5220 AVALON AVE BLDG SCHOOL		43229-4753
COLUMBUS BOARD OF EDUCATION	3039 MARYLAND AVE REAR		43209-1538
COLUMBUS BOARD OF EDUCATION	499 F WFISHFIMER RD	COLUMBUS	43214-2238
COLUMBUS BOARD OF EDUCATION	2555 BRIGGS RD	COLUMBUS	43223-3110
	2541 LINDBERGH DR		43223-3124
	775 BARTEIELD DR	COLUMBUS	43207-4153
		COLUMBUS	43207 4135
			43213-2275
	2541 LINDBERGH DR TRI R	COLUMBUS	43223 2120
		COLUMBUS	43223 3124
			43213-1080
	2155 EENTON ST		43232-0008
			43224-2314
			43223-4733
			43223-2018
			43213-1720
			43203-1223
			43207
			43204-2013
			43207-2020
			43204
			43214-2715
			43215-4330
			43205-2050
		COLUMBUS	43229-3730
		COLUMBUS	43219-3434
		COLUMBUS	43205-1148
		COLUMBUS	43215-6415
		COLUMBUS	43202-1453
			43213-2279
		COLUMBUS	43211-2115
	104 W HUBBARD AVE UNIT B	COLUMBUS	43215
		COLUMBUS	43224-5213
			43214-2945
		GALENA	43021-9455
COLUMBUS BOARD OF EDUCATION	5600 E LIVINGSTON AVE ANNX	COLUMBUS	43232-2924
		COLUMBUS	43205-1543
	1249 SMITH KD	COLUMBUS	43207-1572
		COLUMBUS	43229-5214
	SOUU E LIVINGSTUN AVE UNIT SS		43232-2924
	DOD JACK GIBBS BLVD BLDG 101		43215-1720
		COLUMBUS	43229
	1130 S WAVERLY SI		43227-1932
			43224-2137
		COLUMBUS	43220-4179
ICOLUMBUS BOARD OF EDUCATION	5666 OAKMONT DR	COLUMBUS	43232-3043

COLUMBUS BOARD OF EDUCATION	1919 NORTHCLIFF DR	COLUMBUS	43229-5332
COLUMBUS BOARD OF EDUCATION	2949 WHITLOW RD	COLUMBUS	43232-5421
COLUMBUS BOARD OF EDUCATION	2505 BRENTNELL AVE	COLUMBUS	43211-1991
COLUMBUS BOARD OF EDUCATION	664 JACK GIBBS BLVD	COLUMBUS	43215-1708
COLUMBUS BOARD OF EDUCATION	726 FAIRWOOD AVE	COLUMBUS	43205-3011
COLUMBUS BOARD OF EDUCATION	5175 REFUGEE RD	COLUMBUS	43232-5352
COLUMBUS BOARD OF EDUCATION	4405 SCENIC DR	COLUMBUS	43214-3040
COLUMBUS BOARD OF EDUCATION	61 S 6TH ST	COLUMBUS	43215-4725
COLUMBUS BOARD OF EDUCATION	3771 EAKIN RD	COLUMBUS	43228-3001
COLUMBUS BOARD OF EDUCATION	5141 GODOWN RD	COLUMBUS	43220-7203
COLUMBUS BOARD OF EDUCATION	1833 STRATFORD WAY	COLUMBUS	43219-2943
COLUMBUS BOARD OF EDUCATION	1080 BINNS BLVD	COLUMBUS	43204-2381
COLUMBUS BOARD OF EDUCATION	889 E 17TH AVE	COLUMBUS	43211-2492
COLUMBUS BOARD OF EDUCATION	3220 GROVEPORT RD	COLUMBUS	43207-3259
COLUMBUS BOARD OF EDUCATION	600 JACK GIBBS BLVD	COLUMBUS	43215
COLUMBUS BOARD OF EDUCATION	540 JACK GIBBS BLVD	COLUMBUS	43215-1720
COLUMBUS BOARD OF EDUCATION	2555 BRIGGS RD	COLUMBUS	43223-3110
COLUMBUS BOARD OF EDUCATION	2989 VALLEYVIEW DR	COLUMBUS	43204-2012
COLUMBUS BOARD OF EDUCATION	31 N 17TH ST	COLUMBUS	43203-1802
COLUMBUS BOARD OF EDUCATION	345 E DESHLER AVE	COLUMBUS	43206-2712
COLUMBUS BOARD OF EDUCATION	3001 VALLEYVIEW DR	COLUMBUS	43204-2013
COLUMBUS BOARD OF EDUCATION	1400 SHADY LANE RD	COLUMBUS	43227-2110
COLUMBUS BOARD OF EDUCATION	2155 FENTON ST	COLUMBUS	43224
COLUMBUS BOARD OF EDUCATION	600 JACK GIBBS BLVD	COLUMBUS	43215
COLUMBUS BOARD OF EDUCATION	2633 MAYBURY RD	COLUMBUS	43232-6608
COLUMBUS BOARD OF EDUCATION	4077 KARL RD FRNT	COLUMBUS	43224-2137
COLUMBUS BOARD OF EDUCATION	2400 MOCK BD	COLUMBUS	43219-5300
COLUMBUS BOARD OF EDUCATION	5855 SAWMILL RD	DUBLIN	43017-2532
COLUMBUS BOARD OF EDUCATION	2155 FENTON ST	COLUMBUS	43224-2314
COLUMBUS BOARD OF EDUCATION	3770 SHATTUCK AVE	COLUMBUS	43220-4179
COLUMBUS BOARD OF EDUCATION	2989 VALLEYVIEW DR	COLUMBUS	43204-2012
COLUMBUS BOARD OF EDUCATION	2510 PARK CRESCENT DR	COLUMBUS	43232-4742
COLUMBUS BOARD OF EDUCATION	1469 E MAIN ST	COLUMBUS	43205-2152
COLUMBUS BOARD OF EDUCATION	4360 MAIZE RD	COLUMBUS	43224-1064
COLUMBUS BOARD OF EDUCATION	2950 PARSONS AVE TRLR 2	COLUMBUS	43207-3742
COLUMBUS BOARD OF EDUCATION	4077 KARL RD	COLUMBUS	43224-2137
COLUMBUS BOARD OF EDUCATION	1488 SHADY LANE RD	COLUMBUS	43227-2110
COLUMBUS BOARD OF EDUCATION	2571 NEIL AVE	COLUMBUS	43202-2522
COLUMBUS BOARD OF EDUCATION	5321 E LIVINGSTON AVE	COLUMBUS	43232-2864
COLUMBUS BOARD OF EDUCATION	5600 E LIVINGSTON AVE UNIT NS	COLUMBUS	43232-2924
COLUMBUS BOARD OF EDUCATION	288 REEB AVE	COLUMBUS	43207-1936
COLUMBUS BOARD OF EDUCATION	4841 E LIVINGSTON AVE	COLUMBUS	43227-2172
COLUMBUS BOARD OF EDUCATION	3399 KOHR BLVD	COLUMBUS	43224-3051
COLUMBUS BOARD OF EDUCATION	3039 MARYLAND AVE	COLUMBUS	43209-1538
COLUMBUS BOARD OF EDUCATION	2500 N CASSADY AVE	COLUMBUS	43219-1514
COLUMBUS BOARD OF EDUCATION	120 W HUBBARD AVF	COLUMBUS	43215-6415
	640 CLEVELAND AVE BEAR	COLUMBUS	43215-1775
	3039 MARYLAND AVE		43209-1538
COLUMBUS BOARD OF EDUCATION	3500 ALUM CREFK DR	COLUMBUS	43207-3423
COLUMBUS BOARD OF EDUCATION	1488 SHADY LANF RD	COLUMBUS	43227-2110
COLUMBUS BOARD OF EDUCATION	3039 MARYLAND AVF	COLUMBUS	43209-1538
COLUMBUS BOARD OF EDUCATION		COLUMBUS	43229
COLUMBUS BOARD OF EDUCATION	104 W HUBBARD AVE UNIT A	COLUMBUS	43215-6415
	2950 PARSONS AVE TRIR 1	COLUMBUS	43207-3742
		COLUMBUS	43229-5332
COLUMBUS BOARD OF EDUCATION	1265 KOEBEL RD	COLUMBUS	43207-2620



90.1 (2004) Standard

Report Date: 09/18/09

Data filename: P:\2006 Jobs\06X006 Columbus Public Schools - New Career Center\ cuments\ca\closeout\comchecks\901-2004\CPS Sullivant (90,1 2004).cck

Section 1: Project Information

Project Type: New Construction

Project Title : Sullivant Elementary School

Construction Site: 791 Griggs Ave. Columbus, OH 43223 Owner/Agent: Columbus Public Schools Designer/Contractor:

Section 2: General Information

Building Use Description by:

Building Type School/University Floor Area 49998

Section 3: Requirements Checklist

Interior Lighting:

Total proposed watts must be less than or equal to total allowed watts.

Allowed Watts	Proposed Watts	Complies
59998	57892	YËS

2. Exit signs 5 Watte or less per side.

Controls, Switching, and Wiring:

- 3. Independent manual or occupancy sensing controls for each space (remote swil with indicator allowed for safety or security).
- 4. Occupant sensing control in class rooms, conference/meeting rooms, and employee lunch and break rooms. Exceptions;

Spaces with multi-scene control; shop classrooms, laboratory classrooms, at preschool through 12th grade classrooms.

5. Automatic shutoff control for lighting in >5000 sq.ft buildings by time-of-day devi-occupant sensor, or other automatic control. Exceptions:

24 hour operation lighting; patient care areas; where auto shutoff would end: jer safety or security.

- 6. Master switch at entry to hotel/motel guest room.
- 7. Separate control device for display/accent lighting, case lighting, task lighting, n / visual lighting, lighting for sale, and demonstration lighting.
- 8. Photocell/aetronomical time switch on exterior lights. Exceptions:

Covered vehicle entrance/exit areas requiring lighting for safety, security and ye adeptation.

9. Tendem wired one-lamp and three-lamp ballasted luminaires (No single-lamp br ists).

- Exceptions:
 - Electronic high-frequency ballasts;
 - Luminaires not on same switch;

Recessed luminaires 10 ft. apart or surface/pendiant not continuous;

Luminaires on emergency circuits.

Attachment 6 Supporting Documents Page 5 of 5



90.1 (2004) Standard

Report Date:

Data filename: P:/2006 Jobs/06X006 Columbus Public Schools - New Career Centerl cuments/ca/closeout/comchacks/901-2004/CPS Sullivent (90.1 2004).cck

Section 1: Allowed Lighting Power Calculation

А	B Floor Area	Ç Xilowad 'atts / ft2	D Allowed Watte
School/University	49998	1.2	59998
	Total.	owed Watts	= 59998

Section 2: Proposed Lighting Power Calculation

A Fixture ID : Description / Lamp / Wattage Per Lemp / Ballast	La Fl:	asi 1re	C # of Fixtures	D Fixture Walt.	(C X D)
School/University (49998 bq.n.)					
T8 / T12 Fluorescent 1; CH-1; 48° T8 32W / Electronic		2	L 43	64	2752
T8 / T12 Fluorescent 3: CH-3: 48" T8 32W / Electronic		2	Ģ	64	384
T8 / T12 Fluorescent 4: R-1: 48° T8 32W / Electronic		2	496	64	31744
T8 / T12 Fluorescent 5: R-2: 48" T8 32W / Electronic		Ż	34	64	2176
T8 / T12 Fluorescent 6: R-3: 48" T8 32W / Electronic		3	50	96	4800
T8 / T12 Fluorescent 7; R-4; 48" T8 32W / Electronic		3	12	98	1152
Compact Fluorescent 1: R-5: Triple 4-pln 32W / Electronic		I -	36	32	1152
T8 / T12 Fluorescent 8: R-6: 48" T8 32W / Electronic		1	12	128	1536
T8 / T12 Fluorescent 9: R-7: 48" T8 32W / Electronic		2	10	64	640
Compact Fluorescent 2: R-8: Triple 4-pin 32W / Electronic		1	1	32	32
T8 / T12 Fluorescent 10: S-1: Other / Electronic		\$	21	240	5040
T8 / T12 Fluorescent 11: S-2: Other / Electronic		\$	3	240	720
T8 / T12 Fluorescent 12: S-3: 48" T8 32W / Electronic		5	7	192	1344
T8 / T12 Fluorescent 13: S-4: 46" T8 32W / Electronic		3	5	96	480
Compact Fluorescent 3: S-5: Twin Tube 36/39W / Electronic		7	4	273	1092
Incandescent 1: T-1: Other		1	12	200	2400
T8 / T12 Fluorescent 14: W-1: 48" T8 32W / Electronic		2	3	64	192
T8 / T12 Fluorescent 2; CH-2; 48" T8 32W / Electronic		2	4	64	256
	··· ••	To	tal Propose	ed Walls =	57892

Section 3: Compliance Calculation

If the Total Allowed Watts minus the Total Proposed Watts is greater than or equal to 2 = 5, the building complies.

Total Allowed Watts =	59998
Total Proposed Watts =	57692
Project Compliance =	2109

Interior Lighting PASSES: Design 4% botter than code.

Project Title: Sullivant Elementary School

Data filename: P:\2006 Jobs\06X006 Columbus Public Schools - New Career Centerki uments\ca\closeout\comohecks\901-2004\CPS Sullivant (90.1 2004).cck

Report date: 09/18/09 Page 3 of 4

Attachment 8 - Prescriptive Lighting Protocols for the work papers that provide all methodologies, protocols and practices used in this application Page 1 of 56



AEP GridSMART

KEMA Operations Manual Supplement – Summary of Deemed Savings for Incentives Year 2009



Attachment 8 - Prescriptive Lighting Protocols for the work papers that provide all methodologies, protocols and practices used in this application Page 2 of 56



Summary of Common Deemed Savings Measures

The below table contains prescriptive measures in a convenient format for viewing the default deemed savings.

Measure	Unit	Incentive Per Unit	kW Per Unit	Total kWh Per Unit	Years Life
Screw in CFL 5-15 Watts	Lamp	\$2.00	0.029	155	2
Screw in CFL 16-26 Watts	Lamp	\$2.00	0.054	290	2
Screw in CFL 27 Watts or higher	Lamp	\$3.00	0.069	368	2
Hardwired CFL 29W or Less	Fixture	\$30.00	0.052	276	12
Hardwired 30W or Greater	Fixture	\$60.00	0.103	544	12
T12 to T8 Conversion (with electronic ballast): 2-foot & 3-foot T12 to T8	Lamp	\$6.00	0.012	60.5	11
T12 to T8 Conversion (with electronic ballast): 4-foot T12 U Tube to T8 U Tube	Lamp	\$5.00	0.009	46.7	11
T12 to T8 Conversion (with electronic ballast): 4-foot T12 to HP or RW T8	Lamp	\$7.00	0.012	62	11
T12 to T8 Conversion (with electronic ballast): 8-foot T12 to Reduced Wattage T8	Lamp	\$7.00	0.016	78.7	11
Standard T8 to Reduced Wattage T8 (Lamp Only): 4-foot T8 to RW T8 (lamp only)	Lamp	\$1.00	0.005	28.8	3
Standard T8 to Reduced Wattage T8 (Lamp Only): 8-foot T8 to RW T8 (lamp only)	Lamp	\$1.00	0.005	24.6	3
Delamping (Combined with T8 ballast retrofit): 2-foot & 3 -foot delamping	Lamps Removed	\$5.00	0.022	119.3	11
Delamping (Combined with T8 ballast retrofit): 4-foot delamping	Lamps Removed	\$7.50	0.032	172.3	11
Delamping (Combined with T8 ballast retrofit): 8-foot delamping	Lamps Removed	\$12.50	0.062	333.7	11
LED Exit Signs	Fixture	\$25.00	0.042	343.4	16
Cold Cathode Lamps	Lamp	\$5.00	0.020	108	5
Lighting Occupancy Sensors	Controlled kW	\$90.00	0.300	1385	8
New T8/T5 Fixture	kW Reduction	\$350.00	0.916	4914	11
Lighting Density	kW Reduction	\$400.00	0.916	4914	11
LED Traffic Signals	Lamp	\$15.00	0.085	275	6
LED Pedestrian Signals	Lamp	\$15.00	0.044	150	8

Attachment 8 - Prescriptive Lighting Protocols for the work papers that provide all methodologies, protocols and practices used in this application Page 3 of 56



AEP GridSMART

KEMA Operations Manual Appendix A – AEP Ohio Prescriptive Lighting Protocols





Attachment 8 - Prescriptive Lighting Protocols for the work papers that provide all methodologies, protocols and practices used in this application Page 4 of 56

Table of Contents

Lighting	2
Compact Fluorescent Lamps, Screw-In	
Compact Fluorescent Fixtures, Hardwired	14
Permanent Lamp Removal	
High Performance and Reduced Wattage 4-foot T8 Lamps and Ballast	22
Reduced Wattage 4-foot Lamp Only	
Reduced Wattage 8-foot	
2-foot & 3-foot T8 Lamps and Ballast	
U-Tube T8 Lamps and Ballast	
Cold Cathode	
Exit Signs	41
Occupancy Sensors	
New T5/T8 Fluorescent Fixtures	
LED Traffic Signals	
Lighting Density	51

1

Attachment 8 - Prescriptive Lighting Protocols for the work papers that provide all methodologies, protocols and practices used in this application Page 5 of 56



Lighting



Most lighting measures presented in these work papers use the same methodology. The following provides the assumptions and methods used for calculating energy savings.

Baseline and retrofit equipment assumptions, i.e. wattages, are specific to the measure. Most lighting retrofits assume an early replacement of existing technologies where the baseline represents the equipment removed.

Savings are calculated by appyling operating hours and other parameters that define the energy savings. These workpapers base the energy savings methodology on the California 2005 DEER Study¹ assumptions. The DEER database is a tool that was jointly developed by the California Public Utilities Commission (CPUC) and the California Energy Commission with support and input from the Investor-Owned Utilities and other interested stakeholders. DEER provides operating hours, interative effects and coincidence factors by building type; however, savings for AEP Ohio Program will not be dependent on building type. Savings presented here are calculated using averages of DEER building type values.

Lighting factors used in savings calculations are listed in the table below. This document explains how these values and the resulting savings were derived.

CFL Annual Operating Hours	Other Lighting Annual Operating Hours	Demand Interactive Effects	Coincident Diversity Factors	Energy Interactive Effects
4,321	4,389	1.19	0.77	1.12

Table 1: Average Lighting Factors

Annual energy savings and the peak coincident demand savings were calculated using the equations below:

Non-coincident kW reduction = kW of existing equipment - kW of replacement equipment

Energy savings are based on the difference between baseline and efficient equipment connected wattage and annual operating hours, according to the following formula:

¹ 2005 Database for Energy Efficiency Resources (DEER) Update Study Final Report - Residential and Commercial Non-Weather Sensitive Measures



kWh Reduction = (kW of existing equipment - kW of replacement equipment) * (Annual operating hours)*(Energy Interactive Effects)

Coincident demand savings are calculated by applying the coincidence factor and the demand interactive effect, according to the following formula:

Coincident kW savings = non-coincident kW savings * Coincidence Factor * Demand interactive effect

Interactive factors account for savings that the measures achieve through avoided air conditioning load because of reduced internal heat gains from energy-efficient lighting. The interactive effects do not apply to exterior lighting.

The annual operating hours, the coincidence factors, and the interactive effect factors are all derived from DEER figures.

The following table lists building types set by DEER. A straight average across DEER building types would heavily weight sectors that happen to have multiple DEER categories. For instance, DEER has four sectors in education and only two in medical. A straight average of operating hours would have weighted the education sector twice as heavily as the medical sector where in reality the two are similar in electric demand.² Instead, our average values are that of sector groupings as stated in the table below.

² AEP Ohio 2009 to 2028 Energy Efficiency, Peak Demand Reduction Potential Study, Volume 2. Page 48. Summit Blue Consulting, Inc. August 13, 2009.

Attachment 8 - Prescriptive Lighting Protocols for the work papers that provide all methodologies, protocols and practices used in this application Page 8 of 56



Table 2: DEER Building Types

DEER	Average Grouping	
Education – Primary School	K 12 School	
Education – Secondary School	K-12 SC1001	
Education – Community College		
Education – University	College/Offiversity	
Grocery	Grocery	
Health/Medical – Hospital	Modical	
Health/Medical – Nursing Home	Medical	
Lodging – Hotel		
Lodging – Motel	Hotel/Motel	
Lodging – Guest Room		
Manufacturing – Light Industrial	Light Industry	
Office – Large	Office	
Office – Small	Onice	
Restaurant – Sit-Down	Pestaurant	
Restaurant – Fast-Food	Restaurant	
Retail – 3-Story Large		
Retail – Single-Story Large	Retail/Service	
Retail – Small		
Storage – Conditioned		
Storage – Unconditioned	Warehouse	
Warehouse – Refrigerated		

The following tables list DEER values. Compact fluorescent lamps (CFLs), LED lighting (unless otherwise noted), and integrated ballast ceramic metal halides have CFL lighting operating hours. Other lighting categories have different operating hours as shown below.

Attachment 8 - Prescriptive Lighting Protocols for the work papers that provide all methodologies, protocols and practices used in this application Page 9 of 56



DEER Market Sector	Demand Interactive Effects	Energy Interactive Effects
Education – Primary School	1.23	1.15
Education – Secondary School	1.23	1.15
Education – Community College	1.22	1.15
Education – University	1.22	1.15
Grocery	1.25	1.13
Medical – Hospital	1.26	1.18
Medical – Clinic	1.26	1.18
Lodging Hotel	1.14	1.14
Lodging Motel	1.14	1.14
Lodging – Guest Rooms	1.14	1.14
Manufacturing – Light Industrial	1.08	1.04
Office – Large	1.25	1.17
Office – Small	1.25	1.17
Restaurant – Sit-Down	1.26	1.15
Restaurant – Fast-Food	1.26	1.15
Retail – 3-Story Large	1.19	1.11
Retail – Single-Story Large	1.19	1.11
Retail – Small	1.19	1.11
Storage Conditioned	1.09	1.06
Storage Unconditioned	1.09	1.06
Warehouse	1.09	1.06

Table 3: Interactive Effects by Building Type from DEER



DEER Market Sector	Coincident Diversity Factors
Education – Primary School	0.42
Education – Secondary School	0.42
Education – Community College	0.68
Education – University	0.68
Grocery	0.81
Medical – Hospital	0.74
Medical – Clinic	0.74
Lodging Hotel	0.67
Lodging Motel	0.67
Lodging – Guest Rooms	0.67
Manufacturing – Light Industrial	0.99
Office – Large	0.81
Office – Small	0.81
Restaurant – Sit-Down	0.68
Restaurant – Fast-Food	0.68
Retail – 3-Story Large	0.88
Retail – Single-Story Large	0.88
Retail – Small	0.88
Storage Conditioned	0.84
Storage Unconditioned	0.84
Warehouse	0.84

Table 4: Coincident Diversity Factors from DEER



DEER Market Sector	CFL Annual Operating Hours	Other Lighting Annual Operating Hours
Education – Primary School	1,440	1,440
Education – Secondary School	2,305	2,305
Education – Community College	3,792	3,792
Education – University	3,073	3,073
Grocery	5,824	5,824
Medical – Hospital	8,736	8,736
Medical – Clinic*	4,212	4,212
Lodging Hotel	8,736	8,736
Lodging Motel	8,736	8,736
Lodging – Guest Rooms	1,145	NA
Manufacturing – Light Industrial*	4,290	4,290
Office – Large	2,739	2,808
Office – Small	2,492	2,808
Restaurant – Sit-Down	3,444	4,368
Restaurant – Fast-Food	6,188	6,188
Retail – 3-Story Large	4,259	4,259
Retail – Single-Story Large	4,368	4,368
Retail – Small	3,724	4,004
Storage Conditioned*	2,860	4,859
Storage Unconditioned*	2,860	4,859
Warehouse*	2,600	4,859

Table 5: Annual Operating Hours from DEER

* Not from DEER

Industrial-operating hours are assumed based on the following sources:

- DEER estimates hours to be 2,860.
- Efficiency Vermont Technical Reference User Manual's (No. 2004-29) estimates 5,913 hours.
- The 2004-2005 PG&E work papers assumed 6,650 hours for process industrial and 4,400 for assembly industrial.

DEER's estimated hours are far lower than figures other sources have provided and so we have increased the DEER values by 50% or to 4,290 hours. This value is reasonable and on the conservative side of the averages. We will use this conservative value until more data is available for AEP Ohio or other MidWestern utility territory.



Similarly, we believe that the DEER storage and warehouse operating hours are low as well. Using data from other programs in the region, KEMA has seen average operating hours that are significantly higher and is using a higher value of 4,859 as a better estimate of deemed operating hours for this region.

DEER has set Medical-Hospital operating hours at 8,736. We have lowered this value for the purposes of calculating our average by using operating hours that are 50% above that of offices or 4,212 hours (Medical-Clinic operating hours). This reduction accounts for areas in medical facilities that behave more like offices and do not operate around the clock. The value used in our calculations is the average of the DEER Hospital and the revised clinic operating hours.

Hotel/Motel operating hours are the average of guest room hours and either hotel or motel operating hours since a facility can only be one or the other.

Incremental costs are taken from a number of sources. The AEP Ohio 2009-2028 Energy Efficiency/Peak Demand Reduction Potential Study conducted in August of 2009 provides costs for some measures. Since this study was prepared specifically for AEP, the utility's costs are used whenever applicable. Because some measures listed in the study do not match with that of the program, costs are derived from other sources as well including DEER, KEMA, and the Commonwealth Edison Company's 2008-10 Energy Efficiency and Demand Response Plan prepared by ICF International. The ICF document is referenced as the ICF Portfolio Plan.
Attachment 8 - Prescriptive Lighting Protocols for the work papers that provide all methodologies, protocols and practices used in this application Page 13 of 56



Compact Fluorescent Lamps, Screw-In				
Measure Description	ENERGY STAR-rated CFLs with lamp/ballast efficacy of ≥ 40 lumens per Watt. Measure applies only if incandescent or HID lamps are being replaced.			
Units	Per lamp			
Base Case Description	Incandescent or HID lamps.			
Measure Savings	Source: KEMA			
Measure Incremental Cost	Source: AEP Ohio Potential Study			
Effective Useful Life	Source: DEER 2.5 years			

This incentive applies to screw-in lamps and applies only if an incandescent or high-intensity discharge (HID) lamp is being replaced. All screw-in CFLs must be ENERGY STAR® rated. The lamp/ballast combination must have an efficacy ≥40 lumens per Watt (LPW). For screw-in CFLs, electronic ballasts are required for lamps ≥18 Watts.

Measure Savings

Baseline and retrofit equipment assumptions are presented in the next table. Most lighting retrofits assume an early replacement of existing technologies where the baseline represents the equipment removed. The table shows the wattages used for the savings calculations.

Attachment 8 - Prescriptive Lighting Protocols for the work papers that provide all methodologies, protocols and practices used in this application Page 14 of 56



Measure	Base Wattage (Watts)	Retrofit Wattage (Watts)	kW Reductions (kW)
15 W or less	75	15	0.060
15 W or less	60	15	0.045
15 W or less	60	14	0.046
15 W or less	50	14	0.036
15 W or less	65	13	0.052
15 W or less	60	13	0.047
15 W or less	40	13	0.027
15 W or less	40	11	0.029
15 W or less	40	10	0.030
15 W or less	35	7	0.028
15 W or less	30	7	0.023
15 W or less	25	7	0.018
15 W or less	30	9	0.021
15 W or less	25	9	0.016
15 W or less	25	5	0.020
15 W or less	20	5	0.015
16W-25W	100	25	0.075
16W-25W	75	25	0.05
16W-25W	100	23	0.077
16W-25W	100	20	0.08
16W-25W	75	20	0.055
16W-25W	75	19	0.056
16W-25W	75	18	0.057
16W-25W	60	18	0.042
16W-25W	60	16	0.044
26W and Greater	150	40	0.11
26W and Greater	150	36	0.114
26W and Greater	100	30	0.07
26W and Greater	100	28	0.072
26W and Greater	100	26	0.074
26W and Greater	75	26	0.049

Table 6: Baseline and Retrofit Wattages



Table 7: Wattage Reduction

Wattage Category	Average Wattage Reduction
≤15	32
16 to 26	60
>26	76

The following tables provide the measure savings using the above wattage reduction assumptions.

Table 8: Measure Savings for 15 W or less

Annual Operating Hours	Demand Interactive Effects	Coincident Diversity Factors	Energy Interactive Effects	Peak kW Savings	kWh Savings
4,321	1.19	0.77	1.12	0.029	155

Table 9: Measure Savings for 16 – 26 W

Annual Operating Hours	Demand Interactive Effects	Coincident Diversity Factors	Energy Interactive Effects	Peak kW Savings	kWh Savings
4,321	1.19	0.77	1.12	0.054	290

Table 10: Measure Savings for > 26 W

Annual Operating Hours	Demand Interactive Effects	Coincident Diversity Factors	Energy Interactive Effects	Peak kW Savings	kWh Savings
4,321	1.19	0.77	1.12	0.069	368

Measure Savings Analysis

Annual energy savings and the peak coincident demand savings were calculated using the equations below.

Noncoincident kW reduction = kW of existing equipment - kW of replacement equipment

Energy savings are based on the difference between baseline and efficient equipment connected wattage and annual operating hours, according to the following formula:



kWh Reduction = (kW of existing equipment - kW of replacement equipment) * (Annual operating hours)*(Energy Interactive Effects)

Coincident demand savings are calculated by applying the coincidence factor and the demand interactive effect, according to the following formula:

Coincident kW savings = noncoincident kW savings * Coincidence Factor * Demand interactive effect

Interactive factors account for savings that the measures achieve through avoided air conditioning load because of reduced internal heat gains from energy-efficient lighting.

The annual operating hours, the coincidence factors, and the interactive effect factors are all derived from DEER figures.³

Measure Life and Incremental Measure Cost

The following table provides the measure life and incremental measure cost (IMC) documented for this measure as well as the source of the data.

Incremental cost is the cost difference between the energy-efficient equipment and the less efficient option. For lighting measures, the IMC is equal to the full measure cost since the cost of the less efficient option, i.e., not conducting the retrofit, is \$0.

Wattage Category		Value	Source
All	Measure Life	2.5	DEER 2005
≤15W	Incremental Measure Cost	\$4.13	AEP Ohio Potential Study
16W-26W	Incremental Measure Cost	\$4.13	AEP Ohio Potential Study
> 26W	Incremental Measure Cost	\$4.13	AEP Ohio Potential Study

 Table 11: Measure Life and Incremental Measure Cost

³ 2005 Database for Energy Efficiency Resources (DEER) Update Study Final Report - Residential and Commercial Non-Weather Sensitive Measures

Attachment 8 - Prescriptive Lighting Protocols for the work papers that provide all methodologies, protocols and practices used in this application Page 17 of 56



Compact Fluorescent Fixtures, Hardwired				
Measure Description	New fixtures or modular retrofits with hardwired electronic ballasts qualify. The CFL ballast must be programmed start or programmed rapid start with a PF \geq 90 and THD \leq 20%.			
Units	Per fixture			
Base Case Description	Incandescent or HID lamps.			
Measure Savings	Source: KEMA			
Measure Incremental Cost	Source: KEMA			
Effective Useful Life	Source: DEER 12 years			

Hardwired CFL incentives apply only to complete new fixtures or modular (pin-based) retrofits with hardwired electronic ballasts. The CFL ballast must be programmed 'start' or programmed 'rapid start' with a PF \geq 90 and THD \leq 20 percent.

Measure Savings

Baseline and retrofit equipment assumptions are presented in the table below. Most lighting retrofits assume early replacement of existing technologies where the baseline represents the equipment removed. The following table shows the wattages used for the savings calculations.



Measure	Base Wattage	Retrofit Wattage	kW Reduction
29W or Less	100	28	0.072
29W or Less	125	27	0.098
29W or Less	110	27	0.083
29W or Less	100	26	0.074
29W or Less	75	26	0.049
29W or Less	100	25	0.075
29W or Less	75	25	0.05
29W or Less	100	23	0.077
29W or Less	75	20	0.055
29W or Less	75	19	0.056
29W or Less	75	18	0.057
29W or Less	60	18	0.042
29W or Less	60	16	0.044
29W or Less	60	15	0.045
29W or Less	60	14	0.046
29W or Less	60	13	0.047
29W or Less	40	13	0.027
29W or Less	40	9	0.031
30W or Greater	120	30	0.09
30W or Greater	120	40	0.08
30W or Greater	200	55	0.145
30W or Greater	200	65	0.135

Table 12: Baseline and Retrofit Wattages

Table 13: Wattage Reduction

Wattage Category	Average Wattage Reduction
≤29	57
≥30W	113

The following tables provide the measure savings using the above wattage reduction assumptions.

Annual Operating Hours	Demand Interactive Effects	Coincident Diversity Factors	Energy Interactive Effects	Peak kW Savings	kWh Savings
4,321	1.19	0.77	1.12	0.052	276

-



Annual Operating Hours	Demand Interactive Effects	Coincident Diversity Factors	Energy Interactive Effects	Peak kW Savings	kWh Savings
4,321	1.19	0.77	1.12	0.103	544

Table 15: Measure Savings for ≥30W

Measure Savings Analysis

Annual energy savings and the peak coincident demand savings were calculated using the equations below. The annual operation hours, the coincidence factors, and the interactive effect factors were all derived from the DEER database.⁴ DEER values by building type were averaged for the AEP Ohio Program.

Non-coincident kW reduction = kW of existing equipment - kW of replacement equipment

Energy savings are calculated by applying the annual operating hours and the energy interactive effect, according to the following formula:

```
kWh Reduction = non-coincident kW savings * Annual operating hours * Energy interactive
effect
```

Coincident demand savings are calculated by applying the coincidence factor and the demand interactive effect, according to the following formula:

Coincident kW savings = non-coincident kW savings * Coincidence Factor * Demand interactive effect

Measure Life and Incremental Measure Cost

The table below provides the measure life and IMC documented for this measure as well as the source of the data.

Incremental cost is the cost difference between the energy-efficient equipment and the less efficient option. For lighting measures, the IMC is equal to the full measure cost since the cost of the less efficient option, i.e., not conducting the retrofit, is \$0.

⁴ 2005 Database for Energy Efficiency Resources (DEER) Update Study Final Report - Residential and Commercial Non-Weather Sensitive Measures

Attachment 8 - Prescriptive Lighting Protocols for the work papers that provide all methodologies, protocols and practices used in this application Page 20 of 56



Table 16: Measure Life and Incremental Measure Cost

Wattage Category		Value	Source
All	Measure Life	12	DEER
≤29	Incremental Measure Cost	\$95	KEMA
≥30W	Incremental Measure Cost	\$132	KEMA

Attachment 8 - Prescriptive Lighting Protocols for the work papers that provide all methodologies, protocols and practices used in this application Page 21 of 56



Permanent Lamp Removal					
Incentives are paid for the permanent removal of existing a 3' and 2' fluorescent lamps. Unused lamps, lamp holders, ballasts must be permanently removed from the fixture. Th measure is applicable when retrofitting from T12 lamps to lamps or simply removing lamps from a T8 fixture. Remov lamps from a T12 fixture that is not being retrofitted with T lamps are not eligible for this incentive.					
Units	Per lamp				
Base Case Description	Various configurations of fluorescent fixtures before removal of lamps.				
Measure Savings	Source: KEMA				
Measure Incremental Cost Source: ICF Portfolio Plan					
Effective Useful Life	Source: DEER 11 years				

Incentives are paid for the permanent removal of existing fluorescent lamps resulting in a net reduction of the number of foot-lamps. Customers are responsible for determining whether or not to use reflectors in combination with lamp removal in order to maintain adequate lighting levels. Unused lamps, lamp holders, and ballasts must be permanently removed from the fixture. This measure is applicable when retrofitting from T12 lamps to T8 lamps or simply removing lamps from a T8 fixture. Removing lamps from a T12 fixture that is not being retrofitted with T8 lamps is not eligible for this incentive. A Pre-approval Application is required for lamp removal projects in order for KEMA to have the option of conducting a pre-retrofit inspection.

Measure Savings

Non-coincident demand savings are summarized by the following table:

Wattage Category	Average Wattage Reduction
8 Foot Lamp Removal	68
4 Foot Lamp Removal	35
2 Foot or 3 Foot Lamp Removal	24

Table 17: Wattage Reduction

Attachment 8 - Prescriptive Lighting Protocols for the work papers that provide all methodologies, protocols and practices used in this application Page 22 of 56



Table 18: Measure Savings for 8-Foot Lamp Removal

Annual Operating Hours	Demand Interactive Effects	Coinciden t Diversity Factors	Energy Interactive Effects	8-foot Lamp Peak Savings (kW)	8-foot Savings (kWh)
4,389	1.19	0.77	1.12	0.062	333.7

Table 19: Measure Savings for 4-Foot Lamp Removal

Annual Operating Hours	Demand Interactive Effects	Coincident Diversity Factors	Energy Interactive Effects	4-foot Lamp Peak Savings (kW)	4-foot Savings (kWh)
4,389	1.19	0.77	1.12	0.032	172.3

Table 20: Measure Savings for 2-Foot or 3-Foot Lamp Removal

Annual Operating Hours	Demand Interactive Effects	Coincident Diversity Factors	Energy Interactive Effects	2-foot or 3-foot Lamp Peak Savings (kW)	2-foot or 3-foot Savings (kWh)
4,389	1.19	0.77	1.12	0.022	119.3

Measure Savings Analysis

Annual energy savings and the peak coincident demand savings were calculated using the equations below. The annual operating hours, the coincidence factors, and the interactive effect factors were all derived from the DEER database.⁵ However, DEER values by building type were averaged for the AEP Ohio Program.

Non-coincident kW reduction = kW of existing equipment - kW of replacement equipment

⁵ 2005 Database for Energy Efficiency Resources (DEER) Update Study Final Report - Residential and Commercial Non-Weather Sensitive Measures

Attachment 8 - Prescriptive Lighting Protocols for the work papers that provide all methodologies, protocols and practices used in this application Page 23 of 56



Energy savings are calculated by applying the annual operating hours and the energy interactive effect, according to the following formula:

```
kWh Reduction = non-coincident kW savings * Annual operating hours * Energy interactive effect
```

Coincident demand savings are calculated by applying the coincidence factor and the demand interactive effect, according to the following formula:

Coincident kW savings = non-coincident kW savings * Coincidence Factor * Demand interactive effect

Baseline assumptions are presented in the next table. Most lighting retrofits assume an early replacement of existing technologies where the baseline represents the equipment removed. The table shows the wattages used for the savings calculations. Weighted average savings values are used when determining deemed savings for each 8 foot or 4 foot lamp permanently removed.

 Table 21: Wattages for Eight-foot Lamps

Baseline	Base Wattage	Lamp Removed Wattage	Weight Percentages
Two 8' T12 (60W/75W)	140	70	85%
Two 8' T8 (59W)	111	56	15%
Total Weighted Average		68	

Table 22: Wattages for Four-foot Lamps

Baseline	Base Wattage	Lamp Removed Wattage	Weight Percentages
Two 4' T8 (32W)	65	36	3%
Two 4' T12 (34W/40W)	72	36	8%
Three 4' T8 (32W)	92	31	7%
Three 4' T12 (34W/40W)	115	38	22%
Four 4' T8 (32W)	118	30	15%
Four 4' T12 (34W/40W)	144	36	45%
Total Weighted Average		35	



Baseline	Base Wattage	Lamp Removed Wattage	Weight Percentages
Two 3' T12 (30W)	76	38	15%
Two 3' T8 (34W/40W)	48	24	15%
Two 2' T8 (17W)	31	15	30%
Two 2' T12 (20W)	56	28	30%
Three 2' T8 (17W)	46	16	2.5%
Three 2' T12 (20W)	62	21	2.5%
Four 2' T8 (17W)	60	15	2.5%
Four 2' T12 (20W)	112	28	2.5%
Total Weighted Average		24	

Table 23: Wattages for Two and Three-foot Lamps

Measure Life and Incremental Measure Cost

The following table provides the measure life and incremental measure cost (IMC) documented for this measure as well as the source of the data.

Incremental cost is cost difference between the energy efficient equipment and the less efficient option. For lighting measures, the IMC is equal to the full measure cost since the cost of the less efficient option, i.e., not conducting the retrofit, is \$0.

Measure Category		Value	Source
All	Measure Life	11	DEER
8-Foot Lamp Removal	Incremental Measure Cost	\$25.91	ICF Portfolio Plan
4-Foot Lamp Removal	Incremental Measure Cost	\$25.70	ICF Portfolio Plan
2-Foot or 3-Foot Removal	Incremental Measure Cost	\$25.70	KEMA

Attachment 8 - Prescriptive Lighting Protocols for the work papers that provide all methodologies, protocols and practices used in this application Page 25 of 56



High Performance and Reduced Wattage 4-foot T8 Lamps and Ballast						
Measure Description	This measure consists of replacing existing T12 4' lamps and magnetic ballasts with high performance 32W T8 lamps or reduced wattage 28W or 25W lamps and electronic ballasts. Both the lamp and ballast must meet the Consortium for Energy Efficiency (CEE) high performance or reduced wattage T8 specification (www.cee1.org) summarized below.					
Units	Per lamp					
Base Case Description	T12 lamp and magnetic ballasts					
Measure Savings	Source: KEMA					
Measure Incremental Cost	Source: AEP Ohio Potential Study					
Effective Useful Life	Source: DEER 11 years					

This measure consists of replacing existing T12 lamps and magnetic ballasts with highperformance T8 lamps or reduced wattage (28 or 25W) T8 lamps and electronic ballasts. This measure is based on the Consortium for Energy Efficiency (CEE) high-performance T8 or reduced wattage specification (<u>www.cee1.org</u>) and is summarized below. A list of qualified lamps and ballasts can be found at: <u>http://www.cee1.org</u>. Both the lamp and ballast must meet the specification to qualify for an incentive. The incentive is calculated based on the number of lamps installed. A manufacturer's specification sheet must accompany the application.

For reduced wattage 4-foot T8 lamps, the nominal wattage must be 28 W (\geq 2,585 Lumens) or 25 W (\geq 2,400 Lumens) to qualify. The mean system efficacy must be \geq 90 MLPW, CRI \geq 80, and lumen maintenance at 94 percent. Other requirements can be found on the CEE website using the links above.

The table below provides the specification for high performance systems.



Table 25: High-Performance T8 Specifications

Performance Characteristics for Systems							
Maan avatam office ov	≥ 90	≥ 90 Mean Lumens per Watt (MLPW) for Instant Start Ballasts					
Mean system enicacy	≥ 88 MLPW for Programmed Rapid Start Ballasts						
Performance Characteristics for Lamps							
Color Rendering Index (CRI)			≥ 80				
Minimum initial lamp lumens			≥ 3100 Lumens ⁶				
Lamp life			≥ 24,000 hours				
Lumen maintenance or			≥ 90% or				
minimum mean lumens		≥ 2	,900 Mean Lumens				
Performance Characteristics for Ballasts							
		Instar	nt-Start Ballast (BEF)				
	Lamps	Low BF ≤ 0.85	Norm 0.85 < BF ≤ 1.0	High BF ≥ 1.01			
	1	> 3.08	> 3.11	NA			
Ballast Efficacy Factor	2	> 1.60	> 1.58	>1.55			
(BEF)	3	≥ 1.04	≥ 1.05	≥ 1.04			
	4	≥ 0.79	≥ 0.80	≥ 0.77			
BEF = (BF x 100) / Ballast		Programme	d Rapid Start Ballast (E	BEF)			
Input Watts	1	≥ 2.84	≥ 2.84	NA			
	2	≥ 1.48	≥ 1.47	≥ 1.51			
	3	≥ 0.97	≥ 1.00	≥ 1.00			
	4	≥ 0.76	≥ 0.75	≥ 0.75			
Ballast Frequency	20 to 33 kHz or ≥ 40 kHz						
Power Factor	≥ 0.90						
Total Harmonic Distortion		≤ 20%					

Measure Savings

Savings are summarized by the following table:

Table 26: Measure Savings for High-Performance or Reduced Wattage 4-foot Lamp andBallast (per lamp)

Coincident Demand Savings (kW)	Energy Savings (kWh)	
0.012	62.0	

⁶ For lamps with temperature ≥4500K, 2,950 minimum initial lamp lumens are specified.

Attachment 8 - Prescriptive Lighting Protocols for the work papers that provide all methodologies, protocols and practices used in this application Page 27 of 56



Measure Savings Analysis

Annual energy savings and the peak coincident demand savings were calculated using the equations below. The annual operating hours, the coincidence factors, and the interactive effect factors were all derived from the DEER database and shown in the following table. However, DEER values by building type were averaged for the AEP Ohio Program.

Table 27: Factors used for Calculating Lighting Savings

Annual	Demand	Coincident	Energy
Operating	Interactive	Diversity	Interactive
Hours	Effects	Factors	Effects
4,389	1.19	0.77	1.12

Non-coincident kW reduction = kW of existing equipment - kW of replacement equipment

Energy savings are calculated by applying the annual operating hours and the energy interactive effect, according to the following formula:

kWh Reduction = non-coincident kW savings * Annual operating hours * Energy interactive effect

Coincident demand savings are calculated by applying the coincidence factor and the demand interactive effect, according to the following formula:

Coincident kW savings = non-coincident kW savings * Coincidence Factor * Demand interactive effect

Baseline and retrofit equipment assumptions are presented in the table below.



Table 28: Baseline and Retrofit Wattages for High-Performance or Reduced WattageFixture Retrofits

	T8, 4-foot Configuration	Base Fixture Wattage	Retrofit Lamp Wattage	Retrofit Fixture Wattage	Demand Savings per fixture (kW)	Demand Savings per lamp (kW)	Weight Percentages
	4-lamp	144	32	108	0.036	0.009	9%
gh	3-lamp	103	32	83	0.02	0.007	4%
Ï	2-lamp	72	32	54	0.018	0.009	8%
	1-lamp	43	32	28	0.015	0.015	4%
	4-lamp	144	28	96	0.048	0.012	15%
be	3-lamp	103	28	72	0.031	0.010	10%
Š	2-lamp	72	28	48	0.024	0.012	15%
	1-lamp	43	28	25	0.018	0.018	10%
	4-lamp	144	25	85	0.059	0.015	9%
Ž	3-lamp	103	25	66	0.037	0.012	4%
L	2-lamp	72	25	44	0.028	0.014	8%
	1-lamp	43	25	22	0.021	0.021	4%
	Weighted Average					0.0126	

Measure Life and Incremental Measure Cost

The table below provides the measure life and IMC documented for this measure as well as the source of the data. Incremental cost is the cost difference between the energy-efficient equipment and the less efficient option. In this case, the IMC is equal to the full measure cost since cost of the less efficient option is 0.

Table 29: Measure	e Life and Incremental Measu	re Cost
-------------------	------------------------------	---------

	Measure Category	Value	Source	
Measure Life	Lamp and Ballast	11	DEER	
Incremental Measure Cost	4 Foot Lamp and Ballast	\$13.14	AEP Ohio Potential Study	



R	Reduced Wattage 4-foot Lamp Only					
Measure Description	This measure consists of replacing existing standard T8 4' lamps and electronic ballasts with reduced wattage T8 lamps. The lamp must meet the Consortium for Energy Efficiency (CEE) reduced wattage T8 specification (www.cee1.org). The nominal wattage for 4 foot lamps must be 28W (\geq 2585 Lumens) or 25W (\geq 2400 Lumens) to qualify. The mean system efficacy must be \geq 90 MLPW, CRI \geq 80, and lumen maintenance at 94%. A manufacturer's specification sheet must accompany the application.					
Units	Per lamp					
Base Case Description	Standard T8 fixtures.					
Measure Savings	Source: KEMA					
Measure Incremental Cost	Source: ICF Portfolio Plan					
Effective Useful Life	Source: KEMA 3 years					

Incentives are available when replacing standard 32-Watt T8 lamps with reduced-wattage T8 lamps when an electronic ballast is already present. The lamps must be reduced wattage in accordance with the Consortium for Energy Efficiency (CEE) specification (www.cee1.org). Qualified products can be found at http://www.cee1.org. The nominal wattage must be 28 W (\geq 2,585 Lumens) or 25 W (\geq 2,400 Lumens) to qualify. The mean system efficacy must be \geq 90 MLPW, CRI \geq 80, and lumen maintenance at 94 percent. A manufacturer's specification sheet must accompany the application.

Measure Savings

Savings are summarized by the following table:

Table 30: Measure	Savings f	for Reduced	-Wattage 4-foot	Lamp Only
-------------------	-----------	-------------	-----------------	-----------

Coincident Demand Savings (kW)	Energy Savings (kWh)		
0.005	28.8		

Measure Savings Analysis

Annual energy savings and the peak coincident demand savings were calculated using the equations below. The annual operating hours, the coincidence factors, and the interactive effect factors were all derived from the DEER database and shown in the next table. However, DEER values by building type were averaged for the AEP Ohio Program.



		00	8 8
Annual Operating Hours	g Demand Coincident Interactive Diversity Effects Factors		Energy Interactive Effects
4,389	1.19	0.77	1.12

 Table 31: Factors used for Calculating Lighting Savings

Non-coincident kW reduction = kW of existing equipment - kW of replacement equipment

Energy savings are calculated by applying the annual operating hours and the energy interactive effect, according to the following formula:

kWh Reduction = non-coincident kW savings * Annual operating hours * Energy interactive effect

Coincident demand savings are calculated by applying the coincidence factor and the demand interactive effect, according to the following formula:

Coincident kW savings = non-coincident kW savings * Coincidence Factor * Demand interactive effect

Baseline and retrofit equipment assumptions are presented in the next table.

T8 Configuration	Base Lamp Wattage	Base Fixture Wattage	Retrofit Lamp Wattage	Retrofit Fixture Wattage	Demand Savings per fixture (kW)	Demand Savings per lamp (kW)	Weight Percentages
4 ft, 4-lamp	32	112	28	96	0.016	0.004	18%
4 ft, 3-lamp	32	85	28	72	0.013	0.004	13%
4 ft, 2-lamp	32	58	28	48	0.01	0.005	15%
4 ft ,1-lamp	32	32	28	25	0.007	0.007	5%
4 ft, 4-lamp	32	112	25	85	0.027	0.007	18%
4 ft, 3-lamp	32	85	25	66	0.019	0.006	13%
4 ft, 2-lamp	32	58	25	44	0.014	0.007	15%
4 ft ,1-lamp	32	32	25	22	0.01	0.010	5%
Weighted Av	reage					0.006	

Table 32: Baseline and Retrofit Wattages for 4-foot T8 Lamp Only

Measure Life and Incremental Measure Cost

The following table provides the measure life and IMC documented for this measure as well as the source of the data. Incremental cost is the cost difference between the energy-efficient equipment and the less efficient option. In this case, the IMC is equal to the full measure cost for

Attachment 8 - Prescriptive Lighting Protocols for the work papers that provide all methodologies, protocols and practices used in this application Page 31 of 56



lamp and ballast retrofit and incremental for lamp only. The lamp and ballast retrofit is a change in technology.

Table 33: Measure Life and Incremental Measure Cost

	Measure Category	Value	Source
Measure Life	Lamp Only	3	KEMA
Incremental Measure Cost	4 Foot Lamp Only	\$2.10	ICF Portfolio Plan

Attachment 8 - Prescriptive Lighting Protocols for the work papers that provide all methodologies, protocols and practices used in this application Page 32 of 56



Reduced Wattage 8-foot					
Measure DescriptionThis measure consists of replacing existing T12 8' lamps magnetic ballasts with reduced wattage T8 lamps and electronic ballasts. Both the lamp and ballast must meet Consortium for Energy Efficiency (CEE) high performance reduced wattage T8 specification (www.cee1.org). Eigh lamps must have a minimum MLPW of 90 and must have nominal wattage of less than 57W. A manufacturer's specification sheet must accompany the application.High wattage T8 (59W) can be replaced with reduced w lamps without replacing the ballast. The lamps must also CEE standards for reduced wattage					
Units	Per lamp				
Base Case Description	T12 lamp and magnetic ballasts or high watt T8 fixtures (for reduced wattage lamp only replacements).				
Measure Savings	Source: KEMA				
Measure Incremental Cost	st Source: DEER and ICF Portfolio Plan				
Effective Useful Life	Source: KEMA and DEER				

This measure consists of replacing existing T12 lamps and magnetic ballasts with reduced wattage lamp and electronic ballast systems. The lamps and ballasts must meet the Consortium for Energy Efficiency (CEE) specification (<u>www.cee1.org</u>). Qualified lamps and ballast products can be found at <u>http://www.cee1.org</u>. Incentives are also available when replacing 59-Watt T8 lamps with reduced-wattage T8 lamps when an electronic ballast is already present. Eight-foot lamps must have a minimum MLPW of 90 and must have a nominal wattage of less than 57 W. A manufacturer's specification sheet must accompany the application.

Measure Savings

Savings are summarized by the following table:

Table 34: Measure	Savings for	Reduced-Wattage	8-foot Lamp and	d Ballast
		U U		

Coincident Demand Savings (kW)	Energy Savings (kWh)
0.016	78.7



Table 35: Measure Savings for Reduced-Wattage 8-foot Lamp Only

Coincident Demand Savings (kW)	Energy Savings (kWh)
0.005	24.6

Measure Savings Analysis

Annual energy savings and the peak coincident demand savings were calculated using the equations below. The annual operating hours, the coincidence factors, and the interactive effect factors were all derived from the DEER database and shown in the table below. DEER values by building type were averaged for the AEP Ohio Program.

Table 36: Factors used for Calculating Lighting Savings

Annual Operating	Demand Interactive	Coincident Diversity	Energy Interactive
Hours	Effects	Factors	Effects
4,389	1.19	0.77	1.12

Non-coincident kW reduction = kW of existing equipment - kW of replacement equipment

Energy savings are calculated by applying the annual operating hours and the energy interactive effect, according to the following formula:

kWh Reduction = non-coincident kW savings * Annual operating hours * Energy interactive effect

Coincident demand savings are calculated by applying the coincidence factor and the demand interactive effect, according to the following formula:

Coincident kW savings = non-coincident kW savings * Coincidence Factor * Demand interactive effect

Baseline and retrofit equipment assumptions are presented in the next table.



	Configuration	Base Lamp Wattage	Base Fixture Wattage	Retrofit Lamp Wattage	Retrofit Fixture Wattage	Demand Savings per fixture (kW)	Demand Savings per lamp (kW)	Weight Percentages
st [–] p	8ft, 2 lamp	60	132	57	102	0.030	0.015	50%
am and alla	8ft, 1-lamp	60	77	57	60	0.017	0.017	50%
ц " щ	Weighted Avera	ge					0.016	
д /	8ft, 2 lamp	59	106	57	102	0.004	0.002	50%
UnC	8ft, 1-lamp	59	68	57	60	0.008	0.008	50%
70	Weighted Avera	ge					0.005	

Table 37: Baseline and Retrofit Wattages for 8-foot

Measure Life and Incremental Measure Cost

The following table provides the measure life and IMC documented for this measure as well as the source of the data. Incremental cost is the cost difference between the energy-efficient equipment and the less efficient option. In this case, the IMC is equal to the full measure cost for lamp and ballast retrofit and incremental for lamp only. The lamp and ballast retrofit is a change in technology.

Measure Value Source Category Lamp and Measure Life 11 DEER Ballast Measure Life 3 Lamp Only KEMA 8 Foot Lamp and **Incremental Measure Cost** DEER \$36.91 Ballast **ICF** Portfolio 8 Foot Lamp Incremental Measure Cost \$5.50 Only Plan

Table 38: Measure Life and Incremental Measure Cost

Attachment 8 - Prescriptive Lighting Protocols for the work papers that provide all methodologies, protocols and practices used in this application Page 35 of 56



2-foot & 3-foot T8 Lamps and Ballast				
Measure Description	This measure consists of replacing existing T12 2-foot and 3- foot lamps and magnetic ballasts with 17W, 2-foot, and 25W, 3- foot, T8 lamps and electronic ballasts.			
Units	Per lamp			
Base Case Description	T12 lamps and magnetic ballast			
Measure Savings	Source: KEMA			
Measure Incremental Cost	Source: PG&E 2006 Work papers			
Effective Useful Life	Source: DEER 11 years			

This measure consists of replacing existing T12 lamps and magnetic ballasts with T8 lamps and electronic ballasts. The lamp must have a color rendering index (CRI) \ge 80 and the ballast must have a total harmonic distortion (THD) \le 32% at full light output and power factor (PF) \ge 0.90. Ballasts must also be warranted against defects for 5 years. The incentive is calculated based on the number of lamps installed. A manufacturer's specification sheet must accompany the application.

Measure Savings

The coincident kW and kWh savings are provided in the following table:

Table 39: Measure Savings for 2	2-foot and 3-foot Lamp and Ballast (per lamp)

2-foot Lamp fi	xtures	3-foot Lamp fi	xtures
Coincident Demand Savings (kW)	Energy Savings (kWh)	Coincident Demand Savings (kW)	Energy Savings (kWh)
0.010	51.6	0.013	69.5

Attachment 8 - Prescriptive Lighting Protocols for the work papers that provide all methodologies, protocols and practices used in this application Page 36 of 56



Measure Savings Analysis

Annual energy savings and the peak coincident demand savings were calculated using the equations below. The annual operating hours, the coincidence factors, and the interactive effect factors were all derived from the DEER database and shown in the following table.

Table 40:	Factors	used for	Calculating	Lighting	Savings
-----------	---------	----------	-------------	----------	---------

Annual	Demand	Coincident	Energy
Operating	Interactive	Diversity	Interactive
Hours	Effects	Factors	Effects
4,389	1.19	0.77	1.12

Non-coincident kW reduction = kW of existing equipment - kW of replacement equipment

Energy savings are calculated by applying the annual operating hours and the energy interactive effect, according to the following formula:

kWh Reduction = non-coincident kW savings * Annual operating hours * Energy interactive effect

Coincident demand savings are calculated by applying the coincidence factor and the demand interactive effect, according to the following formula:

Coincident kW savings = non-coincident kW savings * Coincidence Factor * Demand interactive effect

Baseline and retrofit equipment assumptions are presented in the tables below. The fixture wattages were collected from PG&E's Non-residential Retrofit Program standard fixture wattage table.



Table 41: Baseline and Retrofit Wattages for 2-foot lamps

T8 Configuration	Base Lamp Wattage	Base Fixture Wattage	Retrofit Lamp Wattage	Retrofit Fixture Wattage	Demand Savings per fixture (kW)	Demand Savings per lamp (kW)	Weight Percentages
2 ft, 4-lamp	20	112	17	61	0.051	0.013	2.5%
2 ft, 3-lamp	20	84	17	47	0.037	0.012	2.5%
2 ft, 2-lamp	20	56	17	33	0.023	0.012	65%
2 ft ,1-lamp	20	28	17	20	0.008	0.008	30%
Weighted Average						0.011	

Table 42: Baseline and Retrofit Wattages for 3-foot lamps

T8 Configuration	Base Lamp Wattage	Base Fixture Wattage	Retrofit Lamp Wattage	Retrofit Fixture Wattage	Demand Savings per fixture (kW)	Demand Savings per lamp (kW)	Weight Percentages
3 ft, 4-lamp	30	152	25	87	0.065	0.0163	2.5%
3 ft, 3-lamp	30	114	25	67	0.047	0.0157	2.5%
3 ft, 2-lamp	30	76	25	46	0.030	0.0150	65%
3 ft ,1-lamp	30	38	25	26	0.012	0.0120	30%
Weighted Average						0.014	

Measure Life and Incremental Measure Cost

The table below provides the measure life and IMC documented for this measure as well as the source of the data. Incremental cost is cost difference between the energy-efficient equipment and the less efficient option. In this case, the IMC is equal to the full measure cost since cost of the less efficient option is \$0.

	Measure Category	Value	Source
Measure Life	Lamp and Ballast	11	DEER
Measure Life	Lamp Only	3	KEMA
Incremental Measure Cost	2 Foot Lamp and Ballast	\$10.50	PG&E 2006 Work Paper
Incremental Measure Cost	3 Foot Lamp and Ballast	\$21	PG&E 2006 Work Paper

Attachment 8 - Prescriptive Lighting Protocols for the work papers that provide all methodologies, protocols and practices used in this application Page 38 of 56



	U-Tube T8 Lamps and Ballast
Measure Description	This measure consists of replacing existing T12 U-tube lamps and magnetic ballasts with T8 U-tube lamps and electronic ballasts.
Units	Per lamp
Base Case Description	U-tube T12 lamps and magnetic ballast
Measure Savings	Source: KEMA
Measure Incremental Cost	Source: AEP Ohio Potential Study
Effective Useful Life	Source: DEER 11 years

This measure consists of replacing existing U-tube T12 lamps and magnetic ballasts with Utube T8 lamps and electronic ballasts. The lamp must have a color rendering index (CRI) \ge 80 and the ballast must have a total harmonic distortion (THD) \le 20% at full light output and power factor (PF) \ge 90. Ballasts must also be warranted against defect for 5 years. The incentive is calculated based on the number of lamps installed. A manufacturer's specification sheet must accompany the application.

Measure Savings

The coincident kW and kWh savings are in the following table.

Table 44: Measure Savings for U-tube Lamp and Ballast (per lamp)

Coincident Demand Savings (kW)	Energy Savings (kWh)
0.009	46.7

Measure Savings Analysis

Annual energy savings and the peak coincident demand savings were calculated using the equations below. The annual operating hours, the coincidence factors, and the interactive effect factors were all derived from the DEER database and shown in the following table.⁷

⁷ 2005 Database for Energy Efficiency Resources (DEER) Update Study Final Report - Residential and Commercial Non-Weather Sensitive Measures



Table 45: Factors used for Calculating Lighting Savings

Annual	Demand	Coincident	Energy
Operating	Interactive	Diversity	Interactive
Hours	Effects	Factors	Effects
4,389	1.19	0.77	1.12

Non-coincident kW reduction = kW of existing equipment - kW of replacement equipment

Energy savings are calculated by applying the annual operating hours and the energy interactive effect, according to the following formula:

kWh Reduction = non-coincident kW savings * Annual operating hours * Energy interactive effect

Coincident demand savings are calculated by applying the coincidence factor and the demand interactive effect, according to the following formula:

Coincident kW savings = non-coincident kW savings * Coincidence Factor * Demand interactive effect

Baseline and retrofit equipment assumptions are presented in the following table. The wattages were collected from PG&E's Non-residential retrofit standard wattages table.

T8 Configuration	Base Lamp Wattage	Base Fixture Wattage	Retrofit Lamp Wattage	Retrofit Fixture Wattage	Demand Savings per fixture (kW)	Demand Savings per lamp (kW)	Weight Percentages
U-tube, 2 lamp	35	72	32	59	0.013	0.007	50%
U-tube, 1 lamp	35	43	32	31	0.012	0.012	50%
Weighted Avera	ge					0.010	

 Table 46: Baseline and Retrofit Wattages for U-tube lamps

Measure Life and Incremental Measure Cost

The table below provides the measure life and IMC documented for this measure as well as the source of the data. Incremental cost is cost difference between the energy-efficient equipment and the less efficient option. In this case, the IMC is equal to the full measure cost since cost of the less efficient option is \$0. For U-tubes, it is assumed that the cost is the same as a high performance 4-foot T8 lamp (DEER measure ID D03-852).



	Measure Category	Value	Source				
Measure Life	Lamp and Ballast	11	DEER				
Measure Life	Lamp Only	3	KEMA				
Incremental Measure Cost	U-Tube Lamp and Ballast	\$13.14	AEP Potential Study				

Table 47: Measure Life and Incremental Measure Cost

Attachment 8 - Prescriptive Lighting Protocols for the work papers that provide all methodologies, protocols and practices used in this application Page 41 of 56



Cold Cathode				
Measure Description	All cold cathode fluorescent lamps (CCFLs) must replace incandescent lamps of at least 10 W and not greater than 40 W. Cold cathode lamps may be medium (Edison) or candelabra base. Product must be rated for at least 18,000 average life hours.			
Units	Per lamp			
Base Case Description	Incandescent			
Measure Savings	Source: KEMA, SCE			
Measure Incremental Cost	Source: PG&E			
Effective Useful Life	Source: SCE 5 years			

All cold cathode fluorescent lamps (CCFLs) must replace incandescent lamps of at least 10 W and not greater than 40 W. Cold cathode lamps may be medium (Edison) or candelabra base. The product must be rated for at least 18,000 average life hours.

Measure Savings

Baseline and retrofit equipment assumptions are presented in table below. Most lighting retrofits assume an early replacement of existing technologies where the baseline represents the equipment removed. The table shows the wattages used for the savings calculations from SCE and KEMA research of cold cathode manufacturers.

Table 48: Baseline and Retrofit Wattages

Measures ⁸	Base Wattage (Watts)	Retrofit Wattage (Watts)	Wattage Reduction (Watt)
Incandescent (15W) -> Cold Cathode FL (5W)	15	5	10
Incandescent (30W) -> Cold Cathode FL (5W)	30	5	25
Incandescent (40W) -> Cold Cathode FL (8W)	40	8	32
Average			22

The following table provides the measure savings using the above non-coincident savings.

⁸ Southern California Edison Company, Cold Cathode Fluorescent Lamp Workpaper WPSCNRLG0063. 2007.



Annual Operating Hours	Demand Interactive Effects	Coincident Diversity Factors	Energy Interactive Effects	Peak kW Savings	kWh Savings
4,321	1.19	0.77	1.12	0.020	108

Table 49: Measure Savings

Measure Savings Analysis

Annual energy savings and the peak coincident demand savings were calculated using the equations below. The annual operating hours, the coincidence factors, and the interactive effect factors were all derived from the DEER database.

Non-coincident kW reduction = kW of existing equipment - kW of replacement equipment

Energy savings are calculated by applying the annual operating hours and the energy interactive effect, according to the following formula:

kWh Reduction = non-coincident kW savings * Annual operating hours * Energy interactive effect

Coincident demand savings are calculated by applying the coincidence factor and the demand interactive effect, according to the following formula:

Coincident kW savings = non-coincident kW savings * Coincidence Factor * Demand interactive effect

Measure Life and Incremental Measure Cost

The following table provides the measure life and IMC documented for this measure as well as the source of the data.

Incremental cost is cost difference between the energy-efficient equipment and the less efficient option. In this case, the IMC is equal to the full measure cost since cost of the less efficient option is \$0..



Table 50: Measure Life and Incremental Measure Cost⁹

	Value	Source
Measure Life	5	SCE WP
Incremental Measure Cost	\$9.68	PG&E WP

⁹ Southern California Edison Company, Cold Cathode Fluorescent Lamp Workpaper WPSCNRLG0063. 2007, Pacific Gas & Electric, Lighting WP.doc, 2006.

Attachment 8 - Prescriptive Lighting Protocols for the work papers that provide all methodologies, protocols and practices used in this application Page 44 of 56



Exit Signs		
Measure Description	High-efficiency exit signs must replace or retrofit an existing incandescent exit sign. Electroluminescent, photoluminescent, T1 and light-emitting diode (LED) exit signs are eligible under this category. Non-electrified and remote exit signs are not eligible. All new exit signs or retrofit exit signs must be UL or ETL listed, have a minimum lifetime of 10 years, and have an input wattage ≤5 Watts or be ENERGY STAR qualified.	
Units	Per Sign	
Base Case Description	Incandescent Exit Signs	
Measure Savings	Source: ENERGY STAR	
Measure Incremental Cost	Source: AEP Ohio Potential Study	
Effective Useful Life	Source: DEER 16 years	

High-efficiency exit signs must replace or retrofit an existing incandescent exit sign.

Electroluminescent, photoluminescent, T1 and light-emitting diode (LED) exit signs are eligible under this category. Non-electrified and remote exit signs are not eligible. All new exit signs or retrofit exit signs must be UL or ETL listed, have a minimum lifetime of 10 years, and have an input wattage ≤5 Watts or be ENERGY STAR qualified.

Measure Savings

Baseline and retrofit equipment assumptions are presented in the next table. Most lighting retrofits assume an early replacement of existing technologies where the baseline represents the equipment removed. The table shows the wattages used for the savings calculations.

Table 51: Baseline and Retrofit Wattages

Measure	Base	Retrofit	Wattage
	Wattage	Wattage	Reduction
Two Incandescent Bulbs (20W each) -> LED EXIT Sign (5W)	40	5	35

The measure savings use the above non-coincident savings.

Table 52: Exit Sign Savings

Peak kW Savings	kWh Savings
0.042	343.4

Attachment 8 - Prescriptive Lighting Protocols for the work papers that provide all methodologies, protocols and practices used in this application Page 45 of 56



Measure Savings Analysis

Annual energy savings and the peak coincident demand savings were calculated using the equations below. The coincident diversity factor is 1.0 since the sign is on all the time. The operating hours are 8,760 hours per year.¹⁰

Annual	Demand	Coincident	Energy
Operating	Interactive	Diversity	Interactive
Hours	Effects	Factors	Effects
8,760	1.19	1.00	1.12

Table 53: Factors used for Calculating Savings

Non-coincident kW reduction = kW of existing equipment - kW of replacement equipment

Energy savings are calculated by applying the annual operating hours and the energy interactive effect, according to the following formula:

kWh Reduction = non-coincident kW savings * Annual operating hours * Energy interactive effect

Coincident demand savings are calculated by applying the coincidence factor and the demand interactive effect, according to the following formula:

Coincident kW savings = non-coincident kW savings * Coincidence Factor * Demand interactive effect.

Measure Life and Incremental Measure Cost

The following table provides the measure life and incremental measure cost (IMC) documented for this measure as well as the source of the data.

Incremental cost is cost difference between the energy efficient equipment and the less efficient option. In this case, the IMC is equal to the full measure cost since the cost of the less efficient option, i.e., not conducting the retrofit, is \$0.

¹⁰ 2005 Database for Energy Efficiency Resources (DEER) Update Study Final Report - Residential and Commercial Non-Weather Sensitive Measures



	Value	Source
Measure Life	16	DEER
Incremental Measure Cost	\$82.54	AEP Ohio Potential Study

Table 54: Measure Life and Incremental Measure Cost

Attachment 8 - Prescriptive Lighting Protocols for the work papers that provide all methodologies, protocols and practices used in this application Page 47 of 56



Occupancy Sensors		
Measure Description	Passive infrared, ultrasonic detectors and fixture-integrated sensors or sensors with a combination thereof are eligible. All sensors must be hard-wired and control interior lighting fixtures. The incentive is per Watt controlled.	
Units	Per Connected Watt	
Base Case Description	No Sensor	
Measure Savings	Source: DEER	
Measure Incremental Cost	t Source: DEER	
Effective Useful Life	Source: DEER 8 years	

Passive infrared, ultrasonic detectors and fixture-integrated sensors or sensors with a combination thereof are eligible. All sensors must be hard-wired and control interior lighting fixtures. The incentive is per Watt controlled.

Measure Savings

The annual operation hours, the coincidence factors, and the interactive effect factors were all derived from the DEER database.

Table 55: Measure	Savings for	Occupancy	Sensor per	Connected Watt
-------------------	-------------	-----------	------------	-----------------------

Annual Operating Hours	Demand Interactive Effects	Coincident Diversity Factors	Energy Interactive Effects	Peak Watt Savings	kWh Savings
4,389	1.19	0.77	1.12	0.0003	1.385

Measure Savings Analysis

Annual energy savings and the peak coincident demand savings were calculated using the equations below.

Energy savings are calculated by applying the annual operating hours and the energy interactive effect, according to the following formula:

kWh Reduction = Connected wattage/1000 * Annual operating hours * Energy interactive effect*Occupancy Off Rate

Coincident demand savings are calculated by applying the coincidence factor and the demand interactive effect, according to the following formula:

Attachment 8 - Prescriptive Lighting Protocols for the work papers that provide all methodologies, protocols and practices used in this application Page 48 of 56



Coincident kW savings = Connected wattage/1000 * Occupancy Off Rate * Coincidence Factor * Demand interactive effect

The baseline for this measure is fixtures that do not include any automatic controls, i.e., manual switches. Since the unit is defined as per connected Watt, the baseline demand is one watt. Demand savings depend on whether areas are high or low occupancy. DEER states that occupancy time off rates are at 20 percent for high-occupancy building types and 50 percent for low-occupancy building types.¹¹. The table below shows the assumed range of occupancy off rates. Calculations here are performed with the 28% average sensor off rate.

Average Grouping	Occupancy Sensor Off Rate
Office	20%
School (K-12)	20%
College/University	20%
Retail/Service	20%
Restaurant	20%
Hotel/Motel	20%
Medical	20%
Grocery	20%
Warehouse	50%
Light Industry	50%
Heavy Industry	50%
Average	28%

Table 56:	Occupancy	Off Rate
-----------	-----------	----------

Measure Life and Incremental Measure Cost

The following table provides the measure life and IMC documented for this measure as well as the source of the data.

Incremental cost is cost difference between the energy efficient equipment and the less efficient option. For lighting measures, the IMC is equal to the full measure cost since the cost of the less efficient option, i.e., not conducting the retrofit, is \$0.

¹¹ 2005 Database for Energy Efficiency Resources (DEER) Update Study Final Report - Residential and Commercial Non-Weather Sensitive Measures


Table 57: Measure Life and Incremental Measure Cost

	Value	Source
Measure Life	8	DEER
Incremental Measure Cost	\$0.32	DEER

Attachment 8 - Prescriptive Lighting Protocols for the work papers that provide all methodologies, protocols and practices used in this application Page 50 of 56



	New T5/T8 Fluorescent Fixtures		
Measure DescriptionThis measure consists of replacing one or more existing fixtures with new fixtures containing T8 or T5 lamps and electronic ballasts. The T8 or T5 lamps must have a col rendering index (CRI) \geq 80. The electronic ballast must frequency (\geq 20 kHz), UL listed, and warranted against or for 5 years. Ballasts must have a power factor (PF) \geq 0. Ballasts for 4-foot lamps must have total harmonic disto (THD) \leq 20 percent at full light output. For 2- and 3-foot ballasts must have THD \leq 32% at full light output.			
Units	Per Watt reduced		
Base Case Description	Typically high wattage HID fixtures		
Measure Savings	Source: KEMA		
Measure Incremental Cost	Source: KEMA		
Effective Useful Life	Source: DEER 11 years		

This measure consists of replacing one or more existing fixtures with new fixtures containing T8 or T5 lamps and electronic ballasts. The T8 or T5 lamps must have a color rendering index (CRI) \geq 80. The electronic ballast must be high frequency (\geq 20 kHz), UL listed, and warranted against defects for 5 years. Ballasts must have a power factor (PF) \geq 0.90. Ballasts for 4-foot lamps must have total harmonic distortion (THD) \leq 20 percent at full light output. For 2- and 3-foot lamps, ballasts must have THD \leq 32 percent at full light output.

Measure Savings

The annual operating hours, the coincidence factors, and the interactive effect factors were all derived from the DEER database.¹²

Annual Operating Hours	Demand Interactive Effects	Coincident Diversity Factors	Energy Interactive Effects	Peak Watt Savings	kWh Savings
4,389	1.19	0.77	1.12	0.0009	4.9141

Table 58: Measure Savings for New T8/T5 Fluorescent Fixtures per Watt Reduced

¹² 2005 Database for Energy Efficiency Resources (DEER) Update Study Final Report - Residential and Commercial Non-Weather Sensitive Measures

Attachment 8 - Prescriptive Lighting Protocols for the work papers that provide all methodologies, protocols and practices used in this application Page 51 of 56



Measure Savings Analysis

Annual energy savings and the peak coincident demand savings were calculated using the equations below.

Non-coincident kW reduction = kW of existing equipment - kW of replacement equipment

Energy savings are calculated by applying the annual operating hours and the energy interactive effect, according to the following formula:

kWh Reduction = no-coincident kW savings * Annual operating hours * Energy interactive effect Coincident demand savings are calculated by applying the coincidence factor and the demand interactive effect, according to the following formula:

Coincident kW savings = non-coincident kW savings * Coincidence Factor * Demand interactive effect

Baseline and retrofit equipment assumptions are variable. Because we define this measure with the number of watts reduced, the non-coincident demand savings will be one watt by definition.

Measure Life and Incremental Measure Cost

The following table provides the measure life and IMC documented for this measure as well as the source of the data.

Incremental cost is cost difference between the energy efficient equipment and the less efficient option. For lighting measures, the IMC is equal to the full measure cost since the cost of the less efficient option, i.e., not conducting the retrofit, is \$0.

	Value	Source
Measure Life	11	DEER
Incremental Measure Cost ¹³	\$0.75	KEMA

Table 59: Measure Life and Incremental Measure Cost

Attachment 8 - Prescriptive Lighting Protocols for the work papers that provide all methodologies, protocols and practices used in this application Page 52 of 56



LED Traffic Signals		
	LED traffic signals meeting ENERGY STAR criteria, including	
	arrow signals, that will replace existing incandescent traffic	
Massura Description	signals. Signals shall have a maximum wattage of 25. Signals	
Measure Description	must be installed and active. Lights must be hardwired, with the	
	exception of pedestrian hand signals. Yellow lights are not	
	eligible for rebates.	
Units	Per Signal	
Base Case Description	Incandescent fixtures	
Measure Savings	Source: Michigan Statewide Energy Savings Database	
Measure Incremental Cost	Source: Michigan Statewide Energy Savings Database	
	Source: Michigan Statewide Energy Savings Database	
Effective Useful Life	Trattic Signal: 6 Years Pedestrian Signal: 8 Years	

LED traffic signals that meet ENERGY STAR criteria save 80-90 percent of the energy typically consumed by incandescent traffic signals and LED signals generally last 5-10 times longer. Since traffic signals operate 24 hours a day, 365 days a year, the opportunity for energy savings is significant, particularly in the peak demand. LED Traffic signals perform better than incandescent models and are a better value. They also have lower maintenance costs because they need to be replaced less frequently.

Measure Savings

The energy savings vary for red, green and yellow signals. Savings also vary for round lamps, arrows and pedestrian signals. Reviewing details on California, Wisconsin and Texan programs, the savings below are typical.

In general, savings are greater on car traffic signals and cost generally less than for pedestrian signals. These savings include diversity for each lamp type, and represent an average.

Table 60: Measure Savings Traffic and Pedestrian Signals

Signal Type	kW	kWh
Traffic	0.085	275
Pedestrian	0.044	150

Attachment 8 - Prescriptive Lighting Protocols for the work papers that provide all methodologies, protocols and practices used in this application Page 53 of 56



Measure Life and Incremental Measure Cost

The following table provides the measure life and IMC documented for this measure as well as the source of the data.

Incremental cost is cost difference between the energy efficient equipment and the less efficient option. For lighting measures, the IMC is equal to the full measure cost since the cost of the less efficient option, i.e., not conducting the retrofit, is \$0.

	Signal Type	Value	Source
Measure Life	Traffic	6	KEMA
Incremental Measure Cost	Traffic	\$90	KEMA
Measure Life	Pedestrian	8	KEMA
Incremental Measure Cost ¹⁴	Pedestrian	\$140	KEMA

Table 61: Measure Life and Incremental Measure Cost

Attachment 8 - Prescriptive Lighting Protocols for the work papers that provide all methodologies, protocols and practices used in this application Page 54 of 56



Lighting Density		
Measure Description	Savings for new construction lighting projects will be calculated	
Measure Description	with lighting density.	
Units	Per kW Reduced	
Base Case Description	ASHRAE 90.1-2004 Lighting density.	
Measure Savings	Source: KEMA	
Measure Incremental Cost	Source: NA	
Effective Useful Life	Source: DEER	
	11 Years	

This measure applies only to new construction lighting projects and savings are calculated using the ASHRAE 90.1-2004 new construction lighting density as a baseline. The wattages are given on a per square foot basis and vary with business type.

The following table shows the ASHRAE criteria.

Building Type	Lighting Power Density (W/ft ²)	Building Type	Lighting Power Density (W/ft ²)
Automotive	0.9	Motion Picture Theatre	1.2
Convention Center	1.2	Multi-Family	0.7
Court House	1.2	Museum	1.1
Dining: Bar Lounge/Leisure	1.3	Office	1.0
Dining: Cafeteria/Fast Food	1.4	Parking Garage	0.3
Dining: Family	1.6	Penitentiary	1.0
Dormitory	1.0	Performing Arts Theatre	1.6
Exercise Center	1.0	Police/Fire Station	1.0
Gymnasium	1.1	Retail	1.5
Health Care	1.0	School/University	1.2
Hospital	1.2	Sports Arena	1.1

Table 62: ASHRAE Building Density Criteria



Hotel	1.0	Town Hall	1.1
Library	1.3	Transportation	1.0
Manufacturing Facility	1.3	Warehouse	0.8
Motel	1.0	Workshop.	1.4

Applications must calculate the kW reduction using the above numbers, taking into account the business type as well as the actual building square footage. On a per kW reduced basis, the following table shows the energy and coincident savings.

Table 63: Lighting Density Savings

Annual Operating Hours	Demand Interactive Effects	Coincident Diversity Factors	Energy Interactive Effects	Peak Watt Savings	kWh Savings
4,389	1.19	0.77	1.12	0.916	4,914

Measure Savings Analysis

Annual energy savings and the peak coincident demand savings were calculated using the equations below.

Non-coincident kW reduction = kW of existing equipment - kW of replacement equipment

Energy savings are calculated by applying the annual operating hours and the energy interactive effect, according to the following formula:

kWh Reduction = no-coincident kW savings * Annual operating hours * Energy interactive effect Coincident demand savings are calculated by applying the coincidence factor and the demand interactive effect, according to the following formula:

Coincident kW savings = non-coincident kW savings * Coincidence Factor * Demand interactive effect

Baseline and retrofit equipment assumptions are variable. Because we define this measure as in the number of watts reduced, the non-coincident demand savings will be one kW by definition.

Measure Life

The following table provides the measure life documented for this measure as well as the source of the data.

Attachment 8 - Prescriptive Lighting Protocols for the work papers that provide all methodologies, protocols and practices used in this application Page 56 of 56



Table 64: Measure Life

	Value	Source
Measure Life	11	DEER

This foregoing document was electronically filed with the Public Utilities

Commission of Ohio Docketing Information System on

12/29/2010 10:56:11 AM

in

Case No(s). 10-1870-EL-EEC

Summary: Application of Columbus Board of Education and Columbus Southern Power Company for approval of a special arrangement agreement with a mercantile customer electronically filed by Mr. Matthew J Satterwhite on behalf of Columbus Southern Power Company