

OQ TEST SCORE CONFIRMATION LETTER

Employer Confirmation of Student(s)'s Abilities to do the tasks listed below

7001 Center Street Mer 440

	ntor, ()-255-	OH 44060 5198						
	This fo	orm indicates tha	Module orize the above tes t the necessary Kn confirmation of the	owledge and	Skills have been	evaluated b	y UTI	Circle YES OK to do Tai issued.
	FAX:	614-482-8070 OR		ch person an	d each task.			
	Having results to retu	knowledge of the shown above, I are this form in a sized Signature:	s of names and consess person's train authorize UTI to issuitmety manner could be a suit of the suit o	ing, work exp sue a qualific	erience, job peri	ormance and	d the qualifi as indicate	ication test d. Failure
F1F2 - G1 - H2 H2 - I-1(5-I-1(6) I-1(6) L-1(-1(6) L-1(6) L-1(-1(6) L-1(-1(6) L-1(-1(6) L-1(6) L-1(-1(6) L-1(6) L-1(-1(6) L-1(6) L-1(-1(6) L-1(6) L-1(-1(6) L-1(6) L-1(6) L-1(-1(6) L-1(6) L-	Mech- Excav Instal Instal Contro Attacr 4)-Monito 8)-Monito - Evalue - Readi - Evalue - Monito 1(a) Tappir - Tappir (S) - Pun - Purge Establi	n and Mechanical Jo anical Joining of Pot ation Backfilling I meter regulator se is service lines Joining Corrosion: Inst Anodes, Apply/Rep ining Corrosion-Inse ining Corrosion-Inse ormal Application ng Test Stations, Ev	vethylene Pipe alling Test Leads Elect air Coatings rical Methods beting Rectifiers/Bonds of Corrosion Control al. App. of Above Ground Corr of Above Ground Corr of g Pipelines apping Tees	und Corrosion (Corrosion,		

rpt4Confirmations



OQ TEST SCORE CONFIRMATION LETTER

7001 Center Street Mentor, OH 44060 440-255-5198 Employer Confirmation of Student(s)'s Abilities to do the tasks listed below

		Module	Date	Evaluator	Method	Score	OK to do	
Courtney, Robert A.	GZ21-015294-44	CI-15	6/21/2016	Ted Ressler	E, O	Pass	es or	No
		CL-1	6/21/2016	Ted Ressler	E, O	Pass	Yes or	No
		CL-1b	6/21/2016	Ted Ressler	E, O	Pass	10 (88)	No
		CL-3	6/21/2016	Ted Ressler	E, O	Pass	(es) or	No
		CL-3a	6/21/2016	Ted Ressler	E, O	Pass	Yes or	No
		CL-5	6/21/2016	Ted Ressler	E, O	Pass	(Yes) or	No
		CL-6	6/21/2016	Ted Ressler	E, O	Pass		No
		CM-2	6/21/2016	Ted Ressler	E, O	Pass	(188) or	No
Lette, Tyler E.	TW88-18305F-83	CI-15	6/21/2016	Ted Ressler	E, O	Pass	Yes or	No
		CL-1	6/21/2016	Ted Ressler	E, O	Pass	Yes or	No
		CL-1b	6/21/2016	Ted Ressier	E, O	Pass	Yes or	No
		CL-3	6/21/2016	Ted Ressier	E, O	Pass	Yes or	No
		CL-3a	6/21/2016	Ted Ressler	E, O	Pass	Yes or	No
		CL-5	6/21/2016	Ted Ressler	E, O	Pass	Yes or	No
		CL-6	6/21/2016	Ted Ressler	E, O	Pass	Yes or	No
		CM-2	6/21/2016	Ted Ressler	E, O	Pass	Cos or	No
McCormick, Ryan	ZG37-23A060-66	CI-15	6/21/2016	Ted Ressler	E, O	Pass	Yes or	No
		CL-1	6/21/2016	Ted Ressler	E, O	Pass	Yes or	No
		CL-1b	6/21/2016	Ted Ressler	E, O	Pass	Yes or	No
		CL-3	6/21/2016	Ted Ressier	E, O	Pass	Yes or	No
		CL-3a	6/21/2016	Ted Ressler	E, O	Pass	Yes or	No
		CL-5	6/21/2016	Ted Ressler	E, O	Pass	Yes or	No
		CL-6	6/21/2016	Ted Ressler	E, O	Pass	Yes or	No
		CM-2	6/21/2016	Ted Ressler	E, O	Pass	Yes or	No
Papp, George M.	7096-08C12F-08	CI-15	6/21/2016	Ted Ressler	E, O	Pass	(Tes) or	No
		CL-1	6/21/2016	Ted Ressler	E, O	Pass	Yes or	No
		CL-1b	6/21/2016	Ted Ressier	E, O	Pass	Yes or	No
		CL-3	6/21/2016	Ted Ressler	E, O	Pass	Yes or	No
		CL-3a	6/21/2016	Ted Ressler	E, O	Pass	Yes or	No
		CL-5	6/21/2016	Ted Ressler	E, O	Pass	(10 (89))	No
		CL-6	6/21/2016	Ted Ressler	E, O	Pass	O'BB or	No
		CM-2	6/21/2016	Ted Ressler	E, O	Pass	Yes or	No

Ohio Rural Natural Gas Co-Op 7001 Center Street



OQ TEST SCORE CONFIRMATION LETTER

Employer Confirmation of Student(s)'s Abilities to do the tasks listed below

Mei 440

		nter Stre							
Me	entor, (OH 440	60						
44	0-255-	5198							
				Module	Date	Evaluator	Method	Score	Circle YES if OK to do Task
	This fo	orm indica	tes that the r	ecessary Kr	owledge an	your employee(s d Skills have bee ility to perform th	n evaluated b	y UTI	issued.
	Please FAX:	mark eith 614-482-	8070	N (no) for ea	ch person a	nd each task.			
	MAIL:	4700 Hon	chnologies ir ner Ohio Lan rt, OH 43125						
	Please	check SP	ELLING of na	ames and co	mpany name	es for printing of	certificates a	nd cards.	
	results to retu	shown at rn this fon	nove, I author	rize UTI to is:	sue a qualifi	perience, job per cation certificate he certification be	for the tasks	as indicate	Ication test d. Failure
F1F2 - G1 - H1 - H2 - H1 - H1 (5-14)	Mecha Excavi Install Contro Attach 4)-Monito - Evalua - Readi - Evalua - Monito -1(a) -) - Tappin - Tappin (S) - Purg - Establi	n and Mecha anical Joinin ation Backfi I meter regul i service line colling Corrosi ning Corrosi ning Corrosi tition and Api ning Test Stat tion and Api ring Corrosi Tapping and g Pipelines	ilator sets s s ion: Installing T poly/Repair Coe non-Electrica f plication of Con ions, Eval. Joins, Eval. Joins on Control Bagging Pipeli . Self Tapping s s /Small s Odorant	est Leads Electings sthods Rectifiers/Bonds resion Control o. of Above Gro we Ground Control	und Corrosion	onitoring Atmospheric	e Corresion,		

rpt4Confirmations



OQ TEST SCORE CONFIRMATION LETTER

7001 Center Street Mentor, OH 44060 440-255-5198

Employer Confirmation of Student(s)'s Abilities to do the tasks listed below

		Module	Date	Evaluator	Method	Score	Circle YES if OK to do Task
Lette, Tyler E.	TW88-1B305F-83	CF-1	4/27/2016	Jeff Wolfe	E, O	Pass	Yes or No
		CF-2	4/27/2016	Jeff Wolfe	E, O	Pass	(Yes) or No
		CF-7	4/27/2016	Jeff Wolfe	E, O	Pass	es or No
McCormick, Jack	D552-2701A2-33	CF-1	4/27/2016	Jeff Wolfe	E, O	Pass	Yes or No
		CF-2	4/27/2016	Jeff Wolfe	E, O	Pass	Yes or No
		CF-7	4/27/2016	Jeff Wolfe	E, O	Pass	(es) or No
McCormick, Ryan	ZG37-23A060-66	CF-1	4/27/2016	Jeff Wolfe	E, O	Pass	(Yes) or No
		CF-2	4/27/2016	Jeff Wolfe	E, O	Pass	Yes or No
		CF-7	4/27/2016	Jeff Wolfe	E, O	Pass	(Yes) or No
Papp, George M.	7096-08C12F-08	CF-1	4/27/2016	Jeff Wolfe	E, O	Pass	(Yes) or No
		CF-2	4/27/2016	Jeff Wolfe	E, O	Pass	Yes or No
		CF-7	4/27/2016	Jeff Wolfe	E, O	Pass	Yes or No
Sebring, Ed K.	6071-2D31E8-44	CF-1	4/27/2016	Jeff Wolfe	E, O	Pass	(Yes) or No
		CF-2	4/27/2016	Jeff Wolfe	E, O	Pass	(Yes) or No
		CF-7	4/27/2016	Jeff Wolfe	E, O	Pass	Yes or No
Stanish, David	M257-24726C-18	CF-1	4/27/2016	Jeff Wolfe	E, O	Pass	(Yes) or No
		CF-2	4/27/2016	Jeff Wolfe	E, O	Pass	Yes or No
		CF-7	4/27/2016	Jeff Wolfe	E, O	Pass	(Yes) or No

Please review and authorize the above test scores for your employee(s) so certificates may be issued. This form indicates that the necessary Knowledge and Skills have been evaluated by UTI UTI is requesting your confirmation of the Student Ability to perform the job on site.

Please	mark	either Y	(yes)	or N	(no) fo	or each	person	and	each	task.

FAX: 614-482-8070

OR

MAIL: Utility Technologies International 4700 Homer Ohio Lane

Groveport, OH 43125

Please check SPELLING of names and company names for printing of certificates and cards.

Having knowledge of these person's training, work experience, job performance and the qualification test results shown above, I authorize UTI to issue a qualification certificate for the tasks as indicated. Failure to return this form in a timely manner could result in the certification being placed on hold.

Authorized Signature: \ \Quant \ \Langle \ \Langle \ \Langle \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
Print Name: DARRYL L. KAUGHT
Date: 5/5/16

rpt4Confirmations



OQ TEST SCORE CONFIRMATION LETTER

7001 Center Street Mentor, OH 44060 440-255-5198

Employer Confirmation of Student(s)'s Abilities to do the tasks listed below

		Module	Date	Evaluator	Method	Score	Circle YES If OK to do Task
Lette, Tyler E.	TW88-1B305F-83	CF-6	4/28/2016	Jeff Wolfe	E, 0	Pass	Yes or No
		CL-1a	4/28/2016	Jeff Wolfe	E, O	Pass	Yes or No
McCormick, Jack	D552-2701A2-33	CF-6	4/28/2016	Jeff Wolfe	E, O	Pass	(es) or No
		CL-1a	4/28/2016	Jeff Wolfe	E, O	Pass	or No
McCormick, Ryan	ZG37-23A060-66	CF-6	4/28/2016	Jeff Wolfe	E, O	Pass	(Yes) or No
		CL-1a	4/28/2016	Jeff Wolfe	E, O	Pass	Yes or No
Papp, George M.	7096-08C12F-08	CF-6	4/28/2016	Jeff Wolfe	E, O	Pass	(Yes) or No
		CL-1a	4/28/2016	Jeff Wolfe	E, O	Pass	Yes or No
Sebring, Ed K.	6071-2D31E8-44	CF-6	4/28/2016	Jeff Wolfe	E, O	Pass	(Yes) or No
		CL-1a	4/28/2016	Jeff Wolfe	E, O	Pass	Yes or No
Stanish, David	M257-24726C-18	CF-6	4/28/2016	Jeff Wolfe	E, O	Pass	(Yes) or No
		CL-1a	4/28/2016	Jeff Wolfe	E, O	Pass	Yes or No

Please review and authorize the above test scores for your employee(s) so certificates may be issued. This form indicates that the necessary Knowledge and Skills have been evaluated by UTI UTI is requesting your confirmation of the Student Ability to perform the job on site.

Diagea	mark oither \	((unn) nu h	() f		and each tack
riease	mark enner i	r (Vesior N	(DO) for	'ASCH NAPEON	and each feek

FAX: 614-482-8070

OR

MAIL: Utility Technologies International 4700 Homer Ohlo Lane Groveport, OH 43125

Please check SPELLING of names and company names for printing of certificates and cards.

Having knowledge of these person's training, work experience, job performance and the qualification test results shown above, I authorize UTI to issue a qualification certificate for the tasks as indicated. Failure to return this form in a timely manner could result in the certification being placed on hold.

Authorized Signature: Many L Lough
Print Name: DARRYL L. KNIGHT
Date: 5/5/16

rpt4Confirmations



OQ TEST SCORE CONFIRMATION LETTER

7001 Center Street Mentor, OH 44060 440-255-5198 Employer Confirmation of Student(s)'s Abilities to do the tasks listed below

		Module	Date	Evaluator	Method	Score	Circle YES If OK to do Task
Courtney, Robert A.	GZ21-015294-44	CM-1	6/22/2016	Ted Ressler	E, O	Pass	(Tes) or No
		CM-10	6/22/2016	Ted Ressler	E, O	Pass	(Yes) or No
		CM-12	6/22/2016	Ted Ressier	E, O	Pass	Yes or No
		CM-4	6/22/2016	Ted Ressler	E, O	Pass	(Yes) or No
		CM-5	6/22/2016	Ted Ressier	E, O	Pass	CYSS or No
		CM-5a	6/22/2016	Ted Ressler	E, O	Pass	Yes or No
		CM-5b	6/22/2016	Ted Ressler	E, O	Pass	Yes or No
		CM-8	6/22/2016	Ted Ressler	E, O	Pass	(Yes) or No
ette, Tyler E.	TW88-1B305F-83	CM-1	6/22/2016	Ted Ressier	E, O	Pass	≥7@s or No
		CM-10	6/22/2016	Ted Ressler	E, O	Pass	(Yes or No
		CM-12	6/22/2016	Ted Ressler	E, O	Pass	Yes or No
		CM-4	6/22/2016	Ted Ressler	E, O	Pass	Yes or No
		CM-5	6/22/2016	Ted Ressler	E, O	Pass	Yes or No
		CM-5a	6/22/2016	Ted Ressler	E, O	Pass	Yes or No
		CM-5b	6/22/2016	Ted Ressler	E, O	Pass	res or No
		CM-8	6/22/2016	Ted Ressler	E, O	Pass	es or No
fcCormick, Ryan	ZG37-23A060-66	CM-1	6/22/2016	Ted Ressler	E, O	Pass	Yes or No
		CM-10	6/22/2016	Ted Ressler	E, O	Pass	Yes or No
		CM-12	6/22/2016	Ted Ressler	E, O	Pass	Yes or No
		CM-4	6/22/2016	Ted Ressier	E, O	Pass	Yes or No
		CM-5	6/22/2016	Ted Ressler	E, O	Pass	Yes or No
		CM-5a	6/22/2016	Ted Ressler	E, O	Pass	Yes or No
		CM-5b	6/22/2016	Ted Ressler	E, O	Pass	Yes or No
		CM-8	6/22/2016	Ted Ressler	E, O	Pass	or No
app, George M.	7096-08C12F-08	CM-1	6/22/2016	Ted Ressier	E, O	Pass	Yes or No
		CM-10	6/22/2016	Ted Ressler	E, O	Pass	Yes or No
		CM-12	6/22/2016	Ted Ressler	E, O	Pass	(Yes) or No
		CM-4	6/22/2016	Ted Ressler	E, O	Pass	or No
		CM-5	6/22/2016	Ted Ressler	E, O	Pass	res or No
		CM-5a	6/22/2016	Ted Ressler	E, O	Pass	or No
		CM-5b	6/22/2016	Ted Ressler	E, O	Pass	(as) or No
		CM-8	6/22/2016	Ted Ressler	E, O	Pass	OF No

npt4Confirmations



OQ TEST SCORE CONFIRMATION LETTER

7001 Center Street Mentor, OH 44060 440-255-5198 Employer Confirmation of Student(s)'s Abilities to do the tasks listed below

440-255-	JH 44060 5108						
440-230-	.5 190	Module	Date	Evaluator	Method	Score	Circle YES if OK to do Task
This fo	e review and authorize from indicates that the requesting your cont	e necessary Kr	rowledge ar	d Skills have been	n evaluated l	y UTI	issued.
Please FAX:	mark either Y (yes) 614-482-8070	or N (no) for ea	ch person a	ınd each task.			
MAIL:	Utility Technologies 4700 Homer Ohio L Groveport, OH 4312	ane					
Please	check SPELLING of	names and co	mpany nam	es for printing of (certificates a	nd cards.	
results to retu	g knowledge of these s shown above, I auth im this form in a time rized Signature:	norize UTI to is	sue a qualif	ication certificate	for the tasks	as indicate	
Print N	7	JL L. KA	uc#1		•		
List of Test Me	odules:						
F2 - Mech G1 - Excav H1 - Instal H2 - Instal I-1 - Contr Attacl I-1(1-4)-Monits I-1(5-8)-Monits I-1(a) - Evalue	in and Mechanical Joining anical Joining of Polyethy attion Backfilling II meter regulator sets II service lines colling Corrosion: Installin Anodes, Apply/Repair Corrig Corrosion-Electrical pring Corrosion-Electrical pring Corrosion and Application of Cing Test Stations, Eval.	g Test Leads Ele Coatings Methods g Rectifiers/Bonds corrosion Control	s		c Corrosion,		
I-1(c) - Evalua I-1(d) - Monito L-1/L-1(a) - L-1(b) - Tappir L-1(c) - Tappir L-2/L2(S) - Purg L-2(a) - Purge L-3 - Establ	ation and Application of A oring Corrosion Control Tapping and Bagging Pi ng Pipelines ng Pipeline w. Self Tapping ge Gas Lines /Smatl	bove Ground Cor pelines					

rpt4Confirmations



OQ TEST SCORE CONFIRMATION LETTER

7001 Center Street Mentor, OH 44060 440-255-5198 Employer Confirmation of Student(s)'s Abilities to do the tasks listed below

		Module	Date	Evaluator	Method	Score	OK to de	
Courtney, Robert A.	GZ21-015294-44	CM-14	6/23/2016	Ted Ressier	E, O	Pass	Yes or	No
		CM-16	6/23/2016	Ted Ressler	€, 0	Pass	(Yes or	No
		CM-18	6/23/2016	Ted Ressler	E, O	Pass	Cres or	No
		CM-19	6/23/2016	Ted Ressler	E, O	Pass	Yes or	No
		CM-20	6/23/2016	Ted Ressler	E, O	Pass	Yes or	No
		CO-1	6/23/2016	Ted Ressler	E, O	Pass	Yes or	No
		CO-2	6/23/2016	Ted Ressler	E, O	Pass	Yes or	No
Lette, Tyler E.	TW88-1B305F-83	CM-14	6/23/2016	Ted Ressler	E, O	Pass	Yes or	No
		CM-16	6/23/2016	Ted Ressler	E, O	Pass	Yes or	No
		CM-18	6/23/2016	Ted Ressler	E, O	Pass	Yes or	No
		CM-19	6/23/2016	Ted Ressler	E, O	Pass	Yes or	No
		CM-20	6/23/2016	Ted Ressler	E, O	Pass	Yes or	No
		CO-1	6/23/2016	Ted Ressier	E, O	Pass	Yes or	No
		CO-2	6/23/2016	Ted Ressler	E, O	Pass	Yes or	No
McCormick, Ryan	ZG37-23A060-66	CM-14	6/23/2016	Ted Ressler	E, O	Pass	(Yes) or	No
		CM-16	6/23/2016	Ted Ressler	E, O	Pass	Yes or	No
		CM-18	6/23/2016	Ted Ressler	E, O	Pass	Yes or	No
		CM-19	6/23/2016	Ted Ressler	E, O	Pass	Yes or	No
		CM-20	6/23/2016	Ted Ressler	E, O	Pass	Yes or	No
		CO-1	6/23/2016	Ted Ressler	E, O	Pass	C/89 or	No
		CO-2	6/23/2016	Ted Ressler	E, O	Pass	ces or	No
Papp, George M.	7096-08C12F-08	CM-14	6/23/2016	Ted Ressler	E, O	Pass	Yes or	No
		CM-16	6/23/2016	Ted Ressler	E, O	Pass	Yes or	No
		CM-18	6/23/2016	Ted Ressler	E, O	Pass	Yes or	No
		CM-19	6/23/2016	Ted Ressler	E, O	Pass	Yes or	No
		CM-20	6/23/2016	Ted Ressier	E, O	Pass	Yes or	No
		CO-1	6/23/2016	Ted Ressler	E, O	Pass	Yes or	No
		CO-2	6/23/2016	Ted Ressier	E, O	Pass	Yes or	No

land la loss

W/19/16



OQ TEST SCORE CONFIRMATION LETTER

7001 Center Street Mentor, OH 44060 440-255-5198

Employe	er Co	nfirn	nation	of Stu	ident(s)'s
Abilities	to do	the	tasks	listed	below

Circle YES If Module Date **Evaluator** OK to do Task Please review and authorize the above test scores for your employee(s) so certificates may be issued. This form indicates that the necessary Knowledge and Skills have been evaluated by UTI

Please mark either Y (yes) or N (no) for each person and each task.

FAX: 614-482-8070

MAIL: Utility Technologies International

4700 Homer Ohio Lane Groveport, OH 43125

Please check SPELLING of names and company names for printing of certificates and cards.

UTI is requesting your confirmation of the Student Ability to perform the job on site.

Having knowledge of these person's training, work experience, job performance and the qualification test results shown above, I authorize UTI to issue a qualification certificate for the tasks as indicated. Failure to return this form in a timely manner could result in the certification being placed on hold.

Authorized Signature:	Warry L-Knight
	IL L. KNIGHT
Date: 7/2/16	

List of Test Modules:

F1F2 - Fusion and Mechanical Joining

F2 - Mechanical Joining of Polyethylene Pipe

G1 - Excavation Backfilling

H1 - Install meter regulator sets

H2 - Install service lines

I-1 - Controlling Corrosion: Installing Test Leads Elec. Isolation, Monitoring Atmospheric Corrosion,

Attach Anodes, Apply/Repair Coatings I-1(1-4)-Monitoring Corrosion-Electrical Methods

I-1(5-8)-Monitoring Corrosion-Inspecting Rectifiers/Bonds

I-1(a) - Evaluation and Application of Corrosion Control

I-1(b) - Reading Test Stations, Eval. App. of Above Ground Corrosion Control

I-1(c) - Evaluation and Application of Above Ground Corrosion Control

I-1(d) - Monitoring Corrosion Control

L-1/L-1(a) - Tapping and Bagging Pipelines L-1(b) - Tapping Pipelines L-1(c) - Tapping Pipeline w. Self Tapping Tees L2/L2(S) - Purge Gas Lines /Small

L-2(a) - Purge Service Lines L-3 - Establish/ Maintain Odorant

L-3(s)- Monitor Odorant Levels

rpt4Confirmations

D.O.T. FUSION / MECHANICAL QUALIFICATION

N314-0B7373-93

Unique ID Number

Thomas J. Rowland

Name

Big Oats (Great Plains)

Company Name






API 1104 WELDER QUALIFICATION

Welder ID: 6000000

Name: Thomas Rowland Company: Big Oats Oil Field Supply
Issue Date: 5-16-06 Issued By: Steve Cremean This card certifies that the above weder has been tested and qualified according to the requirements of DOT 49 CFR Part 192.22? and Part 192.229 and adapticable UTI wedding procedures. In addition, the wedder has reviewed aknormal operating conditions and how to properly react.

To maintain qualification, welder is required to perform welds, for each process qualified, that are tested and found acceptable under sections 6 or 9 of API 1104 at least twice each calendar year, not to exceed 7½ months.



To maintain qualification, weder is required to perform welds, for each process qualified, that are tested and found acceptable under sections 6 or 9 of API 1104 at least white each colendar space, not to exceed 7 a months



Utility Technologies International Corp. 4700 Homer Ohio Lane Groveport, OH 43125 (614) 482-8080

Name: Thomas J. Rowland
Fusion / Mechanical Qualification Date:

St. Manual Burt Fusion
M Mechanical - Bolted Compression
 Mechanical - Boltess Compression
 Mechanical - Stab X Self Taping Tee.

Other: Saddle 5/11/15

Dates above expire one year from the qualification date. The person listed above has been successfully tested and evaluated on knowledge, skills and ability

Position: All Position Diameter Range: All Diameters					
Wall Thickness Range.	All Wall Thickness				
Maximum Grade:	X60				
Further Qualification:					
	VELDER REQUALIFICATION	RECORD			
Welding Inspector	Date	Type of Tess			
John Lucas	8-18-15	Br-Annual Requalification			

Process.	S QUALIFIED TO WELD ST	CEL FIFE AS FOLLOWS:
Position.	All Positions	
Diameter Range:	All Diameters	
Wall Thickness Range	All Wall Thicknesses	
Maximum Grade:	X60	
Further Qualification	1100	
W	ELDER REQUALIFICATION	
Welding Inspector		RECORD
John Lucas	Date	Type of Test
JOHN LUCAS	2-23-16	6mm Requalification

Name/UID: Thomas J. Rowland / N314-087373-93
NISource Specific Martilles / Nat Co. 70

	NISource St	secific Madul	es / Date Qua	March.		
	Ni E-1(a):	N/A				
	Ni F-1(a):		Ni I-1(d)	N/A	Ni M-3:	
	Ni F-2:		Ní L-1(a):	N/A	Ni M-7:	N/A
	Ni H-1:	-	Ni L-1(b):	N/A	N/ M-8	N/A
		2.25.1.5	Ni L-1(c):	05/17/11	Ni M-9:	
	Ni H-2:		Ni L-2NoR:	04/14/15	Ni M-10:	N/A
	Ni H-2(a):	N/A	Ni L-2(a):	N/A	Ni M-10(a):	N/A
	Ni I-1(a):	N/A	NI L-3(a):	N/A	Ni G-1:	
	Mi 1-1(b):	N/A	Ni M-1(a):	N/A	Ní G-2:	N/A
	Ni l-1(c):	N/A	NI M-2:	N/A	Ni G-3:	N/A
Task / Date Qualified:					ine Installer:	N/A
	CF-1:	N/A	CI-5:	N/A		N/A
	CF-2:	N/A	CI-6:	N/A	COM 1.3:	
	F-1a;	02/02/11	CI-7:		M-1:	N/A
	F-2:	N/A	CI-8:	N/A	M-2:	N/A
	G-1:	04/14/15		N/A	M-3:	04/14/15
	H-1:		CI-9:	N/A	M-4:	N/A
		N/A	CI-10:	N/A	M-5:	N/A
	H-2:	04/14/15	CI-11:	N/A	M-5.1:	N/A
	i-1c:	05/16/11	CI-12:	N/A	M-5:	N/A
	CI-1:	04/16/15	CI-13:	N/A	M-7FR:	04/15/15
	CI-2:	N/A	L-1:	N/A	M-8:	05/23/11
	C1-3:	N/A	L-3:	N/A	M-9:	
	Cl-4:	N/A	L-3(a):	N/A	M-10:	N/A
						N/A

Utility Technologies International Corp. 4700 Homer Ohlo Lane Groveport, OH 43125 (614) 482-8080

N314-0B7373-93 Unique ID Number

Thomas J. Rowland

Big Oats (Great Plains)
Company Name

Company Name
This card certifies that this Individual has been tested and qualified according to the requirements of D.O.T. 49CFR Part 192 and the applicable tasks identified on the back of the card.

To confirm this individual's qualification please call 614-482-8080

Appendix D. Qualification Status Update Record - Compliance Series THOMAS ROWLAND **Employee Name:** Employee ID Number: UTI · VERIFORCE Employee Job Title or Description: WELDER Employee's Supervisor: JOHN CESSNA Employee's Reporting DARRYL L. KNIGHT Location: ☑ Contractor Employee BIG DATS OILFIELD SUPPLY Contractor Name Date of This Qualification Status Report Status Report Status Report Status Report

The employee identified above is currently qualified to perform the following identified covered tasks checked below:

✓ (check all covered tasks for which the employee is qualified)

	1	
/	CE-1	Weld on Steel Pipelines, 49 CFR 192.225, 192.231, 192.235, 192.245
	CE-2	Visually Inspect Pipe Welds, 49 CFR 192.241, 192.243
1	CE-3	Perform Non-Destructive Tests on Steel Welds, 49 CFR 192.241, 192.243
1	CF-1	Join Plastic Pipe with Heat Fusion VF - # 2110P
J	CF-1.1	Join Plastic Pipe with Butt Fusion, 49 CFR 192.123, 192.273, 192.281, 192.285, 192.287 ✓ F • # 2080 P
-	CF-1.2	Join Plastic Pipe with Socket Fusion, 49 CFR 192.123, 192.273, 192.281, 192.285, 192.287
-	CF-1.3	Join Plastic Pipe with Saddle Fusion, 49 CFR 192.123, 192.273, 192.281, 192.285, 192.287
1	CF-1.4	Join Plastic Pipe with Electrofusion, 49 CFR 192.123, 192.273, 192.281, 192.285, 192.287 VF- * 2100 P
J	CF-2	Join Plastic Pipe with Mechanical Fittings VF-# 2090 P
	CF-2.1	Join Plastic Pipe with Threaded Nut Compression End Fittings, 49 CFR 192.123, 192.273, 192.281, 192.285, 192.287
J	CF-2.2	Join Plastic Pipe with Stab-Type Mechanical Fittings, 49 CFR 192.123, 192.273, 192.281, 192.285, 192.287 VF-# 2,1907
1	CF-2.3	Join Plastic Pipe with Mechanical Compression Fittings, 49 CFR 192.123, 192.273, 192.281, 192.285, 192.287
	CF-3	Join Copper Pipe for Gas Distribution, 49 CFR 192.279
1	CF-4	Join Plastic Pipe with Solvent Cement, 49 CFR 192.273, 192.281, 192.283, 192.285, 192.287, 192.311 VF - #2 50 P

V 12 Appendix D

	CI-10	Inspect and Monitor Exposed Piping for Evidence of Atmospheric	7
1		Corrosion, 49 CFR 192.479, 192.481 VF-#4170 P	
J	CI-11	Install Sacrificial Anodes and Test Stations, 49 CFR 192.465, 192.469	WF-
1	Cl-12	Measure the Extent of Corrosion on Pipeline Facilities, 49 CFR 192.459, 192.475, 192.477, 192.481 ∨ F- # 1186 P	
1	CI-13	Identify Procedures Basic to Inspecting, Applying, and Repairing Pipeline Coatings, 49 CFR 192.459, 192.461 V F- ポリコの P	
_	CI-14	Obtain and Shipping Gas Samples, 49 CFR 192.475, 192.477	
	CI-15	Troubleshoot In-Service Cathodic Protection Systems, 49 CFR 192.463	
_	CK-1	Uprate a Pipeline, 49 CFR 192.105, 192.121, 192.553, 192.555, 192.557, 192.619, 192.621, 192.623	
1	CL-1	Tap Pipelines Under Pressure, 49 CFR 192.151, 192.627 VF-# 6110 P]
	CL-1a	Hot Tapping Pipelines Using Self-Tapping Tees, 49 CFR 192.627	
-	CL-1b	Bagging and Stopping Low Pressure Pipe with Bag, Stopper, or Stopple, 49 CFR 192.151, 192.627	
1	CL-2	Purge Pipelines (Small and Large Diameter), 49 CFR 192.629 VF-4 6136P	
_	CL-3	Odorizer Inspection, Testing, and Preventive/Corrective Maintenance, 49 CFR 192.625	
_	CL-3a	Monitor Odorant Levels, 49 CFR 192.625	
-	CL-4	Monitor and Regulate the Flow and Pressure of Gas from Remote Locations, 49 CFR 192.201, 192.619, 192.621, 192.623, 192.631, 192.741	
J	CL-5	Perform Hot Tapping Operations on Plastic Pipe, 49 CFR 192.151(a), 192.627 VF- # 6 20 P	
-	CL-6	Inspect , Test, and Maintain Actuators, 49 CFR 192.179, 192.181, 192.745, 192.747	1
_	CL-7	Inspect, Test, and Maintain Programmable Logic Controllers, 49 CFR 192.605B, 10(iii), 192.739	
J	CM-1	Perform Patrol and Leakage Surveys on Gas Pipeline Facilities, 49 CFR 192.5, 192.613, 192.705, 192.706, 192.721, 192.723 VF-* 4360 P	
J	CM-2	Locate and Mark Underground Facilities, 49 CFR 192.614, 192.707 VF-	#6060P
4	CM-3	Pressure Testing Gas Pipelines, 49 CFR 192.503, 192.505, 192.507, 192.509, 192.511, 192.513, 192.725 VF-4 6020 P	
-	CM-4	Inspect and Test Pressure Limiting Stations, Relief Devices, and Pressure Regulating Devices, 49 CFR 192.201, 192.731, 192.739, 192.743, 192.749, 192.751	
1	CM-5	Inspect, Service, and Operate Line Valves, 49 CFR 192.179, 192.181, 192.745, 192.747	
-	CM-5a	Inspect Emergency Valves, 49 CFR 192.745, 192.747, 192.803	
_	CM-5b	Valve Corrective Maintenance, 49 CFR 192.747	
-	CM-6	Monitor Compressor Station Gas Leak Detection Equipment, 49 CFR 192.735, 192.736	
J	CM-7	Prevent Accidental Ignition, 49 CFR 192.751 VF. SAFETY CULTURE."	
J	CM-8	Make Field Repairs on Gas Pipelines, 49 CFR 192.245, 192.307, 192.309, 192.311, 192.703, 192.711, 192.713, 192.715, 192.717	
115.4	TALAD	7224P V 12 Appendix D	

VF 4 7060P 7220P 7050P 7190P V 12 Appendix D

	T	
	CF-5	Visually Inspect Polyethylene Pipe Joints for Indicators of Proper
-		Construction/Assembly, 49 CFR 192.123, 192.273, 192.281, 192.283, 192.285, 192.287
1	CF-6	Install Tubing and Fittings for Instrumentation, Control, and Sampling, 49 CFR 192.203, 192.279 VF-# 2170P
J	CF-7	Join Pipe with Flange Assembly, 49 CFR 192.147 VF. # 2150 P
	CG-1	Verify Excavating and Backfilling Operations that Minimize Excavation
1		Damage to Pipeline Facilities, 49 CFR 192.307, 192.317, 192.319,
1		192.321, 192.325, 192.327, 192.361, 192.461, 192.614 VF.# 6070P
-	CG-2	Identify Basic Installation Methods for Mains and Transmission Pipelines, 49 CFR 192.307, 192.313, 192.315, 192.317, 192.319, 192.321, 192.323, 192.325, 192.327, 192.707
_	CG-3	Install Aboveground Pipelines, 49 CFR 192.161, 192.307, 192.317, 192.479, 192.481, 192.707
,	CG-4	Install Mains and Transmission Pipelines Using Trenchless Methods, 49
J		CFR 192.307, 192.321, 192.325, 192.327 VF-# 3310P, 3320P
_	CG-5	Moving In-Service Pipelines, 49 CFR 192.319, 192.321, 192.323, 192.325,
		192.327192.459, 192.605, 192.614, 192.615, 192.707
,	CH-1	Install Customer Gas Meter and Regulator Sets, 49 CFR 192.353, 192.355,
1		192.357, 192.359 VF- #3020P
	CH-2	Install Customer Gas Service Lines, 49 CFR 192.151, 192.361, 192.363,
-		192.365, 192.367, 192.369, 192.373, 192.375, 192.377, 192.379, 192.381
_	CH-3	Deactivate Gas Metering Services, 49 CFR 192.727
	CH-4	Install Residential Customer Service Line Valves, 49 CFR 192.363,
-		192.365, 192.381, 192.383
_	CH-5	Maintenance of Service Valves Upstream of Customer Meter (in development), 49 CFR 192.363, 192.365
1	CI-1	Perform Pipe-to-Soil Potential Surveys on Effectively Coated Buried or
V		Submerged Pipelines, 49 CFR 192.463
1	CI-2	Determine Areas of Active Corrosion Using Close Interval Survey
J		Methods, 49 CFR 192.453, 192.465 VF-# 4170P
_	CI-3	Measure Soil Resistivity, 49 CFR 192.453, 192.465
1	CI-4	Inspect the External Condition of Exposed Buried Metal Piping to
4		Determine if Repair or Replacement is Necessary, 49 CFR 192.459,
	CLE	192.461(a), 192.483, 192.485, 192.487, 192.489 VF-#40WP
	CI-5	Inspect and Maintain Rectifiers, 49 CFR 192.465 VF 440807
	CI-6	Inspect for the Effects of Interference Current, 49 CFR 192.465, 192.473
J	CI-7	Install Test Leads to Monitor and Control External Corrosion, 49 CFR 192.465, 192.469, 192.471 V 두 - # 년[20 후
,	CI-8	Install and Test Insulation to Control External Corrosion by Electrical
√		Isolation, 49 CFR 192.467 VF. # 4110P
1	CI-9	Inspect for Evidence of Internal Corrosion, 49 CFR 192.475, 192.477

VF-#4140P

_	CM-9	Repair and Protect Cast Iron Pipe, 49 CFR 192.275, 192.489, 192.753, 192.755
	CM-10	Abandon or Deactivate Gas Pipeline Facilities, 49 CFR 192.727
J	CM-11	Recognize and React to Generic Abnormal Operating Conditions, 49 CFR 192.751 VF ≠ 2010 P
-	CM-12	Launch and Receive Pipeline Pigs, 49 CFR 192.150
1	CM-13	Investigate Reported Gas Leaks and Odors in Buildings VF.* (0500 P
-	CM-14	Inspect Vault Conditions, 49 cFR 192.749, 192.751
_	CM-15	Operate and Maintain Compressor Station Components, 49 CFR 192.167, 192.169, 192.171, 192.173, 192.199, 192.201, 192.605(a)(b)(6)(7), 192.731, 192.743
_	CM-16	Inspect, Test, and Maintain Sensing Devices, 49 CFR 192.739, 192.741, 192.743
1	CM-17	Squeeze-Off Steel Pipe, 49 CFR 192.615 VF . # 7640 P
-	CM-18	Station Emergency Shut Down System: Inspection, Testing, and Corrective Maintenance, 49 CFR 192.167, 192.171, 192.731, 192.736
J	CM-19	Installing and Maintaining Customer Pressure Regulating, Pressure Limiting, and Pressure Relief Devices: Large Commercial and Industrial, 49 CFR 192.199, 192.743 VF- *3040 P
_	CM-20	Reciprocating Compressor Inspection, Testing, and Corrective Maintenance, 49 CFR 192.731
1	CM-23	Measure and Characterize Mechanical Damage on Installed Pipe and Components, 49 CFR 192.307, 192.309 ソド・ギー含の子
_	CO-1	Conduct Indirect Pipe Inspections, 49 CFR 192.925, 192.947
_	CO-2	Conduct Direct Pipe Examinations, 49 CFR 192.927, 192.947

Approved by:

Signature Signature L. Knuglif	Title EXECUTIVE DIRECTUR	Date 5/18/16
Daniel to Lought	W B	6/17/16
Route Copies to: Name	Title	Location

Dana Rymarczyk

From:

Andrea Magana <andrea.magana@veriforce.com>

Sent: To: Friday, June 17, 2016 10:04 AM pia1@big-oats.com

Subject:

Records for Thomas Rowland

Hi Dana,

Please see the current CCTs for Thomas:

QUITMINATED E		Carringett Mans	SEATON
5/25/2016	401	Thomas Rowland	Pass
5/25/2016	502	Thomas Rowland	Pass
5/25/2016	607	Thomas Rowland	Pass
5/25/2016	619	Thomas Rowland	Pass

Thanks!

Andrea Magana Operator Liaison

Veriforce, LLC

19221 I-45 South, Suite 200 | Shenandoah, TX 77385 Phone: 281.916.1618 | Toll Free: 800.426.1604 andrea.magana@veriforce.com www.veriforce.com





Completed	Veriforce - CCT 402 Apply Approved Coating to Above Ground Piping w/Exam Veriforce LLC	n Veriforce LLC	4020P	3/28/2016	3/28/2019
Completed	Veriforce - CCT 202 Monitoring of Welding Process w/Exam	Veriforce LLC	2020P	3/28/2016	3/28/2019
Completed	Veriforce - CCT 304 Installing Customer Pressure Regulating, Limiting, and Relief Device - Large Commercial & Industrial w/Exam	Veriforce LLC	3040P	3/28/2016	3/28/2019
Completed	Veriforce - CCT 421 Measurement of Depth of Pitting with Pit Gage w/Exam	Veriforce LLC	4210P	3/28/2016	3/28/2019
Completed	Veriforce - CCT 408 inspect Cathodic Protection Rectifier w/Exam	Veriforce LLC	4080P	3/28/2016	3/28/2019
Completed	Veriforce - CCT 331 Installation of Plastic Pipe in a Bore w/ Exam Vaniforce - CCT 323 Installation of Blackin Biocket Black of Blacking (Amil Installation	Veriforce LLC	3310P	3/25/2016	3/25/2021
Completed	VENIONCE - CCI 352 Installation of Flastic ripe by Flowing (Full-lift Flanting) W/Exam	Veriforce LLC	3320P	3/25/2016	3/25/2019
Completed	Veriforce - CCT 211 Perform Plastic Fusion Inspection W/Exam Variforce - CTT 405 Protection of Castings From Abous Ground Securities	Veriforce LLC	2110P	3/25/2016	3/25/2019
Completed	W/Exam	Veriforce LLC	4050P	3/25/2016	3/25/2019
Completed	Veriforce - CCT 001 Provide Security for Pipeline Facilities w/Exam Veriforce - CCT 404 Pertention of Costone Error Ba-Hilling and Foun Baham	Veriforce LLC	0010P	3/25/2016	3/25/2019
Completed	Ground Support W/Exam	Veriforce LLC	4040P	3/25/2016	3/25/2019
Completed	Veriforce - CCT 006 Inspection of Breakout Tanks w/ Exam Veriforce - CCT 303 Installing Creticings Maskers I amp Commonical and	Veriforce LLC	40900	3/24/2016	3/24/2019
Completed	Industrial W. Examines to Industrial W. Examines for Internal Correction Without Displays to Demonstrated W.	Veriforce LLC	3030P	3/24/2016	3/24/2019
Completed	W/Exam	Veriforce LLC	4140P	3/24/2016	3/24/2019
Completed	Veriforce - CCT 435 Messure and Identify Mechanical Damage on Installed Pipe and Components w/Exam	Veriforce LLC	435OP	3/24/2016	3/24/2019
Completed	Veriforce - CCT 401 Examination of Buried Pipe When Exposed w/Exam	Veriforce LLC	4010P	3/24/2016	3/24/2019
Completed	Veriforce - CCT 427 Inspection of Above or Below Ground Coatings w/Exam	Veriforce LLC	4270P	3/24/2016	3/24/2019
Completed	Veriforce - CCT 214 Joining of Metal Pipe - Threaded Connections w/Exam Veriforce - CCT 213 Ioining of Metal Pine - Threaded and Elanged	Veriforce LLC	2140P	3/24/2016	3/24/2019
Completed	Connections W/Exam	Veriforce LLC	2130P	3/24/2016	3/24/2019
Completed	Veriforce - CCT 209 Plastic Pipe Joining: Mechanical Joining w/Exam	Veriforce LLC	2090P	3/23/2016	3/23/2017
Completed	Veriforce - CCT 330 Installation of Plastic Pipe in a DRch w/ Exam	Veriforce LLC	3300P	3/23/2016	3/23/2019

4/8/2019	4/8/2019	4/7/2019	4/7/2019	4/7/2019	4/7/2019	4/7/2019	4/7/2019	4/7/2019	4/7/2019	4/7/2019	4/7/2019	4/7/2019	477/2019	4/5/2019	4/5/2019	4/5/2019	4/5/2019	3/31/2019	3/31/2019	3/31/2019	3/30/2019
4/8/2016	4/8/2016	4/7/2016	4/7/2016	4/7/2016	4/7/2016	4/7/2016	4/7/2016	4/7/2016	4/7/2016	4/7/2016	4/7/2016	4/7/2016	4/7/2016	4/5/2016	4/5/2016	4/5/2016	4/5/2016	3/31/2016	3/31/2016	3/31/2016	3/30/2016
4840P	2010P	4260P	2040P	2040P	9000e	2050P	2050P	2060P	2060P	2070P	2070P	4070P	4110P	4100P	4060P	4150P	4120P	7010P	7030P	2030P	4170P
Veriforce LLC	Veriforce LLC	Veriforce LLC	Veriforce LLC	Veriforce LLC	Veriforce LLC	Veriforce LLC	Veriforce LLC	Veriforce LLC	Veriforce LLC	Veriforce LLC	Veriforce LLC	Veriforce LLC	Veriforce LLC	Veriforce LLC	Veriforce LLC	Veriforce LLC	Veriforce LLC	Veriforce LLC	Veriforce LLC	Veriforce LLC	Veriforce LLC
Veriforce - CCT 484 Apply Approved Coatings by Wrap Application w/ Exam Veriforce - CCT 201 Abnormal Operating Conditions Related to Welding an	Pipelines w/ Exam	Veriforce - CCT 426 Inspect Pipe Coating with Holiday Detector w/Exam Veriforce - CCT 204 Non-Destructhe Testing (Dve Penetrant)	w/Acknowledgement Veriforce - CCT 204 Non-Destructive Testing (Jove Penetrant)	w/Acknowledgement Veriforce - CCT 900 Rights-Of-Way (ROW) Observante II-hantifutus Econium	Facilities) w/Exam Veriforce - CCT 205 Non-Destructive Testing (Mae Particle)	w/Acknowledgement Veriforce - CCT 205 Non-Destructive Texting (Nag Particle)	w/Acknowledgement Veriforce - CCT 205 Non-Destructive Testing (Ultrasonic)	w/Acknowledgement Veriforce - CCT 206 Non-Destructive Testing (Ultrasonic)	w/acknowledgement	Veriforce - CCT 207 Non-Destructive Testing (X-Ray) w/Acknowledgement	Veriforce - CCT 207 Non-Destructive Testing (X-Ray) w/Acknowledgement	Veriforce - CCT 407 Perform Cathodic Protection Survey w/Exam Veriforce - CCT 411 Inspect/Test to Assure Electrical Isolation is Adequate	w/Exam	Veriforce - CCT 410 Clear Shorted Casing w/ Exam Veriforce - CCT 406 Conduct Test to Determine Cathodic Protection Current	Requirements w/Exam Veriforce - CCT 415 Monitoring for Internal Corrosion with Probes and	Coupons w/Exam Veriforce - CCT 412 Install CP Leads on Ploeline Using Exothermic Weld	W/Exam Verifities - CCT 201 Datevilling Disaling and Lockeds Consequent	Instrument w/Exam	Veriforce - CCT 703 Placing/Maintaining Line Markers w/Exam Veriforce - CCT 203 Visual Inspection of Weiris not Non-Dastronthiais Tasted	w/Exam	Veriforce – CCT 417 Atmospheric Corrosion Monitoring w/Exam
Completed	Completed	Completed	Completed	Completed	Completed	Completed	Completed	Completed	Completed	Completed	Completed	Completed	Completed	Completed	Completed	Completed	Completed	Completed	Completed	Completed	Completed

	****	Rov	RowlandThomas CBP		
Completion Status 11tie	litie	Company	2	Date Expiration	ion
Completed	Veriforce - CCT 436 Perform Close interval Survey w/ Exam	Veriforce LLC	4360P	4/27/2016	4/27/2019
Completed	Veriforce - CCT 040 Isolation of Pipe with Mud Plug w/ Exam	Verlforce LLC	0400P	4/27/2016	4/27/2019
Completed	Veriforce - CCT 650 inside Gas Leak investigation w/ Exam	Veriforce LLC	6500P	4/26/2016	4/26/2019
Completed	Verfforce - CCT 434 Visual inspection of installed Pipe and Components for Mechanical Damage w/ Exam	Veriforce LLC	4340p	4/12/2016	4/12/2019
Completed	Veriforce - CCT 608 Damage Prevention for Blasting Near a Pipeline w/Exam	Verlforce LLC	9080P	4/11/2016	4/11/2019
Completed	Veriforce - CCT 428 Pin Brazing to Install CP Leads on Pipeline w/Exam	Veriforce LLC	4280P	4/11/2016	4/11/2019
Completed	Veriforce - CCT 606 Locate and Mark Submerged Pipelines w/ Exam Veriforce - CCT 606 I prate I had het all Tammonan Mayulose de Busine de Busines	Veriforce LLC	6060P	4/11/2016	4/11/2019
Completed	W/Exam Veriforce - CCT 416 Monitoring for Internal Portroising with Gas Camulas/	Veriforce LLC	6050P	4/11/2016	4/11/2019
Completed	Exam	Veriforce LLC	4160P	4/11/2016	4/11/2019
Completed	Veriforce - CCT 706 Permanent Field Repair Using Composite Materials (Armor Plate) W/Acknowledgement	Veriforce LLC	7060P	4/8/2016	4/8/2019
Completed	Veriforce - CCT 706 Permanent Field Repair Using Composite Materials (Armor Plate) w/Acknowledgement	Veriforce LLC	7060P	4/8/2016	4/8/2019
Completed	Veriforce - CCT 705 Permanent Field Repair Using Composite Materials (Clockspring) w/Acknowledgement	Veriforce LLC	7050P	4/8/2016	4/8/2017
Completed	Veriforce - CCT 705 Permanent Field Repair Using Composite Materials (Clockspring) w/Acknowledgement	Veriforce LLC	7050P	4/8/2016	4/8/2017
Completed	Veriforce - CCT 722 Permanent Field Repair Using Composite Materials (Aqua Wrap) w/Acknowledgement	Veriforce LLC	7220P	4/8/2016	4/8/2019
Completed	Veriforce - CCT 719 Permanent Field Repair Using Composite Materials (Wrapmaster) w/Acknowledgement Veriforce - CCT 014 Maintain/Prove Flow Meters for rPM Hazardous Limid	Veriforce LLC	7190P	4/8/2016	4/8/2017
Completed	Leak Detection Veriforce - CCT 418 General and Localized Correction Massuromost	Veriforce LLC	0140P	4/8/2016	4/8/2019
Completed (Veriforce LLC	4180P	4/8/2016	4/8/2019

Completed	Veriforce - CCT 480 Apply Approved Coating by Hand Application w/ Exam	Veriforce LLC	4800P	3/23/2016	3/23/2019
Completed	Veriforce - CCT 614 Purge Pipeline Facilities With Air or Inert Gas w/Exam	Veriforce LLC	6140P	3/23/2016	3/23/2019
Completed	Veriforce - CCT 208 Plastic Pipe Joining: Butt Fusion w/ Exam	Veriforce LLC	2080P	3/23/2016	3/23/2017
Completed	Veriforce - CCT 210 Plastic Pipe Joining: Electrofusion Joining w/Exam	Veriforce LLC	2100P	3/23/2016	3/23/2017
Completed	Veriforca - CCT 302 Installation of Customer Meters and Svc Regulators (Residential and Small Comm) w/ Exam	Veriforce LLC	3020P	3/23/2016	3/23/2019
Completed	Veriforce - CCT 215 Joining of Metal Pipe - Flanged Connections w/Exam	Veriforce LLC	2150P	3/23/2016	3/23/2019
Completed	Veriforce - CCT 301 Install Tracer (electrically conductive) Wire w/Exam	Veriforoe LLC	3010P	3/23/2016	3/23/2019
Completed	Veriforce - CCT 016 Purging - Hazardous Liquids w/ Exam	Veriforce LLC	0160P	3/22/2016	3/22/2019
Campleted	Veriforce - CCT 218 Plastic Pipe Joining: Solvent Cement w/ Exam	Veriforce LLC	2180P	3/22/2016	3/22/2017
Completed	Veriforce - CCT 906 Rights-Of-Way Clean-Up w/Exam	Veriforce LLC	9060P	3/22/2016	3/22/2019
Campleted	Veriforce - CCT 902 Field Bending of Pipe w/Exam Veriforce - CCT 607 Damage Prevention: Observation of Excavating and	Veriforce LLC	9020P	3/22/2016	3/22/2019
Completed	Backfilling w/Exam Veriforce - CCT 103 Nondestructive Testing {Other Than Testing of Welds}	Veriforce LLC	6070P	3/21/2016	3/21/2019
Completed	Mag Particle w/Exam	Veriforce LLC	103OP	3/21/2016	3/21/2019
Completed	Veriforce - CCT 482 Apply Approved Coatings by Mechanical Spray and Hand Application Methods w/ Exam	Veriforce LLC	4820P	3/21/2016	0100/10/6
Cremoloton	Veriforce - CCT 413 Anode Installation on Submerged Pipeline or Facilities w/			0,44,4010	6102/12/6
Completed	Exam Veriforce - CCT 217 Small Diameter Metal Tubing and Fitting Installation	Veriforce LLC	4130P	3/21/2016	3/21/2019
Completed	w/Exam	Veriforce LLC	2170P	3/21/2016	3/21/2019
Completed	Veriforce - CCT 2.16 Joining of Metal Pipe - Compression Couplings w/ Exam	Veriforce LLC	2160P	3/18/2016	3/18/2019
Completed	Veriforce - CCT 409 inspect Interference Bonds w/Exam	Veriforce LLC	4090P	3/18/2016	3/18/2019
Completed	Veriforce - CCT 602 Monitoring Pipeline Pressure w/Exam	Veriforce LLC	6020P	3/17/2016	3/17/2019
Completed Completed	Verforce - CCT 613 Purge Pipeline Facilities With Gas w/Exam Verforce - CCT 612 Hot Tap (Plastic Pipe) w/Exam	Veriforce LLC Veriforce LLC	6130P 6120P	3/11/2016 3/11/2016	3/11/2019 3/11/2019

3/10/2019	3/10/2019 3/10/2019	3/10/2019	3/10/2019		3/9/2017 3/9/2019 3/9/2019	
3/10/2016	3/10/2016 3/10/2016	3/10/2016	3/10/2016	3/10/2016	3/9/2016 3/9/2016 3/9/2016 3/9/2016	3/9/2016
1040P	0210P 0070P	0120P	4030P	SafetyCulture	2190P 7640P 6110P	
Veriforce LLC	Veriforce LLC	Veriforce LLC	m Veriforce LLC Veriforce LLC	Veriforce LLC	Veriforce LLC Veriforce LLC Veriforce LLC	Veriforce LLC
Veriforce - CCT 104 Nondestructive Testing (Other than Testing of Welds) - Oye Penetrant Inspection (DPI) w/ Exam Veriforce - CCT 02.1 Startup/Shutdown of Liquid Pipeline to Assure Operation	within MOP w/ Exam Veriforce - CCT 007 Operate Valves w/Exam Veriforce - CCT 012 Inspect, Test and Maintain Liquid Leak Defection Flow	Computers	Veriforce - CCT 403 Apply Approved Coating to Below Ground Piping w/Exam Veriforce LLC VeriSource Drug and Alcohol Help Video	INGAA - A Culture of Safety	Veriforce - CCT 219 Plastic Pipe Joining: Stab Fittings w/Exam Veriforce - CCT 764 Squeeze Off Steel Pipe w/ Exam Veriforce - CCT 611 Hot Tap - Steel Pipe w/ Exam Reasonable Suspicion Testing for Drugs (60 minutes)	Reasonable Suspicion Testing for Alcohol (60 minutes)
Completed	Completed	Completed	Completed	Completed	Completed Completed Completed	Completed

JANX

P.O. Box 190 Parma, MI 49269-0190 (517) 531-8210 Fax (517) 531-3911

OPERATOR QUALIFICATION & EMPLOYEE CERTIFICATION

Employee: Timothy Coss Emp ID: 02857 Method: RT Level: II JANX Task No: CT02 Certification Date: 4/10/15 Restrictions: none This certification expires in 3 years Vision Acuity: Pass **Latest Eye Examination Date:** 4/7/16 Natural: X Corrected: Eye Examination Expires: 4/7/17 Color Contrast: Pass Shades of Gray: Pass

This individual is a participant in a DOT approved Drug and Alcohol Misuse Program.

Education Record:

Grade School: X High School: X Vocational: College: Other:

Experience Record:

Company	Level	Months
Prime NDT	I	>9
Prime NDT	n	>36

Training Record:

Course	By	Hours
RT Level I	IUOE Local 112	40
RT Level II	TUOE Local 112	40

Examination Scores: General / Basic Specific Practical / Method Average **Method Tests:** 100% 95% 90% 95% **AOC Test: Pass** HAZMAT Training - 49 CFR 172 Subpart H Tested: 4/10/15

The information provided in this certification record is in accordance with the latest edition of: The American Society for Nondestructive Testing's Recommended Practice SNT-TC-1A, 49 CFR Part 192, Subpart N, and 49 CFR Part 195, Subpart G.

All information provided is true and correct to the best of this company's knowledge. Copies of tests and testing procedures and requirements are on file at JANX.


I can't Williams This certification was administered by: Daniel Williams, ASNT NDT Level III No. 56554

FORM# A001-0509

JANX VISION EXAMINATION PER JAEGER 1 OR EQUIVALENT

Near Vision Acuity: This test shall show that the employee has near distance acuity in at least one eye so that the employee is capable of reading a minimum of Jaeger Number 1 or equivalent size and type letter at a distance of not less than 12 inches on a standard Jaeger test chart or, that the employee has the ability to perceive an Ortho-Rater minimum of 8 or similar test pattern.

perceive an Ortho-Rater m	inimum of 8 or	similar test pati	em.		
Employee Name:	in Co	220			
Test Method Administered		D			
Times N	lew Roman 4.5 Equivalent Ortho-Rater	(list) ()			_
Results:	Acceptable Unacceptable	×	Natural Corrected		
Color Contrast Differential differentiate colors that ar of 8 pseudoisochromatic pl	e used in the pa	rticular method	s of nondestructiv	the ability to disti ve testing. Accept	nguish and able results are 8
Employee has the ability to	distinguish and	i differentiate c	olors:	Yes	No □
Shades of Gray Contrast D and differentiate shades of results are a minimum of 2 equivalent.	gray that are u	sed in the partic	ular methods of i	nondestructive tes	iting. Acceptable
Employee has the ability to	distinguish and	differentiate si	nades of gray:	Yes	No □
Limitations / Comments:					
Declaration: The vision exa given above are true and co	minations have	been administe of my knowle	red to this emplo dge.	yee on this date a	nd the results as
Signature of Examiner:	Ohio	Mane	2	Heter 4	-7-16
Title of Examiner:		0		Date:	
Determination: i, having the this employee has successfutesting technician.	e authority for t	the JANX, have it is hereby consider	reviewed this eye lered visually qua	examination and lified to work as a	concluded that nondestructive
Signature of authority:	ala M	(John)	No 🛘		
Title of authority:	ity Syste	ns Oldin	instrator	Date: 4/	1/14
Comments:		J			
Rev2, June 2011	-				



OQ Task Information

Utility Technologies International, Corporation 4700 Homer Ohio Lane, Groveport, OH 43125 614-482-8080

Big Oats (Great Plains) 38700 Pelton Road

Willoughby, OH 44094 440-942-1876

*E = Exam, O = Observation by Simulation (No Observation on M-7 required) Prefixes of "NI_" are NiSource-specific modules, suffixes of "Propane" are propane modules

*Task Criteria = Criteria Established by Specific Veriforce Contractor Criteria

Rowland,	Thomas J.	N:	314-0B737		*Veriforce Task Company	
ITS Task#	Qualifier	Evaluation Date	Expiration Date	*Qualification Method	Notes	(if applicable- NiSourceTrans/Dominion)
CI-1	Linda Kuhlman	4/16/2015	4/16/2018	E, O	Pass	
F-1_F-2	Jack Lurty	5/11/2015	5/10/2016	E, O	Pass	
F-1_Other					Saddle 5/11/15	
F-2	Jack Lurty	5/11/2015	5/10/2016	E, O		
G-1	Linda Kuhlman	4/14/2015	4/14/2018	E, O	Pass	
H-2	Linda Kuhlman	4/14/2015	4/14/2018	E, O	Pass	
I-1C	Jeff Wolfe	5/16/2011	5/16/2014	E, O	Pass	
Last SLI calc		10/26/2007	10/26/2010			
M-3	Linda Kuhlman	4/14/2015	4/14/2018	E, O	Pass	
M-7FR	Linda Kuhlman	4/15/2015	4/15/2018	E	Pass	
M-8	Jack Lurty	5/23/2011	5/23/2014	E, O	Pass	
Ni_L-1(c)	Jack Lurty	5/11/2015	5/11/2018	E, O	Pass	
Ni L-2NoR	Linda Kuhlman	4/14/2015	4/14/2018	E. O	Pass	



Appendix D Qualification Status Update Record – Utility Series
Employee Name:
Employee ID Number:
Employee Job Title or Description:
Employee's Supervisor:
Employee's Reporting
Location:
Elevele Elevel. II Pingline Operating Company
Employee's Employer: Pipeline Operating Company
☐ Contractor Employee
Contractor Name
Date of This Qualification Status Report

The employee identified above is currently qualified to perform the following identified covered tasks checked below:

√ (check all covered tasks for which the employee is qualified)

Task	E-1	Weld on steel pipelines, 49 CFR 192.235, 192.241, 192.245
Task	E-2	Test welds using non-destructive process(es), 49 CFR 192.243
Task	F-1	Join plastic pipe with heat fusion, 49 CFR 192.281, 192.287
Task	F-2	Join plastic pipe with mechanical fittings, 49 CFR 192.281, 192.287
Task	F-3	Join copper pipe, 49 CFR 192.279
Task	G-1	Verifying excavation & backfilling operations to minimize damage, 49 CFR 192.317, 192.319, 192.325, 192.327, 192.361, 192.373, 192.461, 192.614
Task	G-2	Horizontal Directional Drilling, 49 CFR 192.307, 192.313, 192.315, 192.317, 192.319, 192.321, 192.323, 192.325, 192.701
Task	G-3	Boring by other methods, 49 CFR 192.161, 192.307, 192.317, 192.479, 192.481, 192.707
Task	H-1	Install domestic meter and regulator sets, 49 CFR 192.357
Task	H-2	Install domestic service lines, 49 CFR 192.361, 192.365, 192.367, 192.369

Tas	k I-1(1-4)	I-1.1 Perform pipe-to-soil potential surveys on effectively coating buried or submerged pipelines I-1.2 Determine areas of active corrosion on buried or submerged metal piping using pipe-to-soil potential I-1.3 Determine areas of active corrosion on buried or submerged metal piping using a surface potential survey I-1.4 Examine the external condition of exposed buried metal piping to determine if repair or replacement is necessary, 49 CFR 192.455, 192.457, 192.459, 192.465, 192.467, 192.613
Tas	k I-1(5-8)	I-1.5 Inspect rectifiers I-1.6 Inspect interference current bonds I-1.7 Install test leads to monitor and control external corrosion I-1.8 Install insulators to control external corrosion by electrical isolation, 49 CFR 192.455, 192.457, 192.459, 192.465, 192.467, 192.613
Tas	k I-1(9-10)	1-1.9 Inspect for evidence of internal corrosion I-1.10 Monitor internal corrosion control of piping when transporting corrosive gas, 49 CFR 192.475, 192.477, 192.613
Tasi	k I-1(11-12)	I-1.11 Inspect exposed piping for evidence of atmospheric corrosion I-1.12 Monitoring atmospheric corrosion control of exposed piping, 49 CFR 192.479, 192.481, 192.613
Tasi	k I-1(13,14,15)	I-1.13 Determine remedial measures for controlling corrosion on transmission lines I-1.14 Determine remedial measures for controlling corrosion on distribution lines I-1.15 Determine remedial measures for controlling corrosion on cast iron and ductile iron pipelines, 49 CFR 192.485, 192.487, 192.489, 192.613
Tasi	k I-1(16-17)	I-1.16 Attach anode leads to metal piping I-1.17 Apply / repair pipeline coating, 49 CFR 192.471, 192.613
Tasl	k I-1 Combo	I-1.7 Install test leads to monitor and control external corrosion I-1.8 Install insulators to control external corrosion by electrical isolation I-1.11 Inspect exposed piping for evidence of atmospheric corrosion I-1.12 Monitoring atmospheric corrosion control of exposed piping I-1.16 Attach anode leads to metal piping I-1.17 Apply / repair pipeline coating, 49 CFR 192.455, 192.457, 192.459, 192.465, 192.467, 192.471, 192.479, 192.481, 192.613
Tasi	(L-1	Tap pipelines under pressure, 49 CFR 192.627
Tasi	(L-2	Purge gas lines, 49 CFR 192.629

		· · · · · · · · · · · · · · · · · · ·
Task	L-3	Establish and maintain proper odorant levels in natural gas systems, 49 CFR 192.625
Task	L-3s	Monitoring odorant levels, 49 CFR 192.625
Task	M-1	Perform leakage and patrolling surveys, 49 CFR 192.613, 192.705, 192.706, 192.721, 192.723
Task	M-2	Locate and mark underground pipeline facilities WITH electronic equipment, 49 CFR 192.613, 192.707
Task	M-2(a)	Locate and mark w/o electronic locating equipment, 49 CFR 192.613, 192.707
Task	M-3	Test service lines, 49 CFR 192.725
Task	M-4	Inspect and test pressure limit stations, relief devices and pressure regulating stations, 49 CFR 192.731, 192.739, 192.741, 192.743, 192.749
Task	M-5	Maintain line valves in gas transmission/distribution piping, 49 CFR 192.745, 192.747
Task	M-5.1	Operate Valves – Ball, Plug, Gate, Butterfly, 49 CFR 192.745, 192.747
Task	M-6	Monitor compressor station gas detection equipment, 49 CFR 192.736
Task	M-7FR	Prevent accidental ignition, First Responder 49 CFR 192.751
Task	M-8 (Includes I-1.9 &	M-8 Installing/replacing & repairing natural gas piping I-1.9 Inspect for evidence of internal corrosion I-1.10 Monitor internal corrosion control of piping when transporting corrosive gas, 49 CFR 192.475, 192.477, 192.711, 192.713, 192.715, 192.717
Task	M-9	Repair/protect cast iron pipe, 49 CFR 192.753, 192.755
Task	M-10	Abandon/deactivate gas pipeline systems, 49 CFR 192.727

Approved by:

Signature	Title	Date

Route Copies to:		
Name	Title	Location
		•

V 12 Appendix D

Appendix E, Recommended re-qual. Intervals & use of non-qualified personnel

Appendix E. Recommended re-qualification intervals and whether the task can be performed by non-qualified personnel under direct supervision — Compliance Series.

Listed below are UTI's recommendations on re-qualification intervals for each task, and whether or not the task should be performed by non-qualified personnel if under direct supervision. Your company may choose differently.

You must complete the appropriate sections on re-qualification intervals and the use of non-qualified personnel for each covered task in Appendix B.

Task Qualification Re-Evaluation Interval Determination

DIF Calculation Basis:

Assign a value to each of the first 3 columns (DIF) relative to the identified covered task.

1st column: A difficult (complex) task should have a score of 5; a simple task a score of 1.

2nd column: If the safety consequence of improper performance of the task is serious the score should be 5; if minor the score should be 1.

3rd column: A frequently performed task should have a score of 1; an infrequently performed task should have a score of 5.

Add across columns 1 through 3 to obtain the Total Rating.

If the Total Rating is:

Less than or equal to 6, the Re-evaluation Interval is 36 months. Less than 12 but greater than 6, the Re-evaluation Interval is 24 months. Greater than or equal to 12, the Re-evaluation Interval is 12 months.

		_		_			
Task No.	Task Name	DR	IR	FR	Tot.	Requal. Interval Months	Can task be performed by non- qualified person
CE-1	Weld on Steel Pipelines, 49 CFR 192.225, 192.231, 192.235, 192.245	N/A*	N/A*	N/A*	N/A*	6	No**
CE-2	Visually Inspect Pipe Welds, 49 CFR 192.241, 192.243	2	2	2	6	36	No
CE-3	Perform Non-Destructive Tests on Steel Welds, 49 CFR 192.241, 192.243	4	4	4	12	12	No
CF-1	Join Plastic Pipe with Heat Fusion	N/A*	N/A*	N/A*	N/A*	12	No**
CF-1.1	Join Plastic Pipe with Butt Fusion, 49 CFR 192.123, 192.273, 192.281, 192.285, 192.287	N/A*	N/A*	N/A*	N/A*	12	No**
CF-1.2	Join Plastic Pipe with Socket Fusion, 49 CFR 192.123, 192.273, 192.281, 192.285, 192.287	N/A*	N/A*	N/A*	N/A*	12	No**
CF-1.3	Join Plastic Pipe with Saddle Fusion, 49 CFR 192.123, 192.273, 192.281, 192.285, 192.287	N/A*	N/A*	N/A*	N/A*	12	No**

V 12 Appendix E

Join Plastic Pipe with Electrofusion, 49 CFR 192.123, 192.273, 192.281, 192.285, 192.287	N/A*	N/A*	N/A*	N/A*	12	No**
Join Plastic Pipe with Mechanical Fittings	N/A*	N/A*	N/A*	N/A*	12	No**
Join Plastic Pipe with Threaded Nut Compression End Fittings, 49 CFR 192.123, 192.273, 192.281, 192.285, 192.287	N/A*	N/A*	N/A*	N/A*	12	No**
Join Plastic Pipe with Stab-Type Mechanical Fittings, 49 CFR 192.123, 192.273, 192.281, 192.285, 192.287	N/A*	N/A*	N/A*	N/A*	12	No**
Join Plastic Pipe with Mechanical Compression Fittings, 49 CFR 192.123, 192.273, 192.281, 192.285, 192.287	N/A*	N/A*	N/A*	N/A*	12	No**
Join Copper Pipe for Gas Distribution, 49 CFR 192.279	1	2	3	6	36	No**
Join Plastic Pipe with Solvent Cement, 49 CFR 192.273, 192.281, 192.283, 192.285, 192.287, 192.311	1	2	3	6	36	No**
Visually Inspect Polyethylene Pipe Joints for Indicators of Proper Construction/Assembly, 49 CFR 192.123, 192.273, 192.281, 192.283, 192.285, 192.287	2	2	2	6	36	No
Install Tubing and Fittings for Instrumentation, Control, and Sampling, 49 CFR 192.203, 192.279	2	2	2	6	36	Yes
Join Pipe with Flange Assembly, 49 CFR 192.147	1	2	3	6	36	Yes
Verify Excavating and Backfilling Operations that Minimize Excavation Damage to Pipeline Facilities, 49 CFR 192.307, 192.317, 192.319, 192.321, 192.325, 192.327, 192.361, 192.461, 192.614	2	2	1	5	36	No
Identify Basic Installation Methods for Mains and Transmission Pipelines, 49 CFR 192.307, 192.313, 192.315, 192.317, 192.319, 192.321, 192.323, 192.325, 192.327, 192.707	2	2	2	6	36	Yes
Install Aboveground Pipelines, 49 CFR 192.161, 192.307, 192.317, 192.479, 192.481, 192.707	2	2	2	6	36	Yes
Install Mains and Transmission Pipelines Using Trenchless Methods, 49 CFR 192.307, 192.321, 192.325, 192.327	2	2	1	5	36	No
	CFR 192.123, 192.273, 192.281, 192.285, 192.287 Join Plastic Pipe with Mechanical Fittings Join Plastic Pipe with Threaded Nut Compression End Fittings, 49 CFR 192.123, 192.273, 192.281, 192.285, 192.287 Join Plastic Pipe with Stab-Type Mechanical Fittings, 49 CFR 192.123, 192.273, 192.281, 192.285, 192.287 Join Plastic Pipe with Mechanical Compression Fittings, 49 CFR 192.123, 192.273, 192.281, 192.285, 192.287 Join Copper Pipe for Gas Distribution, 49 CFR 192.273, 192.281, 192.285, 192.287 Join Plastic Pipe with Solvent Cement, 49 CFR 192.279 Join Plastic Pipe with Solvent Cement, 49 CFR 192.273, 192.281, 192.283, 192.285, 192.287, 192.311 Visually Inspect Polyethylene Pipe Joints for Indicators of Proper Construction/Assembly, 49 CFR 192.123, 192.273, 192.281, 192.283, 192.285, 192.287 Install Tubing and Fittings for Instrumentation, Control, and Sampling, 49 CFR 192.203, 192.279 Join Pipe with Flange Assembly, 49 CFR 192.147 Verify Excavating and Backfilling Operations that Minimize Excavation Damage to Pipeline Facilities, 49 CFR 192.307, 192.317, 192.319, 192.321, 192.325, 192.327, 192.317, 192.319, 192.321, 192.307, 192.313, 192.315, 192.317, 192.319, 192.321, 192.327, 192.313, 192.315, 192.317, 192.319, 192.327, 192.307, 192.313, 192.323, 192.325, 192.327, 192.307 Install Aboveground Pipelines, 49 CFR 192.141, 192.707 Install Mains and Transmission Pipelines Using Trenchless Methods, 49 CFR	CFR 192.123, 192.273, 192.281, 192.285, 192.287 Join Plastic Pipe with Mechanical Fittings	CFR 192.123, 192.273, 192.281, 192.285, 192.287	CFR 192.123, 192.273, 192.281, 192.285, N/A* N/A*	CFR 192.123, 192.273, 192.281, 192.285,	CFR 192.123, 192.273, 192.281, 192.285, N/A* N/A*

V 12 Appendix E

CG-5	Moving In-Service Pipelines, 49 CFR 192.319, 192.321, 192.323, 192.325, 192.327192.459, 192.605, 192.614, 192.615, 192.707	3	2	1	6	36	No
CH-1	Install Customer Gas Meter and Regulator Sets, 49 CFR 192.353, 192.355, 192.357, 192.359	2	2	1	5	36	No
CH-2	Install Customer Gas Service Lines, 49 CFR 192.151, 192.361, 192.363, 192.365, 192.367, 192.369, 192.373, 192.375, 192.377, 192.379, 192.381	2	2	1	5	36	No
CH-3	Deactivate Gas Metering Services, 49 CFR 192.727	3	2	1	6	36	No
CH-4	Install Residential Customer Service Line Valves, 49 CFR 192.363, 192.365, 192.381, 192.383	2	2	1	5	36	No
CH-5	Maintenance of Service Valves Upstream of Customer Meter (in development), 49 CFR 192.363, 192.365	2	2	1	5	36	Yes
CI-1	Perform Pipe-to-Soil Potential Surveys on Effectively Coated Buried or Submerged Pipelines, 49 CFR 192.463	2	2	1	5	36	Yes
CI-2	Determine Areas of Active Corrosion Using Close Interval Survey Methods, 49 CFR 192.453, 192.465	3	2	1	6	36	Yes
CI-3	Measure Soil Resistivity, 49 CFR 192.453, 192.465	3	2	1	6	36	Yes
CI-4	Inspect the External Condition of Exposed Buried Metal Piping to Determine if Repair or Replacement is Necessary, 49 CFR 192.459, 192.461(a), 192.483, 192.485, 192.487, 192.489	2	2	1	5	36	Yes
CI-5	Inspect and Maintain Rectifiers, 49 CFR 192.465	3	2	1	6	36	Yes
CI-6	Inspect for the Effects of Interference Current, 49 CFR 192.465, 192.473	3	2	1	6	36	Yes
CI-7	Install Test Leads to Monitor and Control External Corrosion, 49 CFR 192.465, 192.469, 192.471	2	2	2	6	36	Yes
CI-8	Install and Test Insulation to Control External Corrosion by Electrical Isolation, 49 CFR 192.467	3	2	1	6	36	Yes
CI-9	Inspect for Evidence of Internal Corrosion, 49 CFR 192.475, 192.477	2	2	2	6	36	Yes
CI-10	Inspect and Monitor Exposed Piping for Evidence of Atmospheric Corrosion, 49 CFR 192.479, 192.481	2	2	2	6	36	Yes
Cl-11	Install Sacrificial Anodes and Test Stations, 49 CFR 192.465, 192.469	2	2	2	6	36	Yes

V 12 Appendix E

CI-12	Measure the Extent of Corrosion on Pipeline Facilities, 49 CFR 192.459, 192.475, 192.477, 192.481	3	2	1	6	36	Yes
CI-13	Identify Procedures Basic to Inspecting, Applying, and Repairing Pipeline Coatings, 49 CFR 192.459, 192.461	2	2	2	6	36	Yes
CI-14	Obtain and Shipping Gas Samples, 49 CFR 192.475, 192.477	2	2	1	5	36	Yes
CI-15	Troubleshoot In-Service Cathodic Protection Systems, 49 CFR 192.463	3	2	1	6	36	Yes
CK-1	Uprate a Pipeline, 49 CFR 192.105, 192.121, 192.553, 192.555, 192.557, 192.619, 192.621, 192.623	3	2	1	6	36	Yes
CL-1	Tap Pipelines Under Pressure, 49 CFR 192.151, 192.627	3	2	1	6	36	No
CL-1a	Hot Tapping Pipelines Using Self-Tapping Tees, 49 CFR 192.627	2	2	1	5	36	No
CL-1b	Bagging and Stopping Low Pressure Pipe with Bag, Stopper, or Stopple, 49 CFR 192.151, 192.627	3	2	1	6	36	No
CL-2	Purge Pipelines (Small and Large Diameter), 49 CFR 192.629	2	2	1	5	36	Yes
CL-3	Odorizer Inspection, Testing, and Preventive/Corrective Maintenance, 49 CFR 192.625	2	2	1	5	36	Yes
CL-3a	Monitor Odorant Levels, 49 CFR 192.625	1	2	2	5	36	Yes
CL-4	Monitor and Regulate the Flow and Pressure of Gas from Remote Locations, 49 CFR 192.201, 192.619, 192.621, 192.623, 192.631, 192.741	2	2	2	6	36	Yes
CL-5	Perform Hot Tapping Operations on Plastic Pipe, 49 CFR 192.151(a), 192.627	3	2	1	6	36	No
CL-6	Inspect , Test, and Maintain Actuators, 49 CFR 192.179, 192.181, 192.745, 192.747	2	2	2	6	36	Yes
CL-7	Inspect, Test, and Maintain Programmable Logic Controllers, 49 CFR 192.605B, 10(iii), 192.739	3	2	1	6	36	Yes
CM-1	Perform Patrol and Leakage Surveys on Gas Pipeline Facilities, 49 CFR 192.5, 192.613, 192.705, 192.706, 192.721, 192.723	2	2	2	6	36	Yes
CM-2	Locate and Mark Underground Facilities, 49 CFR 192.614, 192.707	2	2	1	5	36	Yes
CM-3	Pressure Testing Gas Pipelines, 49 CFR 192.503, 192.505, 192.507, 192.509, 192.511, 192.513, 192.725	2	2	1	5	36	Yes

V 12 Appendix E

					_		
CM-4	Inspect and Test Pressure Limiting Stations, Relief Devices, and Pressure Regulating Devices, 49 CFR 192.201, 192.731, 192.739, 192.743, 192.749, 192.751	2	2	2	6	36	Yes
CM-5	Inspect, Service, and Operate Line Valves, 49 CFR 192.179, 192.181, 192.745, 192.747	2	2	1	5	36	Yes
CM-5a	Inspect Emergency Valves, 49 CFR 192.745, 192.747, 192.803	2	2	1	5	36	Yes
CM-5b	Valve Corrective Maintenance, 49 CFR 192.747	2	2	1	5	36	Yes
CM-6	Monitor Compressor Station Gas Leak Detection Equipment, 49 CFR 192.735, 192.736	2	2	1	5	36	Yes
CM-7	Prevent Accidental Ignition, 49 CFR 192.751	3	2	1	6	36	No
CM-8	Make Field Repairs on Gas Pipelines, 49 CFR 192.245, 192.307, 192.309, 192.311, 192.703, 192.711, 192.713, 192.715, 192.717	2	2	2	6	36	Yes
CM-9	Repair and Protect Cast Iron Pipe, 49 CFR 192.275, 192.489, 192.753, 192.755	2	2	2	6	36	Yes
CM-10	Abandon or Deactivate Gas Pipeline Facilities, 49 CFR 192.727	2	2	1	5	36	Yes
CM-11	Recognize and React to Generic Abnormal Operating Conditions, 49 CFR 192.751	3	2	1	6	36	No
CM-12	Launch and Receive Pipeline Pigs, 49 CFR 192.150	3	2	1	6	36	Yes
CM-13	Investigate Reported Gas Leaks and Odors in Buildings	3	2	1	6	36	No
CM-14	Inspect Vault Conditions, 49 CFR 192.749, 192.751	2	2	1	5	36	Yes
CM-15	Operate and Maintain Compressor Station Components, 49 CFR 192.167, 192.169, 192.171, 192.173, 192.199, 192.201, 192.605(a)(b)(6)(7), 192.731, 192.743	2	2	2	6	36	Yes
CM-16	Inspect, Test, and Maintain Sensing Devices, 49 CFR 192.739, 192.741, 192.743	2	2	1	5	36	Yes
CM-17	Squeeze-Off Steel Pipe, 49 CFR 192.615	2	2	1	5	36	Yes

V 12 Appendix E

CM-18	Station Emergency Shut Down System: Inspection, Testing, and Corrective Maintenance, 49 CFR 192.167, 192.171, 192.731, 192.736	3	2	1	6	36	Yes
CM-19	Installing and Maintaining Customer Pressure Regulating, Pressure Limiting, and Pressure Relief Devices: Large Commercial and Industrial, 49 CFR 192.199, 192.743	2	2	2	6	36	Yes
CM-20	Reciprocating Compressor Inspection, Testing, and Corrective Maintenance, 49 CFR 192.731	3	2	1	6	36	Yes
CM-23	Measure and Characterize Mechanical Damage on Installed Pipe and Components, 49 CFR 192.307, 192.309	3	2	1	6	36	Yes
CO-1	Conduct Indirect Pipe Inspections, 49 CFR 192.925, 192.947	3	2	1	6	36	Yes
CO-2	Conduct Direct Pipe Examinations, 49 CFR 192.927, 192.947	3	2	1	6	36	Yes

Approved by:

Signature:	Title:	Manage Reguet 19016
		0 4 0

^{*} Not Applicable due to specific code requirements
** Cannot use non-qualified personnel do to specific code requirements

Appendix F
Operator Qualification Field
Operation Record

Appendix F – Operator Qualification Field Observation Record – Compliance Series

Company Obse	nued		Observe			
Location	1700		Observe		ate:	
Employees Obs	erved		•		ate.	
Name	Number (Employee # or SSN)	Task Observed	Were tas complete accordar &M plan requirem OQ plan	ed in ice to O and	Were employed able to recognize and react to AOC's	
			Yes	No	Yes	No
					 	-
Comments (If ar task without sup implemented)	ny no's were answe ervision and the ap	red employee mus propriate provision	st be stopp ns of the O	ed from pe Q plan sho	rforming uld be	covered
Continuous Impresponsible for C	ovement Recommo Q Plan implement	endations (This mu ation.	ust be prov	ided to the	person	
Action Taken			10.			
Ву:			Date			



Utility Technologies International (614) 482-8080 Fax (614) 482-8070

V 12 Appendix F

Appendix F – Operator Qualification Field Observation Record – Utility Series

Company Obs	erved		Observe	er		
Location					ate:	
Employees Ob	served					
Name	Number (Employee # or SSN)	Task Observed	complet accorda &M plan	nce to O and nents of		
			Yes	No	Yes	No
		1	_		-	-
				<u> </u>	 	
Comments (If a covered task washould be implemented)	any no's were ans vithout supervisio lemented)	wered employe n and the appro	e must be s priate provi	topped fro sions of th	m perfo ne OQ pl	rming lan
Continuous Im	provement Recon	nmendations (T	his must be	provided	to the pe	erson
Action Taken						
Bv:			Date			



Utility Technologies International (614) 482-8080 Fax (614) 482-8070

Ohio Rural Natural Gas, Co-Op

Distribution Integrity Management Plan (DIMP)



	оню і	RURAL NATU	RAL GAS CO-OP	
1" PLASTIC	2" PLASTIC	4" PLASTIC	1" STEEL	
17	4	5,400	3	
	930	550	13	
	163	1,700		
	311	7,075		
	302	545		
	304	765		
	326			
17	2,340	16,035	16	TOTAL FEET
0.003	0.443	3.037	0.003	TOTAL MILES

INFO				
17'	1" P	13164 LEROY CTR RD - LEROY		
3'	1" S	6970 WILLIAMS RD - CONCORD		
13'	1" S	12321 CARTER RD - LEROY		
4'	2" P	800 OAK ST - PAINESVILLE		
930'	2" P	SUGARBUSH DR - MENTOR		
163'	2" P	SUGARBUSH DR - MENTOR		
311	2" P	TIN MAN STORAGE - MENTOR		
302	2" P	TIN MAN STORAGE - MENTOR		
304	2" P	TIN MAN STORAGE - MENTOR		
326	2" P	TIN MAN STORAGE - MENTOR		
5400'	4" P	ELLSWORTH RD - MAHONING CTY		
550'	4" P	EAST AVE - MENTOR		
1700'	4" P	S. DUCK CREEK RD - MAHONING		
7075'	4" P	HALLOCK YOUNG & LYNTZ RDS		
545'	4" P	FRACCI COURT - MENTOR		
765'	4" P	TIN MAN RD - MENTOR		

Table of Contents

1. Introduction a. Overview 1. Purpose Scope 2.

- Elements of DIMP b.
- 2. Knowledge
 - General a.
 - **DOT Annual Report Information** b.
 - Additional Information c.
 - Knowledge of the System d.
 - Documentation e.
- 3. **Identify Threats**
 - **Primary Threats** a.
 - **Identify Threats b**.
- **Evaluate and Prioritize Risk** 4.
 - General a.
 - Information Evaluation b.
 - Methods c.
 - Risk Evaluation
 - Validation
- Identify and Implement Measures to Address Risks 5.
 - General a.
 - Leak Management Program Ъ.
- 6. Measure Performance, Monitor Results and Evaluate Effectiveness
 - a. General
 - Guidelines for Developing Performance Measures b.
 - Performance Measures
 - **Monitor Results** d.
 - **Evaluate Effectiveness**
- 7. Periodic Evaluation and Improvement
 - Review of Written Plan a.
 - b. Review of Effectiveness

- 8. Report Results
 - a. General
- 9. Forms
- 10. Part 192 Subpart P Gas Distribution Pipeline Integrity Management
- 11. GPTC Guide Material Appendix G-192-8

1. Introductions

a. Overview

1. Purpose

This is the Distribution Integrity management Plan for Ohio Rural Natural Gas (ORNG). This plan provides the requirements for compliance with the Distribution Integrity Management Program, Subpart P, 49CFR Part 192 Transportation of Natural and Other Gas by Pipeline: Minimum Federal Safety Standards. The objective of this plan is to increase the safety and integrity of the pipeline facilities. The person(s) responsible for the administration and implementation of this plan is/ are Lauren Tristano, Compliance Manager and Darryl Knight, President.

2. Scope

This plan addresses all gas distribution facilities defined in 49 CFR 192.3 including mains, service lines, service regulators, and low, medium and high pressure distribution.

b. Elements of DIMP

Below are the general elements that will be considered and addressed within the program. These elements are addressed in greater detail in the following sections of the plan.

- 1. Knowledge
- 2. Identify Threats
- 3. Evaluate and Prioritize Risk
- 4. Identify and Implement Measures to Address Risks
- 5. Measure Performance, Monitor Results and Evaluate Effectiveness
- 6. Periodic Evaluation and Improvement
- 7. Report Results

2. **Knowledge (192.1007(a))**-Below are Ohio Rural Natural Gas Co-Op's methods of gathering information; as well as the specific information to be gathered in order to demonstrate a working knowledge of the company's facilities. This is followed by a summary of knowledge which will describe in detail the results of the information gathered thus far, as of the current revision (1.0) of this program.

a. General

Information pertaining to the pipeline system and the environment will be gathered. This information will assist with indentified the threats that apply to particular sections of the facilities. If particular information is not available, estimations will be concluded based on individual knowledge of the facilities (i.e. SME). New information obtained through the normal course of operations and maintenance activities will be incorporated into the program. It is not necessary to conduct excavation activities to gather system information. Whenever possible, information gathered with existing procedures will be utilized; such as during additions to existing facilities or performing routine inspections and maintenance. If significantly different systems/areas are identified within the entire pipeline system, separate consideration will be given to these groups within the program.

Subject Matter Experts

Subject Matter Experts (SME's) are individuals with specific knowledge of the entire system, or of a particular section or component of the system. As Ohio Rural Natural Gas Co-Op is an entirely new system with no preOexisting facilities, we anticipate several employees who will become SME's based on not only their required duties, but also due to the exchanging of information within the company moves forward.

- Darryl Knight, President
- Lauren Tristano, Compliance Manager
- Jack McCormick, Field Operator
- Dave Stanish, Field Technician/Supervisor
- Ryan McCormick/ Field Technician

b. DOT Annual Report Information

The PMHSA Form F7100.1-1 is an annual form which contains basic information regarding pipeline facilities. Pipe sizes, materials, lengths, leaks, leaks eliminated etc. are reported. This information assists us in implementing the DIMP, as it contains basic information which is essential to understanding and knowing the system.

c. Personnel Knowledge

Field personnel will be utilized in gathering system knowledge. They may have specific knowledge of construction techniques and materials used when other sources of information are not available. Information that is particularly important includes pipe specification and component information, construction and installation methods and corrosion control systems and methods. This information will be part of the documentation of knowledge process.

d. Knowledge of the system

Physical Infrastructure

Physical infrastructure includes the location, material composition, piping sizes, construction methods, dates of installation, operating pressure, maximum allowable operating pressure and design pressure.

To the extent possible the following data will be collected:

Pipe Material

- a. Plastic
 - Polyethylene (PE)
 - Polyamide 11 (PA11)
 - Poly Vinyl Chloride (PVC)
 - Acrylonitrile Butadiene Stryrene (ABS)
 - Cellulose Acetate Butyrate (CAB)
 - Aldyl-A
 - Polybutylene (PB)
- b. Steel
- c. Copper
- d. Cast Iron
- e. Ductile Iron
- f. Aluminum
- g. Fiberglass
- h. Other

Pipe Specifications

- a. Diameter
- b. Joint length (for cast iron)
- c. Manufacturer
- d. Year manufactured
- e. Steel pipe specs
 - Grade
 - Wall thickness
- f. Plastic pipe specs
 - Medium/high density
 - SDR
 - Straight lengths (stick or coil)

Operating Conditions

- a. Pressure
- b. Gas Quality
- c. Odorization
- d. Odorant Detection
- e. Abnormal Operation Conditions (AOC's)

Construction

- a. Year installed
- b. Pipe joining method
- c. Installation method (open trench, plow, boring, directional drilling)
- d. Location (from lot line or centerline, class location, end points

- e. Cover
 - Depth (original, current, restored)
 - Type (backfill, pavement, grass, dirt, gravel, above ground)
- f. Company or contractor completing installation
- g. Casings
- h. Crossings (highway, bridge, underwater)
- i. Expansion loops (thermal effects)
- j. Pipe support systems

Corrosion Control Systems

- a. Below ground coating type (coal tar, fusion bond epoxy, yellow jacket, wax)
- b. Cathodic protection (galvanic anode, bank or distributed, impressed current)
- c. Electrical isolation (type, location)
- d. Years without cathodic protection
- e. Stray current areas (interference, diodes, bonds, reverse current switch)
- f. Rock shield
- g. Above ground coating types

Valves

- a. Size
- b. Type
- c. Location
- d. Usage (emergency, station shutoff, bypass, convenience)
- e. Manufacturer
- f. Material of construction
- g. End connections
- h. Year of manufacture/installation
- i. Pressure rating (ANSI or WOG)

System pressure regulation

- a. Size
- b. Location
- c. Differential pressure
- d. Capacity
- e. Operation (Pilot, spring, weight)
- f. Manufacturer
- g. Means of over pressure protection (relief, monitor, slam shut)

Other

- a. Specialized components (insulating joint, union, meter swivel, anodeless riser, etc.)
- b. Fabricated or homemade fittings (reducers, couplings, etc.)
- c. Experimental or trial fittings
- d. Critical facility under the Homeland Security definition

Operating Experience

Information of what is currently happening within the pipeline system along with historical information will be gathered and reviewed to determine if action is necessary. This information will come from the following routine operation and maintenance activities.

1. Results of inspections and surveys

- a. Leak surveys
- b. Corrosion inspections
- c. Patrols
- d. Liquids removed
- Documentation of leaks and other maintenance performed
 - a. Repairs
 - b. Corrosion control systems
 - c. Equipment or component replacements
 - e. Material failure reports
 - f. Incident reports
 - g. Part C of the annual F7100 report
- 3. Excavation activity
 - a. Damage reports
 - b. Number of underground locate requests received
 - c. Proposed significant construction activities
- 4. Geological conditions
 - a. Frost areas
 - b. Earthquake zones
 - c. Known washout areas
 - d. Land subsidence areas
- 5. Operating Pressure/MAOP
 - a. Maximum actual operating pressure experienced
 - b. Minimum operating pressure experienced (i.e. peak day)
 - c. Normal operating pressure
 - d. Fluctuations (seasonal, random)
 - e. Previous upratings performed

e. Documentation

As ORNG is an entirely new system, all data is to be captured and retained as new knowledge. Unless there are acquisitions of older, pre-existing systems; the basis of the knowledge of our system will come from documentation and records of properly completed paperwork associated with newly installed facilities. It is not applicable to gather or research additional methods for gathering missing historical information.

Documents may already exist to fulfill the requirements of Federal and/or state standards, company policy, or devised solely to fulfill the DIMP. Section 9 of this plan contains forms to be utilized by ORNG in order to fulfill requirements and simultaneously gather data to attain system knowledge System knowledge information will be gathered and organized. Methods for doing this include:

- 1. Identifying relevant system components on maps
- 2. Maintaining electronic records
- 3. Maintaining hard copy files
- Any combination of the above

All information gathered will be incorporated using these methods. The following forms provide guidance and a format for collecting system data. This data can be entered manually or through electronic spreadsheets.

	T													· · · · · · · · · · · · · · · · · · ·						
System Nume								В			ant.		- C I		. 11	l Pip				
System Number						Į.		Н	ro	per	THE	25 (OT I	nsta	anec	מוץ נ)ei	ıne	38	
System Location	<u> </u>									<u>L</u>			, ,	11000		· · ·				
Pîpe	Pipe			Yunr	Steel	Wall	Plastic		Join	Installation	Coating	Cathodic	Electrical	Years w/o	Stray	Above Ground	# of Test	Test Pts.	Test Station	Compliance
Longth	Material	Diameter	Manufacturer	Year	Grade	Thickness	Density	SDR	Method	Method	Тура	Protection	Isolatioin	Cathodic Pro.	Current Areas	Coating	Staiona	Critorio	Repairs	OK
	-								 				-							
				-	-		 													
								1												
	 		-																	
				<u> </u>																
<u> </u>								\vdash												
																		. !		
					-															
															-		-			
							-													
								_												
								\neg	\neg		\neg		i							
				\neg	,			-										_		
	-				-	-	-	-1	-		-					-	-		-	
	\rightarrow	-			-		-	\rightarrow			-		_							
				-	-			-												
					_			_												
		- 1															T	T		

System Main System Main System Local	ber					Regul	ator inv	entory
	:					<u> </u>		
Location	Size	Туре	i e priére luga	Year	Andied: Pressure	Outlet Pressure	One present	Compliance OK
	1							
Notes:					:			

System Nam System Num					·	+	Valve I	nventor	'V
System Local							valve i	- Circoi	γ
	i	;		<u> </u>	:	Pressure	Critical	Crit Valve	NonCrit Valve
Line ID	Valve Size	Valve Type	Manufacturer	Year	Material	Rating	Valve	Compliance	Compliance
					-		1		
		-			†				
					j				
								 	
								 - 	
								1	
					i				
									
	ļ								
Notes:	1		\$		and the state of the state of			E	(*************************************
								Provide - 48-1-10-1 - 1 - 1-1-1-1-1	

Abbreviations			
Pipe Material		Test Stations	
Coated Steel	CS	# of Test Stations	Insert Qty
Bare Steel	BS	Test Stations below Criteria	Insert Qty
Copper	CU	Test Station Repairs	Insert Qty
Cast Iron	CI	Compliance OK	Yes/No
Ductile Iron	DI	the companies of processing and a sign of	gi
Aluminum	AL	Density	es open
Fiberglass	FG	Medium Density	MD
Other	0	High Density	HD
Plastic	e statute meta managarak orang 1 statute meta mengarak orang	Installation Method	A STATE OF THE STATE OF T
Polyethelene	PE	Open Trench	ОТ
Polyamide 11	PA11	Plow	P
Poly Vinyl Chloride	PVC	Boring	В
Acrylonitrile Butadiene Styrene	ABS	Directional Drilling	DD
Cellulose Acetate Butyrate	CAB	The state of the s	market No.
Aldyl A	AA	Stray Current Areas	
Polybutylene	РВ	Interference	IN
Other	0	Diodes	DI
Manager and Principles	i E	Bonds	В
Joining Method	4	Reverse Current Switch	RCS
Coupling	CO	See Attachment	Attach
Welded	W		ACTION 3.6 Library amendase where d
Threaded	TH	Above Ground Coating	
Fused	F	Paint	Р
Electro Fusion	EF	Таре	Т
Adhesive	AD		В

Summary of Knowledge – Below is a summary of the existing facilities of Ohio Rural Natural Gas Co-Op.

As of 2015, Ohio Rural Natural Gas is an entirely new distribution system. There are no natural gas facilities in this system acquired or constructed prior to the year 2015.

As of this current version (1.0) of DIMP, Ohio Rural Natural Gas Co-Op has approximately 13,728' (feet) of 4" PE Plastic pipe, in a Class 1 location. The pipeline is currently inactive, and if activated will have an operating pressure below 60psi. There are no pipelines or other facilities operated by ORNG that were constructed prior to 2015.

13,728' of 4" PE pipe was installed out of compliance with 49 C.F.R. §192.13(c) and with O.A.C. 4901:1-16-06(D). Therefore, this installation requires serious consideration when identifying threats, risks, and taking preventative/improving measures. This segment will be discussed in further detail in the following sections of this plan.

3. Identify Threats (§192.1007(b))

a. Threats

Once system knowledge is collected and evaluated, ORNG is to determine how the following threats may compromise the integrity of the distribution system.

- 1. Corrosion
- 2. Natural forces
- 3. Excavation damage
- 4. Other outside force damage
- 5. Material or weld failure
- 6. Equipment malfunction
- 7. Inappropriate operation
- 8. Other

b. Threat Identifications

This section identifies all primary threats to the ORNG distribution system. Below is a list of primary threats, a description of each threat, followed by an explanation of how each threat pertains to the distribution system.

Corrosion

As of this current revision (1.0), Ohio Rural Natural Gas Co-Op does not operate any below ground steel piping. Shall ORNG anticipate the addition of underground steel piping, the threat of corrosion will be evaluated and implemented into the program. There are plans to operate town border or regulator stations within the year. Such facilities are susceptible to corrosion. Due to the frequency in which ORNG will inspect for corrosion; which is at a minimum once per calendar year NTE 15 months per §192.465, combined with the low number of potential corrosion areas within this first year of operations; corrosion will be a low threat for the system.

There are no indications or expectations of liquid within any ORNG natural gas facilities which may induce internal corrosion.

All above ground metallic facilities are subject to atmospheric corrosion. While currently not operating any as of this revision (1.0), regulator stations and meter sets are anticipated to occur within this year. Meter readers, technicians, and any other field personnel are instructed to perform atmospheric corrosion inspections whenever possible during other routine duties. These inspections are supplements to a dedicated atmospheric corrosion inspection that is performed at least once every 3 years per §192.481. The system is also currently in its infancy, and will remain at most a small system throughout the period of which this plan covers, the threat of atmospheric corrosion will be low as well.

Any possible threat of corrosion occurring would be isolated.

Corrosion Likelihood Threat: 1

Natural Forces.

As of this current version (1.0), there are no facilities located in areas prone to natural forces such as land subsidence, washout areas, flooded areas, sinkholes, or bodies of water. ORNG does not anticipate the addition of facilities located in such areas within the year. Due to the climate of the region (Northeast Ohio), the facilities may be susceptible to frost or ice damage. Our SME's do not view this as a high threat.

The likelihood threat for all subcategories of natural forces will be extremely low, and isolated.

Natural Forces Likelihood Threat: 1

Excavation Damage

Damage to facilities caused by excavation is a system-wide threat. Therefore it is generally the greatest cause of leaks in a natural gas distribution system. Service lines are more susceptible to damage as a result of home or business owner excavation. In other words, non-excavation professionals who are likely to be less aware of the threats of not utilizing the one-call system. Current ORNG facilities exist in a Class 1 location with infrequent development and construction activity. ORNG is also a member of the Ohio Utilities Protection Service (OUPS) and participates in a public awareness program to reduce the threat of excavation damage. Combining these factors, the current risk for excavation damage will remain low but relatively higher than other threats to the ORNG system.

Excavation Damage Threat: 4

Other Outside Force Damage

ORNG does not operate in any locations prone to high vehicular traffic or nearby heavy equipment, nor does it anticipate doing so within the year of this revision (1.0). There are no current or potential locations where vandalism, wreckage, our unauthorized operations have been known to occur. The likelihood factor for Outside Force Damage is low, and such an incident would be extremely isolated.

Outside Force Likelihood Threat: 1

Material or Weld Failure

As a new facility, Ohio Rural Natural Gas has no prior experience with malfunctions or defects of any pipe, fittings, components, or joints. ORNG does not and will not utilize any type of piping materials which have been known to malfunction such as Aldyl A pipe manufactured prior to 1973. Mechanical fitting failures will be recorded and reported annually to PHMSA per §191.12. Section 9 contains the form utilized by Ohio Rural Natural Gas to record failures in mechanical fittings.

The threat of material or weld failures in this system is low, and an occurrence would likely be an isolated incident.

Material or Weld Failure Likelihood Threat: 1

Equipment Malfunction

Failures of equipment such as regulators and relief valves or other repeated failures of piping components such as threaded joints shall be identified.

As of this version (1.0) of the program, ORNG does not operate any regulators or relief valves with any historical failures. The threat for equipment malfunctions occurring on the ORNG system is low, and the occurrence would be localized.

Equipment Malfunction Likelihood Threat: 1

Inappropriate Operation

In January 2015, approximately 13,728 ft. of 4" PE plastic pipe was installed by a third party contractor on behalf of Ohio Rural Natural Gas Co-Op. This section is located in Lordstown, in Trumbull County, Ohio. It was installed prior to the company's implementation of an Operating and Maintenance Program, an Operator Qualification Program, and a DIMP.

As a result, the procedures used by the third party contractor to install the pipe could not be O.Q. approved by ORNG during the time of installation. Although the O.Q. of the contractor has since been reviewed and the procedures are approved by the developed O.Q. Plan of ORNG; this section has been identified as an area where the pipeline integrity may be compromised due to inappropriate operation.

This likelihood threat will remain high in relative terms, but low overall as information indicates that the pipe segments have been properly installed. This is the only segment of piping installed out of compliance, and future installations of pipeline and facilities will likely have a much lower perceived threat of hazardous leaks due to inappropriate operations.

Inappropriate Operation Likelihood Threat: 3

Other

Any other threats that may be found shall be identified. These threats would most likely be attributable to special circumstances within the piping system.

ORNG cannot identify any special circumstances or anticipated factors could cause damage to its facilities. This threat is low.

Likelihood of Other Types of Threats: 1

Threat Identification Table

Table 3.1 will be used as a tool to assist with assessing the threats to the pipeline. This information will be used to further analyze the threats and assign likelihood factors as part of the evaluation and prioritization of risk in section four.

		Threat Identification - Table 3.1	Ţ		
			Ext	tent of Thr	
Primary Threat	Threat Subcategories	Questions to Check Subcategory Applicability to System	General	Local	N/A
Corrosion	External corrosion: bare steel pipe	-Does bare steel exist in the system? -Is the pipe cathodically protected? -Have corrosion leaks occurred? -Do exposed pipe inspections indicate external corrosion? -Are cathodic protection readings consistently adequate during annual			✓
		monitoring? -Are there known sources of stray electrical currents in the area?			
	External corrosion: cast iron pipe	-Does cast iron or ductile iron exist in the system? -Have fractures occurred in the pipe, other than those related to excavation activities? -Are those fractures limited to certain diameter pipe? -Are there known sources of stray electrical currents in the area? -Do exposed pipe inspections indicate external corrosion?			✓
	External corrosion: coated and wrapped pipe	-Does coated and wrapped steel exist in the system? -Is the pipe cathodically protected? -Have corrosion leaks occurred? -Are there known sources of stray electrical currents in the area? -Are cathodic protection readings consistently adequate during annual monitoring? -Do exposed pipe inspections indicate external corrosion? -Do exposed pipe inspections indicate coating deterioration?			✓
	Other metallic materials	-Do other metallic materials exist in the system? -Is the pipe cathodically protected? -Have corrosion leaks occurred?			√
	Internal corrosion	-Does metallic pipe exist in the system? -Does piping inspection indicate internal corrosion?			✓

		Threat Identification - Table 3.1			
			Ext	ent of Thr	eat
Primary	Threat	Questions to Check Subcategory	General	Local	N/A
Threat	Subcategories	Applicability to System			
		-Have internal corrosion leaks			
		occurred?			
		-Have liquids been found in your	1	İ	
		system?			
Natural Forces	Outside	-Do portions of the system lie in areas			
	force/weather:	of know land subsidence, landslides,			1
	steel pipe	earthquake fault zones, or washouts?			
	Outside	-Has outside force caused plastic pipe to fail?			
	force/weather:	-Do portions of the system lie in areas of known	[✓
		land subsidence, landslides, earthquake fault zones, or washouts?			
	Outside	-Are there leaks due to ground	+		
	force/weather:	movement, frost heave, or earth			1
	cast iron pipe	subsidence?	i i		
Excavation	Operator (or its	-Are damages being caused by crews			
Damage	contractor)	not following One-Call laws?			
Daniago	contractor)	-Have damages from mis-located lines			
		or poorly performing locators been			1
		experienced?			•
		-Are facilities marked out, and marked			
		out accurately?			
		-Are damages being caused failure to		ļ	
	i	protect pipe during backfill operations?			
	Third-party	-Has an increase in construction activity			
	Tilliu-party	been experienced?			
	i	-Is there a One-Call system covering			1
]	the system?			•
		Are damages being caused from mis-			
		located lines or poorly performing			
		locators?			
		-Are damages being caused failure to	ŀ		1
		protect pipe during backfill operations?			•
		-Have leaks been experienced on the			
	l	system where previous damage has	i		
		occurred?			
		-Are there known areas of blasting or			
		demolition activities?			
		-Have leaks occurred due to blasting?			
		-Do portions of the system exist in			
		areas where excavation in the area of			
		the pipeline would require the use of			
		explosives?			
Other Outside	Vehicular	-Are above ground facilities being hit			
Force Damage	* official	by vehicles?			
oree Dailiage		-Are aboveground facilities located near			
		a roadway, driveway, or other location			1
		where there may be susceptible to			*
		vehicular damage?			
		-Are susceptible aboveground facilities			
		protected from vehicular damage?			

		Threat Identification – Table 3.1			
			Ext	ent of Thr	eat
Primary Threat	Threat Subcategories	Questions to Check Subcategory Applicability to System	General	Local	N/A
	Vandalism	-Has damage or leakage been caused by malicious actions of unauthorized individuals? -Has gas theft occurred?			4
Weld Failure defects	Manufacturing defects	-Have manufacturing defects in pipe or non-pipe components been experienced?			✓
	Mechanical damage	-Have failures due to mechanical damage been experienced, such as underground structures in contact with facilities?			✓
	Materials/Plastic	-Do any of the following materials exist in the system? Century Utility Products Low-ductile inner wall Aldyl a pipe manufactured by Dupont Company before 1973? PE 3306?			V
Equipment Malfunction	System Equipment	-Have failures been experienced due to leaking seals or gaskets? -Have regulator or control malfunctions been experienced?			✓
Inappropriate Operation	Inadequate procedures	-Have failures been experienced due to inadequate procedures?			✓
	Inadequate safety practices	-Have failures been experienced due to inadequate safety practices?			✓
Con	Construction/ workmanship defects	-Have failures been experienced due to workmanship defects?			✓
	Failure to follow procedures	-Have failures been experienced due to a failure to follow procedures?			✓
Other		-Have failures been experienced due to other reasons?			✓

4. Evaluate and Rank Risk (§192.1007(c))

a. General

Various factors will be considered when evaluating and prioritizing risk. Listed below are some of these factors.

- 1. Determining if more measures should be taken or modified to prevent and reduce risks.
- 2. Developing a method for evaluating and ranking risks.
- 3. Grouping facilities that have similar rankings of risks and threats.
- 4. Considering a facility's specific operating requirements and characteristics when evaluating risks.
- 5. Develop a strategy for compensating for unavailable information, if it exists.

b. Information Evaluation

Information about facilities and pipelines of the Ohio Rural Natural Gas system can be collected during the course of all other routine operations and activities. Technicians and operators are instructed to be "investigative" when determining the causes of issues such as low cathodic reads, leaks, etc. A greater attention to detail allows us to determine how a particular threat may or may not apply to distribution systems or segments.

Information evaluation can be completed using a stand-alone approach or can be more complex using several stand alone approaches to complete the evaluation. Examples of stand-alone approaches include:

- 1. SME review of information.
- 2. Conducting periodic inter-departmental meetings.
- Conducting periodic SME meetings.
- 4. Assigning a centralized group to review all information.
- 5. Using an electronic database.
- 6. Using a software program that evaluates risk.

Method for Risk Evaluation

As the ORNG system is extremely small and not complex in its current state, we will utilize an SME method to evaluate risks of the distribution system. Subject matter experts are to:

- 1. Identify historical problems within the system and relate them to the eight threat categories. Subcategories may be used to provide more detail to the system's threats.
- 2. Demonstrate a thorough understanding of the system and its operations.
- 3. Evaluate and rank risks based on the threats and consequences they have on ORNG facilities.
- 4. Correctly address risks when they are evaluated.
- 5. Establish performance measures for risk management activities and monitor them accordingly.
- 6. Evaluate and adjust program activities.
- 7. Report and document information as required.

e. Risk Evaluation

A simple formula will be used to evaluate and prioritize risks on the distribution facilities. This formula allows ORNG to determine the most critical risks. It is the product of likelihood of a threat occurring multiplied by its consequence.

Risk = Likelihood x Consequence

Grouping of Facilities

Facilities within the system that have common attributes will be grouped together to allow us to more easily identify the extent of our risks; and to follow trends that may occur among similar systems. These shared traits consist of the following:

- Class location/population of area
- Operating pressure of facilities
- Size of the pipeline

The traits above play a role in determining the Consequence Factor of a leak should one occur.

Determining Threats

Based on historical data and the judgement of our SME's, each of the identified threats is ranked with a number from 1 to 10 to indicate the likelihood of the threat occurring. This number is called the likelihood factor and is based on threat identification, with 1 representing the lowest threat occurrence and 10 being the greatest. This number is determined based on analysis performed in Section 3 – Identify Threats, which begins on Page 15 of this document.

The table below demonstrates the likelihood factors of threats occurring on the QRNG system. As can be seen, excavation damage (4) and inappropriate operation (3) have been determined to the most likely occurring threats on the system.

Table 4.1 Thi	reats
Threat	Likelihood Factor
Corrosion	1
Natural Forces (frost, landslides)	1
Excavation Damage	4
Other Outside Force damage	1
Material or weld failure	1
Equipment Malfunction	1
Inappropriate Operation	3
Other	1

Determine Consequence Factor

The consequence of a system failure or hazardous leak can be given a value based on a number of variables. Characteristics of a pipeline and surrounding populations are important factors in determining the severity of a leak, should one occur. To calculate a consequence factor, features of a facility and its surroundings are grouped into three categories: Population, Operating Pressure, and Size. The higher the number, the greater the consequence that could result from a hazardous leak or condition. These three numbers are then added together to create a single number known as the Consequence Factor. A summary of Consequence Factors appears on the table below (4.2). It should be noted that not all of these factors are present on the ORNG system, but the table shows that these values have already been determined should the factors be created in the system.

Table 4.2 Consequence Factors				
Description	Consequence Factor			
Population/Location				
Rural (Class 1 or 2)	3			
Suburban (Class location 3)	6			
Urban (Class location 4)	8			
Sensitive facility in Class location 3 or 4	10			
Isolated sensitive facility	7			
Concentrated population (e.g. business district)	7			
Facility near buildings (e.g. service line, meter set)	6			
Facility away from buildings (e.g. street main)	4			
Operating Pressure				
< 60 psig	2			
> 60 psig	4			
Nominal Size				
2"	2			
4"	4			
Larger than 4"	6			

As of this current revision (1.0) of the plan, the ORNG system contains only one Consequence Factor of 9

Rural Location (3) + <60 psig (2) + 4" pipe (4) = (9)

Determine Relative Risk

Relative Risk is the result of a formula that multiplies likelihood of an occurring threat by the consequence factor of a given facility's location and features. The table below (4.3) depicts the Relative Risk Calculation for the entire ORNG distribution system.

Table 4.3 – Relative Ris	k Calculatio	an .			
Threat	Likelihoo d	Consequence			Relative Risk
		Pop.	Pressure	Size	
Corrosion	1	3	2	4	9
Excavation Damage	4	3	2	4	36
Natural Forces	1	3	2	4	9
Other Outside Force	1	3	2	4	9
Material or weld failure	1	3	2	4	9
Equipment Malfunction	1	3	2	4	9
Operation	3	3	2	4	27
Other	1	3	2	4	9

This calculation is to be completed for every existing threat and for each unique consequence group. As of this version (1.0) of the plan, there only exists one consequence grouping within the ORNG system. The results of the above Relative Risks will allow us to identify the system's most urgent problems and to develop further means of addressing them in a structured manner.

f. Validation

In order to validate the results of our risk rankings, we will determine:

- 1. Whether or not the company's records of maintenance and operations reflect the same emphasis on higher risk ranked facilities
- 2. Whether the company's SME's agree with the ranking of the risks

If there is not a consistency among either of the above two referencing methods, we will review and seek to revise the criteria used in this plan for gathering knowledge. An inconsistency does not necessarily indicate a flawed process, but can simply mean that there is a correlation or difference that is not understood. Further investigation would then be conducted to remedy the inconsistency.

5. Identify and Implement Measures to Address Risks (§192.1007(d))

a. Techniques

Once risks have been identified, evaluated, and ranked, the goal is to eliminate the risk, reduce the likelihood of threats, and/or to reduce the consequences of all system issues. The following procedures will be performed in order to address risks to the ORNG distribution system:

- 1. Prevention
- 2. Remediation
- 3. Mitigation
- 4. Additional or Accelerated (A/A) Actions

Methods used to address risks will vary depending on specific attributes, locations, and threats to a facility. These actions can address either the likelihood of a threat occurring, the resulting consequences of a risk, or both. The priority and intensity of the actions taken is determined by the relative risk ranking. Table 5.1 below provides examples of actions which will be taken to address specific threats.

	Table 5.1 – A/A, Prevention, R	emediation, Mitigation
	Threats	Possible Actions
Primary	Subcategory	1 ossible Actions
Corrosion	External corrosion:	-Increase frequency of leak surveys.
	Bare steel pipe (CP)	-Replace, insert or rehab.
	 Bare steel pipe (No CP) 	-Provide hot spot protection (e.g., install
	 Wrapped steel pipe (CP) 	anodes at anodic locations).
	Wrapped steel pipe (No CP)	-Correct cathodic protection deficiencies.
	CI pipe (Graphitization)	
	Internal corrosion	-Increase frequency of leak surveys.
		-Install drips.
		-Install pipe liner.
		-Install moisture removal or control
		equipment.
		-Evaluate gas supply inputs and take
		corrective action with supplier.
	Atmospheric corrosion	-Coat (paint) the exposed pipe.
		-Increase survey frequency.
		-Replace or rehab.
		-Relocate.
Natural	Outside force/weather:	-Relocate pipe from high risk locations.
Forces	(e.g., earth movement, lighting, heavy	-Replace pipe in high risk locations
	rains/floods, temperature extremes,	-Install slip or expansion joints for earth
	high winds)	movement.
	Steel pipe	-Install strain gages on pipe.
	Plastic pipe	-Install automatic shut-offs.
	Cast iron pipe	-Expand the use of excess flow valves.
		-Conduct leak survey after significant
379		earthquake or other event.
Excavation	Third-party damage	-Conduct enhanced awareness education.
Damage	Operator damage	-Request regulatory intervention.

	Table 5.1 – A/A, Prevention, I	Remediation, Mitigation
Primary	Threats Subcategory	Possible Actions
		-Inspect targeted excavation and backfill activitiesInspect for facility supportImprove accuracy of line locatingParticipate in pre-construction meetings with project engineers and contractors in high risk areasUse warning tapeExpand the use of excess flow valvesImprove system map accuracy and availabilityRecruit support of public safety officials (e.g., fire departments)Install additional line markers.
Other Outside Force Damage	Fire/explosion (primary)	-Provide first responder trainingInstall curb valvesImprove response capabilityExpand the use of excess flow valves.
	Vehicular	-Expand policy on when and how to install protectionIncrease frequency of patrols/inspections of high risk facilitiesExpand the use of excess flow valves.
	Leakage (previous damage)	-Inspect exposed pipe prior to backfillIncrease frequency of leak surveys.
	Vandalism	-Install or improve fences/enclosuresIncrease surveillanceRelocate hard-to-protect or critical facilities.
	Blasting	-Perform leak survey after blastingRelocate away from frequent blast areas (e.g., mines) -Replace with more ductile pipe material.
Material or Weld Failure	 Manufacturing defects Construction/workmanship defects Mechanical damage: Steel pipe Plastic pipe Pipe components 	-Increase frequency of leak surveysReplace or repairRevise construction proceduresRevise material standardsTrend material failures.

	Table 5.1 – A/A, Prevention, R	Remediation, Mitigation
	Threats	D!LL A-4!
Primary	Subcategory	Possible Actions
Equipment Malfunction	Malfunction of system equipment	-Replace or repairIncrease frequency of inspection/monitoringInvestigate if a type of joint or equipment is being used in inappropriate situations/locationsImprove installation procedureTrend equipment failure.
Inappropriate Operation	 Inadequate procedures Inadequate safety practices Failure to follow procedures 	-Improve proceduresImprove trainingEvaluate locations where inadequate practices may have been usedPerform internal audits or inspections.
Other		-Increase frequency of leakage surveyIncrease odorant levelIncrease frequency of odorant testingImprove choices of odorant testing locations.

b. Leak Management Program

Ohio Rural Natural Gas's policy regarding leaks is to immediately repair all leaks when found. But in the event that it is not possible to do so, and because leak management should be a high priority concern for any distribution system, a Leak Management Program is in place as part of the DIMP. Company policies, and guidelines set forth by state, federal, and industry standards form the basis of the leak management program.

The basic elements of a leak management program include:

Locate the leaks in the distribution system;

Evaluate the actual or potential hazards associated with these leaks;

Act appropriately to mitigate these hazards;

Keep records; and

Self-assess to determine if additional actions are necessary to keep people and property safe.

1. Locate the leaks. Company personnel will be qualified to perform leak surveys, respond to odor complaint calls, and other relevant duties. They will use industry-approved equipment and techniques, while following ORNG policies to perform these tasks.

- 2. Evaluate the severity of leaks. Leaks will be evaluated according to industry-approved guidelines and/or additional specific State standards based on the potential hazard of the leak. This program defines the criteria for leak classification;
 - Grade 1 Leak
 - A leak that represents an existing or probable hazard to persons or property, and requires immediate repair or continuous monitoring until the conditions are no longer hazardous.
 - Grade 2 Leak
 - A leak that is non-hazardous at the time of detection, but justifies scheduled inspection and repair based on probable future hazard.
 - Grade 3 Leak
 - A leak that is non-hazardous at the time of detection and can reasonably be expected to remain non-hazardous.

Re-inspections of Grade 2 and Grade 3 leaks shall be conducted according to ORNG's existing procedures.

Above Ground Leaks

The categorizations above allow us to determine occurrences of reportable hazardous leaks. Leaks on outside piping facilities can be detected with sight, sound, smell, or touch. In such a case, immediate evacuation would be necessary to protect the public.

Small leaks at the threads or fittings of sound piping may only be detectible with sensitive instruments or barely visible indications with leak detection soap. In such a case, the leak may be repaired immediately through minor adjustments of facilities or tightening of fittings. Such an instance would not be considered a reportable leak.

- 3. Act accordingly to mitigate the possible hazards associated with every leak. Once leaks are graded, follow company policies relevant to the grade.
- 4. Document and file all maintenance and inspection activities. All documentation should allow us to evaluate the efficiency of the leak management program.
- 5. The program will be periodically assessed to measure the effectiveness and determine if adjustments are necessary, and the type of adjustments to be made.

Below is some of the criteria used to evaluate the leak management program:

- Ensure that leak surveys are completed on time, per §192.723
- Verify that leak repairs and reevaluations are completed on time.
- Make sure that all leaks are repaired and cleared.
- Evaluate odor complaints to determine if there are any trends.
- Make certain that responses to odor complaints were timely.

- Review all actions which were taken to mitigate leaks.
- Attempt to recognize any trends in leak grading.
- Determine if there have been any incidents according to Federal or state definitions.
- Determine if there are any improvements to be made that could improve the program.

c. Primary Threats

Based on the risk calculation of Table 4.3 above, excavation damage and inappropriate operation have been noted as the two highest risks to the integrity of the Ohio Rural Natural Gas distribution system. While these two risks are still ranked low overall, they are the greatest perceived risks in relation to all other risks. Below is an overview of these higher ranking threats and the means by which ORNG will address them.

1. Excavation Damage

Excavation damage has received the highest risk ranking to the ORNG system. This is based primarily on knowledge of Subject Matter Experts who are veterans of the natural gas industry. As operations have not yet began on this distribution system, SME's are aware of contemporary trends in the natural gas industry which have indicated that excavation damage is the most common cause of hazardous leaks in a plastic distribution system. The following will provide a further in-depth description of the actions taken to prevent, mitigate, and remedy the risks involved with the threat of excavation damage to the system. These techniques were outline in the above Table 5.1:

- ❖ A Public Awareness program to comply with federal requirements of §192.616, §192.615, §192.614; which includes
 - o Continuing educational actions to notify the public, government organizations, and excavators to recognize pipeline-related emergencies and to report them to the proper officials. This program is provided in English and any other language which may be spoken by a significant portion of the population where ORNG facilities are located.
 - Emergency responder liaison activities to establish and maintain a liaison with fire, police, and other appropriate public officials; and coordinate with them on preplanned and actual responses during an emergency.
 - o Damage prevention plan to prevent damage to pipelines by excavation activities.
- Educating new and possible service customers about the importance of using the 8-1-1 system, and of recognizing and being aware of the location and properties of underground piping near their facilities. This includes providing educational information along with company documents, bill stuffers, and verbal discussions with company staff.

- Installing excess flow valves on all service lines to curtail the effects of severed pipe.
- Placing properly labeled line marker test points at frequent intervals, such as every 500 feet.
- Utilize technology to provide system mapping as accurately as possible.
- Hold pre-construction meetings with engineers, excavators, and city officials; and maintain communications throughout the course of new projects.
- Meet with administrators of facilities within Class 3, Class 4, or other high-risk locations to educate them.
- Assure that all employees and contractors operating on behalf of ORNG are operator qualified in all procedures they perform, including excavation and backfilling.

2. Inappropriate Operation

With a likelihood factor of 3, and the second highest relative risk of 27 (Per Table 4.3 above), Inappropriate Operation is currently the second highest perceived threat to the system. This is due to the circumstances under which approximately 13,728' of 4" PE was installed. This pipe was installed by a third party contractor prior to the development of an O.Q. program, and O&M manual by ORNG.

To address this issue, ORNG will evaluate the qualifications of the contractor after the development of its O.Q. plan, and investigate the procedures which were used by the contractor to ensure they comply with the O&M manual. If the contractor is found to not be qualified per ORNG's O.Q. plan, or if the procedures used are inappropriate per the O&M manual, the 13,728 feet of pipe will be removed or abandoned.

If the procedures used by the contractor are approved by ORNG per O.Q. and O&M, the pipeline will remain part of the ORNG system and eventually be utilized for distribution. At that point, the pipeline will be subjected to an increased frequency of leak surveys (4 times per year NTE 3 ½ months) and line patrols (4 times per year NTE 3 ½ months).

3. The remaining low threats have resulted in extremely low risk factors. The actions listed on Table 4.3 above will be performed to mitigate, curtail, and prevent the likelihoods of the threats occurring. These measures along with proper training, knowledge assessment, and professional duties of daily operations are estimated to keep other likelihood factors low in the foreseeable future.

6. Measure Performance, Monitor Results and Evaluate Effectiveness (§192.1007(e))

General

ORNG must measure its performances in order to determine whether risk management activities are effective or not. Each method used in measuring the performance will vary depending on the risk management technique used. Measurements may be conducted for specific sections of the system, or can cover the entire system. Information is to be gathered on an annual basis, and compared to previous years in order to recognize trends, and whether the integrity management is improving, staying the same, or getting worse.

The list below contains performance items that must be measured according to §192.1007(e):

- 1. Number of hazardous leaks either eliminated or repaired, per $\S 192.703(c)$, categorized by cause;
- 2. Number of excavation damages;
- 3. Number of excavation tickets received by OUPS (local underground protection agency);
- Number of excess flow valves installed;
- 5. Total number of leaks either eliminated or repaired, categorized by cause;
- 6. Number of hazardous leaks either eliminated or repaired per $\S192.703(c)$, categorized by material; and
- 7. Any additional measures to evaluate the effectiveness of the program in controlling each identified threat.

b. Guidelines for Developing Performance Measures

The following guidelines will be considered when developing or selecting performance measures:

- 1. Performance measures will address the specific risk management practices of the DIMP
- 2. Performance measures will be able to be counted, tracked, monitored, supported, and recorded.
- 3. The number of critical measurements will be kept to an effective minimum. Too many measurements can decrease the measurement's effectiveness and prevent us from properly determining their effectiveness.
- 4. Measurements will be recorded numerically in order to provide quantifiable, objective, and easily-interpreted results.
- 5. Possible non-numeric data can still be utilized to analyze the effectiveness of the performance measures or program performance.

c. Performance Measures

Below are examples of performance measures that may be used based on the eight primary threats. This list is not all inclusive and different situations may require the addition or deletion of performance measures for consideration.

1. Corrosion

a. Leaks due to internal or external corrosion.

- b. Exposed pipe reports that found corrosion or coating damage.
- c. Repairs required due to non-leaking pitting or coating damage (above or below ground).
- d. Low cathodic protection reading levels.
- e. Areas of active corrosion found (unprotected pipe).

Natural Forces

- Leaks due to weather or other natural forces.
- b. Repair, replacement or relocation actions due to natural forces.

Excavation

- a. Excavation caused damage (first/second/third party).
- b. Normalized damages (damage ratio) defined as damages per 1000.
- c. Ratio of ticket no-show to total tickets received by the operator.
- d. Failure by notification center to accurately transmit tickets to the operator.
- e. Damages by cause, facility type (mains, services) and responsible party. Cause categories may include the following.
 - 1. Excavator's failure to call.
 - 2. Excavator's failure to provide accurate ticket information.
 - 3. Operator's failure to mark.
 - 4. Operator's failure to mark accurately.
 - 5. Excavator's failure to wait required time for marking.
 - 6. Excavator's failure to protect marks.
 - Excavator's failure to utilize precaution when excavating within the tolerance zone.
 - 8. Excavator's failure to properly and protect facility.
- f. Leaks or failures on previously damaged pipe.
- g. Repairs implemented as a result of first/second/third party damage prior to leak or failure.
- h. Excavation notices versus number of locates (not all will require actual locate)
- i. Locates timely or untimely made.
- j. Negative callbacks timely or untimely made if state law, the one-call center, or another entity requires such calls.
- k. Mis-locates later identified.

4. Other outside force damage

- a. Leaks or failures caused, or repairs necessitated, by vandalism.
- b. Leaks or failures caused, or repairs necessitated, by vehicular damage.
- c. Instances of damage that is secondary to non-pipeline fire or explosion.
- d. Leaks or failures on previously damaged pipe.
- e. Leaks, failures, damage, or movement caused by blasting.
- f. Leaks, failures, damage, or movement caused by heavy vehicle traffic over or near pipelines.

Material or welds

- a. Pipe failures during pressure tests.
- b. Joint failures during pressure tests.
- c. In-service pipe or joint failures (not caused by outside forces or excavation damage).
- d. Production joints rejected by an inspector other than the joiner.
- e. Joiners failing re-qualification.

6. Equipment

- a. Regulator failures.
- b. Relief valve failures.
- c. Seal, gasket or o-ring failure.
- d. Regulators or relief valves found with set points outside of acceptable range.
- e. Emergency valves found inoperable.
- f. SCADA failures, system upsets, or false readings.

7. Operations

- a. Service outages due to operator error.
- b. Odor tests finding insufficient odorant.
- c. Response times to leak or odor calls.
- d. Hazardous leaks made safe or repair times.
- 8. Other case by case determination

d. Monitor Results

The performance measures above will be monitored on an annual basis to determine if issues are remaining the same, increasing, or decreasing in frequency. This information will then be evaluated to determine the effectiveness of the DIMP. As 2015 is the first year of operations, there are no historical records to access in order to determine trends. 2015 will be the first year in which performance measures can be recorded. The table below shows how information will be gathered and recorded from year to year.

	Table 6.1 – Monitor 1	Results				
Primary Threat	Performance Measure	2015	2016	2017	2018	2019
Corrosion	Leaks due to internal or external corrosion					
	Exposed pipe reports that found corrosion or coating damage					
	Repairs required due to non-leaking pitted or coating damage					
	Low cathodic protection reading levels					
	Areas of active corrosion found					
Natural Forces	Leak due to weather or other natural forces					
	Repair, replacement or relocation actions due to natural forces					
Excavation	Excavation caused damage					
	Normalized damages defined as damages per 1000					
	Ratio of ticket no-show to total tickets received					
	Failure by notification center to accurately transmit tickets to the operator					
	Damages by cause, facility type and responsible party. Cause categories may include the following.					
	Excavators failure to call				7	
	 Excavators failure to provide accurate ticket information 					
	Operators failure to mark					
	Operators failure to mark accurately					
	Excavators failure to wait required time for marking			_		_
	Excavators failure to protect marks					
	Excavators failure to utilize precaution when excavating within the tolerance zone					
	Excavators failure to properly protect facility					

	Table 6.1 – Monitor 1	Results				
Primary Threat	Performance Measure	2015	2016	2017	2018	2019
	Leaks or failures on previously damaged pipe				··	
	Repairs implemented as a result of first/second/third party damage prior to leak or failure					
	Excavation notices versus number of locates complete					
	Locates timely complete					
	Locates untimely made					
	Mis-locates later identified					
Other Outside	Leaks or failures caused, or repairs necessitated by vandalism					
Force Damage	Leaks or failures caused, or repairs necessitated by vehicular damage					
	Instances of damage that is secondary to non-pipeline fire or explosion					
	Leaks or failures on previously damaged pipe					
	Leaks, failures, damage, or movement caused by blasting					
	Leaks, failures, damage, or movement caused by heavy vehicle traffic over or near pipelines					
Material or	Pipe failures during pressure tests					
Welds	Joint failures during pressure tests					
	In-service pipe or joint failures					
	Production joints rejected by an inspector other than the joiner					_
	Joiner failing re-qualification					
Equipment	Regulator failures					
	Relief valve failures					
	Seal, gasket or o-ring failure					
	Regulators or relief valves found with set points outside of acceptable range					
	Emergency valves found inoperable					
	SCADA failures, system upsets, or false readings					
Operations	Service outages due to operator failure					
	Odor tests finding insufficient odorant					
	Response times to leak or odor calls unacceptable					
	Hazardous leaks made safe repair times unacceptable					
Other	Case by case determination - if necessary					

e. Evaluate Effectiveness

DIMP effectiveness will be evaluated every 5 years. The results of the performance measures will be monitored to determine if the program is adequate, and what adjustments to the program are necessary.

The actual DIMP will be reviewed, and updated annually if necessary. The plan may require more frequent reviews if specific changes or circumstances require it.

7. Periodic Evaluation and Improvement (§192.1007(f))

An evaluation of the DIMP will be conducted annually, or more frequently should special circumstances require it. The review will ensure that all processes in the program are functioning and interacting properly. The accuracy and relevance of data will be looked at, and the overall effectiveness of the plan will be studied. All sections of the plan will be cross-referenced with system knowledge. The program itself will be reviewed, along with its effectiveness.

a. Review of Written Program

- 1. The written plan will be reviewed annually. Accurate and up-to-date information will be verified, and added. Any possible improvements will be considered.
- 2. All personnel not attending the review are to be notified by supervisors or attendees of the results of the review, and any changes to the plan.
- 2. In addition to the annual review, reviews at other points will be considered, such as special circumstances or major changes to the system such as pipe replacement, abandonment, or changes in MAOP.
- 3. If the program's performance measures require a change to be made to the plan, the changes will be implemented.
- 4. A log will be kept to document reviews, evaluations, and updates of the DIMP. The end of this section contains the review of previous years.
- 5. Pertinent regulatory agencies will be notified of major changes or updates to the plan via email or telephone contact, and a copy will be provided to them. Such changes could result either from routine annual reviews or required by special circumstances.

b. Review of Effectiveness

- 1. The use of performance measures' effectiveness will be reviewed on a timely basis. This will determine the effectiveness of risk management or accelerated actions taken.
- 2. During the review, we will analyze the information which was initially gathered to form the basis of the plan. This is information which was utilized to support the performance measures used for risk management. The veracity of the data collected, the method in which the data was collected, and the interpretation of the data collected will all be reviewed.
- 3. This review will be an opportunity to look at our performance measures and confirm whether or not they are adequate in providing sufficient information. Changes to which measures are performed and how they are performed may be made.
- 4. When evaluating the effectiveness of performance measures, it is important to recognize patterns, trends, and changes in the results of the implementation of the plan. Therefore it may take several years to properly assess and evaluate performance measure data. All performance measures will be reviewed at intervals not to exceed 5 years.

<u>DISTRIBUTION INTEGRITY MANAGEMENT PROGRAM REVIEW, UPDATE AND TRAINING LOG</u>

Review, update and training conducted by:	Date	Comments, changes, or issues
	·	
	<u> </u>	
	·	
	<u> </u>	

8. Report Results (§192.1007(g))

a. General

Information that is required to be gathered for State and Federal annual reports will be gathered as efficiently and accurately as possible.

The information below is required to be reported to state and federal regulatory agencies annually, and is also required to be reported as per the DIMP. The form to be used for tracking the information in DIMP is located in the Forms section. The form used to report the information to state and federal authorities is the RSPA 7100 report, which is due annually by March 15th of the following reporting year. It is submitted to state agencies via email, traditional mail, or fax. The form is submitted to federal agencies via the official website.

- Total Leaks Eliminated/Repaired by Cause
- 2. Number of Excavation Damages
- 3. Number of Locate Tickets
- 4. Number of EFVs Installed to Date
- 5. Mechanical Fitting Failures Resulting in a Hazardous Leak
- 6. Total Number of Leaks on Federal Land Repaired or Scheduled for Repair
- b. What must an operator report when mechanical fittings fail? (§192.1009)

Mechanical fitting failures will be recorded and reported annually to PHMSA per $\S191.12$. Section 9 contains the form utilized by Ohio Rural Natural Gas to record failures in mechanical fittings.

c. What records must an operator keep? (§192.1011)

Previous editions of the DIMP will be maintained for at least 10 years. They will be readily available in their entirety for viewing in either electronic or hard copy format.

9. Forms

Attached to the original, hard copy of this section are company documents and reports used to record information pertaining to the implementation of the DIMP, as well as that information required by State and Federal agencies.

Reporting Results

Reported Results (As provided on DOT annual 7100 Report	t)	Year						
	2015	2016	2017	2018	2019			
Total Leaks Eliminated								
Excavation								
Corrosion								
Outside Forces								
Inappropriate Operations								
Natural Forces								
Material or Weld Failure								
Equip Malfunction								
Other								
Total Locate Tickets								
Number of EFV's Installed		-						
Mechanical Fitting Failures Causing Leaks								
# of Leaks on Federal land repaired or to be repaired								

OHIO RURAL NATURAL GAS ABANDON/REPLACE/RELOCATE FACILTIES REPORT (§192.727)

System Name:	System No:	Taxing	District:	
adoned Pipeline				
Location:	W.C	O.# When In	stalled (If Kno	wn)
Footage: Size:	-	Type:	☐ Plastic	☐ Steel
Was Line Purged: ☐ yes ☐ no				
If yes, what was the line purged with: Air	☐ Nitrogen	Other_		
Were ends sealed: ☐ yes ☐ no				
Were any service lines abandoned with main:	□ yes □ r	10		
If yes, list C.A.N. or address of service lines abando	oned:			
1	2			
3				
5	6			
Was any pipe removed: ☐ yes ☐ no	If yes, Footage:		Size:	
Abandoned Service Line				
C.A.N. or Address:				
Footage: Size:		Type:	☐ Plastic	☐ Steel
v. re ends sealed:	any pipe removed:	□ yes	□ no	
Stations				
☐ Relocated ☐ Removed Old Station N	Vame	New Sta	ation Name	
Old System N	Number	New Sy	stem Number	
REPLACEMENTS Remove Key	Valve#	Remove	e Cathodic TP#	
Replacement Pipeline				
Location:			W.O.#	
Footage: Size:		Type:	☐ Plastic	□ Steel
Replacement Service Line				
C.A.N. or Address (If same as abandoned service-lea	ave blank):			
Footage: Size:		Type:	□ Plastic	□ Steel
Comments:				
I certify that the above pipe was abandoned in accord	dance with O&M Plan	Section 1.7	7.	
contrary man me above hipe was abandoned in accord				

F30 R3

OHIO RURAL NATURAL GAS GAS LEAK AND REPAIR REPORT

Receipt of Report			Report No:
? Report of Leakage N	o:		
2) Other (describe):			
Leak Data System N	ame:	System 1	No:
			ated By:
Location of the leak (incl	ude sketch with dimensions):	Before Sketch
	rmation concerning this leak		
	ended by GPTC Guide Ap		
('e 2 Requires re	ere) Requires prompt, conting e-evaluation every 6 months, re) Requires re-evaluation e	repair by 15 months.	
GMI/CGI Readings (Co	nvert all reads to %Gas U	EL) : (please indicate read	ing locations on sketch)
Highest %Gas Reading Le	evel :		
Direction #1 :Ft.		Direction#3:Ft.	ding Location on GRADE 2 & 3 LEAKS Direction#4:Ft.
Date:Highest Level:	Date: Highest Level:	Date:Highest Level:	Date:Highest Level:
Direction1:Direction2:	Direction1:Direction2:	Direction1:Direction2:	Direction1:Direction2:
Direction3:Direction4:	Direction3:Direction4:	Direction3:Direction4:	Direction3:Direction4:
Grade: 1 2 3 By:	Grade: 1 2 3 By:	Grade: 1 2 3 By:	Grade: 1 2 3 By:
Direction1: Direction2: Direction4:	Direction1:Direction2:Direction4:	Direction1:Direction2:Direction4:	Date:Highest Level: Direction1:Direction2: Direction3:Direction4: Grade: 1 2 3 By:
-	, <u> </u>		

GAS LEAK AND REPAIR REPORT - Page 2

	☐ Other Utility ☐ Vehicle A☐ Material or Welds ☐ Con				
aging Party					
1		Company Name:			
	ny:				
	· 		0		
			ess Card Attached? yes		
Vehicle/Equipmen	nt Make:	Model:	License:	Color:	
Accident Report #	•				
Working for: St	tate 🛘 County 🖛 City 🗘 To	ownship 🛭 Public U	tility 🗆 Self		
☐ Other Cor	ntractor (Name)		Other (Name)		
	Additional Information				
Was OUPS (811) o	contacted prior to work star	rting? □ yes □ no T	icket #:		
Proposed excavation	on marked in white on arriv	val? □ ves □ no. Acc	curately according to OH	PS Ticket? □ ves □	nο
Damaged Facilitie Public Right of V	es Information Vay Private Right of Wa	y □ Under Road □ C	Other		
Pipe Size:	Pipe Pressure:	Size of Hole:_	Duration of	Gas Loss:	
TransmissionDistribution (MService Line	Pipe Type ☐ Steel (☐ Fusion B [ain) ☐ Cast Iron ☐ Plastic (MFG: ☐ Other	Тур	e:SDR:_	<u> </u>	
Internal Inspection s the inside of the p	(if accessible) pipe accessible: Smooth Pitted	_	Ť	no	
rnal Inspection					
ipe condition:	Smooth Pitted	Depth of Pits			
Coating Type (if co	ated):	Condition: \Box	good 🛛 fair	poor	

GAS LEAK AND REPAIR REPORT - Page 3

Repair Information

Describe repair in detail:	
<u></u>	
· · · · · · · · · · · · · · · · · · ·	
Backfill condition: ☐ good ☐ fair ☐ poor	Repair Sketch Following DIMP Requirements
Is this pipe under cathodic protection: yes yes	no
New anodes installed: ☐ yes ☐ no	
How many Size	
DIMP Requirements	
Information gathered from existing facilities ☐ y	ves □ no
Information gathered from new facilities [] yes	□ no
Repair Sketch area showing DIMP yes no	
Repaired material GPS'ed [] yes [] no	
aired by:	
Date:	
Test Data	
Retested: Test pressure:	Duration:
Replaced: Test pressure:	Duration:
Pretested (for mainline only - services must be	e replaced or retested): Pretested pipe number
Company performing test:	
inspected/approved by:	Date:
Follow-Up Leak Survey (required within 10 days	on grade 1 leak repairs except for dig-ins)
Performed by:	Date:
	no Copy given to Inventory Department [] yes [] no

PAGE 3 OF 3

Ohio Rural Natural Gas

GAS LEAK AND REPAIR REPORT

Service Line ONLY

eipt of Report	SL Report No:
1) Report Of Leakage No:	
Leak Report Date: / / Time Reported: Time M	
Leak Reported By: Contact Info:	
Leak Data System Name:	
Did excavator call <u>911</u> ? Were other appropriate authorities at the	
Location of the leak (include sketch with dimensions):	Leak Location SKETCH
If leakage was from a dig-in, was OUPS previously contacted: yes	□ no
Describe in detail all information concerning this leak:	
Leak Grade (as recommended by GPTC Guide Appendix G-192-11)	
Grade 1 (most severe) Requires prompt, continuous action.	
Grade 2 Requires re-evaluation every 6 months, repair by 15 m	
Grade 3 (least severe) Requires re-evaluation every 15 months	
GMI/CGI Readings (Convert all reads to %Gas UEL): (please indic	ate reading locations on sketch)
Highest %Gas Reading Level :	
Document ZERO READING DISTANCES: N/S/E/W (4 Directions) from	
Direction #1:Ft. Direction#2:Ft. Direction#3:	Ft. Direction#4:Ft.
Leak Re-Evaluations (Convert all reads to % gas UEL)	
Date: Highest Level: Date: Highest Level: Date:	Highest Level: Date: Highest
Level:	
Directions (D) D1: D2: D1: D2: D1:	D2: D1: D2:
D3:D4: D3: D4: D3:	D4:D4:
Grade: 1 2 3 By: Grade: 1 2 3 By: Gr	ade: 1 2 3 By: Grade: 1 2 3
☐ Corrosion ☐ Natural Forces ☐ Exca	vation Other outside force damage
☐ Material or Welds ☐ Equipment ☐ Oper	

☐ Steel (☐ Fusion Bonded Epoxy ☐ Extruded Polyet ☐ Cast Iron	the pipe able to be located □ yes □ no thylene □ Tar & Wrap □ Bare SDR:MFG DATE:)
Other	
Internal Inspection (steel pipe only) Is the inside of the pipe accessible: □ yes □	no Any Fluid: □ yes □ no
Internal Condition (if accesssible):	Pitted Depth of Pits
External Inspection (steel pipe only)	
Is this pipe under cathodic protection: yes	□ no
Pipe condition:	Depth of Pits
Coating condition (if coated): good fair	□ poor
Backfill condition:	
New anodes installed: ☐ yes ☐ no	How many Size
Location:	
☐ Repaired Serv	rice Replaced Service
Performed by:	Date:
Describe Repair in detail:	
- ,	
i -	
Test Data	
Tested: Test pressure: Duration:	Sketch Old & New Facilities in the space
provided here.	
Company performing test:	
measurements Increased/approved by the second of the seco	Old & New Facility SKETCH Date:
Inspected/approved by:Replacement Service Line Info	Date.
Main to curb footage: Curb to meter footage:	
Pipe Size: Manufacturer: Riser Size: Manufacturer:	
Number and Type of fittings:	
Tracer wire footage:	
Abandoned Service Line Info	
Footage: Size: Type: Plastic Stee	.1
e ends sealed: Yes No	
Was any pipe removed: ☐ Yes ☐ No	
PAGE 2	2 OF 2
IAGE 2	- V

OHIO RURAL NATURAL GAS INVESTIGATION OF FAILURE (§192.617)

			Report No:	_
Description of Failure:				
Failure Occurred During:	☐ Installation ☐	Uprating	Testing	
	☐ Normal Operations	Other		
Operating Pressure at Time	of Failure:	Pressure	Rating of Failed Component:	-
Reported By:		Da	ate Of Failure:	-
Cause of Failure:				
ý.				
Required Changes:				
Comments:				_
nvestigated By:			Date:	

OHIO RURAL NATURAL GAS LEAK SURVEY REPORT (§192.723)

F em Name:					
Area Covered: From:					
To:					<u> </u>
Is This Gas Odorized? (192.625):	□ Yes	□ No			
Class Location:	□ 2	□ 3	□ 4		
Survey Interval Required: An	nual NTE 15 n	no 🛘 3 Year	□ 5 Year □	Tim	es Per Year
Type Of Detection Used: ☐ Flame	Ionization 🗆 C	GI/Barhole 🗆 V	egetation Surve	ey 🛘 Other	
Were Any Leaks Discovered?:	Yes□ No				
					
					Gas Leak & Repair
	Location			Grade	Report Number
				,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
Method used:	Walking [Other:			
Was there any construction along or	near the pipelin	ne system?:	yes 🗆	no	
Vere there any of the following unu	usual conditions	found during th	e survey?:		
None Found	☐ Railroad ☐ F	Highway 🛭 Fore	ign Pipeline 🗆	Buildings Ot	ther:
Vere there any conditions found that	at could affect th	ne present or futi	are safety of this	system?: 🛘 y	es 🗆 no
Are there missing line markers in th	is system?:	g yes	no		
f yes to any of the questions above,	to whom was it	reported:			
Additional Comments:					
` `ormed Bv:			Date:		

OHIO RURAL NATURAL GAS LINE PATROL REPORT (§192.721)

tem Name:		Sy	rstem No:
Area covered:			
System type:	☐ Distribution	☐ Transmission	
Class location:		2	
Patrol frequency:	☐ 4 Times/yr	☐ 2 Times/yr ☐ Annual	
		☐ Other	
Method used to patr		□ Walk □ Other:	
	nd: 🛘 yes		
If yes, gas leak and	repair report no:		
		the pipeline system:	
If yes, give reference	e to nearest line marke	er or address:	
e there any unus	ual conditions found	at any of the following places:	
Lone Found		☐ Steams/Rivers	☐ Railroad
☐ Highway		☐ Foreign Pipeline	☐ Buildings
		present or future safety of this systen	n: 🛘 yes 🔻 no
		n the system?:	10
Comments:			
	<u> </u>		
D. rmad D.		_	
c nined By:		Date	*

OHIO RURAL NATURAL GAS ODOR COMPLAINT REPORT

Caller's Name:	Phone			
Location(or address)			S	ystem #
section #1: Odor Complaint (Do NOT use this section to d	ocument a leak call –	Use Section	#2 for leaka	ge)
) Is the smell inside or outside (circle one)?	5) Is there a cont	ractor wo	rking in tl	ne area? Y N
Can you smell the gas now? Y N	6) Additional Inf	io:		
) How long have you smelled gas?				
) Can you hear any gas? Y N				
If the caller indicates a very strong odor inside, advise them to \underline{l}				
ashlights, candles, matches, telephone, etc) and then vacate th				
rive ASAP. Is the caller following these instructions?				
ection #2: Pipeline or Station Leak Complaint		ection #3:		
Is the pipeline or station on fire? Y N		-		narp pungent odor? Y N
Is the pipeline or station blowing gas now? Y N	•	•		d/coal/kerosene? Y N
How bad is the gas blowing?		_		che/Dizzy/Nausea/None
Is the gas being freely vented? Y N	· ·			ning: How long?
How close is the nearest building?				How old?
Does the road(driveway, yard, etc.)need barricaded	· ·			consult a doctor? Y N
Was anyone injured? Y N	*	If caller ha	as any syr	nptoms, do step 5
Did you call OUPS? Y N Ticket Info:	6)	Addition	nal Info: _	
Was excavator instructed to promptly report damage	ge			
to 911? Y N (only if harmful or endangering life	e)			
0) Additional Info:				
eceived By:	Date: _	/	/	Time:
vestigated By:	Date: _	/	/	Time:
lade Safe By:	Date: _	/_		Time:
escribe actions taken (use back of form if needed)				

Use this box to grade any non-hazardous leaks on stations and meter sets. Document all other leaks on Gas Leak and Repair Form.

OHIO RURAL NATURAL GAS SYSTEM TURN-ON REPORT

'em Name:		System No:
County:		Township:
Jurisdictional Telephone Numbers		
		E
Fire Department:		Emergency:
Address:		Business No:
Law Enforcement:		Emergency:
Address:		Business No:
Turn-On Data		
Date of Turn-On:	_	By:
Odorant Level:		By:
	% Gas	Ву:
Comments:		

^{*}Attach maps or drawings of new facilities along with any other pertinent information
nments should include purging details (e.g. Pipe Size, Time of Purge, Location(s) of Purge, Total CF Purged)

OHIO RURAL NATURAL GAS PIPELINE INSPECTION REPORT

em Name:			System No:		
ocation or Area Uncovered (C					
			·		
ine Type Transmission Distribution Service Line Gathering Pipe Typ Cast Iro Plastic (Other	n	Extruded Poly	yethylene□ Tar	& Wrapped□ Bar	
nternal Inspection the inside of the pipe accessible ac	le):	Pitted D	epth of Pits		
xternal Inspection this pipe under cathodic prote condition: Smooth	ection: 🛘 yes 🔻 🗘	no			
oating condition (if coated):		_			
ackfill condition: ew anodes installed: ew Anode Location:	yes 🗓 no	How many _		Size	
hat other corrective measures	ts:				
omments:					
rformed By:					

Ohio Rural Natural Gas

Cathodic Protection Inspection Report (§192.465)

Inspection Frequency: Once every calendar year, NTE 15 months

en Name	System Number							
				i				
Test Point#	Test Point Location	is the test point properly labeled?	Veerl	(Previous Year) Reading	(Current Yr) Inspection Date	(Prev. Yr) Inspection Date	Remedial Action Required?	inspecte d By

Ohio Rural Natural Gas

Critical Valve Inspection Report (§192.747, §192.181)

Inspection Frequency: Once every calendar year, NTE 15 months

		System Number					
	•						
Valve#	Valve Description	Was Valve Accessible? Y/N	Was Valve Partially Operated? Y/N	Inspection Date	Prev. Inspection Date	Inspected By	
· · · · · · · · · · · · · · · · · · ·							
(

Comments:

System#:			-	1	IVICIC	eriui Lis	st-DIMP		Company	
	/ Ticket No.		-	ì		1		Odor/Gre	L&R Reference No.	
WE KO	, ITEREL HO.		4	1 1					Lack Rejerence No.	1
Project N	ame or Ad	iress		T			Dat	e	WO Number	
Charation I	Balan.			1		ļ				
Starting I			1						1	
/est Inter			-		The second of th	The state of the s	1 Th his free to do the service commence of		A commence of the confidence of	7-10-11
Soil Type		Fond		Clay	Book Charac		- Condestina	Total III	ilian proportion and accommodate	
Circle)		Sand	Loam	Clay	Rock Slurry	Main Line	e or Service Line (Circle)	(Circle)	thod Trench Bore	e Insert drawl From In
Station	C/L	Item	Pipe	<u>P</u>	Manufacturer	Part#	Type/Size	Mfg Date	Lot Number	SDR
Start at 0+	00 Distance	Number	Pipe Footage							
		 	-			1		1	i	
						1				
			-							
	-		 				!			
			-			1		-	ļ	
	1									-
			-							
	-			+						
						1				
				_						
				-		1				
	1			- 1						
				_						
5			e and pi	pe only	1	could have a	unique Mfg Date and Lo ketches		4	its own en
ote: Foo 15 Project	Name	n is for wir	e and pi	pe only	1				ach item MUST have	0
5	Name			pe only	1			3 	WO Number	
5	Name	0		pe only	1			3 	4	0
5	Name	0		pe only	1			3 	WO Number	0
5	Name	0		pe only	1			3 	WO Number	0
5	Name	O N DETAIL SKETC		pe only	1			3 	WO Number	0
5	Name	O N DETAIL SKETC		pe only	1			3 	WO Number	0
5	Name	O N DETAIL SKETC		pe only	1			3 	WO Number	0
5	Name	O N DETAIL SKETC		pe only	1			3 	WO Number	0
5	Name	O N DETAIL SKETC		pe only	1			3 	WO Number	0
5	Name	O N DETAIL SKETC		pe only	1			3 	WO Number	0
5	Name	O N DETAIL SKETC		pe only	1			3 	WO Number	0
5	Name	O N DETAIL SKETC		pe only	1			3 	WO Number	0
5	Name	O N DETAIL SKETC		pe anly	1			3 	WO Number	0
5	Name	O N DETAIL SKETC		pe only	1			3 	WO Number	0
5	Name	O N DETAIL SKETC		pe only	1			3 	WO Number	0
5	Name	O N DETAIL SKETC	H	pe only	1			711	WO Number HINDETAIL SKETCH	0
5	Name	O N DETAIL SKETC	H	pe only	Com	pletion SI		711	WO Number	0
5	Name	O N DETAIL SKETC	H	pe anly	1	pletion SI		711	WO Number HINDETAIL SKETCH	0
5	Name	O N DETAIL SKETC	H	pe anly	Com	pletion SI		711	WO Number HINDETAIL SKETCH	0
5	Name	O N DETAIL SKETC	H	pe only	Com	pletion SI		711	WO Number HINDETAIL SKETCH	0
5	Name	O N DETAIL SKETC	H	pe only	Com	pletion SI		711	WO Number HINDETAIL SKETCH	0
5	Name	O N DETAIL SKETC	H	pe only	Com	pletion SI		711	WO Number HINDETAIL SKETCH	0
5	Name	O N DETAIL SKETC	H	pe anly	Com	pletion SI		711	WO Number HINDETAIL SKETCH	0
5	Name	O N DETAIL SKETC	H	pe anly	Com	pletion SI		711	WO Number HINDETAIL SKETCH	0
5	Name	O N DETAIL SKETC	H	pe anly	Com	pletion SI		711	WO Number HINDETAIL SKETCH	0

Ohio Rural Natural Gas INVESTIGATION OF MECHANICAL FITTING FAILURE (§192.1009)

Date of Failure:	Report No:
L cription of Failure:	
Mechanical Fitting Involved: ☐ Stab ☐	Nut Follower ☐ Bolted ☐ Other Compression Type Fitting:
Type of Mechanical Fitting: ☐ Service	or Main Tee Tapping Tee Transition Fitting Coupling Riser
☐ Adapte	r 🛮 Valve 🗆 Sleeve 🗆 End Cap 🗈 Other:
Leak Location: Aboveground or B	elowground ☐ Inside or ☐ Outside
🛘 Main-to-Main or 🗘 M	fain-to-Service or ☐ Service-to-Service or ☐ Meter Set
Year Installed: Year Manufac	ctured: If both is unknown, Provide Decade Installed:
Manufacturer:	Part or Model Number: Lot Number:
Other Attributes:	
	ber / Lot Number cannot be identified, enter "Unknown")
Fitting Material: Steel Plastic Combin	nation Plastic & Steel Brass Unknown Other:
SPECIFY THE TWO MATERIALS BEING	JOINED:
a) First Pipe:	
Nominal Size: [] 1/4" [] 1/2" [] 3/4" [] 1	" □ 1-1/4" □ 1-1/2" □ 1-3/4" □ 2" □ 3" □ 4" □6" □8"or larger
Unit: ☐ IPS ☐ CTS ☐ NPS	
Material: Steel Cast/Wrought In	ron 🛘 Ductile Iron 🖟 Copper 🖟 Plastic 🖨 Unknown 🖨 Other:
IF PLASTIC: □ Polyethylene(PE) □	Polyvinyl Chloride(PVC) Cross-Linked Polyethylene(PEX)
\square Polybutylene(PB) \square Polypropylen	e(PP) Acrylonitrile Butadiene Styrene (ABS) Polyamide(PA)
	Other(Specify):
b) Second Pipe	
Nominal Size: ☐ ¼" ☐ ½" ☐ ¾" ☐ 1 Unit: ☐ IPS ☐ CTS ☐ NPS	" □ 1-1/4" □ 1-1/2" □ 1-3/4" □ 2" □ 3" □ 4" □6" □8"or larger
Material: ☐ Steel ☐ Cast/Wrought Ir	on 🗆 Ductile Iron 🗆 Copper 🗈 Plastic 🗆 Unknown 🗇 Other:
IF PLASTIC: \Box Polyethylene(PE) \Box	Polyvinyl Chloride(PVC) Cross-Linked Polyethylene(PEX)
☐ Polybutylene(PB) ☐ Polypropylene	e(PP) Acrylonitrile Butadiene Styrene (ABS) Polyamide(PA)
☐ Cellulose Acetate Butyrate(CAB)	Other(Specify):
Apparent Cause of Leak:	
☐ Corrosion ☐ Other Outside Force Damage	☐ Equipment ☐ Incorrect Operation
☐ Natural Forces (Was there thermal expansion	•
	age occurred: At time of leak discovery Previous to leak discovery)
	□ Construction/Install Defect □ Material Defect □ Design Defect)
How did the leak occur? Leaked Through S	
Comments:	
Investigated By:	Date:

10. Part 192 Subpart P – Gas Distribution Pipeline Integrity Management

Subpart P—Gas Distribution Pipeline Integrity Management (IM)

Source: 74 FR 63934, Dec. 4, 2009, unless otherwise noted.

§ 192.1001 What definitions apply to this subpart?

The following definitions apply to this subpart:

Excavation Damage means any impact that results in the need to repair or replace an underground facility due to a weakening, or the partial or complete destruction, of the facility, including, but not limited to, the protective coating, lateral support, cathodic protection or the housing for the line device or facility.

Hazardous Leak means a leak that represents an existing or probable hazard to persons or property and requires immediate repair or continuous action until the conditions are no longer hazardous.

Integrity Management Plan or IM Plan means a written explanation of the mechanisms or procedures the operator will use to implement its integrity management program and to ensure compliance with this subpart.

Integrity Management Program or IM Program means an overall approach by an operator to ensure the integrity of its gas distribution system.

Small LPG Operator means an operator of a liquefied petroleum gas (LPG) distribution pipeline that serves fewer than 100 customers from a single source.

§ 192.1003 What do the regulations in this subpart cover?

General. This subpart prescribes minimum requirements for an IM program for any gas distribution pipeline covered under this part, including liquefied petroleum gas systems. A gas distribution operator, other than a master meter operator or a small LPG operator, must follow the requirements in §§192.1005–192.1013 of this subpart. A master meter operator or small LPG operator of a gas distribution pipeline must follow the requirements in §192.1015 of this subpart.

§ 192.1005 What must a gas distribution operator (other than a master meter or small LPG operator) do to implement this subpart?

No later than August 2, 2011 a gas distribution operator must develop and implement an integrity management program that includes a written integrity management plan as specified in §192.1007.

§ 192.1007 What are the required elements of an integrity management plan?

A written integrity management plan must contain procedures for developing and implementing the following elements:

- (a) Knowledge. An operator must demonstrate an understanding of its gas distribution system developed from reasonably available information.
- (1) Identify the characteristics of the pipeline's design and operations and the environmental factors that are necessary to assess the applicable threats and risks to its gas distribution pipeline.
- (2) Consider the information gained from past design, operations, and maintenance.

- (3) Identify additional information needed and provide a plan for gaining that information over time through normal activities conducted on the pipeline (for example, design, construction, operations or maintenance activities).
- (4) Develop and implement a process by which the IM program will be reviewed periodically and refined and improved as needed.
- (5) Provide for the capture and retention of data on any new pipeline installed. The data must include, at a minimum, the location where the new pipeline is installed and the material of which it is constructed.
- (b) *Identify threats*. The operator must consider the following categories of threats to each gas distribution pipeline: Corrosion, natural forces, excavation damage, other outside force damage, material, weld or joint failure (including compression coupling), equipment failure, incorrect operation, and other concerns that could threaten the integrity of its pipeline. An operator must consider reasonably available information to identify existing and potential threats. Sources of data may include, but are not limited to, incident and leak history, corrosion control records, continuing surveillance records, patrolling records, maintenance history, and excavation damage experience.
- (c) Evaluate and rank risk. An operator must evaluate the risks associated with its distribution pipeline. In this evaluation, the operator must determine the relative importance of each threat and estimate and rank the risks posed to its pipeline. This evaluation must consider each applicable current and potential threat, the likelihood of failure associated with each threat, and the potential consequences of such a failure. An operator may subdivide its pipeline into regions with similar characteristics (e.g., contiguous areas within a distribution pipeline consisting of mains, services and other appurtenances; areas with common materials or environmental factors), and for which similar actions likely would be effective in reducing risk.
- (d) Identify and implement measures to address risks. Determine and implement measures designed to reduce the risks from failure of its gas distribution pipeline. These measures must include an effective leak management program (unless all leaks are repaired when found).
- (e) Measure performance, monitor results, and evaluate effectiveness.
- (1) Develop and monitor performance measures from an established baseline to evaluate the effectiveness of its IM program. An operator must consider the results of its performance monitoring in periodically re-evaluating the threats and risks. These performance measures must include the following:
- (i) Number of hazardous leaks either eliminated or repaired as required by §192.703(c) of this subchapter (or total number of leaks if all leaks are repaired when found), categorized by cause;
- (ii) Number of excavation damages;
- (iii) Number of excavation tickets (receipt of information by the underground facility operator from the notification center);
- (iv) Total number of leaks either eliminated or repaired, categorized by cause;
- (v) Number of hazardous leaks either eliminated or repaired as required by §192.703(c) (or total number of leaks if all leaks are repaired when found), categorized by material; and
- (vi) Any additional measures the operator determines are needed to evaluate the effectiveness of the operator's IM program in controlling each identified threat.
- (f) Periodic Evaluation and Improvement. An operator must re-evaluate threats and risks on its entire pipeline and consider the relevance of threats in one location to other areas. Each operator must determine the appropriate period for conducting complete program evaluations based on the complexity of its system and changes in factors affecting the risk of failure. An operator must conduct a complete program re-evaluation at least every five years. The operator must consider the results of the performance monitoring in these evaluations.

(g) Report results. Report, on an annual basis, the four measures listed in paragraphs (e)(1)(i) through (e)(1)(iv) of this section, as part of the annual report required by §191.11. An operator also must report the four measures to the state pipeline safety authority if a state exercises jurisdiction over the operator's pipeline.

§ 192.1009 What must an operator report when compression couplings fail?

Each operator must report, on an annual basis, information related to failure of compression couplings, excluding those that result only in non-hazardous leaks, as part of the annual report required by §191.11 beginning with the report submitted March 15, 2011. This information must include, at a minimum, location of the failure in the system, nominal pipe size, material type, nature of failure including any contribution of local pipeline environment, coupling manufacturer, lot number and date of manufacture, and other information that can be found in markings on the failed coupling. An operator also must report this information to the state pipeline safety authority if a state exercises jurisdiction over the operator's pipeline.

§ 192.1011 What records must an operator keep?

An operator must maintain records demonstrating compliance with the requirements of this subpart for at least 10 years. The records must include copies of superseded integrity management plans developed under this subpart.

§ 192.1013 When may an operator deviate from required periodic inspections under this part?

- (a) An operator may propose to reduce the frequency of periodic inspections and tests required in this part on the basis of the engineering analysis and risk assessment required by this subpart.
- (b) An operator must submit its proposal to the PHMSA Associate Administrator for Pipeline Safety or, in the case of an intrastate pipeline facility regulated by the State, the appropriate State agency. The applicable oversight agency may accept the proposal on its own authority, with or without conditions and limitations, on a showing that the operator's proposal, which includes the adjusted interval, will provide an equal or greater overall level of safety.
- (c) An operator may implement an approved reduction in the frequency of a periodic inspection or test only where the operator has developed and implemented an integrity management program that provides an equal or improved overall level of safety despite the reduced frequency of periodic inspections.

§ 192.1015 What must a master meter or small liquefied petroleum gas (LPG) operator do to implement this subpart?

- (a) General. No later than August 2, 2011 the operator of a master meter system or a small LPG operator must develop and implement an IM program that includes a written IM plan as specified in paragraph (b) of this section. The IM program for these pipelines will reflect the relative simplicity of these types of pipelines.
- (b) Elements. A written integrity management plan must address, at a minimum, the following elements:
- (1) Knowledge. The operator must demonstrate knowledge of its pipeline, which, to the extent known, will include the approximate location and material of its pipeline. The operator must identify additional information needed and provide a plan for gaining knowledge over time through normal activities conducted on the pipeline (for example, design, construction, operations or maintenance activities).
- (2) Identify threats. The operator must consider, at minimum, the following categories of threats (existing and potential): Corrosion, natural forces, excavation damage, other outside force damage, material or weld failure, equipment failure, and incorrect operation.
- (3) Rank risks. The operator must evaluate the risks to its pipeline and estimate the relative importance of each identified threat.
- (4) Identify and implement measures to mitigate risks. The operator must determine and implement measures designed to reduce the risks from failure of its pipeline.

- (5) Measure performance, monitor results, and evaluate effectiveness. The operator must monitor, as a performance measure, the number of leaks eliminated or repaired on its pipeline and their causes.
- (6) Periodic evaluation and improvement. The operator must determine the appropriate period for conducting IM program evaluations based on the complexity of its pipeline and changes in factors affecting the risk of failure. An operator must re-evaluate its entire program at least every five years. The operator must consider the results of the performance monitoring in these evaluations.
- (c) Records. The operator must maintain, for a period of at least 10 years, the following records:
- (1) A written IM plan in accordance with this section, including superseded IM plans;
- (2) Documents supporting threat identification; and
- (3) Documents showing the location and material of all piping and appurtenances that are installed after the effective date of the operator's IM program and, to the extent known, the location and material of all pipe and appurtenances that were existing on the effective date of the operator's program.

11. GPTC Guide Material Appendix G-192-8 (Provided in original hard copy of current revision of DIMP)

GUIDE MATERIAL APPENDIX G-192-8

(See §§192.1001, 192.1003, 192.1005, 192.1007, 192.1009, 192.1011, 192.1015, and Guide Material Appendix G-192-8A)

DISTRIBUTION INTEGRITY MANAGEMENT PROGRAM (DIMP)

CONTENTS

4	IN.	TR	OΙ	וומ	CTI	ON

- 1.1 Scope.
- 1.2 Glossary of abbreviations.
- 1.3 How to use this guide material.
- 1.4 Overview.

2 ELEMENTS OF A DISTRIBUTION INTEGRITY MANAGEMENT PLAN

- 2.1 General.
- 2.2 Develop and implement a written plan.

3 KNOWLEDGE

- 3.1 General.
- 3.2 DOT Annual Report information.
- 3.3 Additional information.
- 3.4 Knowledge of what is physically happening in the system.
- 3.5 Documentation.

4 IDENTIFY THREATS

- 4.1 Primary threats.
- 4.2 Identify threats.
- 4.3 Sample threat identification method.

5 EVALUATE AND RANK RISK

- 5.1 General.
- 5.2 Information evaluation.
- 5.3 Methods.
- 5.4 Example of risk evaluation.
- 5.5 Validation.

6 IDENTIFY AND IMPLEMENT MEASURES TO ADDRESS RISKS

- 6.1 General.
- 6.2 Leak Management Program.
- 6.3 A/A actions.

7 MEASURE PERFORMANCE, MONITOR RESULTS, AND EVALUATE EFFECTIVENESS

- 7.1 Guidelines for developing performance measures.
- 7.2 Examples of performance measures.

8 PERIODIC EVALUATION AND IMPROVEMENT

- 8.1 Review of the written plan.
- 8.2 Review of effectiveness.
- 9 REPORT RESULTS

OHIO RURAL NATURAL GAS CONTINUING SURVEILLANCE REPORT (§192.613)

Inspection Frequency: Once per calendar year, NTE 15 months

{	em Name: System No	o:	
Fac	ility Or Area Covered:		
		Yes	No
1)	Are any updates required in the class locations listed for this facility in the current O&M Plan?	Ō	
2)	Have there been any failures or incidents associated with this facility?		
-	Has there been an unusual leakage history for this facility since the last continuing surveillance was performed?		
4)	Are there any apparent corrosion or corrosion control problems?		
5)	Have there been any substantial changes in cathodic protection requirements since the last annual surveillance?		
6)	Have any abnormal pressures or pressure differentials been observed?		
7)	Are there high levels of construction activity that may effect the integrity of the system?		
8)	Are there any landslips, streams or rivers that may effect the integrity of the system?		
9)	Have any unusual fluid accumulations been observed?		
]	Are there any changes required in the MAOP listed for this facility in the current O&M Plan?		
11)	Have there been any changes in the odorization requirements?		
12)	Are any changes necessary in the leakage survey requirements as outlined in the current O&M Plan?		
13)	Are there any designated buildings in this system that need to be added to system records?		
14)	Are more critical valves needed to safely operate the system?		
15)	Do critical valve maps need updated?		
(6)	Have there been any regulatory changes that will affect the current O&M Plan?		
17)	Have there been any other changes or observations that may affect the safe operation or integrity of this facility?		
	e answer to any of the above questions is yes, please describe the condition in deta what updates were made to the current O&M Plan, if any.	ail, list what a	ctions were tak
Ų			
erf	ormed By: Date:		
	Previous Insp. Date:		

OHIO RURAL NATURAL GAS REGULATOR & RELIEF VALVE INSPECTION REPORT (§192.739)

System Name:	. <u> </u>	\$	System	ı No:		Station Name	p 0			
'k Performed: □	Initial Turn-	On 🛘	Perio	dic Ins	pection	☐ Maint				
ulator Type:							gulator			
Inspection Interval:	☐ Annual	NTE 1	5 mo.	□ 120) months		-			
						essure check o	nly**			
	□ 60 mon	iths		Oth	ner					
		PRE	SSUR	E REC	ORDER C	ALIBRATION	SECTION			
Recorder Type:	☐ MiniMa	ax 🗆	RTU		☐ Recor	der 🛭 Tran	smitter/Transd	ucer		
Model:			Serial	No: _			Range:			
			-							
	0%	1	0%		ressure	100%	A -4 - 1			
Test (PSIG/F)	070	1	.070	-	3070	100%	Actual			
In-Test										
Out-Test			-							
% Error In										
% Error Out										
				REG	ULATOR	SECTION				
Make:	Model				N	lake:	Mode	el		
Orif. Size: Spi	ing Color/R	Range: _		_	O	rif. Size:	Spring Cold	or / Ra	mge:	
vntrol □ Monitor □	First Cut [] I	Parallel					nitor First Cu			
S on Inlet Pressure:	MAO	P Inlet/	Outlet	t:			ssure:M			utlet:
Set Point (as found): I				-	_		ınd): Flowing:_			
Set Point (as left): Flo							t): Flowing:			
**Billing Pressure			_							*
Duning I ressure	1.1:					_Conjurmea w	un buung: 🗆			
Regulators checked for	r leakane			N/A		linas nuomaules	roalroad		NO	
Regulators fully stroke	n reakage ed						ly protected			
Tight lockup achieved						vents installed	· -			
Regulator disassemble					-		valves operated			
Regulator rebuilt							pported			
Pilot condition checke	d				Station	adequately pai	nted			
				ם ושם	PET 37 A II 37 II	SECTION				
Make:	_ Model:						Mode	l;		
Pressure Set(as found)										
Was valve partially or	erated?		Yes [] No	W	as valve partia	Illy operated?		□ Y	es 🛮 No
Does valve have bubbl	e tight shut o	ff?	Yes [No	Do	es valve have	bubble tight sh	ut off	? 🗆 Y	es 🗆 No
there any changes	to the system	that w	ould a	ffect tl	he origina	l calculations?	Yes 🛘	No		
If any problems or abn	ormalities we	ere four	ıd, ple	ase ex	plain:					
Performed By:						Date:				

OHIO RURAL NATURAL GAS TEST REPORT

		System No:	Job Name:	W.O. #:
County:	Twp:	Date Installed	(Begin):	(End):
Mainline Size(s)		Wall Thicknes	ss & Grade(Steel)	
SDR(Plastic)	PE		_Total Feet	
Services Tested With	Main (addresses)_			
Service Line Size(s)_		Total Service L	ine Feet	
				PE
				Rating
	No. of fittings_	Lowest Pressure	e Rating	
nstrumentation:	□ Gauge □ C	hart Recorder 0 to	oPr	essure Range
	☐ Gauge ☐ C	hart Recorder 0 to	oPr	essure Range Dead Weight
'est Medium:	☐ Gauge ☐ C	hart Recorder 0 to Gauge/Recorder	oPr r S.N.& Calib.Date: _	ressure Range
'est Medium: 'est Date/Time Starte	☐ Gauge ☐ Cl ☐ Other ☐ Nitrogen d:	hart Recorder 0 to Gauge/Recorder	oPr r S.N.& Calib.Date: _	Dead Weight Dead Weight Water Retest
Test Medium: Test Date/Time Starte Test Date/Time Stopp	☐ Gauge ☐ Cl ☐ Other ☐ Nitrogen d:ed:	hart Recorder 0 to Gauge/Recorder Air D	Pr S.N.& Calib.Date: _ Natural Gas Test Type: uration:	Dead Weight Dead Weight Water Rother Retest
Cest Medium: Cest Date/Time Starte Cest Date/Time Stopp Cest Pressure Start:	☐ Gauge ☐ Cl ☐ Other ☐ Nitrogen d: ed:	hart Recorder 0 to Gauge/Recorder Air Test 1	oPr r S.N.& Calib.Date: _	Dead Weight ☐ Water ☐ Other ☐ Initial ☐ Retest
Test Medium: Test Date/Time Starte Test Date/Time Stopp Test Pressure Start: Teason for Line Loss:	☐ Gauge ☐ Cl ☐ Other ☐ Nitrogen d: ed:	hart Recorder 0 to Gauge/Recorder Air Di Test 1	oPr r S.N.& Calib.Date: _ Natural Gas Test Type: uration: Pressure Stop: Measures Taken:	Dead Weight Dead Weight Water Rother Retest
Test Medium: Test Date/Time Starte Test Date/Time Stopp Test Pressure Start: Teason for Line Loss:	☐ Gauge ☐ Cl ☐ Other ☐ Nitrogen d: ed:	hart Recorder 0 to Gauge/Recorder Air Test 1 Corrective 1	oPr r S.N.& Calib.Date: _ Natural Gas Test Type: uration: Pressure Stop: Measures Taken:	Bessure Range

10 REPORT FITTING FAILURES

- 11 SAMPLE DIMP APPROACHES
- 11.1 SME approach.
- 11.2 Mathematical approach.

1 INTRODUCTION

1.1 Scope.

- (a) This guide material is intended to assist operators with development of a Distribution Integrity Management Program (DIMP), including the written plan, and compliance with Federal Regulations §§192.1001, 192.1003, 192.1005, 192.1007, 192.1009, 192.1011, and 192.1015 on DIMP. It provides operators with practices that may be considered as they develop and maintain a DIMP specific to their gas distribution systems.
- (b) Distribution pipeline systems and associated operating practices can vary widely. Examples of system differences include: materials used, age, manner of construction, operation and maintenance practices, and operating environments (natural and man-made). This guidance recognizes that there is wide diversity among distribution systems and is therefore flexible, allowing operators to identify considerations dealing with their unique threats and to select actions suited to their specific needs.
- (c) The options in this guidance are intended to provide the operator with a selection of possible choices to use in improving the integrity of its distribution system. Operators may not need to consider or perform every step presented. It is not intended that an operator evaluate every option or provide justification or reasons why options were not implemented.
- (d) Section 192.1015 imposes different requirements for small liquefied petroleum gas (LPG) operators (i.e., those serving fewer than 100 customers from a single source) and master meter operators. Since these pipeline systems are less complex, the integrity management requirements are simplified. The appropriate portions of this guide material are valid for those operators. PHMSA-OPS has published "Guidance for Master Meter and Small Liquefied Petroleum Gas Pipeline Operators" to assist operators of these systems to implement requirements of the DIMP rule, which can be found at:
 - primis.phmsa.dot.gov/dimp/docs/GuidanceForMasterMeterAndSmallLiquefiedPetroleumGas PipelineOperators_11_09.pdf.

1.2 Glossary of Abbreviations.

Abbreviation	Meaning
A/A	additional or accelerated (actions)
CP	cathodic protection
LPG	liquefied petroleum gas
PE	polyethylene
SCADA	supervisory control and data acquisition
SDR	standard dimension ratio
SME	subject matter expert

1.3 How to use this guide material.

The guide material is organized to coincide with the seven required elements of a DIMP. The order in which the guidance is presented does not imply the order in which it should be applied. However, the operator needs to address each element in some way. Once an operator determines how it can best accomplish distribution system integrity, the guide material may be used to support or direct the operator's approach. The operator is cautioned that the guide material may not anticipate all conditions that may be encountered, and the operator is not restricted from using other methods to comply with the Regulations.

Two sample DIMP approaches are given in Section 11.

ı

1.4 Overview.

- (a) The objective of a DIMP is to manage the integrity of a gas distribution system. As discussed in detail in Section 5, an essential part of a DIMP is a risk evaluation of the distribution system. One approach to risk evaluation is to group facilities by common traits or problems, and then perform a risk ranking. This process allows the grouping of facilities that experience similar threats to be riskranked together. Then, if necessary, attention can be focused on developing measures that address the greatest risks.
- (b) After identifying the problems, the operator should consider the concept of grouping facilities when first developing its DIMP. Such groupings could significantly affect how the operator assembles data about its system (see Section 3) and how it approaches its threat analysis (see Section 4).
- (c) The operator should also recognize that the development of the DIMP may be an iterative (or repeating) process. That means each time a cycle (e.g., gather knowledge, identify threats, rank risks, take action to reduce risk, measure performance) is completed, areas needing additional data, analyses, or actions may become apparent. For example, the initial general knowledge of the system may be used to group facilities, identify the applicable threats, and begin the risk analysis. In attempting to complete the risk analysis, the operator may determine the need for additional information. The operator may also determine that the facility groupings need to be redefined, such as by subdividing groups or combining groups.

2 ELEMENTS OF A DISTRIBUTION INTEGRITY MANAGEMENT PLAN

2.1 General.

Seven elements have been identified as the essential components of a DIMP, except as modified for those operators identified in §192.1015(a). Collectively, these elements establish a program that should reasonably manage the integrity of distribution pipeline systems on a going-forward basis. These elements are as follows.

- (a) Knowledge (see Section 3).
- (b) Identify threats (see Section 4).
- (c) Evaluate and rank risk (see Section 5).
- (d) Identify and implement measures to address risks (see Section 6).
- (e) Measure performance, monitor results, and evaluate effectiveness (see Section 7).
- (f) Periodic evaluation and improvement (see Section 8).
- (g) Report results, except for master meter and small LPG operators (see Section 9).

2.2 Develop and implement a written plan.

Federal Regulations require that each distribution operator prepare and implement a written plan as a primary component of its DIMP. The function of the plan is to document how each of the applicable seven elements will be addressed and implemented. The DIMP should be complete and address required elements by the implementation dates in §§192.1005 and 192.1015. The plan should be concise, but still be sufficient for operator personnel to understand and implement the program on a consistent basis, and is not intended to include extensive technical justifications or detailed process descriptions.

3 KNOWLEDGE

3.1 General.

(a) Information, such as the materials and type of construction, the operating conditions of the pipe or facility, and other relevant factors within the surroundings in which the system operates, is referred to as the "knowledge of the distribution system."

10 REPORT FITTING FAILURES

- (a) Except for master meter or small LPG operators, operators are required by §192.1009 to submit a report on each mechanical fitting failure, excluding any failure that results only in a nonhazardous leak, in accordance with §191.12. (Note: Hazardous leak and mechanical fitting are defined in §192.1001.)
- (b) See §191.12.

11 SAMPLE DIMP APPROACHES

11.1 SME approach.

Because this approach relies more on personnel knowledge and experience, operators of smaller, less complex systems may find it more appropriate.

- (a) Identify distribution system problems that have occurred and relate these to the eight identified primary threat categories. An operator may choose to break down the primary threat categories into subcategories for more effective understanding and focus.
- (b) Use the knowledge and experience of SMEs and other available information to understand the distribution system and its associated operating and maintenance experience.
- (c) Use the identified threats and associated consequences, evaluate and rank the involved risks.
- (d) If additional or accelerated risk management measures are needed, take reasonable actions to address the targeted risks.
- (e) Establish performance measures for key risk management activities and monitor accordingly.
- (f) Periodically evaluate performance measure trends and indications. Change program procedures or activities as needed.
- (g) Report information as required.

11.2 Mathematical approach.

This approach may require more rigorous segmentation or grouping of specific information. Thus it may be more suited for operators with records and mapping information tracked electronically.

- (a) Identify and gather available information about the distribution system and its associated operating and maintenance experience.
- (b) Establish criteria for identifying facilities or groups of facilities within the distribution system. Then, using the knowledge and experience of SMEs together with other available information, decide which factors (e.g., pipeline traits, threats, consequences, environments) are associated with each identified facility or group of facilities. An operator may choose to break down the primary threat categories into subcategories for more effective understanding and focus.
- (c) Assign weighting values to relevant factors involved and using a mathematical tool, analyze and establish a risk score for each facility or group of facilities. Based on calculated scores and supplemental considerations from SMEs, the facilities or groups of facilities can be ranked accordingly.
- (d) For facilities or groups of facilities where further risk reduction is needed, implement activities that the operator believes will best achieve the desired results.
- (e) Identify and track performance measures to determine whether the efforts to manage targeted risks are effective.
- (f) Periodically evaluate performance measure trends and indications and change program procedures or activities as needed.
- (g) Report information as required.

Reserved

GUIDE MATERIAL APPENDIX G-192-8A

(See §§192.1001, 192.1003, 192.1005, 192.1007, 192.1011, 192.1015, and Guide Material Appendix G-192-8)

DISTRIBUTION INTEGRITY MANAGEMENT PROGRAM (DIMP) CROSS-REFERENCES TO RELEVANT GUIDE MATERIAL

Guide Material Appendix G-192-8, "Distribution Integrity Management Program (DIMP)" contains guide material for complying with the DIMP requirements. It contains Table 4.1 – "Sample Threat Identification Method," which is a table that lists "Primary Threats, Threat Subcategories, and Questions to Check Subcategory Applicability to System." This Guide appendix follows the format of that table and references the other existing guide material sections that may be of assistance in the development of a written integrity management plan.

Primary Threat	Threat Subcategories	Section	Title
ALL	All	603	General provisions
		605	Procedural manual for operations, maintenance, and emergencies
		613	Continuing surveillance
		615	Emergency plans
	i	616	Public awareness
		617	Investigation of failures
		625	Odorization of gas
		627	Tapping pipelines under pressure
		703	General
		721	Distribution systems: Patrolling
		723	Distribution systems: Leakage surveys
		727	Abandonment or deactivation of facilities
		GMA G-191-3	Distribution System Annual Report
		GMA G-192-11	Gas Leakage Control Guidelines For Natural Gas Systems (Methane)
		GMA G-192-	Gas Leakage Control Guidelines For
		11A	Petroleum Gas Systems
CORROSION	External	14	Conversion to service subject to this part
	corrosion:	53	General
	bare steel pipe (CP or no CP)	452	How does this subpart apply to converted pipelines and regulated onshore gathering lines?
		453	General
		455	External corrosion control: Buried or submerged pipelines installed after July 31, 1971
		457	External corrosion control: Buried or submerged pipelines installed before August 1, 1971
		459	External corrosion control: Examination of buried pipeline when exposed
		461	External corrosion control: Protective coating
		463	External corrosion control: Cathodic protection
		465	External corrosion control: Monitoring

		1	
Primary Threat	Threat Subcategories	Section	Title
CORROSION	External	467	External corrosion control: Electrical isolation
(Continued)	corrosion:	469	External corrosion control: Test stations
	bare steel pipe	471	External corrosion control: Test leads
	(CP or no CP)	473	External corrosion control: Interference currents
	(Continued)	483	Remedial measures: General
		487	Remedial measures: Distribution lines other than cast iron or ductile iron lines
		489	Remedial measures: Cast iron and ductile iron pipelines
		491	Corrosion control records
			Criteria for Cathodic Protection and
		Appendix D	Determination of Measurements
	External	14	Conversion to service subject to this part
	corrosion:	1.00	How does this subpart apply to converted
	cast iron pipe (graphitization)	452	pipelines and regulated onshore gathering lines?
i		453	General
			External corrosion control: Buried or
		455	submerged pipelines installed after July 31, 1971
		457	External corrosion control: Buried or submerged pipelines installed before August 1, 1971
		459	External corrosion control: Examination of buried pipeline when exposed
		461	External corrosion control: Protective coating
		463	External corrosion control: Cathodic protection
		465	External corrosion control: Monitoring
		467	External corrosion control: Electrical isolation
		471	External corrosion control: Test leads
		473	External corrosion control: Interference currents
		483	Remedial measures: General
		487	Remedial measures: Distribution lines other than cast iron or ductile iron lines
		489	Remedial measures: Cast iron and ductile iron pipelines
		491	Corrosion control records
		GMA G-192-18	Cast Iron Pipe
	External	14	Conversion to service subject to this part
	corrosion:	53	General
,	coated & wrapped steel pipe (CP or no	452	How does this subpart apply to converted pipelines and regulated onshore gathering lines?
1	CP)	453	General
	-		External corrosion control: Buried or
		455	submerged pipelines installed after July 31, 1971

Primary Threat	Threat Subcategories	Section	Title
CORROSION (Continued)	External corrosion: coated &	457	External corrosion control: Buried or submerged pipelines installed before August 1, 1971
	wrapped steel pipe (CP or no	459	External corrosion control: Examination of buried pipeline when exposed
	CP)	461	External corrosion control: Protective coating
	(Continued)	463	External corrosion control: Cathodic protection
		465	External corrosion control: Monitoring
		467	External corrosion control: Electrical isolation
		469	External corrosion control: Test stations
		471	External corrosion control: Test leads
	<u> </u>	473	External corrosion control: Interference currents
		483	Remedial measures: General
1		487	Remedial measures: Distribution lines other than cast iron or ductile iron lines
		489	Remedial measures: Cast iron and ductile iron pipelines
		491	Corrosion control records
	Other metallic materials	my consum	
	Internal	14	Conversion to service subject to this part
	corrosion	53	General
		452	How does this subpart apply to converted pipelines and regulated onshore gathering lines?
		453	General
		475	Internal corrosion control: General
		477	Internal corrosion control: Monitoring
	Atmospheric	14	Conversion to service subject to this part
	corrosion	452	How does this subpart apply to converted pipelines and regulated onshore gathering lines?
		453	General
		479	Atmospheric corrosion control: General
		481	Atmospheric corrosion control: Monitoring
NATURAL	Outside	103	General
FORCE	forces/weather:	105	Design formula for steel pipe
(e.g., earth	steel pipe	145	Valves
movement,		155	Welded branch connections
lightning,		157	Extruded outlets
heavy		159	Flexibility
rains/floods,		161	Supports and anchors
temperature		181	Distribution line valves
extremes, high winds)		199	Requirements for design of pressure relief and limiting devices

Primary Threat	Threat Subcategories	Section	Title
NATURAL	Outside	317	Protection from hazards
FORCE (e.g., earth	forces/weather: steel pipe	355	Customer meters and regulators: Protection from damage
movement,	(Continued)	357	Customer meters and regulators: Installation
lightning,		365	Service lines: Location of valves
heavy rains/floods,		367	Service lines: General requirements for connections to main piping
temperature extremes, high		GMA G-192-13	Considerations To Minimize Damage By Outside Forces
winds) (Continued)		GMA G-192- 15A	Horizontal Directional Drilling (HDD) for Steel Pipelines
[Outside	59	Plastic pipe
	forces/weather:	161	Supports and anchors
	plastic pipe	193	Valve installation in plastic pipe
		317	Protection from hazards
		367	Service lines: General requirements for connections to main piping
		381	Service lines: Excess flow valve performance standards
		GMA G-192-13	Considerations To Minimize Damage By Outside Forces
		GMA G-192-	Horizontal Directional Drilling (HDD) for Plastic
		15B	Pipe
	Outside	145	Valves
1	forces/weather:	147	Flanges and flange accessories
	cast iron pipe	151	Tapping
1		159	Flexibility
		161	Supports and anchors
		181	Distribution line valves
		317	Protection from hazards
		755	Protecting cast-iron pipelines
		GMA G-192-13	Considerations To Minimize Damage By Outside Forces
		GMA G-192-18	Cast Iron Pipe
DAMAGE	Operator (or its contractor)		
•	Third-party	161	Supports and anchors
		181	Distribution line valves
		381	Service lines: Excess flow valve performance standards
		459	External corrosion control: Examination of buried pipeline when exposed
		614	Damage prevention program
		GMA G-192-13	Considerations To Minimize Damage By Outside Forces
		GMA G-192-15	Design of Uncased Pipeline Crossings of Highways and Railroads
		GMA G-192-18	Cast Iron Pipe
		GMA G-192-6	Substructure Damage Prevention Guidelines For Directional Drilling and Other Trenchless Technologies

Primary Threat	Threat Subcategories	Section	Title
OTHER	Vehicular	317	Protection from hazards
OUTSIDE		353	Customer meters and regulators: Location
FORCE DAMAGE		355	Customer meters and regulators: Protection from damage
		GMA G-192-13	Considerations To Minimize Damage By Outside Forces
	Vandalism	GMA G-192-13	Considerations To Minimize Damage By Outside Forces
	Fire explosion (primary)	GMA G-192-13	Considerations To Minimize Damage By Outside Forces
	Leakage (previous damage)		
	Blasting	103	General
		145	Valves
		155	Welded branch connections
		613	Continuing surveillance
		616	Public awareness
		GMA G-192-13	Considerations To Minimize Damage By Outside Forces
		GMA G-192-16	Substructure Damage Prevention Guidelines (Blasting Operations)
	Mechanical damage	GMA G-192-6	Substructure Damage Prevention Guidelines For Directional Drilling and Other Trenchless Technologies
		GMA G-192-13	Considerations To Minimize Damage By Outside Forces
		GMA G-192-16	Substructure Damage Prevention Guidelines (Blasting Operations)
MATERIAL OR	Manufacturing	59	Plastic pipe
WELD	defects	311	Repair of plastic pipe
		747	Valve maintenance: Distribution systems
	Materials/Plastic	59	Plastic pipe
		311	Repair of plastic pipe
	Weld/Joint		
EQUIPMENT	System	181	Distribution line valves
FAILURE	equipment	195 197	Protection against accidental over pressuring Control of the pressure of gas delivered from high-pressure distribution systems
		199	Requirements for design of pressure relief and limiting devices
		201	Required capacity of pressure relieving and limiting stations
		355	Customer meters and regulators: Protection from damage
		623	Maximum and minimum allowable operating pressure: Low-pressure distribution systems
		739	Pressure limiting and regulating stations: Inspection and testing
		741	Pressure limiting and regulating stations: Telemetering or recording gages

Primary Threat	Threat	Section	
Filliary Tireat	Subcategories	Section	Title
EQUIPMENT	System	743	Pressure limiting and regulating stations:
FAILURE	equipment	743	Capacity of relief devices
(Continued)	(Continued)	747	Valve maintenance: Distribution systems
		749	Vault maintenance
		751	Prevention of accidental ignition
INCORRECT	Inadequate	187	Vaults: Sealing, venting, and ventilation
OPERATION	procedures	189	Vaults: Drainage and waterproofing
		193	Valve installation in plastic pipe
		195	Protection against accidental over pressuring
		197	Control of the pressure of gas delivered from
			high-pressure distribution systems
		201	Required capacity of pressure relieving and
			limiting stations
■ i		203	Instrument, control, and sampling pipe and
		200	components
		229	Limitations on welders
		235	Preparation for welding
i		273	General
		279	Copper pipe
		281	Plastic pipe
		285	Plastic pipe: Qualifying joining procedures
		307	Plastic pipe: Qualifying persons to make joints Inspection of materials
		309	Repair of steel pipe
		311	Repair of steel pipe Repair of plastic pipe
		319	Installation of pipe in a ditch
		321	Installation of plastic pipe
		325	Underground clearance
		353	Customer meters and regulators: Location
		-	Customer meters and regulators: Protection
	İ	355	from damage
		357	Customer meters and regulators: Installation
		361	Service lines: Installation
		363	Service lines: Valve requirements
		365	Service lines: Location of valves
		207	Service lines: General requirements for
		367	connections to main piping
		375	Service lines: Plastic
		377	Service lines: Copper
		629	Purging of pipelines
		739	Pressure limiting and regulating stations:
		100	Inspection and testing
		743	Pressure limiting and regulating stations:
			Capacity of relief devices
	<u> </u>	Subpart N	Qualification of Pipeline Personnel
		GMA G-192-12	Planned Shutdown
		GMA G-192-15	Design of Uncased Pipeline Crossings of
			Highways and Railroads

Primary Threat	Threat Subcategories	Section	Title
INCORRECT OPERATION	Inadequate safety practices	381	Service lines: Excess flow valve performance standards
(Continued)	1	383	Excess flow valve installation
	Failure to follow procedures	321	Installation of plastic pipe
		623	Maximum and minimum allowable operating pressure: Low-pressure distribution systems
		739	Pressure limiting and regulating stations: Inspection and testing
		741	Pressure limiting and regulating stations: Telemetering or recording gages
		749	Vault maintenance
L		751	Prevention of accidental ignition
	Construction/	14	Conversion to service subject to this part
	workmanship	123	Design limitations for plastic pipe
	defects	145	Valves
		147	Valves
		183	Vaults: Structural design requirements
		187	Vaults: Sealing, venting, and ventilation
i		193	Valve installation in plastic pipe
		227	Qualification of welders
		229	Limitations on welders
		235	Preparation for welding
		241	Inspection and test of welds
		243	Nondestructive testing
		245	Repair or removal of defects
		279	Copper pipe
		281_	Plastic pipe
		283	Plastic pipe: Qualifying joining procedures
		309	Repair of steel pipe
		311	Repair of plastic pipe
Į.		313	Bends and elbows
		321	Installation of plastic pipe
		623	Maximum and minimum allowable operating
			pressure: Low-pressure distribution systems
		739	Pressure limiting and regulating stations: Inspection and testing
		741	Pressure limiting and regulating stations: Telemetering or recording gages
		749	Vault maintenance
		751	Prevention of accidental ignition
		GMA G-192-15	Design of Uncased Pipeline Crossings of Highways and Railroads
		GMA G-192- 15A	Horizontal Directional Drilling (HDD) for Steel Pipelines
		GMA G-192- 15B	Horizontal Directional Drilling (HDD) for Plastic Pipe
		GMA G-192-20	Fusion Equipment Maintenance / Repair Inspection Form
THER		181	Distribution line valves
		GMA G-192- 11A	Gas Leakage Control Guidelines For Petroleum Gas Systems

Material L:-DIMP

Work Order Number

Syste

Date
Project Name or Address
Starting Point:

nearest Intersection)

(Distance from

321 Partil Rd

Ohio Rural Natural Gas, Co-Op

HDD	PF	7 7	246																							
Insert	SDR		T	†	\dagger	\dagger	T		1		†	1	\dagger	\dagger		\dagger		\dagger	\dagger		+	†	+	\dagger	\dagger	1
French Bore	Lot Number				Sand Linker	10000 MT 14000			10000000000000000000000000000000000000	150000000000000000000000000000000000000	010151000															
mstan Metnoa (Grde)	Mfg Date)		0.15-15	2/2/2					7-8	(/ 0															
(Circle)	Type/Size	-	Parm Tow	11/24		1,808 1,000		1.81 CO 182	12/2 Ptc	1" Pre . fal Ment out																
	Part#																	:								
	Manufacturer		8,0026	Elaci	Elster	Charest Charter	Wire	Ekti	17/34	C'in Tron																
		ΙΛΛ				Ĭ					T															r
	P{pe	Footage				130,	/30,																			
		Number																								
	1/5	Distance																								
(Circle)	Station	Start at 0+00	04 00	lato	0401																					
	шa	ΡĮ	Н	7	က	4	2	9	_	∞	6	10	11	12	13	14	15	16	17	18	13	20	21	22	23	7.7

Note: Footage Column is for pipe only. Since each item could have a unique Mfg Date and Lot Number, each item MUST have its own entry line

Material L. --DIMP

Work Order Number

Date

Project Name or Address

Starting Point:

5/02/

12321 Cartul

Ohio Rural Natural Gas, Co-Op

	(Distance from nearest intersection)	, in										
	st Intersectio	(m					1					
Soil												
	Type		Sand	Loam (Clay	Rock Slurry	Main Line o	Main Line or Service Line (Grae)	Install Method	od Trench Bore Insert HDD WFI? - Withdrawl From Inventory?	Insert	HDD
	Station	7/5	Item	Pipe	اغ	Manufacturer	Part#	Type/Size	Mfg Date	Lot Number	SDR	H
Start	Start at 0+00	Distance	Number	Footage	JW.							Type
1 0+ 00	20	3/				Muella/		730 tec 1"				
2 0+07	2)	37,				Malays;a	200	2"601" Cechica				
3 0+0		32 '	İ			Balon USA		2" valuc	10-11	2 F-US28-R11		
4 0+0	26	32,		131		-						
5 O+ M	4	, 9 %				Weldend		006		WPR12205		
6 0414	7.	, 94		3.5		Set 80 1"						
7 0114	14	, %				7		906		14PB 12 305		
8 0+14	7/	1961				Mattenal usA		Drin		Ser# 72559		
9 0+14	1.7	195				- 3						
10 02/5	15	43,				Elster		Riser sed / Cets				
1107/	7	167				E19411		Add pter		000000477389		
12				130,		(antra/		1"SON PIPE				
13				130'		2/10						
14						Elster		Rise Sel 1"Ces				
15						12/9461		Addotil		00000172389		
16										10000		
17												
18												
19												
20												ŀ
21												
22												
23												
24												

Note: Footage Column is for pipe only. Since each item could have a unique Mfg Date and Lot Number, each item MUST have its own entry line

3-9.15	8	70	DM EXCANATING	0<	
Installed Date	# of Laborers	Hours on Job	Subcontractor	Hours on Joh	
y company:	Brainsey		Mental Trom		×

Service line Material List

			TOTAL MANAGEMENT PARTY AND THE	104			
item Number	Ohy/Ft.	Type/Size	Manufacturer	Mfg. Date	Lot Member	gro	DIT OF
1217	UP		0 / 0		ESCHARL SOT	NUIC	SUR I'LE 1ype
2	2	TO SALE OCTO	FOLY PIPE	2-3	00000000	-	2000
4	ノン	Bashe T/wine				-	900
520		In President Act CA	C. 40t /	117 01		+	
Cree			283	51-01			
2		MTG HARDWARE					
314		20,0	0 1				
				11-13-14	くらると		7007
		(40 Apt	125	11-22-14	1 - 50		
125		/[" -//-			2 292		
		221/1	いかとうえ	3-12	220010		7 -93 6
٠ ٣		177	7 3		1 22 6		9947
			CACA TO	2-7-14	していってん		7605
						_	

Common 1" CTS Yellow 2406 Items

Common 1" CIS Yellow 2406 Items	Manufacturer Mfg Date Lot Mumber		2406		2 Kr	800		2406	2406			2406	2406	2406	120	00	Ware
of Items	Mfg Date																
I" CIS Yellow Z40	Manufacturer													-			
Common	Type/size	Pipe. PE 2406 1" CTS	Standard 12 Gardo Transv Wine	DILA COORDINATION OF THE CONTROL OF	I racer wire splice Kit	2 X 1 E/F Tap Tee W/ EFV 800	4 X 1 E/F Tap Tee W/ EFV 800	6 X 1 E/E Tan Too	איז ד'/ר ומף וככ	EFV 800 Series	Coupler, Stab 1" CTS/CTS	Ricor 1" CTC Ctool Anodlace	Ricar 1" CTC Clay	1 Drofely Adobas Cot	T LICIAN MISTER SEL	pracket, wall Type 6"	Wall Mounting Hardware
	aty./Ft.																
	Item Number	1317	47	1750	20.74	1662	1731	354	010	QTA	634	31.4	718	520	215		846

Note: Footage Column is for wire and pipe only. Since each item could have a unique Mig Date and Lot Number, each item MUST have its own entry line

- /4	M	ers &	ob 3	Subcontractor DM EXCAUATILE	qo		
service Line installation information	Installed Date	# of Laborers	Hours on Job	Subcontrac	Hours on Job	1	ALTERNATION OF THE RESERVE OF THE PROPERTY OF
	Jtilify Company:		bramard	Marian Principal	Wentor	×	

			TOTAL MANAGEMENT PROPERTY				
Item Number	Ohy/Pt.	Type/Size	Manufacturer	Mfg. Date	Lot Number	SDB	SDR PF True
13(7	137	PE SUDG I'R OF CT.	02/ 0.4				A A A
77	12		241270	7 3	\$1.200000 \$1.200000	~	17,406
T	ر ک/	250Ate 7 / WIRE					
520		In Pre Pub Mits C.+	17000	27.0			
Critic			2	-			
2		141 6 1-AND WARE	(
314		Our me	0.00	בו כודוו	Office and		
					#1200C		とのとと
		(4040H-A	ライクト	11-20-14	596052		
173(イベー 十/146	TO SEE CANO	77.6			
0				61-6	5 62017		4406
276		(FF) (A) (A) (A) (A) (A) (A) (A) (A) (A) (A	アをきるない	3-3-14	ンチンちつケン		3466
						_	
				_		_	

Common 4" CTC Vollan. 340C to

PE TVD		4400		3406	2400	2400	7400	74NP	2406	2406	2406	2400		
SDR		+	1		1	-	1	-						
Lot Number														
Mfg Date														
Manufacturer														
Type/size	Pipe, PE 2406 1" CTS	Standard 12 Gauge Tracer Wire	Tracer Wire Splice Kit	2 X 1 E/F Tap Tee W/ EFV 800	4 X 1 E/F Tap Tee W/ EFV 800	6 X 1 E/F Tap Tee	EFV 800 Series	Coumber Stah 1" CTS/CTS	Oleve 41 Arc Charl Annual	niser, 1. C.13 Steel Anodiess	Riser, 1" CTS Flex	1" Prefab Meter Set	Bracket, Wall Type 6"	Wall Mounting Hardware
CITY./PT.														
Hem Number	1317	47	1759	1662	1731	354	918	634	314		718	520	315	846

T) normation	Installed Date 3-2 -15	# of Laborers	Hours on Job	Subcontractor DIM PYCHUATTI	Hours on Job	
service Line installation information						1
	Hillty Company:		Brainard	Materials Withdrawn From:	Mentor	×

Service line Material List

The same with the same of							
tern number Qty./Ft.	QN/Ft.	Type/Size	Manufacturer	Mfg. Date	Lot Number	SDR	SDR PE Type
1317	100	PE SUDGIPPE CT	Dol. Diaz	7.5	: 20000	=	11. 7.40/
47	100	, ~				=	001
Sto		In the Pap rete Cit	17202	71-01	_	-	
373		MTG HAROWARE					
314		Puser.	Peut Kaleas	11-13.14	717 0212		240/
		Apabha	ELSFR	1-20-14	56.52		
1731		4×1 1/Tec	と思いていると	3-15	224018		2006
876		CEN FOU	Pezma sent	3.3-14	したとうとかつ		24.06
						-	

Common 1" CTS Yellow 2406 Items

PE Type	2406			2406	2406	2406	2406	2406	2406	2406				
SOR		-									-	-	-	
Lot Number														6 Angth from could have a uniform take made for the material of the second of the seco
Mfg Date														for Dates and I at Man
Manufacturer														Manning and phone
Type/size	Pipe, PE 2406 1" CTS	Standard 12 Gauge Tracer Wire	Tracer Wire Splice Kit	2 X 1 E/F Tap Tee W/ EFV 800	4 X 1 E/F Tap Tee W/ EFV 800	6 X 1 E/F Tap Tee	EFV 800 Series	Coupler, Stab 1" CTS/CTS	Riser, 1" CTS Steel Anodless	Riser, 1" CTS Flex	1" Prefab Meter Set	Bracket, Wall Type 6"	Wall Mounting Hardware	Note: Footage Column is for wire and bine only. Since each item,
Qty./Ft.														ofumn is for
Item Number	1317	47	1759	1662	1731	354	918	634	31.4	718	520	315	846	Note: Footage Co

Re 3-9.17	8	4	Subcontractor DM TEX CAU ATTI	5 0	
installed Date	# of Laborers	Hours on Job	Subcontract	Hours on Job	
Utility Company:	X		werterfals with graving From:	Mentor	×

Service line Material List

	The same of the sa						
Item Number	Oby/Ft.	Type/Size	Manufacturer	Mfg. Date	Lot Number	SOR	SOR DE Tuno
1317	as:1	PE SHOW I'R PC CT	D.C. D. 0.	7-1-3			2
47	-				60000000	-	9047
	253	LAGUATE 1/WIRE					
520		In the Fab into Cit	172.02	21,0	A CONTRACTOR OF THE PROPERTY O		
246		MTG 14440 WAY					
2.0							
9 1		7777)		11-13-14	71200	_	2 40/
		A020te	(S) February	11-02-14	546.40		2
וירון					3.9		
		ンとして	のもりような人	3-15	325012		2006
ارچ ا		EFV FOO	Pean Atex	ナリーとしと	しない。このでは		
							400
فيورث كبار فيدار بأراب بسماء المساول فالمراج المراه							
The state of the latest and the state of the							

Common 1" CTS Yellow 2406 Items

PE Type	-			שטויכ	3070	2400	2400	0047	2400	2400	2400		
SDR													
Lot Number	0												
Mfg Date													
Manufacturer													
Type/size	Pipe, PE 2406 1" CTS	Standard 12 Gauge Tracer Wire	Tracer Wire Splice Kit	2 X 1 E/F Tap Tee W/ EFV 800	4 X 1 E/F Tap Tee W/ EFV 800	6 X 1 E/F Tap Tee	EFV 800 Series	Coupler, Stab 1" CTS/CTS	Riser, 1" CTS Steel Anodless	Riser, 1" CTS Flex	1." Prefab Meter Set	Bracket, Wall Type 6"	Wall Mounting Hardware
CITY-/P.C.													
Hem Number	1317	47	1759	1662	1731	354	918	634	314	718	520	315	846

2.9.1	8	70	DM EXCENDETING	00	
nstalled Date	t of Laborers	Hours on Job	ubcontractor	lours on Job	
-	46	-	<i>S</i>	•	
	Y		HOLL WAR	;	X
ry company:	Brainavel	Materials Withholm	Monto		

Service line Material List

Item Number	Qty./Ft.	Type/Size	Manufacturer	Mar Data		-	
1217	12 /	C		IMIR. Date	Lot Number	SOR	SOR PE Type
	3	TE SHOW I'M IPC CTO	Pol. P. P.	カニーツ		-	
47	77	(1 C. De. 1 /					901-7
Š							•
37.3		The Tab Att Ct	17001	カニの		-	
٥		MIT LIAM					
		200 C C C C C C C C C C C C C C C C C C					
9		CUSER	2	7 (] .			
				71-13-14	712001		7007
		140 Apr 6	ה ה ה	21 27-11			
726		C. C			0 163	_	
		2// 1/2	のでとんると	21-12	かったった		2010
2010		1757 FB2	7 3			+	0001
			ころを	ナンリアくの	プイフトライフ	_	2006

		PE Type		2406			2406	2406	2406	2000	2406	2406	2406	2406			
		SDR															
		Lot Number															
06 Itoms	AAGo Dobo	MIR Date															
Common 1" CTS Yellow 2406 Items	Manufacturar	I Supranion in the supr															
Commo	Tvpe/size	200000000000000000000000000000000000000	Pipe, Pt 2406 I" CIS	Standard 12 Gauge Tracer Wire	Tracer Wire Splice Kit	2 X 1 E/F Tan Tee W/ FFV 800	4 X 1 E/F Tap Tee W/ EFV 800		201 day /2 2 1 2	Erv oud series	Coupler, Stab 1" CTS/CTS	Riser, 1" CTS Steel Anodless	Riser, 1" CTS Flex	1" Prefab Meter Set	Bracket, Wall Type 6"	Wall Mounting Hardware	PIRANTE Quie Constitution
	Qty./Ft.																
	Nem Number	1217		47	1759	1662	1731	354	918		634	314	718	520	315	846	

Note: Footage Column is for wire and pipe only. Since each item could have a unique Mfg Date and Lot Number, each item MUST have its own entry line

Ohio Rural Natural Gas

* CV2-00

Critical Valve Inspection Report (§192.747, §192.181)

Inspection Frequency: Once every calendar year, NTE 15 months

	CANIDA	DA DE			There	
 .am Name_	CHICKLE	KI) - VOW	リ	System Number	T1-602	
	17371	CARTER	PD	I EDNI	Onto	ET , 1 T HOMELEN CONTROL OF THE STATE OF
*	16 16		7-12	T KUN		

Valve #	Val	ve Desc	rijation		Was Valve Accessible? Y/N	Was Valve Partially Operated? Y/N	Inspection Date	Prev. Inspection Date	Inspected By
EN 17:001	BALON	211	FULL	Port	1 }	y.	02/4/16	9/02/15	DAVE STANISH
							[/		
						·			
	!				,				
<i>;</i>			· · · · · · · · · · · · · · · · · · ·						
		(

Comments:

PINH 08A-009-0-025-0

Ohio Rural Natural Gas

Critical Valve Inspection Report (§192.747, §192.181)

Inspection Frequency: Once every calendar year, NTE 15 months

System Name DOWO

System Number 77-002

			_	_	 		_	_	 		
Inspected By	0.07	1 STANSA									
Prev. Inspection Date											
Inspection	Adloh.	01001011									
Was Valve Partially Operated?		15.7									
Was Valve Accessible? Y/N	VES										
Valve Description											
Valve #											

Comments:

OHIO RURAL NATURAL GAS REGULATOR & RELIEF VALVE INSPECTION REPORT (§192.739) System Name: DOWD System No: TI-OOZ Station Name: CARTER RD DOWD Work Performed: ✓ Initial Turn-On ✓ Periodic Inspection ☐ Maint Pegulator Type: Town Border District Regulator Service Regulator spection Interval: Annual NTE 15 mo. 120 months ☐ 24 month pressure check only** ☐ 24 months \Box 60 months ☐ Other_____ PRESSURE RECORDER CALIBRATION SECTION Recorder Type: ☐ MiniMax ☐ RTU ☐ Recorder ☐ Transmitter/Transducer Serial No: Model: Range: Pressure 0% 10% 50% 100% Actual Test (PSIG/F) In-Test Out-Test % Error In % Error Out REGULATOR SECTION Make: FISHER Model 627 R Orif. Size: 18 Spring Color / Range: 15-40 Make: Model Orif. Size: Spring Color / Range: ☐ Control ☐ Monitor ▼ First Cut ☐ Parallel ☐ Control ☐ Monitor ☐ First Cut ☐ Parallel Station Inlet Pressure: 263-77 MAOP Inlet/Outlet: 25 Station Inlet Pressure: ____MAOP Inlet/Outlet: ___ Point (as found): Flowing: 25 Lockup: 31 Set Point (as found): Flowing: Lockup: ____ Set Point (as left): Flowing: 25 Lockup: 31 Set Point (as left): Flowing: _____Lockup: ____ **Billing Pressure P.F. S.N. Confirmed With Billing? \(\Delta\) YES \(\Delta\) NO \(\Delta\) YES NO N/A YES NO N/A Regulators checked for leakage Control lines properly valved -Regulators fully stroked П Control lines adequately protected П П П Tight lockup achieved All bug vents installed and clear Regulator disassembled Inlet & outlet station valves operated П Regulator rebuilt Station adequately supported \Box Pilot condition checked Station adequately painted П П П RELIEF VALVE SECTION Make: Fisher Model: 389 H Make: Model: Pressure Set(as found): Pressure Set(as left): Pressure Set(as found): Pressure Set(as left): Was valve partially operated? ✓ Yes □ No Was valve partially operated? ☐ Yes ☐ No Does valve have bubble tight shut off? Yes No Does valve have bubble tight shut off? ☐ Yes ☐ No Are there any changes to the system that would affect the original calculations? \Box Yes \Box No

Date:

If any problems or abnormalities were found, please explain:

Ferformed By: _____

Starting Point: FQ1y Distance from nearest intersection	Farm TAD Sand Loam Clan Item Pipe E	WEI? Clay	OUT TO TO Manufacturer	שמיט					
forde) Start at 0+00 Distance	n oer	<u> </u>	Rock						
Start at 0+00 Distance			Manufacturer	Main Line or Service Line	Service Line	Install Method	Trench	Bore Insert HDD	
2 3 3 4 4 4 5 5 6 6 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9				Part#	Type/Size	Mfg Date	Lot Number	SDR PE	
2 3 4 5 6 8 8			Con T AAL	650073V	K in	4/11	254767	115 76	_
4 4 6 6 7 7 8 8 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9		-	(* S + D M)	(67)	2.50	1756	176031	8	1 10
8 2 9 8		_	3,001	60,000	8	2	12 38(6)	3	_
8 8 8			CCN TRAL	6410025	4in X Din	11/13	30 9809	185	RED
8 0		+	7000	10.13.75	7.77	7117	2011		
6		-	CCNTKAL	07 14 58	7.7	6	2075/1	15%	20
			CENTRAL	6412158	4in	6 114	32 4371	S. S.	60
10									T
11	<u></u>								-
12									_
13									_
14									_
15									_
16									_
17									_
18									_
19									_
20									_
21									_
22									_
23									_
24									7

Note: Footage Column is for wire and pipe only. Since each item could have a unique Mfg Date and Lot Number, each item MUST have its own entry line F35

	3.6.12		70	Subcontractor DM EXCAUATILE	Ø		
	Installed Date	# of Laborers	Hours on Job	Subcontractor	Hours on Job		Complete Management
II+Bity Constraints		Brainard	Marteriale Without course Course	Alexander Control		×	

			TOT INITIALIAN TOTAL TOTAL	797			
tem Number	Qhy/Ft.	Type/Size	Manufacturer	Mfo Data	Loop Missonsham	686	10 1.00
17.7	Ć	O		.0	LOL MUITUEL	Z Z Z	SUK PE 1ype
2	200	TO SOLD OF STREET	Poly Pipe	こし	C CCCC 2	-	70976
47	200	Bange T/Wine				-	4100
250		1 Car Tak Lat. C.4					
			7031	ナーロ	i		
3		MTG HARDWARE					
37.00			,				
		וכויליבע	722	トーニーコー	712 0011		1000
		And And		11 30			0012
1				61-02-31	59657		
100		ナ/ナーゲナー	CLEVEN	772	2000		, , ,
2,2					5.62015		アのガー
		CO-1 V-1 II	resmasent	3-3-14	てかとつとかで		7000
							200
						_	

Common 1" CTS Vollow 2406 te.

	re Iype	2406			1	2406	2406	2406	JAAG	200	2406	2406	2000	2400		
900	Ž				1	1				3						
I of Missher	FOLIMINITES															
Mfg Date																
Manufacturer													,			
Type/size	Pine. PE 2406 1" CTS		ביייים די רפתפי ומרפו אווני	racer Wire Splice Kit	2 X 1 E/F Tap Tee W/ EFV 800	4 X 1 E/F Tap Tee W/ EFV 800	6 X 1 E/F Tan Tee	200 11 200 211	cry guo series	Coupler, Stab 1" CTS/CTS	Riser, 1" CTS Steel Annelless		Kiser, 1" CIS Flex	1" Prefab Meter Set	Reschot Mail Tama Cit	846 Wall Mounting Hardware
Qfy./Ft.																
Hem Number	1317	47	1750	CCTY	1662	1731	354	918		634	314	710	0 40	520	315	846

EXCANATING 83-15 12-12-Ø DM Subcontractor **Installed Date** # of Laborers Hours on Job **Hours on Job** Materials Withdrawn From: Utility Company: Brainard Mentor

Service line Material List

Item Number	Oty/Ft.	Type/Size	Manufacturer	Mfg. Date	Lot Number	SDR	SDR DF Tuna
1317	83	PE SUOG I'RIPC CT	Dol. D.a.	7		\$	and a second
41	B	(25 Me T/ Wille		2	5170000	=	7.40%
Sro		I'm Pre Pab MTz C+	(1700.)	10000		+	
Sac		MTG HAROWARE					
314		Bus Ere	Pull	11-12-14	א ששירו די	+	1000
		A0201-	アカカラ	11-22-14	5CL 72		000
12131		4×1 7/70	CEUTIVAL	2-15	ろうたつこと		3000
2016		GEV SOO	Gens Feat	3-3-14	しょうとん		2000
						-	
						+	
				•		-	

Common 1" CTS Vellow 2405 Home

PE TVDP	т	2004		3406	2400	2400	2400	74Ub	2406	2405	200	2400			
SDR	_	+		-	<u> </u>	+	+	+			-	+	1	+	_
Lot Number															
Mfg Date															
Manufacturer															
Type/size	Pipe, PE 2406 1" CTS	Standard 12 Gauge Tracer Wire	Tracer Wire Splice Kit	2 X 1 E/F Tap Tee W/ EFV 800	4 X 1 E/F Tap Tee W/ EFV 800	6 X 1 E/F Tap Tee	EFV 800 Series	Countar Grah 1" CTC/CTC		Kiser, 1" CTS Steel Anodless	Riser, 1" CTS Flex	1" Prefab Meter Set	Bracket, Wall Type 6"	Wall Mounting Hardware	
aty./Ft.															A
Rem Number	1317	47	1759	1662	1731	354	918	634	24.4	670	718	520	315	846	Markey Residence Co.

Company OHIO RULES NATUR 1 GAR 2.

Odor/Gas L&R Reference No.

Project Name or Address LywTZ.

Inventory Ticket No.

System#:

Date: 1-31-15

WO Number:

% OF Hallock Young -- NOUTH ON WEST SIDE OF LYNTZ

HDD 911 ECL OF NEWTON TOMLIDSON RD -> EAST THEW NOWTH ON LUNTZ Install Method Trench (Bore Insert (Underline/Circle) Main Line or Service Line Rock Slurry Sand / Loam Clay meanest intersection) Starting Point: (Distance from Soll Type

	(Underline/Circle)						(Underline/Circle)	Lougen	Undernne/circle)		ı	
	Station	2	ltem	Pipe	Manufacturer	Part#	Type/Size	Mfg Date	Lot Number	US Number	SDR	PE
041	Start at 0+00	Distance	Number	Footage								Туре
4-1	1 0+32	7/5	90	1741	ock yours	1	NOCTH THE	to Line	ON Hallook You're	lock You	ĭ	
. 4	2				Courtinue	70.	אסמי אבר אסטר	*		-	-	
<u>'''</u>	3 05+74	26UCL		449	PolyPipe		LASTIC PIPE (2CT 14	OCT 14 6099008		13.5	3406
1	4	14.		Andrew .			MALKEL POST	\	\	\	\	\
<u> </u>	5 14	~		Same of the same o	CENTRAL	575008	4" FUS/CPLING	4-14	316205	US 1790		2406
-	10+41	2 Juck	ą	410	Pol. Pipe		4" Prostic Pipe	567 1 4	4009 500h		13.5	7406
	7	1,	\$	1			M/P					
	60	ī		1	CENTRAL	575008	4" FUS/CLPC	カーナ	316205	U4 1790		3000
J,	9 15+29	ų	-	488	Pol. A10C		4" PLASTIC PIPE	*I-170	6099008		13.5	2106
Т	10 11	11		1			M/O.					
Ц	11 11	1,8		1	CELOTRO C	575008	4" FUS. /CLPG	ナーフ	316205	US (790		2406
	12 20+ 04	21 W.C.		415	PolyPioc		4" PLASTIC Pioc Oct 14	の十三	6099006		<u>ب</u>	2400
П	13 11	h.		1	~							
М	14 14	3.t		1	Central	575008	4" FUS. CLPG.	4-14	31625 W1750	UN 1790		2000
П	15 24 + 6.8	22 well		404	Poly Pipe)	4" PLASTIC APP NOULLY	Nov-14			13,0	2406
77	119	ĭ		١					4			
7	17 · 11	14		١	CENTRAL	575008	4" Fus. CLPC	4-14	316205	Us 1750		2406
	18 29 4:34	21 100		4/2	Poly Pipe		4" PLANTIC AR	アーフのハ			13,5	307C
77	11 61	1 (١	1 `							
17	20 11	77		١	CIENTRA	\$75008	4" Fur. Cue	4-14	316205	Us nso		2406
1.4	2131474	20 Va		240	Po LyPipe		4" PLASTIC REC	N-100			13.5	2400
1.41	22 1.1	7-		١	(טייט)	CLEEK)						
371	73 h	11		١	CENTRA	575008	4" Fus. C.P.	<u>م</u>	316205	02C12U		2406
231 201	24 36+64	2.1 wet		(C	PoluPipe		4" PUDSTLE PIPE	No7-14			اع.دا	13.5 2406

Note: Footage Column is for wire and pipe only. Since each item could have unique Mfg Date and Lot Number, each item MUST have its own entry line

P27

Material 'ist-DIMP

Wun Order Number 18-2015 Sy "#: T1-005

Project Name or Address (0970 WILLIAMS Rd. Rick Barn Williams Rd

76' EAST Floom S/L of WILLIAMS RO + CASCADE RD. 147 41° 40' 52" N LOWER 81° 11' 59" W TAP LOCATION

Sand Loam Clay Rock Slurry

nearest Intersection)

Soll Type

(Distance from

Starting Point:

HDD WFI? - Withdrawl From Inventory? Type Install Method (Trench Bore Insert SDR UMC 5219-03/ Lot Number Mfg Date 3015 8-13 " Sch 86 Pipe 900 Fitting 1. TOP-12,00 trec 2" Valve 300# 2"to 1" reduce 2"tol" preduced Type/Size Drip Both 40° Fitting Main Line or Service Line Part# 15 PB Manufacturer MUELLE weldbeno Welchond TO1-635 Bolon Pipe WEIS Footage Pipe 30 " Number Item Distance ひ Start at 0+00 Station 0+00 2 0 501 9 0102 3 040/ 5 0+01 6 0401 8 Otol 4 0+01 7 0401 (Circle) meti 10 11 12 13 14 16 18 17 19 20 21 22 23 24

Note: Footage Column is for pipe only. Since each Item could have a unique Mfg Date and Lot Number, each Item MUST have Its own entry line

Material st-DIMP

070 Company

Inventory Ticket No.

Sysi

Odor/Gas L&R Reference No.

WO Number 8-1 Date Project Name or Address nearest intersection) Starting Point: (Distance from

WFI? - Withdrawl From Inventory? HDD Type 뀚 SOR Insert Bore W PR 907519 WPB 907519 WPB12305 UNC SA BORG Lot Number WPR12305 Trench Install Method Mfg Date 8-13 3015 2" Value 300 # "tol" reduce 2" to 1" 1ccbert 1"+20 fre Type/Size 1" pipe drip herth Pipe Main Line or Service Line 20,0 11,006 (Circle) Part# Slurry Manufacturer Balon weldbend Sch 80 22 Weldbear Sch 90 Mueller 7A7-925 Rock Clay WEIS Footage Pipe Loam 1/1 3 Number tem Sand Distance ス Start at 0+00 Station Soil Type 7 0405 040 5 0108 90+06 0400 3 0+01 8 0 +05 10 0 40 6 2 000 (Circle) meal 11 12 13 14 15 16 17 120 19 20 22 23

Note: Footage Column is for wire and pipe only. Since each item could have a unique Mfg Date and Lot Number, each item MUST have its own entry line

Material L. -DIMP

Ohio Rural

Gas, Co-Op Natural

700-5100 Work Order Number Project Name or Address

Starting Point:

(Distance from

1-7-2015

X 2294423, 4907 Y 739828,8598.

MENTAR, OHIO

4000

PINH 168060BOODO

03.00 Main Line or Service Line SUGAR BUSH & REDOOK - YEAST Slurry Rock Clay Loam Sand nearest Intersection) Soll Type

Insert Install Method Trench Bore

HDD WFI? - Withdrawl From Inventory? Type 7017 3406 2,406 30 WA 2406 72 SDR 110:000002422639 317993 NRD 393241ED WRD 390241EB 311181 Lot Number 000583 Mfg Date 8-15 11.13 2-1 1-1-11-13 11-13 11-9 11-9 2" Purge CAD 2" Pince Cap Type/Size 2"Coupling 2" P'PE 2" P.P. 2" += 5 31/1301 (Circle) 6912125 6912109 5760030 6912107 59152 Part# Central Dura-line Manufacturer Central Dura-line Durd-line Croted C/3+c/ Central **MEIS** Footage 335 Pipe 134 509 Number Item Distance ぴ Start at 0+00 0402 Station 0+00 1734 5 64 43 4 1 4 501 61134 7 1+34 8 4/269 (Gircle) 11 13 12 13 14 15 16 18 19 20 17 22 23 σ

Note: Footage Column is for pipe only. Since each item could have a unique Mfg Date and Lot Number, each item MUST have its own entry line

Critical Valve Inspection Report (§192.747, §192.181) Inspection Frequency: Once every calendar year, NTE 15 months Ohio Rural Natural Gas

System Name SUGAR Bush DR.

System Number 51-002

d By	150		Γ	T	T	T	T	T				
Inspected By	15/2015 0, Stonet											
Prev. Inspection Date	=											
Inspection	02/05/16											
Was Valve Partially Operated?		_										
Was Valve Accessible? Y/N	>-	-										
Valve Description	Coloc											
Valve #	CN7-001						:					

Comments:

How Install Soil SDR NOTE: Footage Column is for wire and pipe only. Each component must be listed on a separate line in the order it was installed. Complete information for each column. Odor / Gas L&R Ref. No. PE Type WD Number Lot Number 7/200 GPS Lon/Lat 18-15 11-11-8 Mfg Date Project Name or Address PROBLEKT HOLLES 9230 SUGARBUSH MENTOR CASO 44060 PARSTIC " Flex Type/Size Main Line or Service Line 2406-2705 (Chole one) 59652 o iscreet Manufacturer ESTER **MEIS** Footage Number あびた Pipe Depth Start at 0+00 Distance Inventory Ticket No. 5 (Distance from neovestime) Starting Point: Installed By F35 11/28/12

In.

학

Q

 \sim

임

0

11

12

16

12

14

1

Material List - DIMP

System #:

məti

Systemas

Inventory Ticket No.

DUCK CREEK

Project Name or Address

Odor/Gas L&R Reference No.

~ 4

40

Company OHIO RURAL NATURA

WO Number:

Date: 1-19-15

Duck CREEK

40

WEST SIDE

20

1200x

00

ST. RT.

Starting Point:

Install Method Trench (Bore)

Main Line or Service Line

ï	- 8		
	fUnder	Mfg Date	•
	(Underfine/Circle)	Type/Size	
		Part#	
		Manufacturer	
		Pipe	,
		Item	Annual Attended to the control of th
		ಕ	1

Slurry

Rock

Clay

Loam

Sand

Sall Type

meal

N

ൻ

4

ú

h

60

ń

3802 SCL ST. RT 18

meorest intersection)

(Distance from

(Underline/Cir	
Underline/Circle)	-
(Unde	

		ь-	_	-
Insert			SDR	
Trench (Bore)		110 11	OS NUMBER	
D	Inche	I of Mumber	i validati	
install Metho	derima/C			_
Inst	(Car	Mfo Date	6	
Mindedinatorial	Company Cardes	Tvpe/Size		
		Part#		
y India	ſ	turer		
3		Manufac		
		Pipe	Footage	
		Item	Number	
	700	\$	Distance	
(Underline/Circle)	Charles	Station	Start at 0+00 Distance N	

HDD		R	F
Insert		SDR	
ch (Bore)		US Number	
Wethod Trench		Lot Number	
Install N (Underlin	H	Ming Date	
(Underline/Circle)	- 10 mm	lype/size	
	Dartit		
	anifacturer		
	Pioe M:	abea.	2924
	Item P	<u></u>	
	ಕ	Distance	
(Underline/Circle)	Station	Start at 0+00	

	3	ij	T								1	٢	9	\	-	
i omenme/circle)	Mfg Date Lot Mumber											1,0000		7.7.7	3	
Louise	Mfø Date	6				10 /13	0	0-12	2			D + 10		4-14		
	Type/Size			A 121 (1)	BEGIN LAN	24 Proce Or		4x2 PENJOER		Foot		- 4" 7-45 FIG 7:00 Oct 10 - 7-66646	,	CENTRAL 57 X 10008 4" FURIOR C. 8/1 4-14 3:1-4/1		•
	Part#		21 10	Т	4								1	27 27 0008		
	Pipe Manufacturer		9/ ST. 12 10		-	してのながった。		-			0 0 0	Ser Line		しゅうしんかし		
	Pipe	Footage	1	١		1	,	\	1	\	000	400				
:	Item	Number														
70	<u>5</u>	Distance	2, 10, 11,	7 7 8	イグがイ	11			-		23 (1001)	3000	-			
Chantan	STATION	Start at 0+00 Distance Number Footage	: 04-00 gtm:	30' = 5'	30 T U L XIGUEL	E. 10	20.	20+03	4	:	And 11 12, 12, 1	-				

2000

Type

2406

13.5- 2406 2406

02/100

\$1 200 4-17 4" PLASTIC PIPE M. POST 4" F/61.PG M POST 575700A CENTRAL Polypipe 5.8 25 WCL 69 + hh | 6

5757008 Poly Plaz 462 26 WCL Ξ

7

9

11

m

Central _ 12 46+ 31

2406 7000

091160

316205

4-14

si d

8005509

Oct 14

4" PLINITIL PIPE

4" F/CLPC

2406 2406

13.5

A002509

4" PRASTIC PIPE OCT 14

051100

316205

4-14

M. Post

24.06 2406

اع دا

3005507

001750

316205

4-14

M. AOST

2406 2406

13.5

\$00550 g

316205

95L109

CENTRAL Poly Pier 4100 1 = = -53+97 = --100 100

51

16 17 18

4" Puster Pire Oct 14 4" PLANTIC PIPE 4" F/CLP6 4" F/CLPG 575700& 5757006 CENTRA AlyApr Blyfipe 459 **-**25mcr 25 wa 7 Ξ 58 + 10 g 62+67 =

Note: Footage Column is for wire and pipe only. Since each item could have unique Mig Date and Lot Number, each item MUST have its own entry line 6099006 Oct 14 4" PLASTIC PIPE PolyPipe 478 25Wa マナナける

2000

13.4

2406 2406

001790

316205

4-14 Oct 14

4" F/CLP6

5757008

CENTROL

=

3 5

22 23

21

81 8

7

24

M. Post

6099008

d

company Office Rucal Natural Gas

Odor/Gas L&R Reference No.

Inventory Ticket No.

CREEK ○ならら Project Name or Address

Date: 1-19-15

WO Number:

CAN'E

Deck.

O

South on WEst Side שבר בדי תד, ול % St. DT. 18 3802 '

Slurry Rock Clay Loam

Sand

Soil Type

meanust intersection)

(Obtance from

Starting Point:

Main Line or Service Line

Insert Install Method Trench Bore

유

2406 240% 2406 2406 2406 2406 2406 2406 2406 2406 Type 2406 (1. 1. 13,5 3.5 13.5 13.5 13,5 SDR 231500 **US Number** 00 5182 281200 005182 005182 281500 32,7042 327042 8006609 327042 200 550g 8006509 327042 Lot Number 8005509 327042 9000009 327042 (Underline/Circle) Mfg Date 4" RASTICPIPE DGT -19 4" PLASTIC PIPE Oct-14 4" Rashe RPR OCT. 14 41-7 6-14 4" PLASTIC PIPEL OCT 14 51-9 8CT 14 6-14 4-1-9 6-14 4" PLANTE APE 4" F/CLPG 4" F/CLPG 4" F/CLPG F/CLPG 4" F/CLPG 4" F/CLP6 M. Post M. POST M. POST A - Part Type/Size M. POST (Underline/Circle) 4 5757008 S757008 5757008 STSTOOR 5757008 5757008 Part# Poly Pipe Manufacturer Certasi PolyPipe PolyPipe CENTRAL CENTRA PolyPipe CELTRA CENTRA AlyApe CENTRA 458 Footage 503 507 Pipe 457 427 Start at 0+00 | Distance | Number | tem 25wcc 26 veck 24 wa 25 WCL 2 7 = 7 7 2 ă 3 (Underline/Circle) いっナロと 72+48 81+32 らしもなど 86+39 90+97 a 10 Station _ -7 --11 H 135 7 3 16 meri ന ıΩ ø 00 cn. 9 Ħ

Note: Footage Column is for wire and pipe only. Since each item could have unique Mig Date and Lot Number, each item MUST have its own entry line

Ppru 1

2406

281500

32,7042

13.5 2406

300 5509

OCT : 14 6.14

4" PLAITIC P.PC

N. Post

4" F/CLR

3001212

Central

_

99+63

21

-

7

23

١

Poly APC

428

467 | PolyAre

2500

24 104+30

N. Post

13.5 2406

3005509

4" PERITICAR DOCTIA

2406

1815 CO

13.5 2406

3005509 327092

OCT 14 6-14

PLASTIC PIPE

4

PolyApe CEMPRA

438

2511

95+35

8

13 8

=

Ξ

= ---=

M. POST

4" F/CLPG

5757008

Material List-DIMP

COMPONYOHIO RURAL NATURAL GAS

Odor/Gas L&R Reference No.

Inventory Ticket No.

System#:

21-6]-\ patec

WO Number:

South on WERT SIDE OF Dick CLEEK ST. (CT. 18 -> Project Name or Address DUCK (ROSS

ST. RT 18 3802' SCL meanest Intersection)

Starting Point:

(Okstence from

Insert Install Method Trench (Bore) (Underline/Circle) Chain Line of Service Line (Underline/Circle) Slurry Rock Loam Clay Sand (Underline/Circle) Soll Type

HDD

1	from the franchist con in						(Supering Circle)	(LANDENH	(myon was/chas)			
		중	Item	Pipe	Manufacturer	Part#	Type/Size	Mfg Date	Lot Number	US Number	SDR	표
əil	Start at 0+00	Distance	Number	Footage								Type
린	104 ±30	25/0ct		1	Central	575700B	4" F/CLP6	4-9	327042	005782		2406
cl		14		١			N.Post					
ൻ	108+63	1.		433	PolyPipe		1 4" PLANTIL PIPE COTT. 14	QT- 14	8006509		135	2406
4	11	'n										
ம்												
ø												
7												
60												
6												
2												
뒤												
H												
9												
3												
1					4							
16												
83												
원												
8												
21												
22												
2												
74												

Notes Footage Column is for wire and pipe only. Since each item could have unique Mig Date and Lot Number, each item MUST have its own entry line

Materia, St-DIMP

System#:

Company ORNL

WO Number Odor/Gas L&R Reference No. Date 7325 Reynolds Rd Project Name or Address Inventory Ticket No. Starting Point:

HDD Install Method Trench Bore Insert Main Line or Service Ling Slurry Rock Sand Loam Clay nearest intersection) (Distance from Soil Type

ventory?	핊	Type											1													
From Inv	SDR																									
WFI? - Withdrawl From Inventory?	Lot Number		400000 42 M34		000002420825																					
(Circle)	Mfg Date		10-27-14		56																					
(Circle)	Type/Size		Phych	3d"/		Metol Boo																				
	Part#		71200-9		71200-9																					
	Manufacturer		E18ter	A14-Pipe	Elster																					
	زا:	M																								
	Pipe	Footage		155				IP.1																		
	Item	Number																								
	7/5	Distance																					•			
(Circle)	Station	Start at 0+00	0400	otol	1+ 56	14 5%																				
	w	əţl	1	7	ന	4	5	9	7	∞	6	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24

Note: Footage Column is for wire and pipe only. Since each item could have a unique Mfg Date and Lot Number, each item MUST have its own entry line

Material 'ist-DIMP

Www.norder Number 64-2015 Sy - m#: ORNG [1-00]

11-11-15

Project Name or Address

Starting Point:

800 OAK St Lake-Gedund Recovery Court

HDD WFI? - Withdrawl From Inventory? 4710 Type PE Insert SDR VAPPTATANA 5 Install Method (Trench) Bore 58/4000000 Lot Number Mfg Date 3-15 11-17 2/0E 3-15 [Para tap 2" tansition 2" transition Type/Size Main Line or Service Line (Grate) 75905 75905 Part# Slurry Manufacturer Doid-Line Bid OPt 8118 Rock ンがし Clay **MEI**5 Footage Loam 165 Number Item Sand Start at 0+00 | Distance 5 nearest Intersection) (Distance from Station Soll Type 1 0400 1+66 0401 3 6+01 (Grde) meti 4 10 14 15 16 17 'n 11 21 81 9 **D** Ó 18 19 20

Note: Footage Column is for pipe only. Since each item could have a unique Mfg Date and Lot Number, each Item MUST have its own entry line

21

2 2 2

90# Services Line

OF CHILD

p-d-

- E	3
	14 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
WEST No.	
Company O HIO RULAL NATURAL Odor/903 1888 Reference No.	
Company Odor/50a	NCL OF HA Note of HA Note of HA Note of HA State of HA MONtanher A State of HA State of HA MONtanher MONtanher A State of HA State of HA MONtanher MONTanher MONTanh
	2-10-15 We lock the lock that Sink of Mile Pate Lock Lock Lock Lock Lock Lock Lock Lock
IMP	A For CLAS A CALLAR A FOR THE CALL CALL CALL CALLAR A FOR THE CALLAR A FOR
Taterial List-DIMP	Start Can 100 & Sold Start Can Start Can
lateria	The state of the s
	Meavrold Tomaling Fige Manufaciling Float Baly Rock S 147 Footage Manufaciling Footage Manufaciling Footage Manufaciling 478 Footage Manufaciling 478 Footage Manufaciling 478 Footage Manufaciling 478 Footage Manufaciling 478 Footage Manufaciling 601 Footage Manufaciling 602 Footage Manufaciling 603 Footage Manufaciling 603 Footage Manufaciling 603 Footage Manufaciling 604 Footage Manufaciling 605 Footage Manufaciling 606 Footage Manufaciling 607 Footage Manufaciling 607 Footage Manufaciling 607 Footage Manufaciling 608 Footage Manufaciling 6
HAIlack Vo. 1	Loam Gay Rock Itoam Itoam Gay Rock Itoam I
	When the send state of the sen
Systemetr Investory Ticket No. Project Name or Address	Stortlog Paths: (Disminshoun mennst Internation) Soil Type Start at 0+00 Start at 0+0
	Sol 7 4 6 6 4 6 6 4 6 6 6 6 6 6 6 6 6 6 6 6

CA WEST SIDE OF WO Number: Date: 1-31-15 North Hallack Young アイにアイ 0 37 ---Project Name or Address Starting Paint: (Distance from

THEN MOUTH ON CHUTZ EC. OF NEWTON TOMINGSON RD -> EBIT Main Line or Sequice Line Slurry Rock Loam Clay Sand merces interestion! Soil Type

Insert install Method Trench (Bare)

Type 뿚 읖 뚬 (Unidenting/Circle) Item

		S			ĭ	-	ď				1	2			2			[]
		US Number			10 V 305	•		,		1151750				UK 1790			(k 1790	1 1
(Underline/Circle)		Lot Number		Mark Hal	The last		6099008	\		314205 1151190	I MODELLE	20051		31610x Us 1750	9005500 +1-1.50		312 205 1k 1290	60999d8
(Condex)	1.45	Mig Date		1 1 1 1 1 1 1		5	100 T	\		4-7	11 1	1		さずさ	41-1-70		1 - 1	DC FIT
(Underling/Chole)	Tumore	apple And I		マーニューベード 子の日 さしのび		אסקו לי אים הסקר	THE GOOT IN GOODS	MALKIE POST	41.0	T TVICELING	Clarity Code Section 14 14 14 14		4.16	- 1-US//2.LPG	F Pige	- 1	4 145 194 46	4 P. 45+116. P. 10 C 10C-14
	Part#			- 1	4	2			0200	- 1				2 Z50@K			2 POST 4	
	Mamufacturer			THE MOCK YOUNG	CONF MASS	dag 010	34134		Cartino A		TOTAL PIOS	all age		4c-8 0.1 h	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	-	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	2017
	PIDE .	Footage	17.4			990	1	V	1	Ann	Di i	1	1	979	0	ľ	i i	2 \
	Item	Number	20							Г	4	>						
	3	Distance	C/C			27.01.10:	-		<i>z</i>	A A L. CAF	- TOTAL	1	ĩ	=	3	=	2 Prodes	=======================================
L		Start at 0+00	C 1. 312			4 18 - 18 13 A		بد ند	Z .	10 + U.T. 721.1A		=	1	(4+28	11	12	2h+ 04	1
	ULIE	37	⊣	r	4	m	प	L	n	6	P	J	60	en en	3	뒤	검	

2406

2406 7 2406 かかのかん

بو

中の大で

Ul 1750

3 6105

1-1-

GLP. G.

2

STSade

Centrant

Pols P. pe

400

22 w.c.

+ 63

15 24

=

= 2

97 99 뙤 20 7 22

-=

Ę 3 フューフの一流

7 A Pre

かっちゃ

اري درم

2406

Uinto

31620r

are a

Ť ¥

STSook

Central

Fold Pire

18.A

21 wer

1.62

-

11- Cal No.

HIL HR

るという

33.57

2406

Js 1750

316205

_

5750087

CENTRA!

Poliphoe

240

2.0 Max

有型十 4

ŀΫ́

_

<u>-</u>

CALEBIA.

CLORA

Z-73

240kg

50

905%

7040

2406

2406 4106

> 13.57 12.57 Note: Footage Column is for wire and pipe only. Since each frem could have unique hits Date and Lot Number 1995, item MUST have its own entry line いたころ 316 205 4 2014 5716001 CENTRAL 2.11/21 ⇉ 30+08 ₹

Ppr-1

Inventory Ticket No.

Systemat:

8
6
-466
170
- 4
-
-
. 5
4000
- 90
90
45
-
9
20

4

Company O HIS RURAL NATURAL GAL	Odor/Gas L&R Reference No.	Dute: 2-10-15 WO Number:		C NORTH SIDE OF HALLS, V.	TAPI CO HINDS THE PROPERTY OF THE PARTY OF T
Get AVO.	Project Name or Address Hallow	SILITATION TO STATE OF	Storang Point; A Dewto Towler It of	-	911 ECL OF NEWISCHES

		HDD		Type	2106			30/4	پ		3406	<u>.</u>		30/10	-		3045];	20 X		2406	-3		3	i i
•	SANOX	{nsert	SOR		13,5			أسا	=		57	-			3		7 5.51		17 7			13.5 24			13.5 240C	Tal. Cap
•			US Number			9 444	18V [1.05]		05/100		000000				P 100		_	130		01790		-	00179a			Sec. November
	Na J	Mod Trench	Lot Number			0	21000	13 11-70	┿		316200	+	1	256375	+	+	7 14.50	_		31620.5 6	-	٦.	19 203 0	+	1 12	,
-		Underthay Cheek	Mfg þate	-			11-14	-	-	41-17	4-14 31	-	4	4	-	4	-	╄	本	9-4 31	+	+	[7]	4	→ 23 wel	The A. Wall
1			2		79								1.1			=			*	\dashv		+		11-14		
Son Pa	1 2	(Underthrop Carety)	lype/Size	d/d . 15	4x2 Reduced	M/Post	4 P.O.	4" FUS CLPG	_	Pipe	To's C. C.	~	Pipe	4" FUS CLPG	R Par	PIPE	4" Fet O.R.	M/POST	200	FV3 CL63	P. 0.7	113	Port	9Pe	100 a	Parks and I do not have a
NEWTON JOHN IN SON	Edonin Um	tinio)		-C6	T	Σ		203	Σ	4	1	1	4	4	1	4	_	-21		-	43	ø	1 31			Pure Mifre Dark
Tal I	Slurry	72.00						272			800/S/			2787808			\$ 00LSL %	+	2000			800 CSES		3		d have taile
- 1	Rock	Manufacturer		רבאועטאר	-	9 -		TOD LOS	A. Cas	1	-	Dal. Age		EVTCO.	O. C.			D	Central		4APC	4.0	4	The B	NEW AL	ach item cou
בכר סר	AND COMMENT	Pipe			1	C 191	1	1	478 D	7	1	484 D	+		474 0	-	1	441 0	1		318 Po	ت \\\	10			July. Since e
	Loam	Hem	Mumber		-																	+	1-	ľ	9	add plas
	Send		Distance	=	Ξ	19 WCL	=	1	4	=	=	ZONE	Ξ	1,	T.	Ŧ	7.5	Zolvec	=		77.17	= =	N.I.	The state of the s		
	Soil Type	Station	Start at CH-O	S # 912	216+0	17.357	=	2	TI	18	-1	スナーによ	=	-	7 1 +	1	=	E.	=		J		TANT			The second second second seconds second seco
		Ша	11	N	eń	4	Ŋ	-		+			Į,	F	117	3	7				- p					
																		4 40 11	* en ell a se	White the state of	W.a.	÷0,71.	,		-	12.0

Systematic

A
-
0
- 73
- 2
-
- 63
•
2
<u> </u>
E
9
1

Company OHIO PURAL 13 ATURDE CAS

97 von 1		######################################		
		272		
	IN SOM DEADING EAST ON HAILOUK VALLE	2/7		
		17.61	7	HDD
Va Va		2	٩	Insert
rence (2 -	10ck	<u>S</u>
Odor/Gas L&R Reference Na.		que Ect Newton Tombroson (2d - 19" UCL - 19"	4	(Wadenflood Internal Hope Insert Hop
Date: 2-12-15	vermoe.	5 5	5	
Odo	Sek.	ي	Negative in	Variantine/Circles
7	1 2	- U	Prefor	Pante
-17-	2	_	91	
- 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1	14.5	24	whole E.fr.	3
6	2	. CV	g dr Sei	(Writerline/Charles
	1644	1350	Main Line or Service Line	(Cons
	Nos	10	€	
	2	70	Slurny	
	1 Newtow Tombe	leun	tock	Manifestra
72	20	2	Loam Clay Rock	
4272	3	T I	9	Plae
2	34	5	Loar	ltem
or Addre			Sand	ទ
Manne	r Paint: hom	ensections	- 1	Ē
Project Name or Address	Starting Paint: Determenter	Served Adensection)	Sall Type Windenlany Carols)	Station
	_	₩	-7 =	ШE

			_	_																													
		P	Type	ľ		はそのに	2400	10	000																							7	
		SDR			W	ما 2	¥	-	T											+	+									+	+	-	
	A the a to a con-	CO MUMBER		WCL LV	1	7	F 10025	רטי בו פא													+											entry line	
(Wadenhoe/Circle)	Lot Mimbor			10 C C 10 10 10 10	\$004500 A		414.3	305419																								ST have its own	
Chadeno	Mfg Date		7	2 +	10-14	0 14	1	5				+				+			+				+		-			+	•	-		Bach Rens MU	
	Type/Siza		HOWE DISELL AND	-1	J Fresh 1	4 × 2 12 5000	24 DIP		- 1	TO COL																						which with Date and Lot Number, each from MUST have its own entry line	
	731CF		C02-1																													ere unique fi	
Manufachines			100	Palyfipe	A LANGE		1, 1,		!				_																		ABCh Hoon seeded a		
Ploe	Footage	Halida		57.5							1	1				1	1	+				+	-	†	+	+	\dagger	-			nly, Since		
Lterm	Number			1								T				1	1	\dagger	+			-		1	-		+	+	1		and place		
5	Distance	REL	21.12	2007	=	=			1									1	+					-	-		-	+	1	-	in for wire		
-		5+72+	5+78	100	- 7	5+25																								NA WAR	ODERS COLUMN		
LIĘ.	110		ᆏ	n	• [4	ιΩ	u#	r	-	20	65	6	3	픾	175	<u>=</u>	Ä	15	2		ij	9	67	8	2	22	바	24				
																												-	_	_	4		

Innertory Ticket No.

Systema

TINE DINKE

Ohio Rural Natural Gas Lo-Op

Critical Valve Inspection Report (§192.747, §192.181) Inspection Frequency: Once every calendar year, NTE 15 months Ohio Rural Natural Gas

System Name TP ALL I

System Number 51-001

Inspected By	STAMSH									
Prev. Inspection	- Cate									
Inspection	91 5 20	-								
Was Valve Partially Operated?	N.									
Was Valve Accessible?										
Valve Description	2" Ballon ValVE									
Valve #	CV 1-col				-					Comments:

Material st-DIMP

OSair Jas Centil Se. Mentol

30' End of Fracci Court

nearest intersection) (Distance from

Starting Point:

Soil Type (Circle)

Loam (Clay) Sand

Rock

Slurry

Main Line or Service Line

Install Method (Trench) Bore Insert

HDD

				_																						
WFI? - Withdrawl From Inventory?	ЭĒ	Tvne								In the Land	100 CCC															
- Withdra	SDR					T		Γ		7	F					T										T
WFI?	Lot Number		A-105-67	2F - 1533- Pu	1000/	106 7/12 901	1160 326	2 W PRSTNESS!	121 2 2 2 2 2	3.8-592 Intin	1			11 58 A-A 11	77											
(Circle)	Mfg Date	,		8-12	0-12	,	7-13							2013												
Circle)	Type/Size		3" TOP-720 tre	2" Walle 300#	7" F.30 XV "P. P.	900 K. Alm	2" PIPE FROM	900 Fitting	2" Pipe Sel en	O " Value 2000 " 5	Sch 83 10: Pe	2" hilamor House	Sr. 4 80 P.pc	drip- Burle												
	Part#			USA						USA																
	Manufacturer		MucHed	Batton D.	ENelg= X	Malaisia	ENrigex	Maha. A	a/c/din	Ballon	N. son-	Koreh	N:pp/c	Tru-926												
	čl:	ΙM									•															
	Pipe	Footage			587		3		1,1		2,5		, C6													
	Item	Number																								
	궁	Distance		>						}																
	Station	Start at 0+00	00+0	10+0	0+01	0+59	0+54	65 +0	0740	04 60	1940	0+61	1)+0	19+0												
	w	ətl	Н	7	ന	4		ဖ	\rightarrow	00	0	9		\rightarrow	13	14	12	16	17	18	19	70	21	22	23	24

Note: Footage Column is for pipe only. Since each item could have a unique Mfg Date and Lot Number, each item MUST have its own entry line

Work Order Number 61-2015

Project Name or Address

sy. .#: 51-601

Material st-DIMP

Work Order Number LI-2015

Date 9-28-15 Project Name or Address

Starting Point: (Distance from

S, itt: 51-061

Natural Gas, Co-Op Ohio Rural

7001 (enter Se

Menter

Fracci Court

EBB BBB Install Method (Trench) Bore Insert Main Line or Service Line Slurry Rock Clay Loam Sand nearest intersection) Soll Type (Circle)

1	lane)							(Grale)	(Circle)	WFI? - W	Vithdrawl F	WFI? - Withdrawl From Inventory?
ш	Station	ぴ	Item	Pipe	اخ	Manufacturer	Part#	Type/Size	Mfg Date	Lot Number	SDR	PE
əti	-	Distance	Number	Footage	W							Type
린	0400					13 ig ORES		1" Farm 62.	3015			
7	@tol					cloted	75905	2" チャンのキックハ	315	0000003306064	1	
ന	0+01			432		Durd-line	1	2" Polypipe	11-13	11003953411ER		
4	3+39					(entra)		2" 900 Litting				
2	3+39			141		Durd-line		1" Polypipe		N/R0 295, 41 F.B		
9	08 +15					c 18ter	75905	2" trongtion	3-16	00000 230/064/		
7												
00												
თ												
10												
11												
12												
13												
14												
15												
19												
17												
100												
임												
20												
21												
22												
23												
24												

Note: Footage Column is for pipe only. Since each item could have a unique Mfg Date and Lot Number, each item MUST have its own entry line

M~terial List-DIMP

Work Order Number System#:

Project Name or Address Date

Starting Point: (Distance from nearest Intersection)

13/64 Lesoy-Center Rd.

	Soll Type		Sand	Loam	Clay	Rock	Slurry	Main Line	(Main Line) or Service Line	Install Method (hod (Trench) Bore	Insert	유
W	Station	ธี	Item	Olino	E				(Grate)	(Grole)	WFI? - Witho	WFI? - Withdrawl From Inventory?	Ventorv
let1	Start at 0+00	Distance	Number	Footage	SHW	Manufacturer	turer	Part#	Type/Size	Mfg Date	Lot Number	SDR	H
П	0+00					11 80		5					Type
7	1040				1	13/2/		75#	1"TapTer				
m	10+0					Weldbond			2"tol" red secol		BUNCA SONE	1	
1-	040			\int		150/00		いるか	2" Udlyc 300#	8/20	11/2/2/2/2/2/2/2/2/2/2/2/2/2/2/2/2/2/2/	1	T
T	77.0				^	weldben.			24 4014 62 1 221		200000000	1	
$\overline{}$	10.0			2,		11. OrDe	2		, " O . O .		Wr07015/7		
٥	0706					42 th			- ml				
7	0+06			1,2	1	// // // Va			70° titting		3471		
œ	pxq+o			1	1	2 - 2			1" Sch 20'				T
o	0 0000				1	(Jagor)	,		900 Fitting		2000	+	
- 1				7,"		/"Pipe			1. 5.1 80		27.77	1	
	50.40		•		7	701-035							
11					-				arin postie	5102	UMC 52A-037		
17					+							-	
13					+		1						
14					+								
15							1					ig	
16					+								
17					+		1						
18					+								
19					+		1						
20					+		1						
21					+								T
22					+		1						Γ
23					+		1						
24					+		1						
2	Note: East-on Calama				-				-			1	T

Note: Footage Column is for pipe only. Since each Item could have a unique Mfg Date and Lot Number, each Item MUST have its own entry line

Work Order Number Project Number of Address 7.3/6	S ₃ 1#:					Mate	Material st-DIMP	E-DIMP				
Starting Point: Starting Point: Obstance from more in Address Starting Point: Obstance from more thrownesses Starting Point: Obstance from more thrownesses Starting Point: Obstance from more thrownesses Starting Point: Starting Point: Other City Rock Slury Main Line or Service Line Install Method Trench Coty Coty Coty Coty Coty Coty Coty Coty	Work Ore	der Number			ı					Ohio Rural		
Sourting Point: Continue Family Continue Conti	Date Project N	ame or Addr	9-24	-15			of Cent			Gas, Co-Op		
Soli Type Sand Loam Clay Rock Sturry Main Line or Service Line Install Method Trench	Starting F (Distance froi	P oint: m section)										
Start at 0400 Distance Number Footage E	Soil Type (Grde)		Sand	Loam	Clay		Main Line o	r Service Line	Install Meth	Trench Bore	Insert	HDO
0400 0400 0401 Elster Fehrm 730 Gold					III.	Manufacturer	Part#	(drate) Type/Size	(Circle) Mfg Date	WFI? - Withd Lot Number	SDR SDR	Inventory PE
						Big Oats		Farm Tão				Type
## ## ## ## ## ## ## ## ## ## ## ## ##		+				[=\s+0		riser stab 1"ets	8-15-15			
90. wire 90. wire 1"Pely-Place 1"Pre-Fibkinisse Elsev Redopte	_			, 76	1	E IStu		Adapter		827804 E000000		
Elser 1"Pe Fish Hoods See	5			0,00	I	Central		1" Poly - Pipe				
E Sett.	9			2		7.400		4/1				
	7					Eletu		1/10 1-10 Hotel S.R.		1.50,0002		
	0 0					E154W		17 daptel				
11	, 9											
3 4 5 6 7 9 0 1 2 3 4	Ħ	-			1							
3	2											
5 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6	3									-		
6 6 7 8 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9	4											
6 8 8 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9	5				İ							
7 8 9 0 1 2 3 4	.6											
8 0 0 1 1 2 3 4	7											
9 0 1 1 2 2 3 4	80											
1 2 3 4	6				1							
1 2 3 4	0											
3	-				1							
3	2				+							
	3				+							
	4				+							

Note: Footage Column is for pipe only. Since each item could have a unique Mfg Date and Lot Number, each item MUST have its own entry line

Critical Valve Inspection Report (§192.747, §192.181) Ohio Rural Natural Gas

Inspection Frequency: Once every calendar year, NTE 15 months

System Name MUZIC Lengy (BNTSP

System Number 7 - 003

<u>~</u>	1/2	1	Γ		Τ					\vdash]
Inspected By	D.Stanil										
Prev. Inspection Date	9/24/2015										
Inspection	02/04/16										
Was Valve Partially Operated?											
Was Valve Accessible? Y/N											1 (100.
	300 #							:	:		up cu clean
Valve Description	1/4/100									:	nuc-k
Valv	BALON 2"										venon.
Valve #	CV.3-001										Comments: Street ON. WW.

Ohio Rural Natural Gas Co-op

Installed Date: 2 – (3 – 30 (c) # of Laborers:
Hours on Job:
Subcontractor: Mck w Con mill

Service line Material List

	1 14	Pt lype	70hC		Mary Company	2500	25,00							
	GOD	AUG											+	
	Lot Number		03-875-MC	8-18	10-17-15 60000 3476.213	10-19-13 2000 24 18451	10-17-15 20000 2474.313							
21	Mfg. Date		1-46-15	81-8	10-17-15	11-61-01	10-11-15							
ביבר וווכ ועומוביומו בוצו	Manufacturer		OIL CHEST PLASTES	J Then	Elste	10/cm	THE STATE OF THE S							
	Type/Size	PE 241 14 1136	D' Tawee wine	" Peeful	1" George	1" FUE - PISE.	wall browners							
	Qty. / Ft.					,	3							
Itam Mumber	agrant man	1317	47	314	314	3/4	2/2							Moto. F.

Note: Footage Column is for wire and pipe only. Since each item could have a unique MFG. Date and Lot Number, each item must have

Material st-DIMP

Ohio Rural

Natural Gas, Co-Op

Sys. : 0212-3-001

Work Order Number 2015-301

9 E715WORTH Project Name or Address

Starting Point:

nearest intersection)

(Distance from

Slurry Rock Clay Loam Sand

HDD Insert Bore Install Method Trench Main Line or Service Line Soll Type

	(Circle)							(Circle)	(Grele)	WEIZ - Withdraw Even Investment	and Erom	Constant
w	Station	7/5	ltem	Pipe	اغ	Manufacturer	Part#	Type/Size	Mfg Date	10t Nimbor	GNO	nveillOlly:
əţl	Start at 0+00	Distance	Number	Footage	WF	i			0		200	Tro
⊣						CENTRAL	316204	4" andie	1-14	M11491		Dollar.
7				209		BuratiNE	G08 40	4" Pia 1	1-10-15	2110 318	, set	246.00
ო				219		KRISTEH						202
4						CENTRAL	2,6260		11-17-15	11-17-15 001.704		CALL
2				305		anatine	606 56		1-11-15	21218	2011	3240
9				300		Khis T'ECU	2	8 GA- FRACTICUI RE		1		2
_						BENTRAL	8 4R 7//	4" Coupling V	81-1-15	09027		3%10
00				20		B.Roline	0000	C3/1/2/2	71-02-1	Przzyowya 1	1,00	1000
0				08		Kis Tech		yet Theen whee				
9	-					CENTRAL	849711	イルではかいっつ ~		090 8%		3778
11				629		Qualing	G 0650	130.0 00	1-10-15	DISSUNDUZEI B	1,30/1	2/1/2
12				306		QUOALING	043850	4" DIPE	11-2-15	11-3-15- DRUY36-FR	100	W/ 1100
13				130		HIS TECH		& GA. TOWKENIES			22.0	2
14					2	CENTRAC	316,204	4"Coupling	MM	121700		3906
12				414		Parating	60650	47.9%	11-2-15	11-2-15-031120-66	1110	2400
16				717	Ĭ	KRis Tecit		8 GA TOMOFICELLINE			Т	
17						CENTRAL	316204	4" coupling &	1-14	DOC 788		2403
100				417		Questine	60650	4" P. P. 1	11-3-15	11-2-15 034836-68		3708
13				717		Wis Tall		864 TRACER WIRE				
20						CENTRA	314,204	4" washin ~	M-1	681900		300 3
21				576		Durating.	GDS 50	40.06	11-2-15	024 Y36 -FA		Pelis
22				576		Kirs TRUL		Bet. Towanier				
23						C ENTRAC	316,204	4" larptim s	hI-1.	588300		80125
74				217		DURALINE	G-06.50	4. 1.06 1	Stc-11	1024 436 -EM		×4/08
	Note: Footage	e Column	is for wire a	and pine	- And	Since each item con	La base a similar	Note: Footage Column is for wire and nine only. Since each item could have a rinking National at Nine Land and	14 1000			

Note: Footage Column is for wire and pipe only. Since each item could have a unique Mfg Date and Lot Number, each item MUST have its own entry line F35

64 PS: 50 R V

8 Couplings IIX4.5 49.5 Bear RADINS

iystem#: db /01-154/

nventory Ticket No.

Odor/Gas L&R Reference No.

WFI? - Withdrawl From Inventory? HDD Type SDR Insert Install Method (Trench / Bore 8 bolt Date 2/10 - 2/1/-2 - 5WO Number 300# 8 bolt Lot Number USB 52 USA 500 FULL USA 300% Mfg Date Flange 41. 900 Sitting 4" Strel DiAc y" 450 Filthing 4" Steel Pipe 4" x 2" reducer 41" 450 F. Hing JULY 1164 " P Type/Size 40 Butweld Main Line or Service Line 4x10 Jadel 4" Butweld 9 dsket 3" Pipe (Grale) Part# Elsworth + Wadver Slurry Manufacturer Flectine weldbard Weldbeno Weldherd TODER Enersex Rock T.N. 619 Balon Clay **MEIS** Footage Loam Pipe 100 1 Number Item Sand roject Name or Address Distance 7 Starting Point: egrest Intersection) Start at 0+00 Distance from Station 0+00 Soil Type 0400 5050 0+24 0406 D429 0 to/ 0107 2000 ot27 10+0 040

Note: Footage Column is for wire and pipe only. Since each item could have a unique Mfg Date and Lot Number, each item MUST have its own entry line

Material st-DIMP

Ohio Rural Natural Gas, Co-Op

WFI? - Withdrawl From inventory?

임

Insert

Bore

Trench

3006

Type 2708

PE

SDR

Lot Number

Work Order Number

Project Name or Address Date

Sysi

nearest intersection)

(Distance from

Starting Point:

Bee 249 02-45-6-50cm FLHOGHOTC-FRA1927 SSK# 6193815 82-019 35-3644 14743 336378 132-019 10-15 358055 111875 343711 Install Method 10-6-15 11-17-13 11-17-13 Mfg Date 11-17-13 6-15 51-01 12-03 5-13 (Grcle) 7-15 2X4 REDALER 0290 0,06 " 6500 SCHILLE WIRE Type/Size 450 ELbour CHUCK 4" ノイトンを Main Line or Service Line 2º RISE 4" TEE 4" PiPE 2" P. P. 12/15 (Grcle) 1670167 99044013 1910125 10000 340 6911524 6912160 75.90 5 26090 Part# Slurry Manufacturer RISCOPLES This was Charac Kero Ter Riscoplex CENTRAC CENTRAL CENTRAL CENTRAL CENTRAC ELSTER Maister Rock Clay **MEIS** Footage Pipe Loam 181 3 3 18/ Number)tem Sand Distance ょ Start at 0+00 Station Soil Type (Grele) 9 10 11 12 14 16 18 19 20 Item m 4 2 9 00 17 21

5.5 240C

3407

13,5 220

2000

11.5 242

Note: Footage Column is for wire and pipe only. Since each item could have a unique Mfg Date and Lot Number, each item MUST have its own entry line

Materia ist-DIMP

2015.301 S, I#: ORNG-3-001

Work Order Number

Date

12-23-2015 dress ELLSWORTH RD Project Name or Address

Ohio Rural Natural Gas, Co-Op

Starting Point:

(Distance from

nearest intersection)

Soil Type		Sand	Loam	Clay	Rock	Slurry	Main Line or Service Line	Inches Adopted Transle			٠	
(Circle)								norm Memor	Leuch	Bore	Insert	HDD
						i	(Circle)	(Circle)		MARIO LAKE	WICKS With drawn France	
Ctation	1/2	14-		L						DIAA - 11 IAA	INI AWI LIOTH	inventor)

	(Checkel		2	100	Clay	nock stury		Main Line or Service Line	Install Meth	install Method Trench (Bore/ Insert	sert	HDD	
					İ			(Circle)	(Circle)	WFI? - Withdrawl From Inventory?	wl From I	nventory?	
wa			Item	Pipe		Manufacturer	Part#	Type/Size	Mfg Date	lot Nimber	gus	חמ	
भ	Start at 0+00	Distance	Number	Footage	ΙM				•		200	TVT	
-1				217		KRISTECH		8 6 P TRACERUITOR			I	346	
7						KENOTEST	99054011	et Call hat	The state of the s			4 1001.	7.16
m						CENTORL		CUID HALO?			11/200	2/10	E LLUWRY FR
4								The Control of the Co	0/10	448711		3408	
Ŋ													
9													
7													
œ													
6													
10													
11													
12													
13													
14													
15													
16													
17													
18													
19													
20													
21													
22													
23													
24							<i>y</i>						

Note: Footage Column is for wire and pipe only. Since each item could have a unique Mfg Date and Lot Number, each item MUST have its own entry line

MAOP 100 VALUE HAOP 200 COYOLING MAOP

MAGO

1 comp

2502

Materi, List-DIMP

Odor/Gas L&R Reference No.

Inventory Ticket No.

System#:

7325 Reynolds R.

WO Number

WFI? - Withdrawl From Inventory? Type SDR Insert Sec Attachment Install Method Arench Bore C55 A-007 Lot Number Mfg Date 11-6 5/-0 Date Top tee 1" reliver 2015 2016 "C 2" 2" x " x 50) pipe 2"-1" reducer Drip bootele Type/Size 2" 010c Fdrm tap Main Line on Service Line 2" Nipple (Circle) Part# Slurry Manufacturer MJ/Bys/a MJeller Malays. 2 True-435 Rock Dalon Clay 4 **MEIS** Footage Loam 2 78 ė Number Item Sand Project Name or Address Distance 7/5 nearest intersection) Starting Point: Start at 0+00 (Distance from Station 0400 9 0 +08 Soil Type 10+0 7 0 108 0108 4 0+07 0407 10 0108 11 0 40 % 3 0+01 12 Otox (Circle) 14 15 16 17 ın 9 13 19 21 20 22 23 24 2

Note: Footage Column is for wire and pipe only. Since each item could have a unique Mfg Date and Lot Number, each item MUST have its own entry line

F35

Mate. 1 List

Inventory Ticket No.

Odor/Gas L&R Reference No.

	Project Name or Address	or Address	8		7325		Farm Tap	Date	0.	WO Number]	ļ
	Starting Point:	نڌ										V
	nearest intersection)	- la		İ								
	Soil Type		Sand	Loam	Clay	Rock Slurry		Main Line or Service Line (Circle)	Install Method	Trench Bore Insert HDD Withdrawl From Inventory?	ert M From L	HDD
məti	Station Start at 0+00	C/L Distance	Item Number	Pipe Footage	WEIS	Manufacturer	Part#	Type/Size	Mfg Date	Lot Number	SDR	PE
25								1000/02				
56								2' N'DO/2				
27						Pishor	627-R	Caulator				
28								4" Wipole				
53								La Tec				
8								6º Nipole				
17						F.Sher	7-688	regulated		77		
32								1 M' pote				
33								1" Tec				
34								12" N:00/2				
35								13/10				
36								1 8				
37												
38												
39												
40									-			
41												
42												
43												
44												
45												
46												
47												
48												
	Note: Footage Column is for wire and nine only. Since each from could have a mission NAS- Determined	Pa Column	ie for wire			P						

Note: Footage Column is for wire and pipe only. Since each item could have a unique Mfg Date and Lot Number, each item MUST have its own entry line F35

Material st-DIMP

Work Order Number

3-7-16 Project Name or Address

nearest Intersection)

(Distance from

Starting Point:

7347 Reynolds Rd

WFI? - Withdrawl From Inventory? Type Insert SDR Bore Lot Number 695650 Trench Install Method 51-08-21 Mfg Date (Circle) 21.Value 300 Te las 10-12 120 tec 1" Doh 90 pipe 9001 'shiso 5. Hby 90° Sch 80 Firms "tol" reducer 2"col "reducal 1" Sch 80 p ipe 1'sch go pipe Type/Size Main Line or Service Line (Circle) 121-1091-0600 Part# Slurry Manufacturer weldbend weldbend Weldbens weld bend Dresser Balon Rock Clay **MEIS** Ł Footage Pipe Loam . No 7 Number Item Sand Distance り Start at 0+00 Station Soil Type 0400 2 orod 8 0410 9 0+10 7 104/0 3 0+03 5 0 764 6 0404 4 Otos 10 0 + 1/ (Circle)

UMC 52A-033

2015

Drip boate

Tru-gds

11 0 +// 12 0+// 13 04/1

14 15 16 17 18 19 20

Majaac

Marm tap

Brode

Note: Footage Column is for pipe only. Since each item could have a unique Mfg Date and Lot Number, each item MUST have its own entry line



Mate. I List

Systeriu#:

Project Name or Address Inventory Ticket No.

Starting Point:

nearest intersection) (Distance from

2519 Prymathe Rel

Date #116

Odor/Gas L&R Reference No.

WO Number

		Loam		Rock Slurry	Main Line	Wain Line or Service Line (Circle)	instail ivietnoa (Cirle)	WFI? - Withdrawl From Inventory?	sert wl From In	HDD /entory?
Start at 0+00 Distance	ltem Number	Pipe Footage	SIHW	Manufacturer	Part#	· Type/Size	Mfg Date	Lot Number	SOR	PE PE
				Dresser	PO1-101/109	1" top bea	12-30-15	234.384		3 20
		3,				1" Sch 80 Dipe				
			H			2"tol" reducer				
				Bolon		2" Velluc 300 Elars				1
						2"tol" reducer				
		٦				1"Sch 80 10,10c				
				weldbend		900 Sed 80 Fitting				
		7.	4			1"Sch 80 10'0c				
			Ĭ	weldbend		90° Sch 80 Siding				
		Š				Sch 80 01/1 1"				
				True-935		chio borte	4015	114 x 2 H - A 28		
						20# Anode				Γ
				Mai adc.		Farm tho				
			-							
										T
										Ī
									İ	T
										T

Note: Footage Column is for wire and pipe only. Since each item could have a unique Mfg Date and Lot Number, each Item MUST have its own entry line

F35

Mate, I List

Systern#:

Inventory Ticket No.

Project Name or Address

7371 Reynolds Rd

Date 3-8-16

Bore Insert HDD WFI? - Withdrawl From Inventory?

Arench

Install Method

Main Line or Service Line

Slurry

Rock

Loam

Sand

Soil Type (Circle) Station

nearest Intersection)

(Distance from

Starting Point:

Type

UMCSAR-029

2015

900 Sch 80 Fitting 1" Sch 80 Pipe

1" Sc4 80 DIPE

Drip bottle

Tru- 925

1/3

May 232c

40

39

20st Ande Farm tap

SDR

Lot Number

Mfg Date

Type/Size

Part#

Manufacturer

MEIS

Footage Pipe

Number Item

Distance 7/5

Start at 0+00

me‡l

25 0+00

685650

12-30-15

10-12

2" Value 300# c/35

J'Col" Trduce

1"Sch So Pipe

1" CBO 600

0090-16cd-199

Dresser

13

1"Sch 80 Pipe

2"tol" reducer

weldbend

3

29 0 405

 \leftarrow

3

33 0 108

32 0+08

weldbend

Balon

9006ch 80 pipe

WO Number

Odor/Gas L&R Reference No.

Ĥ

Note: Footage Column is for wire and pipe only. Since each item could have a unique Mfg Date and Lot Number, each item MUST have its own entry line

Newtin - A (OUPS Youngstown)

Response Statistics



Exit :

Date 1/1/15

through 08/29/16

(individual day statistics go back 90 days. Before that must use whole months.)

Submit ASCII

Response statistics for date range 1/1/2015 through 08/29/16

code	001	002	003	999	TOTAL
ORNP	122	11	2	36	171
TOTAL	122	11	2	36	171

Legend

Туре	Description
001	No conflict
002	Marked - up to privately owned utility
003	Ticket cancelled
999	No Response given within the 48 hours

Exit

Copyright (c) 2004-2010 Cosmic Computers, Inc.

Powered by **Mewtiri**



Response Statistics

Exit

Date 1/1/16

through 8/29/16

(individual day statistics go back 90 days. Before that must use whole months.)

Submit ASCII

Response statistics for date range 1/1/2016 through 8/29/16

code	001	002	003	999	TOTAL
ORNP	122	11	1	10	144
TOTAL	122	11	1	10	144

Legend

Type	Description
001	No conflict
002	Marked - up to privately owned utility
003	Ticket cancelled
	No Response given within the 48 hours

Exit

Copyright (c) 2004-2010 Cosmic Computers, Inc.

Powered by **Aewtiri**

Response Statistics

2015

Exit

Date 1/1/15
Submit ASCII

through 12/31/15

(individual day statistics go back 90 days. Before that must use whole months.)

Response statistics for date range 1/1/2015 through 12/31/15

code	003	999	TOTAL
ORNP	1	26	27
TOTAL	1	26	27

Legend

Туре	Description
003	Ticket cancelled
999	No Response given within the 48 hours

Exit

Copyright (c) 2004-2010 Cosmic Computers, Inc.

Powered by **Mewtiri**

Date: 10-1-15 Crew: Jock	Prepared By:	Serickland MLWO# SLWO#
Address: 700/ Center St + Fedici Coult	Ctv/Twn	Serickland ML WO# SL WO# Menter Sub./Lot#:
Cust. Name ()sair Sys. Name &		Bldg. Type Res Com Indus.
Company SL Info: New Repair Replace	┙	Customer SL Info: New Repair Replace
Size 2 Length: /4/ PL SDR // ST WT	_	Size: 2 Length: OP PL SDR I ST WT
Installer:(Name or) ORNG Contractor		Installer:(Name or) DING Contractor
Mtr Size/Tag# / Reg/Orf	_	Billable: Y N Direct Observation
EFV Yes No SL Valve Yes No		
Tested By: Jak Pressure 90 PSIG(PSIG)	5 1: 11 -	14 1 0 'c
	Juration / howe Duration	Med Arr Acceptable Test: Y N
Tested By: Pressure (PSIG)	Juration	Med Acceptable Test: Y N
Mai	n Line Inforn	nation
Pipe Type Pipe Diameter: 2"	Is the n	ipe able to be located? Y N
V Plastic	<u> </u>	Prince to so to med. 1. A.
Steel (Fusion Bonded Epoxy Extruded	Polvethylene [Tor & Wron Doro
Other (Specify:		,
Pipe Details: (MFG: Type:		Wall Thickness/SDR: MEG Date:
Internal Inspection		
Is the inside pipe accessible: Y N Interna	1 Condition(If	accessible) Smooth Pitted& Denth
Any Fluid: Y NV Type of Fluid:		
External Inspection	/	
Is the pipe under Cathodic Protection: Y N	Pipe Condi	tion: 🗹 Smooth 🗌 Pitted& Depth:
Coating Condition (If Coated): Good Fair	Poor Bacl	cfill Condition: Good Fair Poor
New Anodes Installed: Y New Many:	A	node Size:
Use sketch area to list additional fitting information	Sketch	Indicate North
		Maiotto I (OI)
OTTO COLUMN TO THE COLUMN TO T		1
GPS Coordinates of Tap: Longitude (X): House Riser to nearest corner of structure	Latitude(Y):	VIVI-
Farm Tap Riser to nearest corner of structure	C/L Dr. to EF C/L Dr. to EF	
Tested and installed according to current O&M Procedures	7!	OLDISL WEFV/VIV.

D. C. Charles		1 // 2 : -
Date: Crew: DALE STRICKE	Prepared By: N	L WO# L 8-2015 SL WO# -0-
Address: (1970 WILLIAMS Rd	Cty/TwpConcorD TWF	Sub./Lot#: 08A 006 B000090
Cust. Name Richard 17, 051301 Sys. Nam	e & No.: TI-005 WILLIAMS FE	Bldg. Type Res Com Indus.
Company SL Info: New Repair Replace		Info: New Repair Replace
Size: Length: 3 PL SDR STAWT 0	Size: Length:	02 PL SDRU ST WT
Installer:(Name or) Contractor		
Mtr Size/Tag# 400/ Reg/Orf 3/16	Billable: V N	Direct Observation
EFV Yes No SL Valve Yes N		
El V les INOPY SL Valve les IN		INFO! DEWELL NOT GOS
Total Day		23807 3/30/11
Tested By: Pressure (PSIG)	Duration Med	Acceptable Test: Y N
Tested By: Pressure (PSIG)	Duration Med	Acceptable Test: Y N
74	T. T. T. C. 4	
n e e e e e e e e e e e e e e e e e e e	ain Line Information	
Pipe Type Pipe Diameter: 2"	Is the pipe able to be lo	ocated? Y N
! —-		1/2
Plastic	.—	_
Steel (X Fusion Bonded Epoxy 🗌 Extrude	ed Polyethylene Tar & Wrap	Bare)
Other (Specify:)	i di m	g 46
Pipe Details: (MFG:Type:_	Steel X 42 Wall Thicknes	s/SDR: 154MFG Date:)
<u>Internal Inspection</u>		
Is the inside pipe accessible: Y N Inter	nal Condition(If accessible)	Smooth Pitted& Depth:
Any Fluid: Y N Type of Fluid:	-NA -	
External Inspection	1277	
Is the pipe under Cathodic Protection: Y N	Pine Condition: X Smooth	Pitted& Denth
Coating Condition (If Coated): Good Fai	r Poor Backfill Condition:	Good Frie Poor
New Anodes Installed: Y N How Mar	Anodo Sizo	Z Dood
110W 1VIAL	Allode Size.	<u></u>
Use sketch area to list additional fitting information	Sketch	Indicate North
and review residence residence and an arrange and a second and a second and a second and a second and a second	SI TOPHERINANE NAVIEW (VISION DESCRIPTION DE SERVICE DE	De De la Companya del Companya de la Companya del Companya de la C
RWER		W TE
V. Sa And Street Control of the Cont	AL BARN	X.
and the state of t	N.A.	3
		76' 4L EAST
	02	CALLE GO
HOUSE	<i>y</i>	WILLIAMS RD
MAO(500		
MAOP 500 OTP 104	- KV	EDGE of RIVER TO
OTP 104		METER_ 150'
2"5766-)	12	E/L of WILLIAMS
and the state of t	T P	TO METER
ck 76'	1201	134'
I CASCADE NOW I LAD		DRIVEWAY TO
GPS Coordinates of Tap: Longitude (X): 81° 11'59" W	110/12/2011.1	VALVE 37'
House Riser to nearest corner of structure	Latitude(Y): 91 90 52"N C/L Dr. to EFV/Vlv.	C/L of St. to EFV/VIv.
Farm Tap Riser to nearest corner of structure	C/L Dr. to EFV/VIv.	C/L of St. to EFV/VIv.
Tested and installed according to current O&M Procedure		Date 041.6.2015

Service Line Order (SLO) Company Date: 3-16-16 Crew: Prepared By: ML WO#

Address: 9230 Suyarbush Cty/Twp MeNTOK Sub./Lot#: ML WO# SL WO# Cust. Name PRobuil Homes Sys. Name & No.: Bldg. Type Res Com Indus. Customer SL Info: New Repair Replace Company SL Info: New Repair Replace Size: Length: FL SDR ST WT Size: Length: PL SDR ST WT Installer:(Name or) Contractor Installer:(Name or) Contractor Mtr Size/Tag# Reg/Orf Billable: Y N Direct Observation EFV Yes No SL Valve Yes No Tested By: Bradley Edget Pressure 120 (PSIG) Duration 10 MIN Acceptable Test: YX Tested By: Pressure (PSIG) Duration Acceptable Test: Y Main Line Information Line Type Pipe Type Pipe Size: 2" Is the pipe able to be located Y N Bare)

Transmission Steel (Fusion Bonded Epoxy Extruded Polyethylene Tar & Wrap Bare) Line Type Distribution Cast Iron Service Line Plastic Gathering Other Pipe Details: (MFG: _____ Lot #: ____ Wall Thickness/SDR: ___MFG Date: ____) Internal Inspection Is the inside pipe accessible: Y N Internal Condition(If accessible) Smooth Pitted& Depth: Any Fluid: Y N Type of Fluid: External Inspection Is the pipe under Cathodic Protection: Y N Pipe Condition: Smooth Pitted& Depth: Coating Condition (If Coated): Good Fair Poor Backfill Condition: Good Fair Poor New Anodes Installed: Y N How Many: Anode Size: Sketch Use sketch area to list additional fitting information Indicate North Naeth sugarbush GPS Coordinates of Tap: Longitude (X): House Riser to nearest corner of structure Riving C/L Dr. to EFV/Viv. C/L of St. to EFV/Vlv. Farm Tap Riser to nearest corner of structure C/L Dr. to EFV/Vlv. C/L of St. to EFV/Vlv. Tested and installed according to current O&M Procedures-Signature & rackey Expel Date 3-16-16

F-34R2

	pared By: Strideline ML WO# SL WO#
Address: 7347 Reynolds Rd Cty Cust. Name Sys. Name & No.:	Twp Mrn+2 Sub./Lot#: Bldg. Type Res Com Indus.
Company SL Info: New Repair Replace	Customer SL Info: New Repair Replace
Size: /" Length: / 3/ PL V SDR //, ST WT Installer: (Name or) ORNC Contractor Mtr Size/Tag# Reg/Orf EFV Yes No SL Valve Yes No	Size: / Length: / 2 / PL YSDR // ST WT Installer: (Name or) Contractor Billable: Y N Direct Observation
Tested By: TRowland Pressure 90 PST (PSIG) Duration Tested By: Pressure (PSIG) Duration	
Main Line	Information
Pipe Type Pipe Diameter: 2"	Is the pipe able to be located? Y N
Steel (Fusion Bonded Epoxy Extruded Polyet Other (Specify:)	hylene 🗗 Tar & Wrap 🔲 Bare)
Pipe Details: (MFG: Type:	Wall Thickness/SDR:MFG Date:)
Internal Inspection Is the inside pipe accessible: Y N Internal Cond	lition(If accessible) Smooth Pitted& Depth
Any Fluid: Y N Type of Fluid:	
External Inspection Is the pipe under Cathodic Protection: Y N Pip	e Condition: A Smooth Ditted & Denth
Coating Condition (If Coated): Good Fair Po	or Backfill Condition: Good Fair Poor
New Anodes Installed: Y N How Many: /	Anode Size: 20#
Use sketch area to list additional fitting information	etch Indicate North
GPS Coordinates of Tap: Longitude (X):	tude(Y):
House Riser to nearest corner of structure C/I	Dr. to EFV/Vlv. C/L of St. to EFY/Vlv.
Farm Tap Riser to nearest corner of structure C/I Tested and installed according to current O&M Procedures-Signature	Dr. to EFV/Vlv. C/L of St. to EFV/Vlv.

Date: 3-9-16 Crew: OPNC Address: 1317 Raynolds Rd			ML WO# SL WO#
Cust. Name Salopeck Sys. Name & N	Cty/Twp No.:	ptanto-	Sub./Lot#: Bldg. Type Res Com Indus.
Company SL Info: New Repair Replace		Customon	
Size: / Length: //o' PL SDR // ST WT Installer:(Name or) ORN/ Contractor Mtr Size/Tag# Reg/Orf EFV Yes No SL Valve Yes No		Size:/" Length	LInfo: New Repair Replace a: 10' PL DSDR 11.5 ST WT e or) ORNG Contractor N Direct Observation
Tested By: Powlard Pressure 90Bit (PSIG) Du Tested By: Pressure (PSIG) Du	ration /0,	Med Med	Acceptable Test: Y N N Acceptable Test: Y N N
Main	Line Infor n	ation	
Pipe Type Pipe Diameter: 2 " Plastic Steel (Fusion Bonded Epoxy Extruded Poly Other (Specify:)	Is the polyethylene [Condition(If Pipe Condition Back	Tar & Wra Wall Thickn accessible)	p Bare) ess/SDR:MFG Date:) Smooth Pitted& Depth: oth Pitted& Depth: n: Good Fair Poor
Use sketch area to list additional fitting information	Sketch		Indicate North
GPS Coordinates of Tap: Longitude (X):	Latitude(Y):		
House Riser to nearest corner of structure	C/L Dr. to EF		C/L of St. to EFV/Vlv.
Farm Tap Riser to nearest corner of structure Tested and installed according to current O&M Procedures-Si	C/L Dr. to EF	V/Vlv.	C/L of St. to EFV/VIv.
	ZH ZBLUFC		LISTE

Date: 3-29-/6 Crew: ORM	Prepared By: /	Powlan ML WO# SL WO#		
Address: 737/ Reynolds Re	Cty/Twp M			
Cust. Name Tillett Sys. Name &	No.:	Bldg. Type Res Com Indus.		
Company SL Info: New Repair Replace	l c	ustomer SL Info: New Repair Replace		
Size:/" Length: Yo' PL SDR//, TST WT Installer:(Name or) ORNG Contractor	7	ze/ Length: % PL SDR // 5ST WT		
		illable: Y N Direct Observation		
Mtr Size/Tag# Reg/Orf EFV Yes ✓ No SL Valve Yes No	1	illable: Y N Direct Observation		
		Med A' Acceptable Test: Y N		
Tested By: Pressure (PSIG) D	uration	Med Acceptable Test: Y N		
Mair	Line Informat	tion		
l 	Is the pipe	e able to be located? Y N		
Plastic		_		
Steel (Fusion Bonded Epoxy Extruded F Other (Specify:		/		
Pipe Details: (MFG: Type:	W.	Vall Thickness/SDR: MFG Date:		
Internal Inspection				
Is the inside pipe accessible: Y N Internal Any Fluid: Y N Type of Fluid:	Condition(If ac	cessible) Smooth Pitted& Depth:		
External Inspection				
Is the pipe under Cathodic Protection: Y N	Pipe Conditio	n: Smooth Pitted& Depth;		
Coating Condition (If Coated): Good Fair Poor Backfill Condition: Good Fair Poor				
New Anodes Installed: Y N How Many:	Ano	de Size: 20		
		· · · · · · · · · · · · · · · · · · ·		
Use sketch area to list additional fitting information	Sketch	Indicate North		
GPS Coordinates of Tap: Longitude (X):	Latitude(Y):			
House Riser to nearest corner of structure	C/L Dr. to EFV/			
Farm Tap Riser to nearest corner of structure	C/L Dr. to EFV/			
Tested and installed according to current O&M Procedures-S	ignature	Date		

	Detail 1 17:16 0 0000000000000000000000000000000000					
	Date: 1-12-15 Crew: ORNG- D. STRICKBARD Prepared By: ML WO# L4-2015 SL WO# L4-2015					
	Address: 800 OAK ST. Puille Cty/Twp Puille Ohr Sub./Lot#:					
	Cust. Name Lake Gleauch A Recovery Centil Sys. Name & No. DRICH TI-DOI Bldg. Type Res Com Indus.					
	Company SL Info: New Repair Replace Customer SL Info: New Repair Replace					
	Size: 2" Length: 4 PL SDR ST WT Size: Length: 165 PL SDR ST WT					
	Installer:(Name or) Contractor Installer:(Name or) ORD Contractor					
	Mtr Size/Tag# Reg/Orf Billable: Y N Direct Observation					
	EFV Yes No SL Valve Yes No					
5	Tested By: Strickland Pressure QD (PSIG) Duration D min Med A: Acceptable Test: Y N					
A	Tested By: Shrick and Pressure 750 (PSIG) Duration 22445 Med Nitrogen Acceptable Test: Y N					
	Main Line Information					
	Pipe Type Pipe Diameter: Y' Is the pipe able to be located? Y N					
	Plastic					
	Steel (Fusion Bonded Epoxy Extruded Polyethylene Tar & Wrap Bare) Other (Specify:)					
	Pipe Details: (MFG:					
	Internal Inspection					
ı	Is the inside pipe accessible: Y N Internal Condition(If accessible) Smooth Pitted& Depth:					
ı	Any Fluid: Y Ny Type of Fluid:					
	External Inspection					
ı	Is the pipe under Cathodic Protection: Y N Pipe Condition: Smooth Pitted& Depth:					
	Coating Condition (If Coated): Good Fair Poor Backfill Condition: Good Fair Poor					
ľ	New Anodes Installed: Y N How Many: Anode Size:					
ľ	Use sketch area to list additional fitting information Sketch Indicate North					
İ	Telephone internation Sketch E > 1095.614' FRom 6/L of ELMST - EAST 25' FRom 6/L to STATION 25' FROM 6/L to STATION					
	E> 1095.614 FROM E/E C4 EZITOTIE					
1	25' FROM C/L to STATION					
	STATION ZI' FROM E. P./L.					
ı	STATION 21' FROM E. P./L. 165' SERVICE LINE TO BLO.					
ľ	105 502.105					
ľ						
١	1095.614' OAK ST 4, 25' c/c					
	E 21' From 1/2					
	1 Box our st					
	(y)757270.2362 PVILLE ON 44077					
	1/2/22					
	GPS Coordinates of Tapl Longitude (X): /3/2880,46/2 Latitude(Y): House Riser to nearest corner of structure C/L Dr. to EFV/Vlv. C/L of St. to EFV/Vlv.					
II .	Farm Tap Riser to nearest corner of structure C/L Dr. to EFV/Vlv. C/L of St. to EFV/Vlv.					
[Tested and installed according to current O&M Procedures-Signature					

Date: 9-24-13 Crew: ORNG Prepar	A Pur
1 11 (2 1 1	55 W Oil
Cust. Name Muzic Sys. Name & No.:	
	Bldg. Type Res Com Indus.
Company SL Info: New Repair Replace	Customer SL Info: New Repair Replace
Size: /" Length: PL SDR // ST WT	Size: /"Length: 76' PL SDR // ST WT
Installer: (Name or) ORNG Contractor	Installer:(Name or) ORNG Contractor
Mtr Size/Tag# Reg/Orf	Billable: Y N Direct Observation
EFV Yes No SL Valve Yes No	Direct, Observation
Tested By: ORNA Pressure 70 (PSIG) Duration Tested By: Pressure (PSIG) Duration	/o Min Med Air Acceptable Test: Y N N N Acceptable Test: Y N N
Main Line I	formation
Pipe Type Pipe Diameter: Is	the pipe able to be located? Y N
Plastic	
Steel (Fusion Bonded Epoxy Extruded Polyethyl Other (Specify:	
Pipe Details: (MFG:	Wall Thickness/SDR: MEG Date:
Internal Inspection	
Is the inside pipe accessible: Y No Internal Condition	on(If accessible) Smooth Pitted& Denth
Any Fluid: Y N Type of Fluid:	, <u> </u>
External Inspection	
Is the pipe under Cathodic Protection: Y N Pipe C	ondition: Smooth Pitted& Denth
Coating Condition (If Coated): V Good Fair Poor	Backfill Condition: Good Fair Poor
New Anodes Installed: Y NV How Many:	Anode Size:
Use sketch over the list of the latter of th	
Use sketch area to list additional fitting information Sketc	Indicate North
) \
	J ₃ V
Horse	
	160 riv
925 J	/ P. V
1-10-38	
Tary	g de Main
16-31	9
Rodd	
GPS Coordinates of Tap: Longitude (X): Latitude(Y)	n-
Datingo()	to EFV/Vlv. C/L of St. to EFV/Vlv.
Farm Tap Riser to nearest corner of structure C/L Dr.	to EFV/VIv. C/L of St. to EFV/VIv
Tested and installed according to current O&M Procedures-Signature	Date 9-24-15

Date: 9-2/15 Crew:	Prepared By: Serikle	
Address: /232/ Cotter Pol Cust. Name Develd Sys. Nam	ne & No.:	
		Bldg, Type Res Com Indus.
Company SL Info: New Repair Replace	<u>ce</u> Customer	SL Info: New Repair Replace
Size: / Length: PL VSDR // ST WT		ngth: /30' PL VSDR // ST WT
Installer: (Name or) ORNG Contractor Mtr Size/Tag# Reg/Orf	Installer: (N	Name or) ORNG Contractor
Mtr Size/Tag# Reg/Orf EFV Yes No V SL Valve Yes N	Io Diliable: YI	N Direct Observation
Tested By: ORNA Pressure 90 (PSIG) Tested By: 77 (KIMPressure 750 (PSIG)	Duration /o n' Med / Duration Med /	Acceptable Test: Y N N
N	Tain Line Information	,
!	Is the pipe able to	be located? Y N
☐ Plastic☐ Plastic☐ Steel (☐ Fusion Bonded Epoxy☐ Extrud☐ Other (Specify:)	ed Polyethylene 🗹 Tar & W	/rap 🔲 Bare)
Pipe Details: (MFG: Type:	Wall Thic	kness/SDR: MFG Date:
Internal Inspection		
Is the inside pipe accessible: Y N Inter	rnal Condition(If accessible)	Smooth Pitted& Depth:
Any Fluid: Y N Type of Fluid: External Inspection		
Is the pipe under Cathodic Protection: Y N	Pipe Condition: Sm	nooth Pitted& Denth
Coating Condition (If Coated): Good Fa	ir 🗌 Poor Backfill Condit	ion: Good Fair Poor
New Anodes Installed: Y N Mem How Man	ny: Anode Size:_	
Use sketch area to list additional fitting information	Sketch	Indicate North
, and the second		
	Horse	V
Miles	& Drive	
gas Line	ر من ا	STEWERDS
	903	
	Road	- KGis Pedin
		and details format (all 10 pages 27 cite to
GPS Coordinates of Tap: Longitude (X):	Latitude(Y):	
House Riser to nearest corner of structure Farm Tap Riser to nearest corner of structure	C/L Dr. to EFV/VIv.	C/L of St. to EFV/VIv.
Tested and installed according to current O&M Procedure	C/L Dr. to EFV/VIv.	C/L of St. to EFV/VIv.

System Name: _CA	System No: OROG TI-002
Area covered:	From: 43' EAST of Property LINE - 97' Along Fromt o
	From: 43' EAST of Property Live - 97' Along Front or To: Peiperty Along ORWIDE & 130' Along Service Lin Distribution Transmission
System type:	☐ Distribution ☐ Transmission
Class location:	
Patrol frequency:	☐ 4 Times/yr ☐ 2 Times/yr ☐ Annual
	☐ 5 years ☐ Other
Method used to patro	: Truck Walk Other:
	□ yes □ no
If yes, gas leak and re	pair report no:
	ction along or near the pipeline system: yes no
	o nearest line marker or address:
	No.
Were there any unusua	l conditions found at any of the following places:
None Found	☐ Steams/Rivers ☐ Railroad
Highway	☐ Foreign Pipeline ☐ Buildings
Other:	11.00
fixes evaluing	at could affect the present or future safety of this system: yes no
	narkers anywhere in the system?: yes no
f ves to any above que	tion to whom was it was all a
Comments:	stion, to whom was it reported:
erformed By:	Date: 1-4-16

Carter Rd

our st

System Name: 01	ak st.	System No: ORNG TI-00
Area covered:	From: Worth west End of Property	267' F.AST ALDON
	From: Wordh west End of Property To: Cobra's likeline South 200' A	Long SEKVILL Line
System type:	☐ Distribution ☐ Transmission	
Class location:		
	✓ 4 Times/yr ☐ 2 Times/yr ☐ An	ทบลโ
	☐ 5 years ☐ Other	
Method used to patr	rol: Truck Walk Other:	
Were any leaks foun	nd:	
	repair report no:	
	ruction along or near the pipeline system: yes	
	e to nearest line marker or address:	
		The second second
Were there any unusu	ual conditions found at any of the following places:	
None Found	□ Steams/Rivers	□ Railroad
☐ Highway	☐ Foreign Pipeline	☐ Buildings
	that could affect the present or future safety of this sys	stem: 1 yes no
	e markers anywhere in the system?:	J ^m no
If yes, give location:		
If yes to any above qu	nestion, to whom was it reported:	
Comments:		
Performed By:	1/1/10	
1 Monned By: / Jon	7 1 1 D	Pate: 1.4-13
()"	NOTE Stanish	

System Name: WI	Winns Rd Baco	<u> </u>	System No: 71-005
Area covered:	From: TAP 80' West	ALONG O	TP 104 North 200'
	To: ALONG MP 104	ALUNG S	SERVICE LINE - ALONG ORWG
System type:		ransmission	62'
Class location:		□ 4	
Patrol frequency:		yr 🛭 A	nnual
Method used to patro	ol: 🗆 Truck 📈 Walk	Other:	
	nd:		
If yes, gas leak and re	epair report no:		
	ruction along or near the pipeline syst		
	to nearest line marker or address:	-	
Were there any unusu	ual conditions found at any of the follo	owing places:	
□ None Found	Steams/Ri	vers	☐ Railroad
Highway	Foreign Pi	peline	□ Buildings
Other:	that could affect the present or future	O MADE	SOR 11 2" PE 2406
Are there any factors t	that could affect the present or future	safety of this s	ystem: yes no
	e markers anywhere in the system?:	-	no
If yes, give location: _			
f yes to any above que	estion, to whom was it reported:		
Comments:			
erformed By: 🔨 🚙	1 the for		Date: 2-4-//

Williams Rd Born

System Name:	System No: T1-006
Area covered:	From: Williams Rd.
	To:
System type:	☐ Distribution ☐ Transmission
Class location:	
Patrol frequency:	
	☐ 5 years ☐ Other
Method used to patro	ol: Truck Walk Other:
Were any leaks found	d: □ yes
If yes, gas leak and re	epair report no:
Was there any constru	ruction along or near the pipeline system: yes no
If yes, give reference	to nearest line marker or address:
Were there any unusu	ual conditions found at any of the following places:
None Found	☐ Steams/Rivers ☐ Railroad
☐ Highway	☐ Foreign Pipeline ☐ Buildings
	11
	that could affect the present or future safety of this system: \Box yes \Box no
	e markers anywhere in the system?: yes no
	lestion, to whom was it reported:
Comments:	
Performed By:	Date: 2-4-16

System Name: 1154 March System No: 012053-00
Area covered: From: ELSWO(+h)
To: 5. OUCKCREEK RO
System type: Distribution Transmission
Class location: \Box 1 \Box 2 \Box 3 \Box 4
Patrol frequency: 4 Times/yr 2 Times/yr
☐ 5 years ☐ Other
Method used to patrol: Truck Walk Other:
Were any leaks found:
If yes, gas leak and repair report no:
Was there any construction along or near the pipeline system: yes no
If yes, give reference to nearest line marker or address:
Were there any unusual conditions found at any of the following places:
 □ None Found □ Highway □ Steams/Rivers □ Foreign Pipeline □ Buildings
Other:
Are there any factors that could affect the present or future safety of this system: yes yes
If yes, explain:
Are there missing line markers anywhere in the system?: yes no
Are there missing line markers anywhere in the system?: yes no If yes, give location:
If yes, give location:
If yes, give location: If yes to any above question, to whom was it reported:
If yes, give location:
If yes, give location: If yes to any above question, to whom was it reported:
If yes, give location: If yes to any above question, to whom was it reported:
If yes, give location: If yes to any above question, to whom was it reported:
If yes, give location: If yes to any above question, to whom was it reported:

System Name: Sugar Bush System No: 51-002
Area covered: From: 9221 Sulangush EAST Along Street
To: 9220 Suline Bush ALONG Line on
System trace
Class location: \Box 1 \Box 2 \Box 3 \Box 4 \Box 4 \Box 6 SUG-AR BLS
Patrol frequency: 4 Times/yr 2 Times/yr Annual
☐ 5 years ☐ Other
Method used to patrol: Truck Walk Other:
Were any leaks found: yes no
If yes, gas leak and repair report no:
Was there any construction along or near the pipeline system: yes ino
If yes, give reference to nearest line marker or address: (5' NETAREST LINE MARKET
ADDRESS 9230 SULTARBUSH OR
MENTOR ONO 44060 PINH 16BOGOBDOOK
Were there any unusual conditions found at any of the following places:
None Found Highway Other: Okull Notural Coac Line Buildings
Are there any factors that could affect the present or future safety of this system: yes no
If yes, explain:
Are there missing line markers anywhere in the system?: yes no
If yes, give location:
If yes to any above question, to whom was it reported:
Comments:
Line Markers location A+ 57ATION +
Performed By: Date: 3-3-16

Sugar Bush

Sur R

Vegetation Survey Flame Ionization Survey **Available Opening Survey**

> Line PATROL Leak Survey Map


System: ORNGS1-002

MAOP:60 System Length: 850' 4" SDR11

Remarks:

System: ORNG S1-002

Leak record #______ Date:02/05/2016 Time: Performed by: Dave Stanish



Location: Sugar Bush Dr. City: Mentor County: Lake, Ohio 44060

Available Opening Survey Flame Ionization Survey Vegetation Survey

System: Frace Date: 2/5/11 € Performed by: Leak record # INE TATROL Leak Survey Map

ON HENSO System: ORW 104 4" Steel Longitude: 81 20'16.46"W atitude: 41 '40' 46.82"N 432" 2" SDR 11 Fracci Ct. PIN# 16-8-039-0-00-005-0 Tap: ORNG T1-003 Regulation Station 7000 Fracci Ct. Center St.

Location: 7000 Fracci Ct. Mentor Lake County Ohio

System Name: FR	ALI CT System No: 5 -00
Area covered:	From: FND of FRACE: CT. PIN# 16B 0390006
	From: FND of FRACE; CT. PIN# 68 0390009 To: PIN# 163.039-000050 7000FRACE; C
System type:	
Class location:	
Patrol frequency:	✓ 4 Times/yr □ 2 Times/yr □ Annual
	☐ 5 years ☐ Other
Method used to patro	ol: Truck Walk Other:
	d: yes no
	epair report no:
	uction along or near the pipeline system: yes no
	to nearest line marker or address:
Were there any unusu	al conditions found at any of the following places:
None Found	☐ Steams/Rivers ☐ Railroad
Highway	Foreign Pipeline Buildings
Are there any factors t	hat could affect the present or future safety of this system: yes no
	A
	markers anywhere in the system?:
f yes, give location:	
	estion, to whom was it reported:
Comments:	NOW CTUVE
	NEED STICKERS ON Line
	MARCHERS
	Estable OVIDARIO 1000
	1 14 16
erformed By:	Date: 07-5-16

Bruce. Ct

System Name:	11216 13164 Leroy CASTER System No: T1-003
Area covered:	From: 145' From 6/L of Indian Point W
	To: 331/2' 5 to TI-003 90' ALONE 5/L +
System type:	□ Distribution □ Transmission 200' Alow ORW 10 9
Class location:	$\Box 1 \qquad \Box 2 \qquad \boxtimes 3 \qquad \Box 4 \qquad \boxtimes /4 \qquad \boxtimes /4$
	✓ 4 Times/yr ☐ 2 Times/yr ☐ Annual
	□ 5 years □ Other
Method used to patr	rol: Truck Walk Other:
Were any leaks four	nd:
	repair report no:
Was there any constr	ruction along or near the pipeline system: yes no
If yes, give reference	e to nearest line marker or address:
Were there any unusu	ual conditions found at any of the following places:
None Found	☐ Steams/Rivers ☐ Railroad
☐ Highway	☐ Foreign Pipeline ☐ Buildings
Are there any factors	that could affect the present or future safety of this system: yes no
	e markers anywhere in the system?: yes no
	estion, to whom was it reported:
Comments:	
41.	686848 -81.147771
Performed By:	
CHOINEU BY: _///	Date: 2-4-12

Lorox Center

ansalahand vale a dist

DEPARTMENT OF TRANSPORTATION

Pipeline and Hazardous Materials Safety Administration
OFFICE OF PIPELINE SAFETY



U.S. Department of Iranspondtion Pipeline and Hazardous Materials Safety Administration

PIPELINE SAFETY REGULATIONS

PART 192

TRANSPORTATION OF NATURAL AND OTHER GAS BY PIPELINE:
MINIMUM FEDERAL SAFETY STANDARDS
(Current through Amendment 118, as of September 2013)

PIPELINE SAFETY DIVISION (PHP-70) PO BOX 25082 OKLAHOMA CITY, OK 73125-5050

(405) 954-7219

Fax (405) 954-0206

PRINTED MARCH 2015

This foregoing document was electronically filed with the Public Utilities

Commission of Ohio Docketing Information System on

8/30/2016 5:21:03 PM

in

Case No(s). 16-1578-GA-COI

Summary: Testimony of Darryl Knight on behalf of Ohio Rural Natural Gas Co-op (Part 3-Exhibits Continued) electronically filed by Mr. Richard R Parsons on behalf of Ohio Rural Natural Gas Co-op