

Exhibit E. Peak Flow Velocity & Scour Depth Maps




Exhibit F. Soils Map and Descriptions



NRCS

Natural Resources Conservation Service A product of the National Cooperative Soil Survey, a joint effort of the United States Department of Agriculture and other Federal agencies, State agencies including the Agricultural Experiment Stations, and local participants

Custom Soil Resource Report for Marion County, Ohio



Preface

Soil surveys contain information that affects land use planning in survey areas. They highlight soil limitations that affect various land uses and provide information about the properties of the soils in the survey areas. Soil surveys are designed for many different users, including farmers, ranchers, foresters, agronomists, urban planners, community officials, engineers, developers, builders, and home buyers. Also, conservationists, teachers, students, and specialists in recreation, waste disposal, and pollution control can use the surveys to help them understand, protect, or enhance the environment.

Various land use regulations of Federal, State, and local governments may impose special restrictions on land use or land treatment. Soil surveys identify soil properties that are used in making various land use or land treatment decisions. The information is intended to help the land users identify and reduce the effects of soil limitations on various land uses. The landowner or user is responsible for identifying and complying with existing laws and regulations.

Although soil survey information can be used for general farm, local, and wider area planning, onsite investigation is needed to supplement this information in some cases. Examples include soil quality assessments (http://www.nrcs.usda.gov/wps/portal/nrcs/main/soils/health/) and certain conservation and engineering applications. For more detailed information, contact your local USDA Service Center (https://offices.sc.egov.usda.gov/locator/app?agency=nrcs) or your NRCS State Soil Scientist (http://www.nrcs.usda.gov/wps/portal/nrcs/detail/soils/contactus/?cid=nrcs142p2 053951).

Great differences in soil properties can occur within short distances. Some soils are seasonally wet or subject to flooding. Some are too unstable to be used as a foundation for buildings or roads. Clayey or wet soils are poorly suited to use as septic tank absorption fields. A high water table makes a soil poorly suited to basements or underground installations.

The National Cooperative Soil Survey is a joint effort of the United States Department of Agriculture and other Federal agencies, State agencies including the Agricultural Experiment Stations, and local agencies. The Natural Resources Conservation Service (NRCS) has leadership for the Federal part of the National Cooperative Soil Survey.

Information about soils is updated periodically. Updated information is available through the NRCS Web Soil Survey, the site for official soil survey information.

The U.S. Department of Agriculture (USDA) prohibits discrimination in all its programs and activities on the basis of race, color, national origin, age, disability, and where applicable, sex, marital status, familial status, parental status, religion, sexual orientation, genetic information, political beliefs, reprisal, or because all or a part of an individual's income is derived from any public assistance program. (Not all prohibited bases apply to all programs.) Persons with disabilities who require

alternative means for communication of program information (Braille, large print, audiotape, etc.) should contact USDA's TARGET Center at (202) 720-2600 (voice and TDD). To file a complaint of discrimination, write to USDA, Director, Office of Civil Rights, 1400 Independence Avenue, S.W., Washington, D.C. 20250-9410 or call (800) 795-3272 (voice) or (202) 720-6382 (TDD). USDA is an equal opportunity provider and employer.

Contents

Preface	2
How Soil Surveys Are Made	5
Soil Map	8
Soil Map	9
Legend	10
Map Unit Legend	. 11
Map Unit Descriptions	. 12
Marion County, Ohio	. 14
AqUXA—Aquents, clayey-Urban land complex, 0 to 3 percent slopes	. 14
Ble1B1—Blount silt loam, end moraine, 2 to 4 percent slopes	. 15
Blg1A1—Blount silt loam, ground moraine, 0 to 2 percent slopes	. 16
Blg1B1—Blount silt loam, ground moraine, 2 to 4 percent slopes	. 18
FoA—Fox loam, till plain, 0 to 2 percent slopes	. 19
FoB—Fox loam, till plain, 2 to 6 percent slopes	. 21
Gwe5B2—Glynwood clay loam, end moraine, 2 to 6 percent slopes,	
eroded	22
Gwg1B1—Glynwood silt loam, ground moraine, 2 to 6 percent slopes	. 24
KeB—Kendallville loam, 2 to 6 percent slopes	25
MaA—Martinsville loam, 0 to 2 percent slopes	. 26
MaB—Martinsville loam, 2 to 6 percent slopes	. 28
Me—Medway clay loam, rarely flooded	. 29
Mf—Milford silty clay loam, 0 to 2 percent slopes	. 30
MnB—Milton silt loam, 1 to 4 percent slopes	. 31
OcB—Ockley loam, 2 to 6 percent slopes	33
Pk—Pewamo silty clay loam, 0 to 1 percent slopes	34
Sc—Saranac silty clay loam, 0 to 2 percent slopes, frequently flooded	35
SkA—Sleeth loam, 0 to 3 percent slopes	37
So—Sloan silty clay loam, 0 to 1 percent slopes, occasionally flooded	. 38
W—Water	
WhA—Whitaker loam, 0 to 3 percent slopes	40
Poforonoos	42

How Soil Surveys Are Made

Soil surveys are made to provide information about the soils and miscellaneous areas in a specific area. They include a description of the soils and miscellaneous areas and their location on the landscape and tables that show soil properties and limitations affecting various uses. Soil scientists observed the steepness, length, and shape of the slopes; the general pattern of drainage; the kinds of crops and native plants; and the kinds of bedrock. They observed and described many soil profiles. A soil profile is the sequence of natural layers, or horizons, in a soil. The profile extends from the surface down into the unconsolidated material in which the soil formed or from the surface down to bedrock. The unconsolidated material is devoid of roots and other living organisms and has not been changed by other biological activity.

Currently, soils are mapped according to the boundaries of major land resource areas (MLRAs). MLRAs are geographically associated land resource units that share common characteristics related to physiography, geology, climate, water resources, soils, biological resources, and land uses (USDA, 2006). Soil survey areas typically consist of parts of one or more MLRA.

The soils and miscellaneous areas in a survey area occur in an orderly pattern that is related to the geology, landforms, relief, climate, and natural vegetation of the area. Each kind of soil and miscellaneous area is associated with a particular kind of landform or with a segment of the landform. By observing the soils and miscellaneous areas in the survey area and relating their position to specific segments of the landform, a soil scientist develops a concept, or model, of how they were formed. Thus, during mapping, this model enables the soil scientist to predict with a considerable degree of accuracy the kind of soil or miscellaneous area at a specific location on the landscape.

Commonly, individual soils on the landscape merge into one another as their characteristics gradually change. To construct an accurate soil map, however, soil scientists must determine the boundaries between the soils. They can observe only a limited number of soil profiles. Nevertheless, these observations, supplemented by an understanding of the soil-vegetation-landscape relationship, are sufficient to verify predictions of the kinds of soil in an area and to determine the boundaries.

Soil scientists recorded the characteristics of the soil profiles that they studied. They noted soil color, texture, size and shape of soil aggregates, kind and amount of rock fragments, distribution of plant roots, reaction, and other features that enable them to identify soils. After describing the soils in the survey area and determining their properties, the soil scientists assigned the soils to taxonomic classes (units). Taxonomic classes are concepts. Each taxonomic class has a set of soil characteristics with precisely defined limits. The classes are used as a basis for comparison to classify soils systematically. Soil taxonomy, the system of taxonomic classification used in the United States, is based mainly on the kind and character of soil properties and the arrangement of horizons within the profile. After the soil

scientists classified and named the soils in the survey area, they compared the individual soils with similar soils in the same taxonomic class in other areas so that they could confirm data and assemble additional data based on experience and research.

The objective of soil mapping is not to delineate pure map unit components; the objective is to separate the landscape into landforms or landform segments that have similar use and management requirements. Each map unit is defined by a unique combination of soil components and/or miscellaneous areas in predictable proportions. Some components may be highly contrasting to the other components of the map unit. The presence of minor components in a map unit in no way diminishes the usefulness or accuracy of the data. The delineation of such landforms and landform segments on the map provides sufficient information for the development of resource plans. If intensive use of small areas is planned, onsite investigation is needed to define and locate the soils and miscellaneous areas.

Soil scientists make many field observations in the process of producing a soil map. The frequency of observation is dependent upon several factors, including scale of mapping, intensity of mapping, design of map units, complexity of the landscape, and experience of the soil scientist. Observations are made to test and refine the soil-landscape model and predictions and to verify the classification of the soils at specific locations. Once the soil-landscape model is refined, a significantly smaller number of measurements of individual soil properties are made and recorded. These measurements may include field measurements, such as those for color, depth to bedrock, and texture, and laboratory measurements, such as those for content of sand, silt, clay, salt, and other components. Properties of each soil typically vary from one point to another across the landscape.

Observations for map unit components are aggregated to develop ranges of characteristics for the components. The aggregated values are presented. Direct measurements do not exist for every property presented for every map unit component. Values for some properties are estimated from combinations of other properties.

While a soil survey is in progress, samples of some of the soils in the area generally are collected for laboratory analyses and for engineering tests. Soil scientists interpret the data from these analyses and tests as well as the field-observed characteristics and the soil properties to determine the expected behavior of the soils under different uses. Interpretations for all of the soils are field tested through observation of the soils in different uses and under different levels of management. Some interpretations are modified to fit local conditions, and some new interpretations are developed to meet local needs. Data are assembled from other sources, such as research information, production records, and field experience of specialists. For example, data on crop yields under defined levels of management are assembled from farm records and from field or plot experiments on the same kinds of soil.

Predictions about soil behavior are based not only on soil properties but also on such variables as climate and biological activity. Soil conditions are predictable over long periods of time, but they are not predictable from year to year. For example, soil scientists can predict with a fairly high degree of accuracy that a given soil will have a high water table within certain depths in most years, but they cannot predict that a high water table will always be at a specific level in the soil on a specific date.


After soil scientists located and identified the significant natural bodies of soil in the survey area, they drew the boundaries of these bodies on aerial photographs and

identified each as a specific map unit. Aerial photographs show trees, buildings, fields, roads, and rivers, all of which help in locating boundaries accurately.

Soil Map

The soil map section includes the soil map for the defined area of interest, a list of soil map units on the map and extent of each map unit, and cartographic symbols displayed on the map. Also presented are various metadata about data used to produce the map, and a description of each soil map unit.

Custom Soil Resource Report Soil Map



MAP LEGEND

å

Ŷ

Δ

Water Features

Transportation

 \sim

Background

Spoil Area

Stony Spot

Wet Spot

Other

Rails

US Routes

Major Roads

Local Roads

Very Stony Spot

Special Line Features

Streams and Canals

Interstate Highways

Aerial Photography


Area of Interest (AOI)

Area of Interest (AOI)

Soils

Soil Map Unit Polygons

Soil Map Unit Points



Special Point Features

Blowout

Borrow Pit

Clay Spot

Closed Depression

Gravel Pit

Gravelly Spot

Landfill

A Lava Flow

Marsh or swamp

Mine or Quarry

Miscellaneous Water

Perennial Water

Rock Outcrop

→ Saline Spot

Sandy Spot

Severely Eroded Spot

Sinkhole

Slide or Slip

Sodic Spot

MAP INFORMATION

The soil surveys that comprise your AOI were mapped at 1:15.800.

Please rely on the bar scale on each map sheet for map measurements.

Source of Map: Natural Resources Conservation Service Web Soil Survey URL:

Coordinate System: Web Mercator (EPSG:3857)

Maps from the Web Soil Survey are based on the Web Mercator projection, which preserves direction and shape but distorts distance and area. A projection that preserves area, such as the Albers equal-area conic projection, should be used if more accurate calculations of distance or area are required.

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Soil Survey Area: Marion County, Ohio Survey Area Data: Version 22, Jun 11, 2020

Soil map units are labeled (as space allows) for map scales 1:50,000 or larger.

Date(s) aerial images were photographed: Nov 12, 2009—Aug 27, 2016

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.

10

Map Unit Legend

Map Unit Symbol	Map Unit Name	Acres in AOI	Percent of AOI
AqUXA	Aquents, clayey-Urban land complex, 0 to 3 percent slopes	0.1	0.0%
Ble1B1	Blount silt loam, end moraine, 2 to 4 percent slopes	2.8	0.3%
Blg1A1	Blount silt loam, ground moraine, 0 to 2 percent slopes	142.4	14.9%
Blg1B1	Blount silt loam, ground moraine, 2 to 4 percent slopes	2.1	0.2%
FoA	Fox loam, till plain, 0 to 2 percent slopes	7.4	0.8%
FoB	Fox loam, till plain, 2 to 6 percent slopes	7.7	0.8%
Gwe5B2	Glynwood clay loam, end moraine, 2 to 6 percent slopes, eroded	5.1	0.5%
Gwg1B1	Glynwood silt loam, ground moraine, 2 to 6 percent slopes	65.7	6.9%
KeB	Kendallville loam, 2 to 6 percent slopes	2.5	0.3%
MaA	Martinsville loam, 0 to 2 percent slopes	14.4	1.5%
МаВ	Martinsville loam, 2 to 6 percent slopes	56.2	5.9%
Me	Medway clay loam, rarely flooded	358.8	37.5%
Mf	Milford silty clay loam, 0 to 2 percent slopes	25.9	2.7%
MnB	Milton silt loam, 1 to 4 percent slopes	4.3	0.5%
ОсВ	Ockley loam, 2 to 6 percent slopes	10.1	1.1%
Pk	Pewamo silty clay loam, 0 to 1 percent slopes	82.6	8.6%
Sc	Saranac silty clay loam, 0 to 2 percent slopes, frequently flooded	84.8	8.9%
SkA	Sleeth loam, 0 to 3 percent slopes	46.1	4.8%
So	Sloan silty clay loam, 0 to 1 percent slopes, occasionally flooded	1.6	0.2%
W	Water	4.9	0.5%

Map Unit Symbol	Map Unit Name	Acres in AOI	Percent of AOI
WhA	Whitaker loam, 0 to 3 percent slopes	30.4	3.2%
Totals for Area of Interest		955.8	100.0%

Map Unit Descriptions

The map units delineated on the detailed soil maps in a soil survey represent the soils or miscellaneous areas in the survey area. The map unit descriptions, along with the maps, can be used to determine the composition and properties of a unit.

A map unit delineation on a soil map represents an area dominated by one or more major kinds of soil or miscellaneous areas. A map unit is identified and named according to the taxonomic classification of the dominant soils. Within a taxonomic class there are precisely defined limits for the properties of the soils. On the landscape, however, the soils are natural phenomena, and they have the characteristic variability of all natural phenomena. Thus, the range of some observed properties may extend beyond the limits defined for a taxonomic class. Areas of soils of a single taxonomic class rarely, if ever, can be mapped without including areas of other taxonomic classes. Consequently, every map unit is made up of the soils or miscellaneous areas for which it is named and some minor components that belong to taxonomic classes other than those of the major soils.

Most minor soils have properties similar to those of the dominant soil or soils in the map unit, and thus they do not affect use and management. These are called noncontrasting, or similar, components. They may or may not be mentioned in a particular map unit description. Other minor components, however, have properties and behavioral characteristics divergent enough to affect use or to require different management. These are called contrasting, or dissimilar, components. They generally are in small areas and could not be mapped separately because of the scale used. Some small areas of strongly contrasting soils or miscellaneous areas are identified by a special symbol on the maps. If included in the database for a given area, the contrasting minor components are identified in the map unit descriptions along with some characteristics of each. A few areas of minor components may not have been observed, and consequently they are not mentioned in the descriptions, especially where the pattern was so complex that it was impractical to make enough observations to identify all the soils and miscellaneous areas on the landscape.

The presence of minor components in a map unit in no way diminishes the usefulness or accuracy of the data. The objective of mapping is not to delineate pure taxonomic classes but rather to separate the landscape into landforms or landform segments that have similar use and management requirements. The delineation of such segments on the map provides sufficient information for the development of resource plans. If intensive use of small areas is planned, however, onsite investigation is needed to define and locate the soils and miscellaneous areas.

An identifying symbol precedes the map unit name in the map unit descriptions. Each description includes general facts about the unit and gives important soil properties and qualities.

Soils that have profiles that are almost alike make up a *soil series*. Except for differences in texture of the surface layer, all the soils of a series have major horizons that are similar in composition, thickness, and arrangement.

Soils of one series can differ in texture of the surface layer, slope, stoniness, salinity, degree of erosion, and other characteristics that affect their use. On the basis of such differences, a soil series is divided into *soil phases*. Most of the areas shown on the detailed soil maps are phases of soil series. The name of a soil phase commonly indicates a feature that affects use or management. For example, Alpha silt loam, 0 to 2 percent slopes, is a phase of the Alpha series.

Some map units are made up of two or more major soils or miscellaneous areas. These map units are complexes, associations, or undifferentiated groups.

A *complex* consists of two or more soils or miscellaneous areas in such an intricate pattern or in such small areas that they cannot be shown separately on the maps. The pattern and proportion of the soils or miscellaneous areas are somewhat similar in all areas. Alpha-Beta complex, 0 to 6 percent slopes, is an example.

An association is made up of two or more geographically associated soils or miscellaneous areas that are shown as one unit on the maps. Because of present or anticipated uses of the map units in the survey area, it was not considered practical or necessary to map the soils or miscellaneous areas separately. The pattern and relative proportion of the soils or miscellaneous areas are somewhat similar. Alpha-Beta association, 0 to 2 percent slopes, is an example.

An *undifferentiated group* is made up of two or more soils or miscellaneous areas that could be mapped individually but are mapped as one unit because similar interpretations can be made for use and management. The pattern and proportion of the soils or miscellaneous areas in a mapped area are not uniform. An area can be made up of only one of the major soils or miscellaneous areas, or it can be made up of all of them. Alpha and Beta soils, 0 to 2 percent slopes, is an example.

Some surveys include *miscellaneous areas*. Such areas have little or no soil material and support little or no vegetation. Rock outcrop is an example.

Marion County, Ohio

AqUXA—Aquents, clayey-Urban land complex, 0 to 3 percent slopes

Map Unit Setting

National map unit symbol: 2qhvt Elevation: 750 to 1,200 feet

Mean annual precipitation: 34 to 42 inches Mean annual air temperature: 48 to 55 degrees F

Frost-free period: 140 to 180 days

Farmland classification: Not prime farmland

Map Unit Composition

Aquents, clayey, and similar soils: 65 percent Urban land, commercial/industrial: 30 percent

Minor components: 5 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Aquents, Clayey

Setting

Landform: Depressions, till plains

Landform position (two-dimensional): Footslope Landform position (three-dimensional): Interfluve

Down-slope shape: Concave, linear Across-slope shape: Concave, linear

Parent material: Human transported material over wisconsin till derived from

limestone and shale

Typical profile

^C - 0 to 40 inches: clay loam Btgb - 40 to 57 inches: clay Cg - 57 to 80 inches: clay loam

Properties and qualities

Slope: 0 to 3 percent

Depth to restrictive feature: More than 80 inches

Drainage class: Poorly drained

Runoff class: Low

Capacity of the most limiting layer to transmit water (Ksat): Low to moderately high

(0.01 to 0.20 in/hr)

Depth to water table: About 0 to 12 inches

Frequency of flooding: None Frequency of ponding: Frequent

Calcium carbonate, maximum content: 30 percent

Maximum salinity: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)

Available water capacity: Low (about 6.0 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Hydrologic Soil Group: C/D

Ecological site: F111BY203IN - WET ALLUVIUM FOREST

Hydric soil rating: Yes

Description of Urban Land, Commercial/industrial

Setting

Landform: Till plains

Minor Components

Pewamo, urban

Percent of map unit: 5 percent

Landform: Depressions, till plains, ground moraines Landform position (two-dimensional): Toeslope Landform position (three-dimensional): Dip

Down-slope shape: Concave Across-slope shape: Linear

Ecological site: F111BY501IN - TILL DEPRESSION

Hydric soil rating: Yes

Ble1B1—Blount silt loam, end moraine, 2 to 4 percent slopes

Map Unit Setting

National map unit symbol: 2s1j5 Elevation: 700 to 1,300 feet

Mean annual precipitation: 34 to 42 inches Mean annual air temperature: 48 to 54 degrees F

Frost-free period: 140 to 180 days

Farmland classification: Prime farmland if drained

Map Unit Composition

Blount, end moraine, and similar soils: 85 percent

Minor components: 15 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Blount, End Moraine

Setting

Landform: End moraines on till plains

Landform position (two-dimensional): Footslope, backslope

Landform position (three-dimensional): Side slope

Down-slope shape: Linear Across-slope shape: Linear

Parent material: Wisconsin till derived from limestone and shale

Typical profile

Ap - 0 to 9 inches: silt loam
Bt - 9 to 32 inches: silty clay
BC - 32 to 37 inches: clay loam
Cd - 37 to 79 inches: clay loam

Properties and qualities

Slope: 2 to 4 percent

Depth to restrictive feature: 30 to 56 inches to densic material

Drainage class: Somewhat poorly drained

Runoff class: High

Capacity of the most limiting layer to transmit water (Ksat): Low to moderately high

(0.01 to 0.20 in/hr)

Depth to water table: About 6 to 12 inches

Frequency of flooding: None Frequency of ponding: None

Calcium carbonate, maximum content: 35 percent

Maximum salinity: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)

Available water capacity: Low (about 5.6 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 2e

Hydrologic Soil Group: D

Ecological site: F111BY502IN - WET TILL RIDGE

Hydric soil rating: No

Minor Components

Glynwood, end moraine

Percent of map unit: 9 percent

Landform: End moraines on till plains

Landform position (two-dimensional): Backslope, summit Landform position (three-dimensional): Crest, side slope

Down-slope shape: Convex Across-slope shape: Convex

Ecological site: F111BY503IN - TILL RIDGE

Hydric soil rating: No

Pewamo, end moraine

Percent of map unit: 6 percent

Landform: End moraines on till plains

Landform position (two-dimensional): Toeslope Landform position (three-dimensional): Base slope

Down-slope shape: Concave Across-slope shape: Concave

Ecological site: F111BY501IN - TILL DEPRESSION

Hydric soil rating: Yes

Blg1A1—Blount silt loam, ground moraine, 0 to 2 percent slopes

Map Unit Setting

National map unit symbol: 2skcv Elevation: 700 to 1,300 feet

Mean annual precipitation: 34 to 42 inches Mean annual air temperature: 48 to 54 degrees F

Frost-free period: 140 to 180 days

Farmland classification: Prime farmland if drained

Map Unit Composition

Blount, ground moraine, and similar soils: 85 percent

Minor components: 15 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Blount, Ground Moraine

Setting

Landform: Ground moraines on till plains Landform position (two-dimensional): Footslope Landform position (three-dimensional): Interfluve

Down-slope shape: Linear Across-slope shape: Linear

Parent material: Wisconsin till derived from limestone and shale

Typical profile

Ap - 0 to 10 inches: silt loam
Bt - 10 to 33 inches: silty clay
BC - 33 to 39 inches: clay loam
Cd - 39 to 79 inches: clay loam

Properties and qualities

Slope: 0 to 2 percent

Depth to restrictive feature: 31 to 54 inches to densic material

Drainage class: Somewhat poorly drained

Runoff class: High

Capacity of the most limiting layer to transmit water (Ksat): Low to moderately high

(0.01 to 0.20 in/hr)

Depth to water table: About 6 to 12 inches

Frequency of flooding: None Frequency of ponding: None

Calcium carbonate, maximum content: 35 percent

Maximum salinity: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)

Available water capacity: Moderate (about 6.2 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 2w

Hydrologic Soil Group: D

Ecological site: F111BY502IN - WET TILL RIDGE

Hydric soil rating: No

Minor Components

Pewamo, ground moraine

Percent of map unit: 9 percent

Landform: Ground moraines on till plains
Landform position (two-dimensional): Toeslope
Landform position (three-dimensional): Base slope

Down-slope shape: Linear

Across-slope shape: Concave, linear

Ecological site: F111BY501IN - TILL DEPRESSION

Hydric soil rating: Yes

Glynwood, ground moraine

Percent of map unit: 6 percent

Landform: Ground moraines on till plains

Landform position (two-dimensional): Shoulder, backslope Landform position (three-dimensional): Nose slope, side slope

Down-slope shape: Convex Across-slope shape: Linear

Ecological site: F111BY503IN - TILL RIDGE

Hydric soil rating: No

Blg1B1—Blount silt loam, ground moraine, 2 to 4 percent slopes

Map Unit Setting

National map unit symbol: 2s1j6 Elevation: 700 to 1,300 feet

Mean annual precipitation: 34 to 42 inches Mean annual air temperature: 48 to 54 degrees F

Frost-free period: 140 to 180 days

Farmland classification: Prime farmland if drained

Map Unit Composition

Blount, ground moraine, and similar soils: 85 percent

Minor components: 15 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Blount, Ground Moraine

Setting

Landform: Ground moraines on till plains

Landform position (two-dimensional): Summit, backslope

Landform position (three-dimensional): Interfluve

Down-slope shape: Linear Across-slope shape: Linear

Parent material: Wisconsin till derived from limestone and shale

Typical profile

Ap - 0 to 9 inches: silt loam Bt - 9 to 32 inches: silty clay BC - 32 to 37 inches: clay loam Cd - 37 to 79 inches: clay loam

Properties and qualities

Slope: 2 to 4 percent

Depth to restrictive feature: 30 to 54 inches to densic material

Drainage class: Somewhat poorly drained

Runoff class: High

Capacity of the most limiting layer to transmit water (Ksat): Low to moderately high

(0.01 to 0.20 in/hr)

Depth to water table: About 6 to 12 inches

Frequency of flooding: None

Frequency of ponding: None

Calcium carbonate, maximum content: 35 percent

Maximum salinity: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)

Available water capacity: Low (about 5.6 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 2e

Hydrologic Soil Group: D

Ecological site: F111BY502IN - WET TILL RIDGE

Hydric soil rating: No

Minor Components

Pewamo, ground moraine

Percent of map unit: 9 percent

Landform: Ground moraines on till plains
Landform position (two-dimensional): Toeslope
Landform position (three-dimensional): Base slope

Down-slope shape: Linear Across-slope shape: Concave

Ecological site: F111BY501IN - TILL DEPRESSION

Hydric soil rating: Yes

Glynwood, ground moraine

Percent of map unit: 6 percent

Landform: Ground moraines on till plains

Landform position (two-dimensional): Shoulder, backslope Landform position (three-dimensional): Nose slope, side slope

Down-slope shape: Convex Across-slope shape: Linear

Ecological site: F111BY503IN - TILL RIDGE

Hydric soil rating: No

FoA—Fox loam, till plain, 0 to 2 percent slopes

Map Unit Setting

National map unit symbol: 2t6ms Elevation: 620 to 1,150 feet

Mean annual precipitation: 36 to 41 inches Mean annual air temperature: 50 to 52 degrees F

Frost-free period: 155 to 175 days

Farmland classification: All areas are prime farmland

Map Unit Composition

Fox and similar soils: 90 percent Minor components: 10 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Fox

Setting

Landform: Outwash terraces, outwash plains Landform position (two-dimensional): Summit Landform position (three-dimensional): Crest, tread

Down-slope shape: Convex

Across-slope shape: Linear, convex

Parent material: Loamy glaciofluvial deposits over sandy and gravelly outwash

Typical profile

Ap - 0 to 9 inches: loam

Bt1 - 9 to 27 inches: sandy clay loam Bt2 - 27 to 33 inches: gravelly loam

2C - 33 to 79 inches: stratified sand to gravel

Properties and qualities

Slope: 0 to 2 percent

Depth to restrictive feature: 20 to 40 inches to strongly contrasting textural

stratification

Drainage class: Well drained

Runoff class: Low

Capacity of the most limiting layer to transmit water (Ksat): Moderately high to high

(0.60 to 2.00 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Calcium carbonate, maximum content: 55 percent

Maximum salinity: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)

Available water capacity: Low (about 5.8 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 2s

Hydrologic Soil Group: B

Ecological site: F111BY404IN - DRY OUTWASH UPLAND

Hydric soil rating: No

Minor Components

Homer

Percent of map unit: 6 percent

Landform: Outwash terraces, outwash plains
Landform position (two-dimensional): Footslope

Landform position (three-dimensional): Interfluve, tread

Down-slope shape: Concave, linear

Across-slope shape: Linear

Ecological site: F111BY403IN - OUTWASH UPLAND

Hydric soil rating: No

Westland

Percent of map unit: 4 percent

Landform: Depressions, drainageways

Landform position (two-dimensional): Toeslope Landform position (three-dimensional): Tread

Down-slope shape: Concave

Across-slope shape: Concave, linear

Ecological site: R111BY401IN - WET OUTWASH MOLLISOL

Hydric soil rating: Yes

FoB-Fox loam, till plain, 2 to 6 percent slopes

Map Unit Setting

National map unit symbol: 2t6mt Elevation: 620 to 1,150 feet

Mean annual precipitation: 36 to 41 inches Mean annual air temperature: 50 to 52 degrees F

Frost-free period: 155 to 175 days

Farmland classification: All areas are prime farmland

Map Unit Composition

Fox and similar soils: 90 percent Minor components: 10 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Fox

Setting

Landform: Outwash plains, outwash terraces

Landform position (two-dimensional): Summit, shoulder Landform position (three-dimensional): Crest, tread

Down-slope shape: Convex

Across-slope shape: Convex, linear

Parent material: Loamy glaciofluvial deposits over sandy and gravelly outwash

Typical profile

Ap - 0 to 9 inches: loam

Bt1 - 9 to 27 inches: sandy clay loam Bt2 - 27 to 33 inches: gravelly loam

2C - 33 to 79 inches: stratified sand to gravel

Properties and qualities

Slope: 2 to 6 percent

Depth to restrictive feature: 20 to 40 inches to strongly contrasting textural

stratification

Drainage class: Well drained

Runoff class: Low

Capacity of the most limiting layer to transmit water (Ksat): Moderately high to high

(0.60 to 2.00 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Calcium carbonate, maximum content: 55 percent

Maximum salinity: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)

Available water capacity: Low (about 5.8 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 2e

Hydrologic Soil Group: B

Ecological site: F111BY404IN - DRY OUTWASH UPLAND

Hydric soil rating: No

Minor Components

Homer

Percent of map unit: 6 percent

Landform: Outwash terraces, outwash plains Landform position (two-dimensional): Footslope

Landform position (three-dimensional): Interfluve, tread

Down-slope shape: Concave, linear

Across-slope shape: Linear

Ecological site: F111BY403IN - OUTWASH UPLAND

Hydric soil rating: No

Westland

Percent of map unit: 4 percent

Landform: Drainageways, depressions

Landform position (two-dimensional): Toeslope Landform position (three-dimensional): Tread

Down-slope shape: Concave

Across-slope shape: Linear, concave

Ecological site: R111BY401IN - WET OUTWASH MOLLISOL

Hydric soil rating: Yes

Gwe5B2—Glynwood clay loam, end moraine, 2 to 6 percent slopes, eroded

Map Unit Setting

National map unit symbol: 2t6lj Elevation: 720 to 1,320 feet

Mean annual precipitation: 34 to 42 inches Mean annual air temperature: 48 to 54 degrees F

Frost-free period: 140 to 180 days

Farmland classification: All areas are prime farmland

Map Unit Composition

Glynwood, end moraine, and similar soils: 85 percent

Minor components: 15 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Glynwood, End Moraine

Setting

Landform: End moraines on till plains

Landform position (two-dimensional): Shoulder, summit

Landform position (three-dimensional): Side slope, crest

Down-slope shape: Convex

Across-slope shape: Linear, convex

Parent material: Wisconsin till derived from limestone and shale

Typical profile

Ap - 0 to 7 inches: clay loam Bt - 7 to 26 inches: clay

BC - 26 to 30 inches: clay loam Cd - 30 to 79 inches: clay loam

Properties and qualities

Slope: 2 to 6 percent

Depth to restrictive feature: 24 to 42 inches to densic material

Drainage class: Moderately well drained

Runoff class: High

Capacity of the most limiting layer to transmit water (Ksat): Low to moderately high

(0.01 to 0.20 in/hr)

Depth to water table: About 12 to 24 inches

Frequency of flooding: None Frequency of ponding: None

Calcium carbonate, maximum content: 35 percent

Maximum salinity: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)

Available water capacity: Low (about 4.3 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 2e

Hydrologic Soil Group: D

Ecological site: F111BY503IN - TILL RIDGE

Hydric soil rating: No

Minor Components

Blount, end moraine

Percent of map unit: 9 percent

Landform: End moraines on till plains

Landform position (two-dimensional): Footslope, backslope

Landform position (three-dimensional): Side slope

Down-slope shape: Linear Across-slope shape: Linear

Ecological site: F111BY502IN - WET TILL RIDGE

Hydric soil rating: No

Pewamo

Percent of map unit: 6 percent

Landform: End moraines on till plains

Landform position (two-dimensional): Toeslope Landform position (three-dimensional): Base slope

Down-slope shape: Linear Across-slope shape: Concave

Ecological site: F111BY501IN - TILL DEPRESSION

Hydric soil rating: Yes

Gwg1B1—Glynwood silt loam, ground moraine, 2 to 6 percent slopes

Map Unit Setting

National map unit symbol: 2v4bl Elevation: 700 to 1,300 feet

Mean annual precipitation: 34 to 42 inches Mean annual air temperature: 48 to 54 degrees F

Frost-free period: 140 to 180 days

Farmland classification: All areas are prime farmland

Map Unit Composition

Glynwood, ground moraine, and similar soils: 85 percent

Minor components: 15 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Glynwood, Ground Moraine

Setting

Landform: Ground moraines on till plains

Landform position (two-dimensional): Shoulder, backslope Landform position (three-dimensional): Nose slope, side slope

Down-slope shape: Convex, linear Across-slope shape: Linear, convex

Parent material: Wisconsin till derived from limestone and shale

Typical profile

Ap - 0 to 9 inches: silt loam Bt - 9 to 29 inches: clay

BC - 29 to 34 inches: clay loam Cd - 34 to 79 inches: clay loam

Properties and qualities

Slope: 2 to 6 percent

Depth to restrictive feature: 28 to 45 inches to densic material

Drainage class: Moderately well drained

Runoff class: High

Capacity of the most limiting layer to transmit water (Ksat): Low to moderately high

(0.01 to 0.20 in/hr)

Depth to water table: About 12 to 24 inches

Frequency of flooding: None Frequency of ponding: None

Calcium carbonate, maximum content: 35 percent

Maximum salinity: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)

Available water capacity: Low (about 5.2 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 2e

Hydrologic Soil Group: D

Ecological site: F111BY503IN - TILL RIDGE

Hydric soil rating: No

Minor Components

Blount, ground moraine

Percent of map unit: 9 percent

Landform: Ground moraines on till plains

Landform position (two-dimensional): Summit, backslope

Landform position (three-dimensional): Interfluve

Down-slope shape: Linear, convex

Across-slope shape: Linear

Ecological site: F111BY502IN - WET TILL RIDGE

Hydric soil rating: No

Pewamo

Percent of map unit: 6 percent

Landform: Ground moraines on till plains
Landform position (two-dimensional): Toeslope
Landform position (three-dimensional): Base slope

Down-slope shape: Linear Across-slope shape: Concave

Ecological site: F111BY501IN - TILL DEPRESSION

Hydric soil rating: Yes

KeB—Kendallville loam, 2 to 6 percent slopes

Map Unit Setting

National map unit symbol: 5r4k Elevation: 700 to 1.210 feet

Mean annual precipitation: 30 to 42 inches
Mean annual air temperature: 48 to 55 degrees F

Frost-free period: 140 to 180 days

Farmland classification: All areas are prime farmland

Map Unit Composition

Kendallville and similar soils: 85 percent

Minor components: 15 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Kendallville

Setting

Landform: Kames, eskers, outwash terraces, moraines

Landform position (two-dimensional): Summit Landform position (three-dimensional): Interfluve

Down-slope shape: Convex Across-slope shape: Linear

Parent material: Loess over outwash over till

Typical profile

H1 - 0 to 9 inches: loam

H2 - 9 to 40 inches: gravelly clay loam

H3 - 40 to 60 inches: silt loam

Properties and qualities

Slope: 2 to 6 percent

Depth to restrictive feature: More than 80 inches

Drainage class: Well drained

Runoff class: Low

Capacity of the most limiting layer to transmit water (Ksat): Moderately high (0.20

to 0.60 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Calcium carbonate, maximum content: 45 percent Available water capacity: Moderate (about 8.8 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 2e

Hydrologic Soil Group: B

Ecological site: F111BY503IN - TILL RIDGE

Hydric soil rating: No

Minor Components

Glynwood

Percent of map unit: 5 percent

Landform: Ground moraines, end moraines Ecological site: F111BY503IN - TILL RIDGE

Somewhat poorly drained soils

Percent of map unit: 5 percent

Ockley

Percent of map unit: 5 percent

Landform: Terraces

Ecological site: F111BY404IN - DRY OUTWASH UPLAND

MaA—Martinsville loam, 0 to 2 percent slopes

Map Unit Setting

National map unit symbol: 5r4n Elevation: 360 to 1,000 feet

Mean annual precipitation: 30 to 45 inches Mean annual air temperature: 45 to 57 degrees F

Frost-free period: 130 to 210 days

Farmland classification: All areas are prime farmland

Map Unit Composition

Martinsville and similar soils: 90 percent

Minor components: 10 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Martinsville

Setting

Landform: Terraces

Landform position (two-dimensional): Summit Landform position (three-dimensional): Tread

Down-slope shape: Convex Across-slope shape: Linear Parent material: Outwash

Typical profile

H1 - 0 to 10 inches: loam H2 - 10 to 32 inches: loam H3 - 32 to 70 inches: sandy loam

Properties and qualities

Slope: 0 to 2 percent

Depth to restrictive feature: More than 80 inches

Drainage class: Well drained

Runoff class: Low

Capacity of the most limiting layer to transmit water (Ksat): Moderately high to high

(0.60 to 2.00 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Available water capacity: High (about 10.3 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 1

Hydrologic Soil Group: B

Ecological site: F111BY404IN - DRY OUTWASH UPLAND

Hydric soil rating: No

Minor Components

Fitchville

Percent of map unit: 4 percent Landform: Lake plains, terraces Down-slope shape: Concave Across-slope shape: Linear

Ecological site: F111BY102IN - LACUSTRINE FOREST

Whitaker

Percent of map unit: 3 percent

Landform: Till plains, valley trains, stream terraces, outwash plains, lake plains

Ecological site: F111BY403IN - OUTWASH UPLAND

Rarely flooded areas

Percent of map unit: 3 percent

MaB—Martinsville loam, 2 to 6 percent slopes

Map Unit Setting

National map unit symbol: 5r4p Elevation: 360 to 1,000 feet

Mean annual precipitation: 30 to 45 inches Mean annual air temperature: 45 to 57 degrees F

Frost-free period: 130 to 210 days

Farmland classification: All areas are prime farmland

Map Unit Composition

Martinsville and similar soils: 90 percent

Minor components: 10 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Martinsville

Setting

Landform: Terraces

Landform position (two-dimensional): Summit Landform position (three-dimensional): Tread

Down-slope shape: Convex Across-slope shape: Linear Parent material: Outwash

Typical profile

H1 - 0 to 10 inches: loam H2 - 10 to 32 inches: loam H3 - 32 to 70 inches: sandy loam

Properties and qualities

Slope: 2 to 6 percent

Depth to restrictive feature: More than 80 inches

Drainage class: Well drained

Runoff class: Low

Capacity of the most limiting layer to transmit water (Ksat): Moderately high to high

(0.60 to 2.00 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Available water capacity: High (about 10.3 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 2e

Hydrologic Soil Group: B

Ecological site: F111BY404IN - DRY OUTWASH UPLAND

Hydric soil rating: No

Minor Components

Whitaker

Percent of map unit: 10 percent

Landform: Outwash plains, lake plains, till plains, valley trains, stream terraces

Ecological site: F111BY403IN - OUTWASH UPLAND

Me—Medway clay loam, rarely flooded

Map Unit Setting

National map unit symbol: 5r4q Elevation: 900 to 1,100 feet

Mean annual precipitation: 27 to 42 inches Mean annual air temperature: 45 to 55 degrees F

Frost-free period: 140 to 180 days

Farmland classification: All areas are prime farmland

Map Unit Composition

Medway and similar soils: 80 percent Minor components: 20 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Medway

Setting

Landform: Flood plains

Parent material: Loamy alluvium

Typical profile

H1 - 0 to 15 inches: clay loam H2 - 15 to 50 inches: clay loam

H3 - 50 to 60 inches: stratified sandy loam to silty clay loam

Properties and qualities

Slope: 0 to 2 percent

Depth to restrictive feature: More than 80 inches

Drainage class: Moderately well drained

Runoff class: Low

Capacity of the most limiting layer to transmit water (Ksat): Moderately high to high

(0.60 to 2.00 in/hr)

Depth to water table: About 18 to 36 inches

Frequency of flooding: Rare Frequency of ponding: None

Calcium carbonate, maximum content: 20 percent Available water capacity: High (about 9.6 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 1

Hydrologic Soil Group: C

Ecological site: F111BY202IN - DRY ALLUVIUM FLOODPLAIN

Hydric soil rating: No

Minor Components

Sloan

Percent of map unit: 7 percent

Landform: Drainageways, depressions

Ecological site: F111BY201IN - WET ALLUVIUM FLOODPLAIN

Hydric soil rating: Yes

Milford

Percent of map unit: 7 percent

Landform: Drainageways, depressions

Ecological site: F111BY101IN - LACUSTRINE FLATWOOD

Hydric soil rating: Yes

Ockley

Percent of map unit: 6 percent

Landform: Terraces

Ecological site: F111BY404IN - DRY OUTWASH UPLAND

Mf—Milford silty clay loam, 0 to 2 percent slopes

Map Unit Setting

National map unit symbol: 2wp28 Elevation: 640 to 1,150 feet

Mean annual precipitation: 29 to 40 inches

Mean annual air temperature: 46 to 50 degrees F

Frost-free period: 140 to 185 days

Farmland classification: Prime farmland if drained

Map Unit Composition

Milford and similar soils: 90 percent Minor components: 10 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Milford

Setting

Landform: Lake plains

Landform position (three-dimensional): Talf

Down-slope shape: Linear Across-slope shape: Concave Parent material: Lacustrine deposits

Typical profile

Ap - 0 to 13 inches: silty clay loam
Bg1 - 13 to 28 inches: silty clay
Bg2 - 28 to 50 inches: silty clay loam

Cg - 50 to 79 inches: stratified silt loam to silty clay loam to silty clay

Properties and qualities

Slope: 0 to 2 percent

Depth to restrictive feature: More than 80 inches

Drainage class: Poorly drained Runoff class: Negligible

Capacity of the most limiting layer to transmit water (Ksat): Moderately high (0.20

to 0.60 in/hr)

Depth to water table: About 0 to 6 inches

Frequency of flooding: None Frequency of ponding: Frequent

Calcium carbonate, maximum content: 30 percent

Maximum salinity: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)

Available water capacity: High (about 9.8 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 2w

Hydrologic Soil Group: C/D

Ecological site: F111BY101IN - LACUSTRINE FLATWOOD

Other vegetative classification: Mixed/Transitional (Mixed Native Vegetation)

Hydric soil rating: Yes

Minor Components

Del rey

Percent of map unit: 7 percent

Landform: Lake plains

Landform position (three-dimensional): Rise

Down-slope shape: Linear Across-slope shape: Convex

Ecological site: F111BY102IN - LACUSTRINE FOREST

Other vegetative classification: Trees/Timber (Woody Vegetation)

Hydric soil rating: No

Houghton, undrained

Percent of map unit: 3 percent

Landform: Lake plains

Landform position (three-dimensional): Dip

Down-slope shape: Concave Across-slope shape: Concave

Ecological site: R111BY003IN - DEEP MUCK

Other vegetative classification: Mixed/Transitional (Mixed Native Vegetation)

Hydric soil rating: Yes

MnB-Milton silt loam, 1 to 4 percent slopes

Map Unit Setting

National map unit symbol: 5r4s Elevation: 800 to 1,000 feet

Mean annual precipitation: 27 to 42 inches

Mean annual air temperature: 45 to 55 degrees F

Frost-free period: 140 to 210 days

Farmland classification: All areas are prime farmland

Map Unit Composition

Milton and similar soils: 85 percent Minor components: 15 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Milton

Setting

Landform: Till plains

Landform position (two-dimensional): Shoulder Landform position (three-dimensional): Nose slope

Down-slope shape: Convex Across-slope shape: Convex

Parent material: Loess over till over residuum weathered from limestone and

dolomite

Typical profile

H1 - 0 to 12 inches: silt loam H2 - 12 to 29 inches: clay

H3 - 29 to 31 inches: unweathered bedrock

Properties and qualities

Slope: 1 to 4 percent

Depth to restrictive feature: 20 to 40 inches to lithic bedrock

Drainage class: Well drained

Runoff class: Low

Capacity of the most limiting layer to transmit water (Ksat): Moderately low to

moderately high (0.06 to 0.60 in/hr) Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Available water capacity: Low (about 5.1 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 2e

Hydrologic Soil Group: C

Ecological site: F111BY303IN - DRY BEDROCK FOREST

Hydric soil rating: No

Minor Components

Glynwood

Percent of map unit: 8 percent

Landform: Ground moraines, end moraines Ecological site: F111BY503IN - TILL RIDGE

Somewhat poorly drained soils

Percent of map unit: 7 percent

OcB—Ockley loam, 2 to 6 percent slopes

Map Unit Setting

National map unit symbol: 5r4y Elevation: 400 to 1,000 feet

Mean annual precipitation: 34 to 45 inches Mean annual air temperature: 46 to 55 degrees F

Frost-free period: 130 to 180 days

Farmland classification: All areas are prime farmland

Map Unit Composition

Ockley and similar soils: 95 percent *Minor components:* 5 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Ockley

Setting

Landform: Terraces

Landform position (two-dimensional): Summit Landform position (three-dimensional): Tread

Down-slope shape: Convex Across-slope shape: Linear Parent material: Outwash

Typical profile

H1 - 0 to 10 inches: loam H2 - 10 to 26 inches: clay loam

H3 - 26 to 60 inches: gravelly sandy clay loam

H4 - 60 to 70 inches: stratified sand to very gravelly loamy sand

Properties and qualities

Slope: 2 to 6 percent

Depth to restrictive feature: More than 80 inches

Drainage class: Well drained

Runoff class: Low

Capacity of the most limiting layer to transmit water (Ksat): Moderately high to high

(0.60 to 2.00 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Calcium carbonate, maximum content: 30 percent Available water capacity: Moderate (about 8.3 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 2e

Hydrologic Soil Group: B

Ecological site: F111EY404OH - Dry Outwash Upland

Hydric soil rating: No

Minor Components

Fox

Percent of map unit: 3 percent

Landform: Terraces

Ecological site: F111EY404OH - Dry Outwash Upland

Kendallville

Percent of map unit: 2 percent

Landform: Outwash terraces, moraines, kames, eskers

Ecological site: F111EY503OH - Till Ridge

Pk—Pewamo silty clay loam, 0 to 1 percent slopes

Map Unit Setting

National map unit symbol: 2t6lv Elevation: 700 to 1,300 feet

Mean annual precipitation: 32 to 42 inches Mean annual air temperature: 48 to 54 degrees F

Frost-free period: 140 to 180 days

Farmland classification: Prime farmland if drained

Map Unit Composition

Pewamo and similar soils: 85 percent *Minor components*: 15 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Pewamo

Setting

Landform: Drainageways on till plains, depressions on till plains

Landform position (two-dimensional): Toeslope Landform position (three-dimensional): Base slope

Down-slope shape: Linear, concave Across-slope shape: Concave

Parent material: Wisconsin till derived from limestone and shale

Typical profile

Ap - 0 to 11 inches: silty clay loam Btg1 - 11 to 34 inches: silty clay Btg2 - 34 to 47 inches: silty clay BCg - 47 to 57 inches: clay loam Cg - 57 to 79 inches: clay loam

Properties and qualities

Slope: 0 to 1 percent

Depth to restrictive feature: More than 80 inches

Drainage class: Very poorly drained

Runoff class: Negligible

Capacity of the most limiting layer to transmit water (Ksat): Moderately high (0.20

to 0.60 in/hr)

Depth to water table: About 0 to 12 inches

Frequency of flooding: None Frequency of ponding: Frequent

Calcium carbonate, maximum content: 30 percent

Maximum salinity: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)

Available water capacity: Moderate (about 8.5 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 2w

Hydrologic Soil Group: C/D

Ecological site: F111BY501IN - TILL DEPRESSION

Hydric soil rating: Yes

Minor Components

Blount

Percent of map unit: 9 percent

Landform: Ground moraines on till plains, end moraines on till plains

Landform position (two-dimensional): Footslope Landform position (three-dimensional): Interfluve

Down-slope shape: Linear Across-slope shape: Linear

Ecological site: F111BY502IN - WET TILL RIDGE

Hydric soil rating: No

Minster

Percent of map unit: 6 percent Landform: Depressions on till plains

Landform position (two-dimensional): Toeslope Landform position (three-dimensional): Base slope

Down-slope shape: Concave Across-slope shape: Concave

Ecological site: F111BY101IN - LACUSTRINE FLATWOOD

Hydric soil rating: Yes

Sc—Saranac silty clay loam, 0 to 2 percent slopes, frequently flooded

Map Unit Setting

National map unit symbol: 2z6cx Elevation: 640 to 1,150 feet

Mean annual precipitation: 37 to 46 inches Mean annual air temperature: 48 to 55 degrees F

Frost-free period: 165 to 175 days

Farmland classification: Prime farmland if drained and either protected from flooding

or not frequently flooded during the growing season

Map Unit Composition

Saranac, frequently flooded, and similar soils: 85 percent

Minor components: 15 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Saranac, Frequently Flooded

Setting

Landform: Flood plains

Landform position (three-dimensional): Tread

Down-slope shape: Concave Across-slope shape: Linear Parent material: Clayey alluvium

Typical profile

Ap - 0 to 7 inches: silty clay loam Bg - 7 to 44 inches: silty clay Cg - 44 to 69 inches: clay loam

Properties and qualities

Slope: 0 to 2 percent

Depth to restrictive feature: More than 80 inches

Drainage class: Very poorly drained

Runoff class: Negligible

Capacity of the most limiting layer to transmit water (Ksat): Moderately high (0.20

to 0.60 in/hr)

Depth to water table: About 0 to 6 inches Frequency of flooding: FrequentNone

Frequency of ponding: None

Calcium carbonate, maximum content: 20 percent Available water capacity: High (about 10.3 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 3w

Hydrologic Soil Group: C/D

Ecological site: F111BY201IN - WET ALLUVIUM FLOODPLAIN

Other vegetative classification: Mixed/Transitional (Mixed Native Vegetation)

Hydric soil rating: Yes

Minor Components

Sloan, occasionally ponded

Percent of map unit: 8 percent

Landform: Depressions on flood-plain steps Landform position (three-dimensional): Tread

Down-slope shape: Linear Across-slope shape: Concave

Ecological site: F111BY201IN - WET ALLUVIUM FLOODPLAIN

Hydric soil rating: Yes

Shoals, occasionally flooded

Percent of map unit: 7 percent Landform: Flood-plain steps

Landform position (three-dimensional): Tread

Down-slope shape: Linear

Across-slope shape: Linear

Ecological site: F111BY203IN - WET ALLUVIUM FOREST

Hydric soil rating: No

SkA—Sleeth loam, 0 to 3 percent slopes

Map Unit Setting

National map unit symbol: 5r58 Elevation: 400 to 1,000 feet

Mean annual precipitation: 34 to 45 inches Mean annual air temperature: 48 to 55 degrees F

Frost-free period: 130 to 210 days

Farmland classification: Prime farmland if drained

Map Unit Composition

Sleeth and similar soils: 85 percent Minor components: 15 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Sleeth

Setting

Landform: Outwash plains, outwash terraces, stream terraces

Parent material: Loamy outwash over sandy and gravelly outwash

Typical profile

H1 - 0 to 11 inches: loam H2 - 11 to 41 inches: clay loam

H3 - 41 to 60 inches: gravelly sandy loam

H4 - 60 to 80 inches: stratified sand to very gravelly sand

Properties and qualities

Slope: 0 to 3 percent

Depth to restrictive feature: More than 80 inches Drainage class: Somewhat poorly drained

Runoff class: Low

Capacity of the most limiting layer to transmit water (Ksat): Moderately high to high

(0.60 to 2.00 in/hr)

Depth to water table: About 12 to 36 inches

Frequency of flooding: None Frequency of ponding: None

Calcium carbonate, maximum content: 55 percent Available water capacity: High (about 10.3 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 2w

Hydrologic Soil Group: C

Ecological site: F111BY403IN - OUTWASH UPLAND

Hydric soil rating: No

Minor Components

Blount

Percent of map unit: 3 percent

Landform: Rises on ground moraines, rises on end moraines, flats on ground

moraines, flats on end moraines

Landform position (two-dimensional): Summit, shoulder

Down-slope shape: Linear Across-slope shape: Linear

Ecological site: F111BY502IN - WET TILL RIDGE

Bennington

Percent of map unit: 3 percent

Landform: Flats on ground moraines, flats on end moraines, rises on ground

moraines, rises on end moraines

Landform position (two-dimensional): Summit, shoulder

Down-slope shape: Linear Across-slope shape: Linear

Westland

Percent of map unit: 3 percent

Landform: Drainageways, depressions

Ecological site: R111BY401IN - WET OUTWASH MOLLISOL

Hydric soil rating: Yes

Rarely flooded areas

Percent of map unit: 3 percent

Moderately well drained soils

Percent of map unit: 3 percent

So—Sloan silty clay loam, 0 to 1 percent slopes, occasionally flooded

Map Unit Setting

National map unit symbol: 2ydcx Elevation: 520 to 1,340 feet

Mean annual precipitation: 31 to 42 inches Mean annual air temperature: 46 to 54 degrees F

Frost-free period: 140 to 200 days

Farmland classification: Prime farmland if drained

Map Unit Composition

Sloan, occasionally flooded, and similar soils: 90 percent

Minor components: 10 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Sloan, Occasionally Flooded

Setting

Landform: Depressions on flood-plain steps Landform position (two-dimensional): Toeslope

Landform position (three-dimensional): Base slope

Down-slope shape: Linear Across-slope shape: Concave Parent material: Loamy alluvium

Typical profile

Ap - 0 to 12 inches: silty clay loam Bg - 12 to 42 inches: silty clay loam

Cg - 42 to 79 inches: stratified gravelly sandy loam to silty clay loam

Properties and qualities

Slope: 0 to 1 percent

Depth to restrictive feature: More than 80 inches

Drainage class: Very poorly drained

Runoff class: Negligible

Capacity of the most limiting layer to transmit water (Ksat): Moderately high (0.20

to 0.60 in/hr)

Depth to water table: About 0 to 6 inches Frequency of flooding: NoneOccasional Frequency of ponding: Occasional

Calcium carbonate, maximum content: 5 percent

Maximum salinity: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)

Available water capacity: High (about 10.8 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 3w

Hydrologic Soil Group: B/D

Ecological site: F111BY201IN - WET ALLUVIUM FLOODPLAIN

Hydric soil rating: Yes

Minor Components

Shoals

Percent of map unit: 6 percent

Landform: Flood plains

Landform position (two-dimensional): Toeslope Landform position (three-dimensional): Base slope

Down-slope shape: Linear Across-slope shape: Linear

Ecological site: F111BY203IN - WET ALLUVIUM FOREST

Hydric soil rating: No

Sloan, frequently flooded, long duration

Percent of map unit: 4 percent

Landform: Depressions on flood plains

Landform position (two-dimensional): Toeslope Landform position (three-dimensional): Base slope

Down-slope shape: Concave Across-slope shape: Concave

Ecological site: F111BY201IN - WET ALLUVIUM FLOODPLAIN

Hydric soil rating: Yes

W-Water

Map Unit Composition

Water: 100 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

WhA—Whitaker loam, 0 to 3 percent slopes

Map Unit Setting

National map unit symbol: 5r5f Elevation: 360 to 1,000 feet

Mean annual precipitation: 30 to 45 inches Mean annual air temperature: 48 to 55 degrees F

Frost-free period: 140 to 200 days

Farmland classification: Prime farmland if drained

Map Unit Composition

Whitaker and similar soils: 85 percent Minor components: 15 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Whitaker

Setting

Landform: Outwash plains, lake plains, till plains, valley trains, stream terraces

Parent material: Outwash

Typical profile

H1 - 0 to 14 inches: loam H2 - 14 to 41 inches: clay loam

H3 - 41 to 60 inches: stratified coarse sand to silt loam

Properties and qualities

Slope: 0 to 3 percent

Depth to restrictive feature: More than 80 inches Drainage class: Somewhat poorly drained

Runoff class: Low

Capacity of the most limiting layer to transmit water (Ksat): Moderately high to high

(0.60 to 2.00 in/hr)

Depth to water table: About 12 to 36 inches

Frequency of flooding: None Frequency of ponding: None

Calcium carbonate, maximum content: 30 percent Available water capacity: High (about 11.4 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 2w

Hydrologic Soil Group: C

Ecological site: F111BY403IN - OUTWASH UPLAND

Hydric soil rating: No

Minor Components

Pewamo

Percent of map unit: 3 percent

Landform: Drainageways, depressions

Ecological site: F111BY501IN - TILL DEPRESSION

Hydric soil rating: Yes

Milford

Percent of map unit: 3 percent

Landform: Drainageways, depressions

Ecological site: F111BY101IN - LACUSTRINE FLATWOOD

Hydric soil rating: Yes

Bennington

Percent of map unit: 3 percent

Landform: Flats on end moraines, rises on ground moraines, rises on end

moraines, flats on ground moraines

Landform position (two-dimensional): Summit, shoulder

Down-slope shape: Linear Across-slope shape: Linear

Rarely flooded areas

Percent of map unit: 2 percent

Martinsville

Percent of map unit: 2 percent

Landform: Terraces

Ecological site: F111BY404IN - DRY OUTWASH UPLAND

Moderately well drained soils

Percent of map unit: 2 percent

References

American Association of State Highway and Transportation Officials (AASHTO). 2004. Standard specifications for transportation materials and methods of sampling and testing. 24th edition.

American Society for Testing and Materials (ASTM). 2005. Standard classification of soils for engineering purposes. ASTM Standard D2487-00.

Cowardin, L.M., V. Carter, F.C. Golet, and E.T. LaRoe. 1979. Classification of wetlands and deep-water habitats of the United States. U.S. Fish and Wildlife Service FWS/OBS-79/31.

Federal Register. July 13, 1994. Changes in hydric soils of the United States.

Federal Register. September 18, 2002. Hydric soils of the United States.

Hurt, G.W., and L.M. Vasilas, editors. Version 6.0, 2006. Field indicators of hydric soils in the United States.

National Research Council. 1995. Wetlands: Characteristics and boundaries.

Soil Survey Division Staff. 1993. Soil survey manual. Soil Conservation Service. U.S. Department of Agriculture Handbook 18. http://www.nrcs.usda.gov/wps/portal/nrcs/detail/national/soils/?cid=nrcs142p2_054262

Soil Survey Staff. 1999. Soil taxonomy: A basic system of soil classification for making and interpreting soil surveys. 2nd edition. Natural Resources Conservation Service, U.S. Department of Agriculture Handbook 436. http://www.nrcs.usda.gov/wps/portal/nrcs/detail/national/soils/?cid=nrcs142p2 053577

Soil Survey Staff. 2010. Keys to soil taxonomy. 11th edition. U.S. Department of Agriculture, Natural Resources Conservation Service. http://www.nrcs.usda.gov/wps/portal/nrcs/detail/national/soils/?cid=nrcs142p2 053580

Tiner, R.W., Jr. 1985. Wetlands of Delaware. U.S. Fish and Wildlife Service and Delaware Department of Natural Resources and Environmental Control, Wetlands Section.

United States Army Corps of Engineers, Environmental Laboratory. 1987. Corps of Engineers wetlands delineation manual. Waterways Experiment Station Technical Report Y-87-1.

United States Department of Agriculture, Natural Resources Conservation Service. National forestry manual. http://www.nrcs.usda.gov/wps/portal/nrcs/detail/soils/home/?cid=nrcs142p2 053374

United States Department of Agriculture, Natural Resources Conservation Service. National range and pasture handbook. http://www.nrcs.usda.gov/wps/portal/nrcs/detail/national/landuse/rangepasture/?cid=stelprdb1043084

United States Department of Agriculture, Natural Resources Conservation Service. National soil survey handbook, title 430-VI. http://www.nrcs.usda.gov/wps/portal/nrcs/detail/soils/scientists/?cid=nrcs142p2_054242

United States Department of Agriculture, Natural Resources Conservation Service. 2006. Land resource regions and major land resource areas of the United States, the Caribbean, and the Pacific Basin. U.S. Department of Agriculture Handbook 296. http://www.nrcs.usda.gov/wps/portal/nrcs/detail/national/soils/?cid=nrcs142p2_053624

United States Department of Agriculture, Soil Conservation Service. 1961. Land capability classification. U.S. Department of Agriculture Handbook 210. http://www.nrcs.usda.gov/Internet/FSE_DOCUMENTS/nrcs142p2_052290.pdf

Exhibit G. NOAA Atlas 14 Point Precipitation & USDA Curve Numbers

 Table 2-2a
 Runoff curve numbers for urban areas 1/2

				umbers for	
Cover description		hydrologic	soil group		
	Average percent				
Cover type and hydrologic condition	impervious area 2/	A	В	С	D
Fully developed urban areas (vegetation established)					
Open space (lawns, parks, golf courses, cemeteries, etc.):					
Poor condition (grass cover < 50%)		68	7 9	86	89
Fair condition (grass cover 50% to 75%)		49	69	79	84
Good condition (grass cover > 75%)		39	61	74	80
Impervious areas:					
Paved parking lots, roofs, driveways, etc.					
(excluding right-of-way)	•••••	98	98	98	98
Streets and roads:					
Paved; curbs and storm sewers (excluding					
right-of-way)	•••••	98	98	98	98
Paved; open ditches (including right-of-way)		83	89	92	93
Gravel (including right-of-way)		76	85	89	91
Dirt (including right-of-way)		72	82	87	89
Western desert urban areas:					
Natural desert landscaping (pervious areas only) 4		63	77	85	88
Artificial desert landscaping (impervious weed barrier					
desert shrub with 1- to 2-inch sand or gravel mulch					
and basin borders)		96	96	96	96
Urban districts:					
Commercial and business	85	89	92	94	95
Industrial		81	88	91	93
Residential districts by average lot size:	·····				
1/8 acre or less (town houses)	65	77	85	90	92
1/4 acre		61	75	83	87
1/3 acre		57	72	81	86
1/2 acre		54	70	80	85
1 acre		51	68	79	84
2 acres		46	65	77	82
	12	40	00	• • •	02
Developing urban areas					
Newly graded areas		77	0.0	01	0.1
(pervious areas only, no vegetation) 5/		77	(86)	91	94
Illa landa (CNV) and data main. I					
Idle lands (CN's are determined using cover types					
similar to those in table 2-2c).					

¹ Average runoff condition, and $I_a = 0.2S$.

² The average percent impervious area shown was used to develop the composite CN's. Other assumptions are as follows: impervious areas are directly connected to the drainage system, impervious areas have a CN of 98, and pervious areas are considered equivalent to open space in good hydrologic condition. CN's for other combinations of conditions may be computed using figure 2-3 or 2-4.

³ CN's shown are equivalent to those of pasture. Composite CN's may be computed for other combinations of open space cover type.

⁴ Composite CN's for natural desert landscaping should be computed using figures 2-3 or 2-4 based on the impervious area percentage (CN = 98) and the pervious area CN. The pervious area CN's are assumed equivalent to desert shrub in poor hydrologic condition.

⁵ Composite CN's to use for the design of temporary measures during grading and construction should be computed using figure 2-3 or 2-4 based on the degree of development (impervious area percentage) and the CN's for the newly graded pervious areas.

Table 2-2b Runoff curve numbers for cultivated agricultural lands $\underline{\lor}$

	Cover description	Curve numbers for hydrologic soil group				
Cover type	Treatment 2/	Hydrologic condition $\frac{3}{2}$	A	В	C	D
Fallow	Bare soil	_	77	86	91	94
	Crop residue cover (CR)	Poor Good	76 74	85 83	90 88	93 90
Row crops	Straight row (SR)	Poor Good	72 67	81 78	88 85	91 89
	SR + CR	Poor <mark>Good</mark>	71 64	80 (75)	87 82	90 <mark>85</mark>
	Contoured (C)	Poor Good	70 65	79 75	84 82	88 86
	C + CR	Poor Good	69 64	78 74	83 81	87 85
	Contoured & terraced (C&T)	Poor Good	66 62	74 71	80 78	82 81
	C&T+ CR	Poor Good	65 61	73 70	79 77	81 80
Small grain	SR	Poor Good	65 63	76 75	84 83	88 87
	SR + CR	Poor Good	64 60	75 72	83 80	86 84
	C	Poor Good	63 61	74 73	82 81	85 84
	C + CR	Poor Good	62 60	73 72	81 80	84 83
	C&T	Poor Good	61 59	72 70	79 78	82 81
	C&T+ CR	Poor Good	60 58	71 69	78 77	81 80
Close-seeded or broadcast	SR	Poor Good	66 58	77 72	85 81	89 85
legumes or rotation	C	Poor Good	64 55	75 69	83 78	85 83
meadow	C&T	Poor Good	63 51	73 67	80 76	83 80

 $^{^{\}rm 1}$ Average runoff condition, and $I_a \!\!=\!\! 0.2S$

Poor: Factors impair infiltration and tend to increase runoff.

Good: Factors encourage average and better than average infiltration and tend to decrease runoff.

² Crop residue cover applies only if residue is on at least 5% of the surface throughout the year.

 $^{^3}$ Hydraulic condition is based on combination factors that affect infiltration and runoff, including (a) density and canopy of vegetative areas, (b) amount of year-round cover, (c) amount of grass or close-seeded legumes, (d) percent of residue cover on the land surface (good \geq 20%), and (e) degree of surface roughness.

 $\textbf{Table 2-2c} \qquad \text{Runoff curve numbers for other agricultural lands } \underline{1}{}^{\underline{1}}$

Cover description	Curve numbers for hydrologic soil group				
Cover type	Hydrologic condition	A	В	С	D
Pasture, grassland, or range—continuous	Poor	68	79	86	89
forage for grazing. 2/	Fair	49	69	79	84
	Good	39	61	74	80
Meadow—continuous grass, protected from grazing and generally mowed for hay.	_	30	58	<u>71</u>)	78
Brush—brush-weed-grass mixture with brush	Poor	48	67	77	83
the major element. 3/	Fair	35	56	70	77
,	Good	30 4/	48	65	73
Woods—grass combination (orchard	Poor	57	73	82	86
or tree farm). 5/	Fair	43	65	76	82
,	Good	32	58	72	79
Woods. 6/	Poor	45	66	77	83
	Fair	36	60	73	79
	Good	30 4/	55	70	77
Farmsteads—buildings, lanes, driveways, and surrounding lots.	_	59	74	82	86

¹ Average runoff condition, and $I_a = 0.2S$.

Poor: <50%) ground cover or heavily grazed with no mulch.</p>

Fair: 50 to 75% ground cover and not heavily grazed.

Good: > 75% ground cover and lightly or only occasionally grazed.

³ *Poor*: <50% ground cover.

Fair: 50 to 75% ground cover.

Good: >75% ground cover.

⁴ Actual curve number is less than 30; use CN = 30 for runoff computations.

⁵ CN's shown were computed for areas with 50% woods and 50% grass (pasture) cover. Other combinations of conditions may be computed from the CN's for woods and pasture.

⁶ Poor: Forest litter, small trees, and brush are destroyed by heavy grazing or regular burning.

Fair: Woods are grazed but not burned, and some forest litter covers the soil.

Good: Woods are protected from grazing, and litter and brush adequately cover the soil.

 $\textbf{Table 2-2d} \qquad \text{Runoff curve numbers for arid and semiarid rangelands } \underline{\lor}$

Cover description		Curve nui hydrologi	mbers for c soil group		
Cover type	Hydrologic condition 2/	A 3/	В	С	D
Herbaceous—mixture of grass, weeds, and	Poor		80	87	93
low-growing brush, with brush the	Fair		71	81	89
minor element.	Good		62	74	85
Oak-aspen—mountain brush mixture of oak brush,	Poor		66	74	79
aspen, mountain mahogany, bitter brush, maple,	Fair		48	57	63
and other brush.	Good		30	41	48
Pinyon-juniper—pinyon, juniper, or both;	Poor		75	85	89
grass understory.	Fair		58	73	80
	Good		41	61	71
Sagebrush with grass understory.	Poor		67	80	85
	Fair		51	63	70
	Good		35	47	55
Desert shrub—major plants include saltbush,	Poor	63	77	85	88
greasewood, creosotebush, blackbrush, bursage,	Fair	55	72	81	86
palo verde, mesquite, and cactus.	Good	49	68	79	84


 $^{^{\, 1}}$ $\,$ Average runoff condition, and $I_a,$ = 0.2S. For range in humid regions, use table 2-2c.

 $^{^2}$ $\,$ Poor: <30% ground cover (litter, grass, and brush overstory). Fair: $\,$ 30 to 70% ground cover.

Good: > 70% ground cover.


 $^{^{\}scriptscriptstyle 3}$ $\,$ Curve numbers for group A have been developed only for desert shrub.

Exhibit H. FEMA FIRM



FLOOD HAZARD INFORMATION

SEE FIS REPORT FOR DETAILED LEGEND AND INDEX MAP FOR DRAFT FIRM PANEL LAYOUT



Base Flood Elevation Line (BFE)

Jurisdiction Boundary

Limit of Study

OTHER

FEATURES

NOTES TO USERS

For information and questions about this Flood Insurance Rate Map (FIRM), available products associated with this FIRM, including historic versions, the current map date for each FIRM panel, how to order products, or the National Flood Insurance Program (NFIP) in general, please call the FEMA Map Information eXchange at 1-877-FEMA-MAP (1-877-336-2627) or visit the FEMA Flood Map Service Center website at https://msc.fema.gov. Available products may include previously issued Letters of Map Change, a Flood Insurance Study Report, and/or digital versions of this map. Many of these products can be ordered or obtained directly from the website.

listed above.

For community and countywide map dates, refer to the Flood Insurance Study Report for this jurisdiction.

Communities annexing land on adjacent FIRM panels must obtain a current copy of the adjacent panel as well

as the current FIRM Index. These may be ordered directly from the Flood Map Service Center at the number

To determine if flood insurance is available in this community, contact your Insurance agent or call the National Flood Insurance Program at 1-800-638-6620.

Basemap information shown on this FIRM was provided in digital format by the United States Geological Survey (USGS). The basemap shown is the USGS National Map: Orthoimagery. Last refreshed October, 2020.

This map was exported from FEMA's National Flood Hazard Layer (NFHL) on 1/28/2021 4:27 PM and does not reflect changes or amendments subsequent to this date and time. The NFHL and effective information may change or become superseded by new data over time. For additional information, please see the Flood Hazard Mapping Updates Overview Fact Sheet at https://www.fema.gov/media-library/assets/documents/118418

This map complies with FEMA's standards for the use of digital flood maps if it is not void as described below. The basemap shown complies with FEMA's basemap accuracy standards. This map image is void if the one or more of the following map elements do not appear: basemap imagery, flood zone labels, legend, scale bar, map creation date, community identifiers, FIRM panel number, and FIRM effective date.

SCALE

Map Projection:
GCS, Geodetic Reference System 1980;
Vertical Datum: No elevation features on this FIRM
For information about the specific vertical datum for elevation features, datum conversions, or vertical monuments used to create this map, please see the Flood Insurance Study (FIS) Report for your community at https://msc.fema.gov

		- `	, -			
F	1	inch = 2,0	00 feet	t	1:24,0	00
	0	1,000 2,0	00	4,000	6,000	8,000
						F
	0	210 420	840	1,260	1,680	

NATIONAL FLOOD INSURANCE PROGRAM FLOOD INSURANCE RATE MAP MARION COUNTY, OHIO AND INCORPORATED AREAS PANEL 75 of 325

Panel Contains:

COMMUNITY

MARION COUNTY
VILLAGE OF
MORRAL

NUMBER PANEL
390774 0075
390746 0075

83°7'28.3"W 40°35'38.69"N


National Flood Insurance Program

MAP NUMBER 39101C0075D EFFECTIVE DATE July 06, 2010

83°7'29.16"W 40°33'31.85"N

FLOOD HAZARD INFORMATION

SEE FIS REPORT FOR DETAILED LEGEND AND INDEX MAP



— Hydrographic Feature Base Flood Elevation Line (BFE)

Jurisdiction Boundary

Limit of Study

OTHER

FEATURES

NOTES TO USERS

For information and questions about this Flood Insurance Rate Map (FIRM), available products associated with this FIRM, including historic versions, the current map date for each FIRM panel, how to order products, or the National Flood Insurance Program (NFIP) in general, please call the FEMA Map Information eXchange at 1-877-FEMA-MAP (1-877-336-2627) or visit the FEMA Flood Map Service Center website at https://msc.fema.gov. Available products may include previously issued Letters of Map Change, a Flood Insurance Study Report, and/or digital versions of this map. Many of these products can be ordered or obtained directly from the website.

Communities annexing land on adjacent FIRM panels must obtain a current copy of the adjacent panel as well

as the current FIRM Index. These may be ordered directly from the Flood Map Service Center at the number

listed above. For community and countywide map dates, refer to the Flood Insurance Study Report for this jurisdiction.

To determine if flood insurance is available in this community, contact your Insurance agent or call the National Flood Insurance Program at 1-800-638-6620.

Basemap information shown on this FIRM was provided in digital format by the United States Geological Survey (USGS). The basemap shown is the USGS National Map: Orthoimagery. Last refreshed October, 2020.

This map was exported from FEMA's National Flood Hazard Layer (NFHL) on 1/28/2021 4:24 PM and does not reflect changes or amendments subsequent to this date and time. The NFHL and effective information may change or become superseded by new data over time. For additional information, please see the Flood Hazard Mapping Updates Overview Fact Sheet at https://www.fema.gov/media-library/assets/documents/118418

This map complies with FEMA's standards for the use of digital flood maps if it is not void as described below. The basemap shown complies with FEMA's basemap accuracy standards. This map image is void if the one or more of the following map elements do not appear: basemap imagery, flood zone labels, legend, scale bar, map creation date, community identifiers, FIRM panel number, and FIRM effective date.

SCALE

Map Projection: GCS, Geodetic Reference System 1980; Vertical Datum: No elevation features on this FIRM For information about the specific vertical datum for elevation features, datum conversions, or vertical monuments used to create this map, please see the Flood Insurance Study (FIS) Report for your community at https://msc.fema.gov

					,			
	1	inch =	1,000	o fee	t		1:12,0	000
	0	500	1,000		2,000	3	,000	4,000
NI						M	leters	Feet
IN	0	105 21	0	420	630	840		

National Flood Insurance Program

BIZONEX

NATIONAL FLOOD INSURANCE PROGRAM

FLOOD INSURANCE RATE MAP MARION COUNTY, OHIO

AND INCORPORATED AREAS PANEL 210 of 325

Panel Contains:

COMMUNITY CITY OF MARION MARION COUNTY

NUMBER **PANEL** 390376 0210 390774 0210

> MAP NUMBER 39101C0210D EFFECTIVE DATE July 06, 2010

Exhibit I. Pre-Development Project Hydrology Inputs & Outputs

	Pre-development Summary (100-yr / 24-hr)									
Hydrologic	Drainage	Peak Discharge		Volume						
Element	Area (SM)	(CFS)	Time of Peak	(IN)						
DA-1	0.064688	96.8	01Feb2021, 12:35	3.47						
DA-2	0.024219	65.2	01Feb2021, 12:10	3.38						
DA-3	0.122969	144.2	01Feb2021, 12:45	3.36						
DA-4	0.027656	57.1	01Feb2021, 12:20	3.75						
DA-5	0.082031	89.6	01Feb2021, 12:50	3.32						
DA-6	0.051094	105.1	01Feb2021, 12:20	3.57						
DA-7	0.370469	248.5	01Feb2021, 13:45	3.43						
DA-8	0.183438	205.9	01Feb2021, 12:50	3.32						
DA-9	0.081563	110.4	01Feb2021, 12:45	3.66						
DA-10	0.090000	94.8	01Feb2021, 12:55	3.26						
DA-11	0.037969	68.2	01Feb2021, 12:25	3.49						
DA-12	0.036563	67.3	01Feb2021, 12:25	3.49						
DA-13	0.017031	34.5	01Feb2021, 12:20	3.65						
DA-14	0.001563	6.2	01Feb2021, 12:05	3.46						

Mott MacDonald Basin - CN - Tc Calculations Page

1 of 2

MOTT MACDONALD

		MACDOTALD			
Basin	Total Area	COMP	Area		
Dasiii	(ac)	CN	(sm)		
DA 1 Pre	41.40	82.3	0.064688		
	15.50	21.2			
DA 2 Pre	15.50	81.3	0.024219		
DA 3 Pre	78.70	81.3	0.122969		
DASFIE	76.70	01.3	0.122909		
DA 4 Pre	17.70	85.0	0.027656		
2711110		55.5	0.02.000		
DA 5 Pre	52.50	80.9	0.082031		
DA 6 Pre	32.70	83.2	0.051094		
DA 7 Pre	237.10	82.5	0.370469		
DA 8 Pre	117.40	80.9	0.183438		
DA 9 Pre	52.20	84.3	0.081563		
DA 10 Pre	57.60	80.3	0.090000		
DA 11 Pre	24.30	82.5	0.037969		
DA 40 D	00.40	00.5	0.000=65		
DA 12 Pre	23.40	82.5	0.036563		
DA 42 D==	40.00	84.0	0.047024		
DA 13 Pre	10.90	64.0	0.017031		
DA 14 Pre	1.00	82.0	0.001563		
	1.00	02.0	0.001000		

*(Using SCS TR-55 Tc Calculations)

Basin		Sheet F	low, SI	=	Shallo	w Cond	centrate	d Flow	, SCF				nnel Flow-1, SCF		
Dasiii	n	Lf	S, ft/ft	Tc, hrs	Lf	S, ft/ft	k	V	T, hrs	Lf	S, ft/ft	k	V	T, hrs	
DA 1 Pre	0.1	10	0.01	0.03	2150	0.006	10	0.77	0.77	720	0.004	10	6.00	0.03	
DA 2 Pre	0.1	10	0.02	0.02	695	0.02	10	1.41	0.14	1577	0.004	10	6.00	0.07	
DA 3 Pre	0.1	10	0.01	0.03	3380	0.007	10	0.84	1.12	450	0.002	10	6.00	0.02	
DA 4 Pre	0.1	10	0.01	0.03	1330	0.006	10	0.77	0.48	310	0.003	10	6.00	0.01	
DA 5 Pre	0.1	10	0.01	0.03	2475	0.003	10	0.55	1.26	0	0.006	10	6.00	0.00	
DA 6 Pre	0.1	10	0.01	0.03	1650	0.01	10	1.00	0.46	0	0.010	10	6.00	0.00	
DA 7 Pre	0.1	10	0.01	0.03	6075	0.004	10	0.63	2.67	0	0.004	10	6.00	0.00	
DA 8 Pre	0.1	10	0.01	0.03	3370	0.006	10	0.77	1.21	0	0.006	10	6.00	0.00	
DA 9 Pre	0.1	10	0.01	0.03	2840	0.006	10	0.77	1.02	366	0.003	10	6.00	0.02	
DA 10 Pre	0.1	10	0.01	0.03	2950	0.004	10	0.63	1.30	0	0.004	10	6.00	0.00	
DA 11 Pre	0.1	10	0.01	0.03	1650	0.007	10	0.84	0.55	700	0.002	10	6.00	0.03	
DA 12 Pre	0.1	10	0.01	0.03	1900	0.009	10	0.95	0.56	0	0.009	10	6.00	0.00	
DA 13 Pre	0.1	10	0.01	0.03	1290	0.006	10	0.77	0.46	536	0.003	10	6.00	0.02	
DA 14 Pre	0.1	10	0.067	0.01	60	0.067	10	2.59	0.01	830	0.004	10	6.00	0.04	

Mott MacDonald

Basin - CN - Tc Calculations

Page 2 of 2

M MOTT MACDONALD

	_								
	Sheet Flow Table								
0.011	Smoth Surface								
0.05	Fallow (no residye)								
	Cultivated								
0.06	Residue Cover < 20%								
0.17	Residue Cover >20%								
	Grass								
0.15	Short grass, prairie								
0.24	Dense grasses								
0.41	Bermudagrass								
0.13	Range (natural)								
	Woods								
0.4	Light underbrush								
0.8	Dense underbrush								

Shallow Concentrated Flow Table					
k	Description				
2.4934	Forest w/ heavy ground litter				
4.9869	Woodland				
6.9882	Short grass pasture				
8.9895	Cultivated short row				
10.007	Nearly bare & untilled				
14.993	Grassed				
16.109	Unpaved				
20.308	Paved				

2-yr 24-hr RF= 2.53

Basin		(Sum	
Dasiii	Tc, hrs	Tc, min	Lag, hrs	Lag, min
DA 1 Pre	0.83	49.93	0.50	30.0
DA 2 Pre	0.23	13.83	0.14	8.3
DA 3 Pre	1.17	70.25	0.70	42.1
DA 4 Pre	0.52	31.14	0.31	18.7
DA 5 Pre	1.28	76.98	0.77	46.2
DA 6 Pre	0.49	29.17	0.29	17.5
DA 7 Pre	2.70	161.76	1.62	97.1
DA 8 Pre	1.24	74.18	0.74	44.5
DA 9 Pre	1.06	63.79	0.64	38.3
DA 10 Pre	1.32	79.41	0.79	47.6
DA 11 Pre	0.61	36.48	0.36	21.9
DA 12 Pre	0.58	35.05	0.35	21.0
DA 13 Pre	0.52	30.91	0.31	18.5
DA 14 Pre	0.06	3.47	0.03	2.1

Exhibit J. Post-Development Project Hydrology Inputs & Outputs

Post-development Summary (100-yr / 24-hr)							
Hydrologic	Drainage	Peak Discharge		Volume			
Element	Area (SM)	(CFS)	Time of Peak	(IN)			
DA-1	0.064688	77.3	01Feb2021, 12:35	2.78			
DA-2	0.024219	43.3	01Feb2021, 12:10	2.31			
DA-3	0.122969	102.4	01Feb2021, 12:50	2.41			
DA-4	0.027656	46.9	01Feb2021, 12:25	3.06			
DA-5	0.082031	62.9	01Feb2021, 12:55	2.37			
DA-6	0.051094	82.9	01Feb2021, 12:20	2.82			
DA-7	0.370469	160.4	01Feb2021, 13:50	2.28			
DA-8	0.183438	139.8	01Feb2021, 12:50	2.31			
DA-9	0.081563	102.5	01Feb2021, 12:45	3.38			
DA-10	0.090000	66.6	01Feb2021, 12:55	2.33			
DA-11	0.037969	48.5	01Feb2021, 12:25	2.51			
DA-12	0.036563	44.5	01Feb2021, 12:25	2.34			
DA-13	0.017031	27.2	01Feb2021, 12:25	2.88			
DA-14	0.001563	4.9	01Feb2021, 12:05	2.75			

Mott MacDonald

Basin - CN - Tc Calculations

Page 1 of 2

M MOTT MACDONALD

Basin	Total Area (ac)	COMP	Area (sm)
	(0.0)		(0)
DA 1 Post	41.40	75.0	0.064688
DA 2 Post	15.50	69.5	0.024219
D4 0 D /	=0 =0	=4.0	0.400000
DA 3 Post	78.70	71.0	0.122969
DA 4 Post	17.70	78.0	0.027656
DA 5 Post	52.50	70.5	0.082031
DA 6 Post	32.70	75.4	0.051094
DA 7 Post	237.10	69.8	0.370469
DATFOSI	237.10	09.0	0.570403
DA 8 Post	117.40	69.8	0.183438
DA 9 Post	52.20	81.5	0.081563
DA 10 Post	57.60	70.1	0.090000
[, _, _			
DA 11 Post	24.30	72.0	0.037969
DA 12 Post	23.40	70.0	0.036563
DA 13 Post	10.90	76.0	0.017031
DA 14 Post	1.00	74.5	0.001563

*(Using SCS TR-55 Tc Calculations)

Basin		Sheet I	Flow, S	F	Shalle	ow Cond	entrate	d Flow	, SCF	Channel Flow-1, SCF				
Dasiii	n	Lf	S, ft/ft	Tc, hrs	Lf	S, ft/ft	k	V	T, hrs	Lf	S, ft/ft	k	V	T, hrs
DA 1 Post	0.1	10	0.01	0.03	2150	0.006	10	0.77	0.77	720	0.004	10	6.00	0.03
DA 2 Post	0.1	10	0.02	0.02	695	0.02	10	1.41	0.14	1577	0.004	10	6.00	0.07
DA 3 Post	0.1	10	0.01	0.03	3380	0.007	10	0.84	1.12	450	0.002	10	6.00	0.02
DA 4 Post	0.1	10	0.01	0.03	1330	0.006	10	0.77	0.48	310	0.003	10	6.00	0.01
DA 5 Post	0.1	10	0.01	0.03	2475	0.003	10	0.55	1.26	0	0.006	10	6.00	0.00
DA 6 Post	0.1	10	0.01	0.03	1650	0.01	10	1.00	0.46	0	0.010	10	6.00	0.00
DA 7 Post	0.1	10	0.01	0.03	6075	0.004	10	0.63	2.67	0	0.004	10	6.00	0.00
DA 8 Post	0.1	10	0.01	0.03	3370	0.006	10	0.77	1.21	0	0.006	10	6.00	0.00
DA 9 Post	0.1	10	0.01	0.03	2840	0.006	10	0.77	1.02	366	0.003	10	6.00	0.02
DA 10 Post	0.1	10	0.01	0.03	2950	0.004	10	0.63	1.30	0	0.004	10	6.00	0.00
DA 11 Post	0.1	10	0.01	0.03	1650	0.007	10	0.84	0.55	700	0.002	10	6.00	0.03
DA 12 Post	0.1	10	0.01	0.03	1900	0.009	10	0.95	0.56	0	0.009	10	6.00	0.00
DA 13 Post	0.1	10	0.01	0.03	1290	0.006	10	0.77	0.46	536	0.003	10	6.00	0.02
DA 14 Post	0.1	10	0.067	0.01	60	0.067	10	2.59	0.01	830	0.004	10	6.00	0.04

Mott MacDonald

Basin - CN - Tc Calculations

Page 2 of 2

M MOTT MAGDONALD

Sheet Flow Table					
0.011	Smoth Surface				
0.05	Fallow (no residye)				
	Cultivated				
0.06	Residue Cover < 20%				
0.17	Residue Cover >20%				
	Grass				
0.15	Short grass, prairie				
0.24	Dense grasses				
0.41	Bermudagrass				
0.13	Range (natural)				
	Woods				
0.4	Light underbrush				
0.8	Dense underbrush				

Shallow Concentrated Flow Table					
k	Description				
2.4934	Forest w/ heavy ground litter				
4.9869	Woodland				
6.9882	Short grass pasture				
8.9895	Cultivated short row				
10.007	Nearly bare & untilled				
14.993	Grassed				
16.109	Unpaved				
20.308	Paved				

2-yr 24-hr RF= 2.53

Basin	Sum							
Dasiii	Tc, hrs	Tc, min	Lag, hrs	Lag, min				
DA 1 Post	0.83	49.93	0.50	30.0				
DA 2 Post	0.23	13.83	0.14	8.3				
DA 3 Post	1.17	70.25	0.70	42.1				
DA 4 Post	0.52	31.14	0.31	18.7				
DA 5 Post	1.28	76.98	0.77	46.2				
DA 6 Post	0.49	29.17	0.29	17.5				
DA 7 Post	2.70	161.76	1.62	97.1				
DA 8 Post	1.24	74.18	0.74	44.5				
DA 9 Post	1.06	63.79	0.64	38.3				
DA 10 Post	1.32	79.41	0.79	47.6				
DA 11 Post	0.61	36.48	0.36	21.9				
DA 12 Post	0.58	35.05	0.35	21.0				
DA 13 Post	0.52	30.91	0.31	18.5				
DA 14 Post	0.06	3.47	0.03	2.1				

Sum

Exhibit K. Regression Equations and HEC-RAS Hydrology Outputs



Water Resources of the United States

Home Data Maps Software Publications Programs Contact

The following documentation was taken from:

U.S. Geological Survey Water-Resources Investigations Report 94-4002: *Nationwide summary of U.S. Geological Survey regional regression equations for estimating magnitude and frequency of floods for ungaged sites, 1993*

OHIO

STATEWIDE RURAL

Summary

Ohio is divided into three regions (fig. 1). The regression equations developed for these regions are for estimating peak discharges (QT) having recurrence intervals T that range from 2 to 100 years. The explanatory basin characteristics used in the equations are drainage area (A), in square miles; main channel slope (S), in feet per mile; and the percentage of the basin occupied by lakes, ponds, and swamps (St). The constant 1 is added to St in the computer application of the regression equations. The user should enter the actual value of St. These variables can be measured from topographic maps. The regression equations were developed from peak-discharge records for 275 gaging stations and are applicable to rural, unregulated streams having less than 30 percent of the drainage basin strip mined. The standard errors of prediction for the regression equations range from 33 to 41 percent.

Procedure

Topographic maps, the hydrologic regions map (fig. 1), and the following equations are used to estimate the needed peak discharges QT, in cubic feet per second, having selected recurrence intervals T.

Q2 = $(RC)A^{0.782}S^{0.172}(St+1)^{-0.297}$

Q5 = $(RC)A^{0.769}S^{0.221}(St+1)^{-0.322}$

Q10 = $(RC)A^{0.764}S^{0.244}(Si+1)^{-0.335}$

 $Q25 = (RC)A^{0.760}S^{0.264}(St+1)^{-0.347}$

Q50 = $(RC)A^{0.757}S^{0.276}(Si+1)^{-0.355}$

 $Q100 = (RC)A^{0.756}S^{0.285}(St+1)^{-0.363}$

where

RC is the regression constant for a region from the following matrix:

П	Region	Q2	Q5	Q10	Q25	Q50	Q100
	A	56.1	84.5	104	129	148	167
	В	40.2	58.4	69.3	82.2	91.2	99.7
	С	93.5	133	159	191	214	236

Reference

Koltun, G.F., and Roberts, J.W., 1989, Techniques for estimating flood-peak discharges of rural, unregulated streams in Ohio: U.S. Geological Survey Water-Resources Investigations Report 89-4126, 68





Figure 1. Flood-frequency region map for Ohio.


StreamStats Report

Region ID: OH

Workspace ID: 0H20210120144004659000

Clicked Point (Latitude, Longitude): 40.63682, -83.15414

Time: 2021-01-20 08:40:23 -0600



Basin Characteristics						
Parameter Code	Parameter Description	Value	Unit			
DRNAREA	Area that drains to a point on a stream	0.53	square miles			
OHREGC	Ohio Region C Indicator	0	dimensionless			
OHREGA	Ohio Region A Indicator	0	dimensionless			
CSL1085LFP	Change in elevation divided by length between points 10 and 85 percent of distance along the longest flow path to the basin divide, LFP from 2D grid	29.8	feet per mi			
LC92STOR	Percentage of water bodies and wetlands determined from the NLCD	0	percent			

Parameter Code	Parameter Description	Value	Unit
FOREST	Percentage of area covered by forest	1.34	percent
PRECIP	Mean Annual Precipitation	39.3	inches
LC11IMP	Average percentage of impervious area determined from NLCD 2011 impervious dataset	4.93	percent
LC11DEV	Percentage of developed (urban) land from NLCD 2011 classes 21-24	16.4	percent

Peak-Flow Statistics	Parameters[Peak Flow	Full Model Reg B SIR2019 5018]
----------------------	----------------------	--------------------------------

Parameter Code	Parameter Name	Value	Units	Min Limit	Max Limit
DRNAREA	Drainage Area	0.53	square miles	0.04	6309
OHREGC	Ohio Region C Indicator 1 if in C else 0	0	dimensionless	0	1
OHREGA	Ohio Region A Indicator 1 if in A else 0	0	dimensionless	0	1
CSL1085LFP	Stream Slope 10 and 85 Longest Flow Path	29.8	feet per mi	1.21	457
LC92STOR	Percent Storage from NLCD1992	0	percent	0	7.1

Peak-Flow Statistics Flow Report[Peak Flow Full Model Reg B SIR2019 5018]

PII: Prediction Interval-Lower, PIu: Prediction Interval-Upper, SEp: Standard Error of Prediction, SE: Standard Error (other -- see report)

Statistic	Value	Unit	PII	Plu	SEp
50_percent_AEP_flood	49.2	ft^3/s	25.7	94.1	40.1
20_percent_AEP_flood	85.5	ft^3/s	46.7	156	37.2
10_percent_AEP_flood	114	ft^3/s	61.9	210	37.6
4_percent_AEP_flood	154	ft^3/s	82.9	286	38.1
2_percent_AEP_flood	186	ft^3/s	99	349	37.8
1_percent_AEP_flood	220	ft^3/s	116	418	39.6
0_2_percent_AEP_flood	305	ft^3/s	159	586	40.3

Peak-Flow Statistics Citations

Koltun, G.F.,2019, Flood-frequency estimates for Ohio streamgages based on data through water year 2015 and techniques for estimating flood-frequency characteristics of rural, unregulated Ohio streams: U.S. Geological Survey Scientific Investigations Report 2019–5018, xx p. (https://dx.doi.org/10.3133/sir20195018)

USGS Data Disclaimer: Unless otherwise stated, all data, metadata and related materials are considered to satisfy the quality standards relative to the purpose for which the data were collected. Although these data and associated metadata have been reviewed for accuracy and completeness and approved for release by the U.S. Geological Survey (USGS), no warranty expressed or implied is made regarding the display or utility of the data for other purposes, nor on all computer systems, nor shall the act of distribution constitute any such warranty.

USGS Software Disclaimer: This software has been approved for release by the U.S. Geological Survey (USGS). Although the software has been subjected to rigorous review, the USGS reserves the right to update the software as needed pursuant to further analysis and review. No warranty, expressed or implied, is made by the USGS or the U.S. Government as to the functionality of the software and related material nor shall the fact of release constitute any such warranty. Furthermore, the software is released on condition that neither the USGS nor the U.S. Government shall be held liable for any damages resulting from its authorized or unauthorized use.

USGS Product Names Disclaimer: Any use of trade, firm, or product names is for descriptive purposes only and does not imply endorsement by the U.S. Government.

Application Version: 4.4.0


StreamStats Report

Region ID: OH

Workspace ID: 0H20210120144345319000

Clicked Point (Latitude, Longitude): 40.63337, -83.16097

Time: 2021-01-20 08:44:03 -0600



Basin Characteristics					
Parameter Code	Parameter Description	Value	Unit		
DRNAREA	Area that drains to a point on a stream	0.35	square miles		
OHREGC	Ohio Region C Indicator	0	dimensionless		
OHREGA	Ohio Region A Indicator	0	dimensionless		
CSL1085LFP	Change in elevation divided by length between points 10 and 85 percent of distance along the longest flow path to the basin divide, LFP from 2D grid	20.1	feet per mi		
LC92STOR	Percentage of water bodies and wetlands determined from the NLCD	0	percent		

Parameter Code	Parameter Description	Value	Unit
FOREST	Percentage of area covered by forest	0.39	percent
LC11DEV	Percentage of developed (urban) land from NLCD 2011 classes 21-24	8.1	percent
LC11IMP	Average percentage of impervious area determined from NLCD 2011 impervious dataset	2.75	percent
PRECIP	Mean Annual Precipitation	39.3	inches

Peak-Flow Statistics Pa	arameters[Peak Flow Full Model Reg B SIR2019 5018]
-------------------------	--

Parameter Code	Parameter Name	Value	Units	Min Limit	Max Limit
DRNAREA	Drainage Area	0.35	square miles	0.04	6309
OHREGC	Ohio Region C Indicator 1 if in C else 0	0	dimensionless	0	1
OHREGA	Ohio Region A Indicator 1 if in A else 0	0	dimensionless	0	1
CSL1085LFP	Stream Slope 10 and 85 Longest Flow Path	20.1	feet per mi	1.21	457
LC92STOR	Percent Storage from NLCD1992	0	percent	0	7.1

Peak-Flow Statistics Flow Report[Peak Flow Full Model Reg B SIR2019 5018]

PII: Prediction Interval-Lower, PIu: Prediction Interval-Upper, SEp: Standard Error of Prediction, SE: Standard Error (other -- see report)

Statistic	Value	Unit	PII	Plu	SEp
50_percent_AEP_flood	33.4	ft^3/s	17.4	64.2	40.1
20_percent_AEP_flood	57.4	ft^3/s	31.2	105	37.2
10_percent_AEP_flood	76.1	ft^3/s	41.1	141	37.6
4_percent_AEP_flood	102	ft^3/s	54.7	190	38.1
2_percent_AEP_flood	123	ft^3/s	65.1	232	37.8
1_percent_AEP_flood	146	ft^3/s	76.4	279	39.6
0_2_percent_AEP_flood	202	ft^3/s	104	391	40.3

Peak-Flow Statistics Citations

Koltun, G.F.,2019, Flood-frequency estimates for Ohio streamgages based on data through water year 2015 and techniques for estimating flood-frequency characteristics of rural, unregulated Ohio streams: U.S. Geological Survey Scientific Investigations Report 2019–5018, xx p. (https://dx.doi.org/10.3133/sir20195018)

USGS Data Disclaimer: Unless otherwise stated, all data, metadata and related materials are considered to satisfy the quality standards relative to the purpose for which the data were collected. Although these data and associated metadata have been reviewed for accuracy and completeness and approved for release by the U.S. Geological Survey (USGS), no warranty expressed or implied is made regarding the display or utility of the data for other purposes, nor on all computer systems, nor shall the act of distribution constitute any such warranty.

USGS Software Disclaimer: This software has been approved for release by the U.S. Geological Survey (USGS). Although the software has been subjected to rigorous review, the USGS reserves the right to update the software as needed pursuant to further analysis and review. No warranty, expressed or implied, is made by the USGS or the U.S. Government as to the functionality of the software and related material nor shall the fact of release constitute any such warranty. Furthermore, the software is released on condition that neither the USGS nor the U.S. Government shall be held liable for any damages resulting from its authorized or unauthorized use.

USGS Product Names Disclaimer: Any use of trade, firm, or product names is for descriptive purposes only and does not imply endorsement by the U.S. Government.

Application Version: 4.4.0

1/20/2021 StreamStats


StreamStats Report

Region ID: OH

Workspace ID: 0H20210120144646212000

Clicked Point (Latitude, Longitude): 40.61627, -83.14569

Time: 2021-01-20 08:47:04 -0600



Basin Characteristics				
Parameter Code	Parameter Description	Value	Unit	
DRNAREA	Area that drains to a point on a stream	3.9	square miles	
OHREGC	Ohio Region C Indicator	0	dimensionless	
OHREGA	Ohio Region A Indicator	0	dimensionless	
CSL1085LFP	Change in elevation divided by length between points 10 and 85 percent of distance along the longest flow path to the basin divide, LFP from 2D grid	12.2	feet per mi	
LC92STOR	Percentage of water bodies and wetlands determined from the NLCD	0.54	percent	

1/20/2021 StreamStats

Parameter Code	Parameter Description	Value	Unit
FOREST	Percentage of area covered by forest	5.8	percent
LC11DEV	Percentage of developed (urban) land from NLCD 2011 classes 21-24	71.6	percent
LC11IMP	Average percentage of impervious area determined from NLCD 2011 impervious dataset	31.4	percent
PRECIP	Mean Annual Precipitation	39.3	inches

Peak-Flow Statistics Parameters [100 Percent (3.9 square miles) Peak Flow Full Model Reg B SIR2019 5018]

Parameter Code	Parameter Name	Value	Units	Min Limit	Max Limit
DRNAREA	Drainage Area	3.9	square miles	0.04	6309
OHREGC	Ohio Region C Indicator 1 if in C else 0	0	dimensionless	0	1
OHREGA	Ohio Region A Indicator 1 if in A else 0	0	dimensionless	0	1
CSL1085LFP	Stream Slope 10 and 85 Longest Flow Path	12.2	feet per mi	1.21	457
LC92STOR	Percent Storage from NLCD1992	0.54	percent	0	7.1

Peak-Flow Statistics Flow Report[100 Percent (3.9 square miles) Peak Flow Full Model Reg B SIR2019 5018]

PII: Prediction Interval-Lower, Plu: Prediction Interval-Upper, SEp: Standard Error of Prediction, SE: Standard Error (other -- see report)

Statistic	Value	Unit	PII	Plu	SEp
50_percent_AEP_flood	191	ft^3/s	NaN	364	40.1
20_percent_AEP_flood	306	ft^3/s	168	558	37.2
10_percent_AEP_flood	391	ft^3/s	213	717	37.6
4_percent_AEP_flood	506	ft^3/s	274	935	38.1
2_percent_AEP_flood	596	ft^3/s	319	1110	37.8
1_percent_AEP_flood	689	ft^3/s	365	1300	39.6
0_2_percent_AEP_flood	918	ft^3/s	481	1750	40.3

Peak-Flow Statistics Citations

1/20/2021 StreamStats

Koltun, G.F.,2019, Flood-frequency estimates for Ohio streamgages based on data through water year 2015 and techniques for estimating flood-frequency characteristics of rural, unregulated Ohio streams: U.S. Geological Survey Scientific Investigations Report 2019–5018, xx p. (https://dx.doi.org/10.3133/sir20195018)

USGS Data Disclaimer: Unless otherwise stated, all data, metadata and related materials are considered to satisfy the quality standards relative to the purpose for which the data were collected. Although these data and associated metadata have been reviewed for accuracy and completeness and approved for release by the U.S. Geological Survey (USGS), no warranty expressed or implied is made regarding the display or utility of the data for other purposes, nor on all computer systems, nor shall the act of distribution constitute any such warranty.

USGS Software Disclaimer: This software has been approved for release by the U.S. Geological Survey (USGS). Although the software has been subjected to rigorous review, the USGS reserves the right to update the software as needed pursuant to further analysis and review. No warranty, expressed or implied, is made by the USGS or the U.S. Government as to the functionality of the software and related material nor shall the fact of release constitute any such warranty. Furthermore, the software is released on condition that neither the USGS nor the U.S. Government shall be held liable for any damages resulting from its authorized or unauthorized use.

USGS Product Names Disclaimer: Any use of trade, firm, or product names is for descriptive purposes only and does not imply endorsement by the U.S. Government.

Application Version: 4.4.0

Exhibit L. Site Visit Report

Marion Solar Site Photos

Author: Henry Fournier

Date: December 8th 2020


Site Location: Marion Township, Marion County Ohio


Date of Site Visit: Monday, December 7th


Weather Conditions: Overcast 31°F, Snow Flurries,


Ground was saturated

Field Observations: Marion solar site is just outside the main city Marion in Marion County. Marion-Upper Sandusky Rd (State Route 423) borders most of the north east side of the property boundary, while the southern part of the property borders Marion-Williamsport Rd W. Both these roads are heavy in traffic and service a lot of large industrial trucks. To the West of the property boundary sits POET Biorefining which has access to one of the railroads that runs through Marion. North west of the property runs the Little Scioto River. All drainage features seem to run into the Little Scioto River that then merges with the Scioto River about 6 miles south of site. There are 2 drainage features in the north of the site that run directly into the north part of the Little Scioto River. Southern part of the site drains into a stream label as Rock Swale. This stream takes runoff from the east of the property, where there is a bridge outside of property boundary on N Main St (State Route 423 and Ohio State Route 4). Rock Swale Stream also takes runoff south of the property boundary, within site the east and south streams merge and leave site flowing westward. This stream then drains into the Little Scioto River about 3 miles south. There are 3 main culverts that were located on site, these are labeled as Culvert 1, Culvert 3, and Culvert 5. These culverts are under roads and leads runoff through the site to the Little Scioto River.















































<u>Bridge</u>



Note: This bridge is outside of the project boundary, the span of this bridge is ≈ **20ft**
















Culverts						
ID/Name	Lat	Long	Diameter	Material		
Culvert 1	40°37'59.44"N	83° 8'34.24"W	Unknown	Unknown		
Culvert 2	40°37'55.57"N	83° 8'28.71"W	60"	Galvanized		
Culvert 3	40°36'53.79"N	83° 8'20.73"W	12"	Galvanized		
Culvert 4	40°36'53.90"N	83° 8'25.49"W	24"	Concrete		
Culvert 5	40°36'53.89"N	83° 8'26.13"W	28"	Concrete		
Culvert 6	40°36'53.96"N	83° 8'28.67"W	10'	Galvanized		



This foregoing document was electronically filed with the Public Utilities

Commission of Ohio Docketing Information System on

3/5/2021 10:17:24 AM

in

Case No(s). 21-0036-EL-BGN

Summary: Application - 17 of 30 (Exhibit N – Part 2 of 2 - Hydrology Report) electronically filed by Christine M.T. Pirik on behalf of Marion County Solar Project, LLC