

180 E. BROAD STREET, SUITE 3400 COLUMBUS, OH 43215-3192 TELEPHONE: (614) 591-5461 FACSIMILE: (844) 670-6009 http://www.dickinsonwright.com

CHRISTINE M.T. PIRIK CPirik@dickinsonwright.com

June 3, 2022

Ms. Tanowa Troupe, Secretary Ohio Power Siting Board Docketing Division 180 East Broad Street, 11th Floor Columbus, Ohio 43215-3797

> **Re:** Case No. 21-1231-EL-BGN - In the Matter of the Application of Fountain Point Solar Energy LLC for a Certificate of Environmental Compatibility and Public Need to Construct a Solar-Powered Electric Generation Facility in Logan County, Ohio.

Response to Fourth Data Request from Staff of the Ohio Power Siting Board

Dear Ms. Troupe:

Attached please find Fountain Point Solar Energy LLC's ("Applicant") Response to the Fourth Data Request from the staff of the Ohio Power Siting Board ("OPSB Staff"). The Applicant provided this response to OPSB Staff on June 3, 2022.

We are available, at your convenience, to answer any questions you may have.

Respectfully submitted,

<u>/s/ Christine M.T. Pirik</u> Christine M.T. Pirik (0029759) (Counsel of Record) Matthew C. McDonnell (0090164) Dickinson Wright PLLC 180 East Broad Street, Suite 3400 Columbus, Ohio 43215 (614) 591-5461 cpirik@dickinsonwright.com mmcdonnell@dickinsonwright.com

Attorneys for Fountain Point Solar Energy LLC

Cc: Theresa White Randall Schumacher Jon Pawley Grant Zeto TJ November Ms. Tanowa Troupe Fountain Point Solar Energy LLC Case No. 21-1231-EL-BGN Page 2

CERTIFICATE OF SERVICE

The Ohio Power Siting Board's e-filing system will electronically serve notice of the filing of this document on the parties referenced in the service list of the docket card who have electronically subscribed to these cases. In addition, the undersigned certifies that a copy of the foregoing document is also being served upon the persons below this 3rd day of June, 2022.

<u>/s/ Christine M.T. Pirik</u> Christine M.T. Pirik (0029759)

Counsel and Intervenors Movants:

Via Email:

jodi.bair@OhioAGO.gov shaun.lyons@OhioAGO.gov scorchedtrumpet@gmail.com

Via First Class Mail:

Kara Slonecker 922 Township Road 132 West Mansfield, OH 43358

Jeny Hammer 2532 State Route 292 West Mansfield, OH 43358

Jocelyn Kavanagh 2339 CR 8 West Mansfield, OH 43358

Administrative Law Judges: greta.see@puco.ohio.gov jacqueline.St.John@puco.ohio.gov

4858-8215-0946 v1 [39579-58]

BEFORE THE OHIO POWER SITING BOARD

)

)

)

)

)

In the Matter of the Application of Fountain Point Solar Energy LLC for a Certificate of Environmental Compatibility and Public Need to Construct a Solar-Powered Electric Generation Facility in Logan County, Ohio.

Case No. 21-1231-EL-BGN

FOUNTAIN POINT SOLAR ENERGY LLC'S RESPONSE TO THE FOURTH DATA REQUEST FROM THE STAFF OF THE OHIO POWER SITING BOARD

On April 11, 2022, as supplemented on May 16, 2022, Fountain Point Solar Energy LLC ("Applicant"), filed an application ("Application") with the Ohio Power Siting Board ("OPSB") proposing to construct a solar-powered electric generation facility in Logan County, Ohio ("Project" or "Facility").

On May 25, 2022, the Staff of the OPSB ("OPSB Staff") provided the Applicant with OPSB Staff's Fourth Data Request. Now comes the Applicant providing the following response to the Fourth Data Request from the OPSB Staff.

1. In follow-up to the Applicant's response to the first data request set, (question/answer #18, #19, and #31), Fountain Point Solar Energy, LLC seems to indicate that the gen tie transmission line is still under design. Please provide the 10% design or better (i.e., overhead plans, transmission line plan and profile view) for the gen tie transmission line.

<u>Response</u>: Included as Attachment 1 to this response is a 10% design for the preliminary gen tie transmission line. The Applicant is working with the transmission owner, Dayton Power and Light Company, and PJM to determine the location of the point of interconnection ("POI"); however, the final location will not be determined until closer to construction when the final engineering design is determined.

2. In follow-up to the Applicant's response the first data request set (question/answer #6), it is stated that "The Applicant's goal is to utilize these species on at least 25% of the Project Area." in response to staff's recommendation that 70% of the impacted project area be planted in beneficial vegetation. Is beneficial vegetation being planned to be planted around and underneath the proposed solar panel arrays? Or is this referenced goal of 25% only referring to the use of pollinator planting habitat?

Response: The Applicant's goals and expectations for the Project are to plant beneficial vegetation (as outlined by Staff's recommendation) on 70% of the impacted Project Area, at a minimum. The Applicant plans to utilize a pollinator seed mix on 25% of the Project Area that will be used in conjunction with those beneficial vegetative species as well.

3. In the response to Question 6 of the second set of Data Requests regarding the stow mode, references made to Exhibit A for the specifications of the NEXTracker SPT system, which mentions "intelligent wind stowing" as wind protection. Please describe or elaborate on what is meant by intelligent wind stowing, and include the angles involved in accomplishing the stow mode.

Response: Different tracker manufacturers take different approaches to achieve this type of wind stow. However, in general, it typically involves measurement of the current site wind speed, current site wind direction, and the tracker's current tracking angle, and then control logic determines whether the existing conditions require movement of the tracker to the wind stow position. For the current standard NEXTracker SPT system referenced in Exhibit A of the Application, the tracker is designed to be at full tilt angle of 60 degrees facing into the wind during wind stow conditions.

4. When would the selection of the tracker manufacturer be made?

<u>Response</u>: The Applicant would finalize the tracker selection close to the construction phase of the Project, prior to receiving the final stamp of a Professional Engineer in the state of Ohio.

5. Please correct and address the following concern from Ohio Department of Agriculture: The application does not include a "Mapping of agricultural land. The applicant shall identify on a map of at least 1:24,000 scale the proposed facility, all agricultural land, and separately all agricultural district land existing at least sixty days prior to submission of the application located within the project area boundaries. Where available, distinguish between agricultural uses such as cultivated lands, permanent pastureland, managed woodlots, orchards, nurseries, livestock and poultry confinement areas, and agriculturally related structures." While the Narrative notes on page 96 that "There is no agricultural district land within the Project Area," a map of the agricultural land is required by ORC Ohio Adm. Code 4906-4-08(E)(1).

<u>Response</u>: Included as Attachment 2 to this response is a map of agricultural land use classification. This map reflects there are no agricultural district land within the Project Area.

- 6. The application mentions a site grading. To evaluate the grading and its potential impact to future land use, ODA requests a site grading plan that includes: a. Existing and proposed 1' contours
 - a. Drainage arrows which delineate existing and proposed drainage patterns
 - **b.** Estimated earthwork quantities including the amount of cut and fill and the amount of soil to be exported or imported (in cubic yards)
 - c. Location of proposed areas of cut and fill. Include extent and maximum depth of cut and fill.
 - d. Location of proposed improvements including construction entrances, construction roadways, parking areas, solar panel locations and laydown yards.
 - e. North arrow and scale
 - f. Existing surface water locations

<u>Response</u>: Included as Attachment 3 to this response is a preliminary grading plan that includes locations of proposed construction entrances, proposed access roads, proposed laydown/parking areas, proposed solar panel locations, wetland and waterbody delineations, North arrow, and scale.

The Applicant will not have the locations, or extent, for areas of cut and fill until after final equipment selection, right before construction commences and the final design of the Project is completed. However, the Applicant has provided as example of the information that will be provided as Attachment 4 to this response. This example is a 60% civil design that was submitted to the OPSB in advance of the pre-construction conference for the Hardin Solar Energy III, LLC project on March 3, 2022, in Case No. 20-1678-EL-BGN.

7. Additional information on the medium-voltage collection system, to evaluate the effect on future subsurface drainage if the medium-voltage system is not removed as part of decommissioning, including

a. The type of cable (conductor size and material, insulation material and thickness, total diameter, etc.)

<u>Response</u>: Included as Attachment 5 to this response is an example cable cut sheet. Cables are aluminum cables with tree-retardant crosslinked polyethylene insulation (TR-XLPE), copper concentric neutrals and XLPE jacket. The Applicant anticipates final cables will be similar to the attached cutsheet.

b. Will the cable be buried in conduit? Or will there be any other protective layer placed above the cable?

<u>Response</u>: Medium voltage cables will be direct buried and backfilled with native soil that is screened and compacted. Conduits will only be installed in the transitions from underground to overhead – such as at inverter locations and the substation risers.

c. A cross section of the cable trench, including anticipated depth and fill material

<u>Response</u>: Included as Attachment 6 to this response is an example trench detail drawing from the Hardin Solar Energy, LLC project, Case No. 17-773-EL-BGN.

Respectfully submitted,

<u>/s/ Christine M.T. Pirik</u> Christine M.T. Pirik (0029759) (Counsel of Record) Terrence O'Donnell (0074213) Matthew C. McDonnell (0090164) Dickinson Wright PLLC 180 East Broad Street, Suite 3400 Columbus, Ohio 43215 (614) 591-5461 cpirik@dickinsonwright.com mmcdonnell@dickinsonwright.com

Attorneys for Fountain Point Solar Energy LLC


4876-5356-4195 v1 [39579-58]


Attachment 1 Preliminary Gen-tie 10% Design


Invenergy

June 3, 2021










Attachment 2 Agricultural Land Use Classification

Stantec





(Sheet 1 of 2) Fountain Point Solar Energy Project Logan County, Ohio


This map and all data contained within are supplied as is with no warranty. Cardno Inc. expressly disclaims responsibility for damages or liability from any claims that may arise out of the use or misuse of this map. It is the sole responsibility of the user to determine if the data on this map meets the user's needs. This map was not created as survey data, nor should it be used as such. It is the user's responsibility to obtain proper survey data, prepared by a licensed surveyor, where required by law.

Scale: 1:24,000










Attachment 3 Preliminary Grading Plan


Invenergy


June 2, 2022





<u>Legend</u>





Project Layout

Fountain Point Solar Energy Center | Logan County, Ohio

June 02, 2022 Invenergy

Fountain Point Solar Energy LLC Case No. 21-1231-EL-BGN

Attachment 4 Example Information for 60% Design Hardin Solar Energy III, LLC, Case No. 20-1678-EL-BGN

Kimley-Horn

January 21, 2022



APPLICANT/PROJECT OWNER

INVENERGY ONE SOUTH WACKER DRIVE, SUITE 1800 CHICAGO, IL 60606 CONTACT: LAUREN CANNON PHONE: 312-582-1732 CIVIL ENGINEER

KIMLEY-HORN AND ASSOCIATES, INC. 7965 N. HIGH STREET SUITE 200 VIDE N. HIGH STREET SUITE 200 COLUMBUS, OH 43235 CONTACT: CAL CARLSON PHONE: (331) 310-0039 ENGINEER OF RECORD: MICHAEL REEVES, P.E.

SURVEYOR - ALTA

ATWELL 7100 E. PLEASANT VALLEY ROAD, SUITE 220 HDEPENDENCE, OH 44131 CONTACT: ALEX E. MARKS, PLS PHONE:(440) 349-2000

SURVEYOR - TOPOGRAPHY

DRONE DEPLOY 1045 BRYANT ST SAN FRANCISCO, CA 94103 CONTACT: JULIA SOBCZAK PHONE: (507) 593-7663

SOLAR CONSULTANT

INVENERGY INVENDERGY ONE SOUTH WACKER ORIVE, SUITE 1800 CHICAGO, IL 60606 CONTACT: LAUREN CANNON PHONE: 312-582-1732

CONTRACTOR

RES CONSTRUCTION 11101 W 120TH AVE, SUITE #400 BROOMFIELD, CO 80021 CONTACT: DARREN PENCE PHONE: (720) 543 2131

GEOTECHNICAL REPORT

THE GEOTECHNICAL ENGINEERING REPORT FOR THE HARDIN III SOLAR ENERGY CENTER, LLC PROJECT, HARDIN, COUNTY CHIO, PREPARED BY TERRACON, DATED 03/12/2023, AND ALL ADDENDA SHALL BE CONSIDERED PART OF THESE CONSTRUCTION DOCUMENTS.


SITE INFORMATION

PROJECT DESCRIPTION: 250-MW SINGLE AXIS TRACKER SOLAR ARRAY PROJECT

PARCEL ZONING: THE PROJECT AREA IS NOT CURRENTLY ZONED PER HARDIN COUNTY, MARION TOWNSHIP, ROUNDHEAD TOWNSHIP AND MCDDNALD TOWNSHIP ADMINISTRATORS.

SETBACK TABLE					
FEET TO FENCE	FEATURE				
50	CULTURAL RESOURCES				
50	DELINEATED WETLANDS				
100	ROAD RIGHT-OF-WAY				
300	RESIDENCES				
5	UTILITY T-LINE ROW				
200	NON-PARTICIPATING PARCELS				
40	PROJECT TRANSMISSION LINE				
ROW	UTILITY DISTRIBUTION LINE				
80	OTHER BUILDINGS				

PRELIMINARY CIVIL CONSTRUCTION PLANS FOR HARDIN III SOLAR LOCATED IN HARDIN COUNTY, OH





	Sheet List Table
Sheet Number	
C-100	COVER SHEET
C-200	GENERAL NOTES
C-300	EROSION CONTROL PLAN - OVERALL
C-301	EROSION CONTROL PLAN
C-302	EROSION CONTROL PLAN
C-303	EROSION CONTROL PLAN
C-304	EROSION CONTROL PLAN
C-305	EROSION CONTROL PLAN
C-306	EROSION CONTROL PLAN
C-307	EROSION CONTROL PLAN
C-308	EROSION CONTROL PLAN
C-309	EROSION CONTROL PLAN
C-310	EROSION CONTROL PLAN
C-311	EROSION CONTORL PLAN
C-312	EROSION CONTROL PLAN
C-400	EXISTING CONDITIONS AND DEMO - OVERALL
C-401	EXISTING CONDITIONS AND DEMO
C-402	EXISTING CONDITIONS AND DEMO
C-403	EXISTING CONDITIONS AND DEMO
C-404	EXISTING CONDITIONS AND DEMO
C-405	EXISTING CONDITIONS AND DEMO
	EXISTING CONDITIONS AND DEMO
C-406	
C-407	EXISTING CONDITIONS AND DEMO
C-408	EXISTING CONDITIONS AND DEMO
C-409	EXISTING CONDITIONS AND DEMO
C-410	EXISTING CONDITIONS AND DEMO
C-411	EXISTING CONDITIONS AND DEMO
C-412	EXISTING CONDITIONS AND DEMO
C-600	SITE GRADING AND DRAINAGE PLAN - OVERALL
C-601	SITE GRADING AND DRAINAGE PLAN
C-602	SITE GRADING AND DRAINAGE PLAN
C-603	SITE GRADING AND DRAINAGE PLAN
C-604	SITE GRADING AND DRAINAGE PLAN
C-605	SITE GRADING AND DRAINAGE PLAN
C-606	SITE GRADING AND DRAINAGE PLAN
C-607	SITE GRADING AND DRAINAGE PLAN
C-608	SITE GRADING AND DRAINAGE PLAN
C-609	SITE GRADING AND DRAINAGE PLAN
C-610	SITE GRADING AND DRAINAGE PLAN
C-611	SITE GRADING AND DRAINAGE PLAN
C-612	SITE GRADING AND DRAINAGE PLAN
C-800	EROSION CONTROL DETAILS
C-801	EROSION CONTROL DETAILS
C-802	CONSTRUCTION DETAILS
C-802	CONSTRUCTION DETAILS
C-803	
L-300	
L-301	
L-302	LANDSCAPE PLAN
L-303	LANDSCAPE PLAN
L-304	LANDSCAPE PLAN
L-305	LANDSCAPE PLAN
L-306	LANDSCAPE PLAN
L-307	LANDSCAPE PLAN
L+308	LANDSCAPE PLAN
L-309	LANDSCAPE PLAN
L-310	LANDSCAPE PLAN
L-311	LANDSCAPE PLAN
L-312	LANDSCAPE PLAN
L-200	LANDSCAPE GENERAL NOTES



GENERAL CONSTRUCTION NOTES

1. EXISTING UTILITIES RIGHT-OF-WAY AND HORIZONTAL CONTROL SHOWN ON THE DRAWINGS WERE OBTAINED FROM A SURVEY PREPARED ON 11/02/2020

> ATWELL 7100 E. PLEASANT VALLEY ROAD, SUITE 220 INDEPENDENCE, OH 44131 CONTACT: ALEX E. MARKS, PLS PHONE: (440) 349-2000

- 2. EXISTING TOPOGRAPHY WAS OBTAINED VIA AERIAL DRONE SURVEY AND PROVIDED BY DRONEDEPLOY.
- COPIES OF THE SURVEY CAN BE PROVIDED, IF REQUESTED. SITE CONDITIONS MAY HAVE CHANGED SINCE THE SURVEY WAS PREPARED. CONTRACTORS TO VISIT SITE TO FAMILIARIZE THEMESCLYES WITH THE CURRENT CONDITIONS.
- 4. THE CONTRACTOR SHALL BE RESPONSIBLE FOR FURNISHING ALL MATERIAL AND LABOR TO CONSTRUCT THE FACILITY AS SHOWN AND DESCRIBED IN THE CONSTRUCTION DOCUMENTS IN ACCORDANCE WITH THE APPROPRIATE APPROVING AUTHORITES, SPECIFICATIONS AND REQUIREMENTS, CONTRACTOR SHALL CLEAR AND GRUB ONLY AREAS INDICATED, REMOVING TREES, STUMPS ROOTS, MUCK, EXISTING PAVEMENT AND ALL OTHER DELETERIOUS WATERIAL
- 5. EXISTING UTILITIES SHOWN ARE LOCATED ACCORDING TO THE INFORMATION AVAILABLE TO THE ENGINEER AT THE TIME OF THE ALTA SURVEY AND HAVE NOT BEEN INDEPENDENTLY VERIFIED BY THE ENGINEER, GUARANTEE IS NOT MADE THAT ALL EXISTING UNDERGROUND UTILITES ARE SHOWN OF THAT THE LOCATION OF THOSE SHOWN ARE ENTIRELY ACCURATE. FINDING THE THE LOCATION OF THOSE SHOWN ARE ENTIRELY ACCURATE. FINDING THE ACTUAL LOCATION OF ANY EXISTING UTUITES IS THE CONTRACTOR'S RESPONSIBILITY AND SHALL BE GONE BEFORE COMMENCING ANY WORK IN THE VICINITY. FURTHERNORE, THE CONTRACTOR SHALL BE FULLY RESPONSIBLE FOR ANY AND ALL DAMAGES DUE TO THE CONTRACTOR'S SUSTAINED OR COST INCURRED BECAUSE OF THE OPERATIONS'IN THE VICINITY OF EXISTING UTUITES OR STRUCTURES, NOR FOR TEMPORARY SUSTAINED OR COST INCURRED BECAUSE OF THE OPERATIONS'IN THE VICINITY OF EXISTING UTUITES OR STRUCTURES, NOR FOR TEMPORARY BRACING AND SHORING OF SAME. IF IT IS NECESSARY TO SHORE BRACE, SWING OR RELOCATE A UTUITY, THE UTUITY COMPANY OR DEPARTMENT AFFECTED SHALL BE CONTACTED AND THEIR PERMISSION OBTAINED REGARDING THE METHOD TO USE FOR SUCH WORK AND PRIOR TO THE COMMENCEMENT OF THE WORK.
- 6 IT IS THE CONTRACTOR'S RESPONSIBILITY TO CONTACT THE VARIOUS UTILITY COMPANES WHICH MAY HAVE BURIED OR AFRIAL UTILITES WITHIN OR NEAR THE CONSTRUCTION AREA BEFORE COMMENCING WORK. THE CONTRACTOR SHALL PROVIDE 48 HOURS MINIMUM NOTICE TO ALL UTILITY COMPANIES PRIOR TO BEGINNING CONSTRUCTION.
- 7 THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL REQUIRED CONSTRUCTION PERMITS AND BONDS IF REQUIRED PRIOR TO CONSTRUCTION.
- 8. THE CONTRACTOR SHALL HAVE AVAILABLE AT THE JOB SITE AT ALL TIMES ONE COPY OF THE CONSTRUCTION DOCUMENTS INCLUDING PLANS, SPECIFICATIONS, GEOTECHNICAL REPORT AND SPECIAL CONDITIONS AND COPIES OF ANY REQUIRED CONSTRUCTION PERMITS.
- 9. ANY DISCREPANCIES ON THE DRAWINGS SHALL BE IMMEDIATELY BROUGHT TO THE ATTENTION OF THE ENGINEER BEFORE COMMENCING WORK, NO FIELD CHANGES OR DEVIATIONS FROM DESIGN ARE TO BE MADE WITHOUT PRIOR APPROVAL OF THE ENGINEER.
- 10. THE CONTRACTOR SHALL BE RESPONSIBLE FOR DOCUMENTING AND MAINTAINING RECORD INFORMATION WHICH SHALL BE RECORDED AS CONSTRUCTION PROGRESSES OR AT THE COMPLETION OF APPROPRIATE CONSTRUCTION INTERVALS AND SHALL BE RESPONSIBLE FOR PROVIDING FIELD NOTES AND SURVEY VERIFICATION TO THE ENGNEER. ENGNEER WILL PREPARE RECORD DRAWINGS BASED ON INFORMATION PROVIDED BY THE CONTROLVER THE FORCE ON INFORMATION PROVIDED BY THE CONTRACTOR. THE RECORD DRAWINGS WILL NOT BE AN "AS-BUILT" DRAWING IND NO FIELD VERIFICATION WILL BE COMPLETED BY THE ENGINEER
- 11. ANY WELLS DISCOVERED ON SITE THAT WILL HAVE NO USE MUST BE PLUGGED BY A LICENSED WELL DRILING CONTRACTOR IN A MANNER APPROVED BY ALL JURISDICTIONAL AGENCIES. CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ANY WELL ABANDONMENT PERMITS REQUIRED.
- 12. ANY WELL DISCOVERED DURING EARTH MOVING OR EXCAVATION SHALL BE REPORTED TO THE APPROPRIATE JURISDICTIONAL AGENOES.

DEMOLITION NOTES

- 1. ALL MATERIAL REMOVED FROM THIS SIFE BY THE CONTRACTOR SHALL BE DISPOSED OF BY THE CONTRACTOR IN A LEGAL MANNER.
- 2. REFER TO THE TOPOGRAPHIC SURVEY FOR ADDITIONAL DETAILS OF EXISTING REFER TO THE TOPOGRAPHIC SURVEY FOR ADDITIONAL DETAILS OF EXISTING STRUCTURES, ETC., LOCATED WITHIN THE PROJECT STEE ALL EXISTING BUILDINGS, STRUCTURES, SLADS, CONCRETE, ASPHALT, DEBRIS PILES, SIGNS, AND ALL APPURTENANCES ARE TO BE REMOVED FROM THE SITE BY THE CONTRACTOR AND PROPERLY DISPOSED OF IN A LEGAL MANNER AS PART OF THIS CONTRACT, SOME ITEMS TO BE REMOVED MAY NOT BE DEPICTED ON THE TOPOGRAPHIC SURVEY. IT IS THE CONTRACTOR'S RESPONSIBILITY TO MSIT THE SITE AND DETERMINE THE FULL EXTENT OF THEMS TO BE REMOVED. IF ANY THEMS ARE IN QUESTION, THE CONTRACTOR SHALL CONTACT THE OWNER PRIOR TO REMOVAL OF SAID ITEMS.
- 3. NO TREES SHALL BE REMOVED DURING PROJECT CONSTRUCTION TREE PROTECTION FENCING SHOULD BE INSTALLED AS NECESSARY PRIOR TO THE COMMENCEMENT IN THE AREA OF WORK.
- 4. CONTRACTOR SHALL ADJUST GRADE OF ANY EXISTING UTILITIES TO REMAIN
- 5. CONTRACTOR IS RESPONSIBLE FOR ALL UTILITY SERVICES DIRECTLY IMPACTED BY CONTRACTOR'S CONSTRUCTION ACTIVITIES TO ADJACENT PROPERTIES AT ALL TIMES. UTILITY SERVICES SHALL NOT BE INTERRUPTED WITHOUT APPROVAL FROM OWNER IN COORDINATION WITH AD JACENT PROPERTIES AND/OR LOCAL JURISDICTION.
- 5. CONTRACTOR TO COORDINATE WITH RESPECTIVE UTILITY COMPANIES PRIOR TO THE REMOVAL AND/OR RELOCATION OF UTILITIES.

PAVING, GRADING AND DRAINAGE NOTES

- 1. ALL PAMING. CONSTRUCTION. MATERIALS AND WORKMANSHIP WITHIN ALL PAINS, CONSTRUCTION, MATERIALS, AND MOREMANSHIP HITHOUS JARISDICTION'S RICHT-OF-WAY SHALL BE IN ACCORDANCE WITH LOCAL OR COUNTY SPECIFICATIONS AND STANDARDS (LATEST EDITION) OR ODOT SPECIFICATIONS AND STANDARDS (LATEST EDITION) IF NOT COVERED BY LOCAL OR COUNTY PERCENT LOCAL OR COUNTY RECULATIONS.
- 2. ALL UNPAVED AREAS IN EXISTING RIGHTS-OF-WAY DISTURBED BY CONSTRUCTION SHALL BE REGRADED AND REPAIRED TO EXISTING CONDITION OR BETTER, WITH THE EXCEPTION OF COUNTY ROADS.
- TRAFFIC CONTROL ON ALL ODOT, LOCAL AND COUNTY RIGHTS-OF-WAY SHALL MEET THE REQUIREMENTS OF THE MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES (U.S. DOT/FHA) AND THE REQUIREMENTS OF THE STATE AND ANY LOCAL AGENCY HAVING JURSDICTION. IN THE EVENT THAT THE CONTRACT DOCUMENTS AND THE JURSDICTIONAL AGENCY REQUIREMENTS ARE NOT IN AGREEMENT, THE MOST STRINGENT SHALL GOVERN.
- 4. THE CONTRACTOR SHALL GRADE THE SITE TO THE ELEVATIONS INDICATED AND SHALL REGRADE TO THESE ELEVATIONS IN THE IFC CIVIL CONSTRUCTION DRAWINGS PER THE TOPO DATA AND SHALL REGRADE TO THESE ELEVATIONS TIL ADEQUATE STABILIZATION OCCURS.
- 5. ALL AREAS INDICATED ACCESS ROADS SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE TYPICAL SITE ACCESS ROAD DETAILS AS INDICATED THE DRAWINGS.
- 6. THE CONTRACTOR SHALL INSTALL FILTER FABRIC OVER ALL DRAINAGE STRUCTURES THAT DISCHARGE OFF-SITE WITH POTENTIAL TO CARRY SEDIMENT BEYOND THE LIMITS OF DISTURBANCE FOR THE DURATION OF CONSTRUCTION AND UNTIL SUBSTANTIAL COMPLETION. ALL DRAINAGE STRUCTURES SHALL BE CLEANED OF DEBRS AS REOVIRED DURING AND AT THE END OF CONSTRUCTION TO PROVIDE POSITIVE DRAINAGE FLOWS.
- DEWATERING IS REQUIRED, THE CONTRACTOR SHALL OBTAIN ANY APPLICABLE REQUIRED PERMITS.
- 8. IN AREAS WHERE MASS GRADING IS BEING PERFORMED WITHIN THE PV ARRAY, CONTRACTOR SHALL STRIP TOPSOIL AND ORGANIC MATTER TO A MINIMUM DEPTH OF 8". STRIPPED TOPSOIL AND ORGANIC MATTER SHALL BE REPLACED AFTER THE SUBGRADE HAS BEEN CORRECTED. IN AREAS OF ACCESS ROAD OR INVERTER FOUNDATION CONSTRUCTION STRIP ALL TOPSOIL AND ORGANIC WATTER, CONSULT WITH PROJECT GEOTECHNICAL ENGNEER F TOPSOIL AND ORGANIC MATERIAL EXCEED 8" IN DEPTH IN THESE AREAS.
- 9. FIELD DENSITY TESTS SHALL BE TAKEN AND RECORDED IN ACCORDANCE WITH THE GEOTECHNICAL ENGINEER'S RECOMMENDATIONS.
- 10. ALL AREAS DISTURBED BY CONSTRUCTION SHALL BE GRADED AS PER PLANS. THE AREAS SHALL THEN BE STABILIZED BY MEANS AND METHODS APPROVED BY THE LOCAL AGENCY.
- 11. ALL SLOPES SHALL BE 3 (MORIZONTAL) :1 (VERTICAL) OR FLATTER UNLESS OTHERWISE SHOWN.
- 12. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE CONTROL OF DUST AND DIRT RISING AND SCATTERING IN THE AIR DURING CONSTRUCTION AND SHALL PROVIDE WATER SPRINKLING OR OTHER SUITABLE METHODS OF CONTROL. THE CONTRACTOR SHALL COMPLY WITH ALL GOVERNING REGULATIONS PERTAINING TO ENVIRONMENTAL PROTECTION.
- 13. THE CONTRACTOR SHALL TAKE ALL REQUIRED MEASURES TO CONTROL TURBIDITY, INCLUDING BUT NOT LIMITED TO THE INSTALLATION OF TURBIDITY BARRIERS AT ALL LOCATIONS WHERE THE POSSIBILITY OF TRANSFERING SUSPENDED SOLIDS INTO THE RECEIVING WATER BODY EXISTS DUE TO THE PROPOSED WORK. TURBIDITY BARRIERS MUST BE MAINTAINED IN EFFECTIVE CONDITION AT ALL LOCATIONS UNTIL CONSTRUCTION IS COMPLETED AND DISTURBED SOLL AREAS ARE STABILIZED. THEREAFTER, THE CONTRACTOR MUST REMOVE THE BARRIERS. AT NO TIME SHALL THERE BE ANY OFF SITE DISCHARGE WHICH VIOLATES THE WATER DUALITY STANDARDS OF THE GOVERNING CODE.
- 14. EXPOSED SLOPES DREATER THAN 4-1 SHOULD BE STABILIZED WITHIN 48 HOURS OF COUPLETING FINAL GRADING, AND AT ANY OTHER TIME AS NECESSARY, TO PREVENT EROSION, SEDIMENTATION OR TURBID DISCHARGES.
- 15. THE CONTRACTOR MUST REVIEW AND MAINTAIN A COPY OF THE REQUIRED PERMITS COMPLETE WITH ALL CONDITIONS, ATTACHMENTS, EXHIBITS, AND PERMIT MODIFICATIONS IN GOOD CONDITION AT THE CONSTRUCTION SITE. THE COMPLETE PERMIT MUST BE AVAILABLE FOR REVIEW UPON REQUEST BY GOVERNING JURISDICTIONS.

EROSION CONTROL NOTES

- THE STORM WATER POLLUTION PREVENTION PLAN ("SWPPP") IS COMPRISED OF THE EROSION CONTROL PLAN, THE STANDARD DETAILS, THE PLAN NARRATIVE, ATTACHMENTS INCLUDED IN SPECIFICATIONS OF THE SWPPP, PLUS THE PERMIT AND ALL SUBSEQUENT REPORTS AND RELATED DOCUMENTS.
- ALL CONTRACTORS AND SUBCONTRACTORS INVOLVED WITH STORM WATER POLLUTION PREVENTION SHALL OBTAIN A COPY OF THE STORM WATER POLLUTION PREVENTION PLAN AND THE STATE OF OHIO NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM GENERAL PERMIT (NPDES PERMIT) AND BECOME FAMILIAR WITH THEIR CONTENTS.
- 3. THE CONTRACTOR SHALL IMPLEMENT BEST MANAGEMENT PRACTICES AS REQUIRED BY THE SWPPP.
- 4. BEST MANAGEMENT PRACTICES (BWP'S) AND CONTROLS SHALL CONFORM TO FEDERAL, STATE, OR LOCAL REQUIREMENTS OR MANUAL OF PRACTICE, AS APPLICABLE. THE CONTRACTOR SHALL IMPLEMENT ADDITIONAL CONTROLS AS DIRECTED BY THE PERMITTING AGENCY OR OWNER.
- 5. CONTRACTOR SHALL DENOTE ON PLAN THE TEMPORARY PARKING AND STORACE AREA WHICH SHALL ALSO BE USED AS THE EDUIPMENT MAINTENANCE AND CLEANING AREA, EMPLOYEE PARKING AREA, AND AREA FOR LOCATING PORTABLE FACILITIES, OFFICE TRAILERS, AND TOILET FACILITIES.
- 6. ALL CONCRETE WASH OUT WATER SHALL BE DETAINED AND PROPERLY TREATED OR DISPOSED.
- CONTRACTOR SHALL PREPARE AND FOLLOW A SPILL PREVENTION, CONTROL, AND COUNTERKEASURES PLAN (SPCC) IN ACCORDANCE WITH THE EPA OIL POLLUTION PREVENTION, CENERAL REQUIREMENTS FOR SPILL PREVENTION, CONTROL, AND COUNTERMEASURE PLANS (40 CFR 112.7).
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR DUST CONTROL ON SITE. THE USE OF MOTOR OILS AND OTHER PETROLEUM BASED OR TOXIC LIQUIDS FOR DUST SUPPRESSION OPERATIONS IS PROHIBITED.
- 9. RUBBISH, TRASH, GARBAGE, LITTER, OR OTHER SUCH WATERIALS SHALL BE DEPOSITED INTO CONTAINERS. MATERIALS SHALL BE PREVENTED FROM LEAVING THE PREWIESS THROUGH THE ACTION OF WIND OR STORM WATER DISCHARGE INTO ORAINAGE OITCHES OR WATERS OF THE STATE.
- 10. ALL STORM WATER POLLUTION PREVENTION MEASURES PRESENTED ON THE PLAN, SHALL BE INITIATED AS SOON AS PRACTICABLE.
- 11- SITE STABILIZATION REQUIREMENTS ARE AS FOLLOWS:

 - PERMANENT STABILIZATION 1.1. ANY AREAS THAT WILL LIE DORMANT FOR ONE YEAR OR MORE SHALL BE PERMANENTLY STABILIZED WITHIN 14 DAYS OF THE MOST SHALL BE PERMANENTLY STABILIZED WITHIN 14 DAYS OF THE MOST RECENT DISTURBANCE ANY AREAS WITHIN SO FEET OF A SURFACE WATER OF THE STATE AND AT FINAL GRADE SHALL BE PERMANENTLY STABILIZED WITHIN 14 DAYS OF REACHING FINAL GRADE OTHER AREAS AT FINAL GRADE SHALL BE PERMANENTLY STABILIZED WITHIN 14 DAYS OF REACHING FINAL GRADE WITHIN THAT AREA

11.2 TE 11.2.1

- TEMPORARY STABILIZATION: 2.1. ANY DISJURGED AREAS WITHIN 50 FEET OF A SURFACE WATER OF THE STATE AND NOT AT FINAL GRADE SHALL BE TEMPORARILY STABILIZED WITHIN TWO DAYS OF THE MOST RECENT DISTURBANCE IF THE AREA WILL REMAIN IDLE FOR WORE THAN 14 DAYS. 2. ANY DISTURBED AREAS THAT WILL BE DORMANT FOR MORE THAN 14 DAYS BUT LESS THAN ONE YEAR, AND NOT WITHIN 50 FEET OF A SURFACE WATER OF THE SHALL BE TEMPORARILY STABILIZED WITHIN 14 DAYS OF THE MOST RECENT DISTURBANCE WITHIN THE AREA. 11 2.2. AREA.
- 12. ALL CONTROL DEVICES THAT FUNCTION SIMILARLY TO SILT FENCE OR FIBER ROLLS MUST BE REPAIRED, REPLACED, OR SUPPLEMENTED WITH EFFECTIVE CONTROLS WHEN THEY BECOME NONFUNCTIONAL OR THE SEDIMENT REACHES ONE-THIRD THE HEIGHT OF THE DEVICE THESE REPAIRS MUST BE MADE WITHIN 24 HOURS OF THE RAINFALL EVENT OF AS SOON AS FIELD CONDITIONS ALLOW ACCESS.
- CONDITION'S ALLOW ACCESS. 13. ALL SEDIMENT DELTAS AND DEPOSITS MUST BE REMOVED FROM SURFACE WATERS, DRAINAGE WAYS, CATCH BASINS AND OTHER DRAINAGE SYSTEMS. ALL AREAS MHERE SEDIMENT REMOVAL, RESULTED IN EXPOSED SOIL MUST BE RESTABULZED. THE REMOVAL AND STABULZATION MUST TAKE PLACE IMMEDIATELY, BUT NO MORE THAN 7 DAYS AFTER THE RAINFALL EVENT UNLESS PRECLUED BY LEGAL, REGULATORY OR PHYSICAL ACCESS CONSTRAINTS. ALL REASONABLE EFFORTS MUST BE USED TO OBTAIN ACCESS. ONCE ACCESS IS OBTAINED, REMOVAL AND STABULZATION MUST TAKE PLACE IMMEDIATELY, BUT NO MORE THAN 7 DAYS LATER, CONTRACTOR IS RESPONSIBLE FOR CONTACTING ALL APPROPRIATE AUTHORITES AND RECEIVING THE APPLICABLE PERMITS PRIOR TO CONDUCTING ANY WORK.
- 14. IF THE ACTION OF VEHICLES TRAVELING OVER THE GRAVEL CONSTRUCTION ENTRANCES IS NOT SUFFICIENT TO REMOVE THE MAJORITY OF DURT OR MUD, PUBLIC ROADS SHALL BE SWEPT AND EXCESS SEDIMENT SHALL NOT LEAVE THE SIZE. IF WASHING IS USED, PROVISIONS MUST BE WADE TO INTERCEPT THE WASH WATER AND TRAP THE SEDIMENT BEFORE IT IS CARRIED OFF THE EVEN
- 15. ALL WATERIALS SPILLED, DROPPED, WASHED, OR TRACKED FROM VEHICLES ONTO ROADWAYS DR INTO STORM DRAINS MUST BE REMOVED AS SOON AS POSSIBLE
- 16 THE CONTRACTOR SHALL BE RESPONSIBLE FOR REMOVING ANY SEDIMENT CAUSED BY CONSTRUCTION THAT MAY HAVE COLLECTED IN THE STORM SEVER DRIANGE SYSTEMS IN CONJUNCTION WITH THE STABILIZATION OF THE
- 17. ON-SITE SOIL STOCKPILE AND BORROW AREAS SHALL BE PROTECTED FROM EROSION AND SEDIMENTATION THROUGH INPLEMENTATION OF BEST MANAGEMENT PRACTICES. STOCKPILE AND BORROW AREA LOCATIONS SHALL BE NOTED ON THE EROSION CONTROL PLAN AND PERMITTED IN ACCORDANCE WITH GENERAL PERMIT REQUIREMENTS.
- 18. STOCKPILES TO REMAIN IN PLACE FOR MORE THAN THREE DAYS SHALL BE PROVIDED WITH SOIL EROSION AND SOIL CONTROL MEASURES. MATERIAL IS TO BE MAULEO OFF INWEDIATELY AND LEGALLY IF NO STOCKPILE IS TO REMAIN IN PLACE
- 19. ALL TEMPORARY SOIL EROSION AND SEDIMENT CONTROL MEASURES SHALL BE REMOVED WITHIN 30 DAYS AFTER FINAL STABILIZATION IS ACHEVED. TRAPPED SEDIMENT AND OTHER DISTURBED SOILS RESULTING FROM TEMPORARY MEASURES SHALL BE PROPERLY DISPOSED OF PRIOR TO PERMANENT STARUIZATION
- 20. SLOPES SHALL BE LEFT IN A ROUGHENED CONDITION DURING THE GRADING PHASE TO REDUCE RUNOFF VELOCITIES AND EROSION.
- 21. IF GRADE CHANGES ARE NECESSARY DURING THE DEVELOPMENT OF THE PROJECT, THE CONTRACTOR SHALL BE RESPONSIBLE FOR ADJUSTING THE EROSION CONTROL MEASURES (SILT FENCES, ETC.) TO PREVENT EROSION.

EROSION CONTROL NOTES (CONTINUED)

- 23. DURING GRADING OR WORKING IN LARGE, FLAT AREAS, THE CONTRACTOR SHALL STABILIZE THESE AREAS AS QUICKLY AS POSSIBLE, IF EROSION BECOMES A CONCERN, THE CONTRACTOR SHALL IMPELMENT ADDITIONAL EROSION CONTROL MEASURES, INCLUDING, BUT NOT LIMITED TO: FILTER SOCKS OR SILT FENCE STAKED PARALLEL TO THE SLOPE SPACED AT INTERVALS TO SLOW DOWN THE FLOW OF WATER AND DISSIPATE THE CLOW
- FLOW. ADDITIONAL TEMPORARY SEEDING

- 0.5" RAIN EVENT.

EROSION CONTROL MAINTENANCE

ALL MEASURES STATED ON THE EROSION AND SEDIMENT CONTROL PLAN, AND IN THE STORM WATER POLLUTION PREVENTION PLAN, SHALL BE MAINTAINED IN FULLY FUNCTIONAL CONDITION UNTIL NO LONGER REQUIRED FOR A COMPLETED PHASE OF WORK OR FINAL STABILIZATION OF THE SITE, ALL EROSION AND SEDIMENTATION CONTROL MEASURES MAY BE CHECKED BY A QUALIFIED PERSON ON A SCHEDULE THAT MEETS OR EXCEEDS THE GOVERNING REQUIREMENTS, AND CLEANED AND REPAIRED IN ACCORDANCE WITH THE FOLLOWING:

- 1. INLET PROTECTION DEVICES AND BARRIERS SHALL BE REPAIRED OR REPLACED IF THEY SHOW SIGNS OF UNDERMINING, OR DETERIORATION
- 2. ALL SEEDED AREAS SHALL BE CHECKED REGULARLY TO SEE THAT A GOOD STAND IS MAINTAINED. AREAS SHOULD BE WATERED AND RESERVED AS NEEDED.
- SILT FENCES SHALL BE REPAIRED TO THEIR ORIGINAL CONDITIONS IF DAMAGED. SEDIMENT SHALL BE REMOVED FROM THE SILT FENCES WHEN IT REACHES ONE-MALF THE HEIGHT OF THE SILT FENCE.
- 4. THE CONSTRUCTION ENTRANCES SHALL BE MAINTAINED IN A CONDITION WHICH WILL PREVENT TRACKING OR FLOW OF MUD ONTO PUBLIC RIGHTS-OF-WAY, THIS MAY REQUIRE PERIODIC TOP DRESSING OF THE ENTRY OF WAY. CONSTRUCTION ENTRANCES AS CONDITIONS DEMAND.
- 5. THE TEMPORARY PARKING AND STORAGE AREA SHALL BE KEPT IN GOOD CONDITION (SUITABLE FOR PARKING AND STORAGE). THIS MAY REQUIRE PERIODIC TOP DRESSING OF THE TEMPORARY PARKING AS CONDITIONS
- 6. ALL MAINTENANCE OPERATIONS SHALL BE DONE IN A TIMELY MANNER.

PROJECT CLOSEOUT NOTES

- 1. CONTRACTOR SHALL PROVIDE THE NECESSARY ITEMS INCLUDING ANY TESTING, REPORTS, OR CERTIFICATION DOCUMENTS REQUIRED BY THE COVERNING JURISDICTIONS TO PROPERLY CLOSEOUT THE PROJECT BEFORE IT CAN BE DESCHED COMPLETE
- 2 CONTRACTOR SHALL BE RESPONSIBLE FOR DOCUMENTING AND MAINTAINING INFORMATION OF CHANGES TO APPRIVED PLANS DURING CONSTRUCTION. CONTRACTOR SHALL BE RESPONSIBLE FOR PROVIDING RECORD DRAWINGS TO THE ENGINEER AND OWNER AT THE COMPLETION OF CONSTRUCTION. THIS RECORD INFORMATION WILL BE USED TO PRODUCE RECORD / AS-BUILT DRAWINGS, AS REQUIRED.

DRAIN TILE NOTES


- 1 THE CONTRACTOR IS SPECIFICALLY CAUTIONED THAT DRAIN TILES MAY BE PRESENT IN ACRICULTURAL FIELDS. THE LOCATION AND/OR ELEVATION OF POTENTIAL DRAIN TILES ARE UNKNOWN IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO OBTAIN EXISTING DRAIN TILE MAPS FROM THE LAND OWNERS AND LOCATE EXISTING DRAIN TILES PRIOR TO CONSTRUCTION
- 2. THE CONTRACTOR SHALL SPECIFICALLY LOCATE AND PROTECT PERIMETER DRAIN TILE MAIN LINES THAT ARE MUTUALLY BENEFICIAL FOR DRAINING THE PROJECT SITE AND THE ADJACENT PROPERTIES.
- 3. PROPOSED BMPS, INCLUDING BUT NOT UMITED TO GRAVEL SWALES AND NEW ORAIN TILE, SHOULD BE ROUTED FROM AREAS OF HIGH INUNDATION OUT OF PANEL AREAS TO EXISTING PERIMETER DRAIN TILE MAIN LINES.

- ROMINGA AND SEEDING - CRIMPING AND SEEDING - CARTH DIKES AND ROCK CHECK DAWS TO COLLECT AND STORE WATER TO REDUCE THE AMOUNT OF WATER FLOWING ACROSS THE SLOPED AREAS - ADDITIONAL MEASURES AS APPROVED BY THE PROJECT ENGINEER - BWP INSPECTION IS REQUIRED ONCE A WEEK AND WTHIN 24-HOURS OF A

4. CONTRACTOR SHALL CONTACT ENGINEER IMMEDIATELY IF ADDITIONAL ENGINEERING IS REQUIRED BASED ON UNFORESEEN SITE CONDITIONS

	DATE BY	11/19/2021 CPC	01/21/2022 CPC					
	REVISIONS	JOX DESIGN	60% DESIGN					
	NO.				2024 INHILYHORM AND ASSOCIATES, MC 79641 N. HACH STREET 1. SUITE 200	COLUMBUS, DH 43235	WATE KENCE YOUR COM	
	SCALE:	AS NOTED	DESIGNED BY: ERS		DRAWN BY ALM	9	O-COKED BY: CPC	
		7 104	FOF		MIN	IAF Ruc	ξΥ Thoi	2
		PREPARED FOR					DODE NOL LANDO	
				OTAL NOTES	GENERAL NUIES			
				HARDIN III SOLAR	HADDIN COLINTY OH			
)n JE De		кн S	01, A F 16 HEI	INA /21 PRC 87: ET	/2 540 NU	023 CT 044		<u>%</u>





NORTH

2021


c		DATE	11/19/203	01/21/20			
ř	RAPHIC SCALE IN FEET	F			$^+$	ϯ	F
		L					
		L					
LEGEND:		6					
	PROJECT BOUNDARY	REVISIONS					
	ADJ. / INTERIOR	Å					
	PROPÉRTY LINE EX. RIGHT OF WAY	L	N.	ğ			
	EX. EASEMENT	L	JOX OCSICH	GOX OESICA			
<u> </u>	SÉTBACK	Ļ		8	\downarrow		
	APPROXIMATE EX ROAD CENTERLINE	ž	-	~			
£x. ünt	EX. OVERHEAD ELECTRIC	L		s	ų		
GAS GAS	EX. GAS	Ł		0	1110	20 21 c	88
and the second	EX. STREAM EX. TREE LINE	1		Т «	95v Q4	DET, SU M 432	AB7-50 HORN D
Ferrerstower	EX. WETLAND	1		ŝ	TOTI NUMET-HOM AND ASSOCIATES, MC.	N HIGH STREET, SUIT COLUMBUS, OH 43235	PHONE, 630-487-5550 WWW KIMLE - HORN COM
 <u> </u>	EX. WETLAND/STREAM BUFFER			Ę	-A JI WOO	H 100	PHONE WWW
122301802000V	EX. CULTURAL EXCLUSION AREA		2		LEON	296	
	EX. CULTURAL BUFFER			Y			
	EX. CONTOURS	Γ	NOTED	ŝ	Τ	H7	ы С
	EX FLOW (DIRECTION AND SLOPE)	L	A5 N	θ,		18	A.
	PR, CONTOURS	SCALC:		DESIGNED		DRAWN	DIECKED
XX7 <u></u>	PR. FLOW (DIRECTION AND SLOPE)	ľ		ā		<u> </u>	10
TRALE BOOK STREET	PR. GRADING AREA	L					
	PR. GRAVEL ACCESS ROAD	L	Р нот	FOR	.IMI CONS	NA	₹Y cπo
	PR INVERTER	L					
x x	PR. FENCE	┡					
	LIMITS OF DISTURBANCE						
	WRE BACKED SHLT FENCE						
	SUPER SILT FENCE					7	00
	SILT FENCE ROCK OUTLET				Ä		50
	PR. LAYDOWN AREA				-	,	No.
80000000	CONSTRUCTION ENTRANCE		FOR				
	PR STORMWATER PIPE PR. FILTER SOCK		PREPARED FOR				
	PR. EARTH BERN		PREP				
	TEMPORARY DIVERSION DITCH	Г			t		_
	PR. LOW WATER CROSSING SEE DETAIL 4 ON C-803	L			Ž		
EROSION CONTROL	NOTES	L	Z	Ζ	Ę	-	Ļ
-	SUPPORT, SEE DETAIL 4, SHEET C-800.	L	\subseteq	2	<u>n</u> .	<	₹
(R) TEMPORARY STABILIZED	CONSTRUCTION ENTRANCE.	L	0	2.	б		
SEE DETAIL 2, SHEET C	ET, SEE DETAIL 1, SHEET C-800.	L	ŏ	ć	Ŕ		5
D FILTER SOCK, SEE DETA			L		E	C	C
	CONTRACTOR DISCRETION BASED ON				\overline{O}		
0	DETAIL 3, SHEET C-803. TION BASIN, SEE DETAIL 3, SHEET C-801.	F					
0	DITCH, SEE DETAIL 7, SHEET C-801						
(H) SUPER SILT FENCE, SEE				- 4	¥¥	_	
GENERAL NOTES				ζ		₹	
<u>~</u>	ATER CROSSINGS AT ALL ROAD AREAS WITH			=		INN	
HIGH FLOW, IN 90% DESIC UPGRADED TO ELEVATED BASED ON THE LIKELING	ATER CROSSINGS AT ALL ROAD AREAS WIT- SIN, SOME LOW WATER CROSSINGS WILL BE ROADS WITH CULVERTS. THIS WILL BE BO OF WATER POUDING ON THE ROAD AND ON TO BACKUP INTO THE ARRAY AREA AN F THE FLOW FOR BOTH THE CULVERTS AND FS WILL ALSO BE INCLUDED IN 902 DESIGN	L				HARDIN COUNTY	
POTENTIAL FOR INUNDATI ENGINEERING ANALYSIS O	ON TO BACKUP INTO THE ARRAY AREA AN F THE FLOW FOR BOTH THE CULVERTS AND	L			ק	HARI	
THE LOW WATER CROSSIN	IUS WILL ALSO BE INCLUDED IN 90% DESIGN				Ĭ		
		\mathbf{F}	0	RIGIN	AI	ISS	UF
		$\left \right $		01/	21/:	202	2
	оню	\mathbf{F}		168	754	044	•
	Utilities Protection	1	- 5	HEE	1 191	NWD	.c.M

10. SHEET NUMBER

C-300

Click Call or Tap Before You Dig 1-800-362-2764

Utilities Protection SERVICE






LEGEND:


LEGEND:	
	PROJECT BOUNDARY
	ADJ. / INTERIOR PROPERTY LINE
	EX. RIGHT OF WAY
	EX. EASEMENT
	SETBACK
PERSONAL ADDRESS & ADDRESS & ADDRESS	APPROXIMATE ÉX. ROAD CENTERLINE
EX. CHE	EX OVERHEAD ELECTRIC
GAS GAS	EX GAS
	EX STREAM EX. TREE LINE
for the second second second	EX. WETLAND
	EX. WETLAND/STREAM BUFFER
10.20 C 20	EX. CULTURAL EXCLUSION AREA
	EX. CULTURAL BUFFER
	EX. CONTOURS
	EX. FLOW (DIRECTION AND SLOPE)
xx	PR. CONTOURS
	PR. FLOW (DIRECTION AND SLOPE)
and the state of t	PR. GRADING AREA
	PR GRAVEL ACCESS ROAD
	PR. INVERTER
x x	PR. FENCE
	LIMITS OF DISTURBANCE
	WIRE BACKED SILT FENCE
	SUPER SILT FENCE
	SILT FENCE ROCK OUTLET
	PR. LAYDOWN AREA
	CONSTRUCTION ENTRANCE
	PR. STORMWATER PIPE
F5	PR. FILTER SOCK
-0	PR. EARTH BERM
;;;;;/	TEMPORARY DIVERSION DITCH
	PR. LOW WATER CROSSING SEE DETAIL 4 ON C-803
EROSION CONTROL	NOTES
	SUPPORT, SEE DETAIL 4, SHEET C-800
	CONSTRUCTION ENTRANCE.
~	ET, SEE DETAIL 1, SHEET C-800.
(D) FILTER SOCK. SEE DETA	
	OF LAYDOWN AREAS. D CONTRACTOR DISCRETION BASED ON DETAIL 3, SHEET C-803.
-	TION BASIN, SEE DETAIL 3, SHEET C-8
C TEMPORARY DIVERSION	DITCH, SEE DETAIL 7, SHEET C-801


- (G) TEMPORARY DIVERSION DITCH, SEE DETAIL 7, SHEET C-801
- H SUPER SILT FENCE, SEE DETAIL 4. SHEET C-801

GENERAL NOTES









KEY MAP

-


Click, Call or Tap Before You Dig 1-800-362-2764


..... -

90194

-


.....








LEGEND							
	PROJECT BOUNDARY	SNO	ļ				
	ADJ. / INTERIOR PROPERTY LINE	REVISIONS					
P/% P/%	EX. RIGHT OF WAY	1	_	_			
	EX, EASEMENT		DESC	DESIGN			
	SETBACK APPROXIMATE EX.		302	203			
	ROAD CENTERLINE	őN	1	~	╂┤	1	Н
	EX. OVERHEAD ELECTRIC	Г		_	<u> </u>	-	-
CAS	EX. GAS EX. STREAM				1 er 2005		
- management	EX. TREE LINE		-	E	TIN T	3235	8
	EX. WETLAND		3		HALFV-HORN AND ASSOCIATS, 5 N. HOPH SITTER, SUITE 200	COLUMBUS, DH 43235 PHONE, 630-487-5550	Y-HOR
	EX. WETLAND/STREAM BUFFER			2	No.	20 W	N NORE
1997 - 1997 -	EX CULTURAL EXCLUSION AREA		7	Ž	2001 HIML	8 Į	1
	EX. CULTURAL BUFFER		4	5	84		
	EX CONTOURS	L	-			_	
	EX. FLOW (DIRECTION AND SLOPE)		NOTED	i: ERS	HW		Cenc.
	PR CONTOURS		Ş,	KO BY:	84		χ θ 03 0
XKZ	PR. FLOW (DIRECTION AND SLOPE)	SCALE		OC SIGNED	DRAWN		CHECKED
	PR. GRADING AREA						
	PR GRAVEL ACCESS ROAD			RELI	MIN		,
	PR INVERTER	•		FORC			
— x — x —	PR. FENCE	L					
	LIMITS OF DISTURBANCE	⊢					
<u> </u>	WRE BACKED SILT FENCE	L					
	SUPER SILT FENCE	L					
	SILT FENCE ROCK OUTLET	L			Λ	100	
	PR. LAYDOWN AREA	L			1	for	Ē
6666266666	CONSTRUCTION ENTRANCE				-		
fs	PR. STORMWATER PIPE	ļ	2				
	PR. FILTER SOCK						
	TEMPORARY DIVERSION DITCH	ġ					
	PR. LOW WATER CROSSING SEE DETAIL 4 ON C-803				Z		
EROSION CONTROL	NOTES	L		7	DI AN	ב	
SILT FENCE WITH WIRE :	SUPPORT, SEE DETAIL 4, SHEET C-800	L		ō			
TEMPORARY STABIUZED SEE DETAIL 2, SHEET C	CONSTRUCTION ENTRANCE. -800	L		ទ	ō)	
C SILT FENCE ROCK OUTLI	ET. SEE DETAIL 1. SHEET C-800	L		0	ã		
D FILTER SOCK, SEE DETA		L		Ш	Ę	,	
	OF LAYDOWN AREAS. CONTRACTOR DISCRETION BASED ON DETAIL 3, SHEET C=803.				Ĉ	$\overline{\mathbf{S}}$	
F TEMPORARY SEDIMENTA	RON BASIN, SEE DETAIL 3, SHEET C-801	L			_	_	
C TEMPORARY DIVERSION	DITCH. SEE DETAIL 7, SHEET C-801						
() SUPER SILT FENCE, SEE	DETAIL 4, SHEET C-801.			Ω	<		
GENERAL NOTES		L			Į		
1 60% PLANS SHOW LOW WATER CROSSINGS AT ALL ROAD AREAS WITH HIGH FLOW IN 90% DESIGN, SOME LOW WATER CROSSINGS WILL BE UPGRARDED TO ELEVATED ROADS WITH CULVERTS. THIS WILL BE BASED ON THE LIKELHOOD OF WATER PONDING ON THE ROAD AND POTENTIAL FOR INJUDATION TO BACKUP INTO THE ARRAY AREA. AN ENGINEERING ANALYSIS OF THE FLOW FOR BOTH THE CULVERTS AND THE LOW WATER CROSSINGS WILL ALSO BE INCLUDED IN 90% DESIGN				HARDIN III SOLAR HARDIN COUNTY, OH			
KEY MAP			0				<i>1</i> 2 -
		-	_	01/2	1/20	222	
	оню	L		A PR 168	7540	44	1620
94194	Utilities Protection SERVICE Click, Call or Tap Before You Dig			heet C-			
	1-800-362-2764						







x x
aa
6666666666

LEGEND:

_

115

_____XX.5____

_ _ _

FS







PR. GRADING AREA

PR. INVERTER

PR. GRAVEL ACCESS ROAD









- D FILTER SOCK, SEE DETAIL 3, SHEET C-800.
- PRELIMINARY LOCATION OF LAYDOWN AREAS. SITE CONDITIONS, SEE DETAIL 3. SHEET C-803.
- (F) TEMPORARY SEDIMENTATION BASIN, SEE DETAIL 3, SHEET C-801
- (TEMPORARY DIVERSION DITCH, SEE DETAIL 7, SHEET C-801
- (H) SUPER SILT FENCE, SEE DETAIL 4. SHEET C-801,


GENERAL NOTES








C-304
















LEOEND.							
LEGEND:				L/1			
	ADJ. / IN TER			REVISIONS			
	PROPERTY L	NE		RC VI			
	EX. RIGHT O						
	EX. EASEMEN	Ĩ		the notice	0530		
	SETBACK	E.EX.		the state	8		
	ROAD CENTE	RLINE		ĝ.	- ~	Ħ	
EX 2015	EX OVERHEA	D ELECTRIC			_		
GAS GA3	EX. GAS					¥ 82	
	EX. TREE LIN	ιE			ž	ASSOCIATS.	2220 N
[content more]	EX. WETLAND					100	PHONE 630-487-5350
	EX. WETLAND BUFFER)/STREAM				S HORY I NUC	
0.0222200	EX. CULTURA	L EXCLUSION A	REA		Ē	N SOFT	5 M B
	EX. CULTURA	L BUFFER			9	ğ.	
	EX CONTOUT	₹\$					
- + 15 -	EX. FLOW (DIRECTION /	AND SLOPE)		NOTED	ERS	Į.₹	20
	PR CONTOU	RS		4		à	0 87
xx%	PR. FLOW (DIRECTION /	ND SLOPE)		SCALE	DESIGNED	RAWN	ONECKED
Parallel and a second second	PR. GRADING			<u>55</u>	18	18	10
		ACCESS ROAD					
Constant of Arthouse and Arthouse	PR INVERTE						
x x	PR. RIVERIE	R.		1		-01010	001104
	LIMITS OF DI	STURBANCE					
<u> </u>		D SILT FENCE					
	SUPER SILT						
		ROCK OUTLET			_		P
	PR. LAYDOW					Л	600
(/////////////////////////////////////		ON ENTRANCE					er fo
8200830083	PR. STORMW			e.		_	2
FS	PR. FILTER			PREPARED FOR			
	PR EARTH			PARE			
		DIVERSION DITCH	4	PRE			
	PR. LOW WA	TER CROSSING 4 ON C-803				Z	;
EROSION CONTROL					Z	PLAN	1
A SILT FENCE WITH WIRE			T C-800		<u>0</u>		
TEMPORARY STABILIZED SEE DETAIL 2, SHEET C	-800	N ENTRANCE,			S	Ō)
C SILT FENCE ROCK OUTL			00		8	<u> </u>	
D FILTER SOCK, SEE DETA					Ш	Z	
E LAYDOWN AREAS UP TO SITE CONDITIONS, SEE D	CONTRACTOR	DISCRETION BA	SED ON			00)
E TEMPORARY SEDIMENTA	TION BASIN, S	EE DETAIL 3, SH	(C=80)	∟			
C TEMPORARY DIVERSION	DITCH SEE DE	ETAIL 7, SHEET	C-801				
(SUPER SILT FENCE, SEE	DETAIL 4. SH	4EET C-801			ń	-	
GENERAL NOTES						ξΞ	
					S	S ≧	
1 60% PLANS SHOW LOW WATER CROSSINGS AT ALL ROAD AREAS WITH HIGH FLOW. IN 90% DESIGN, SOME LOW WATER CROSSINGS WILL BE UPCRADED TO ELEVATED ROADS WITH CULVERTS. THIS WILL BE BASED ON THE LIKELIHOOD OF WATER PONDING ON THE ROAD AND POTENTIAL FOR INUNDATION TO BACKUP INTO THE ARRAY AREA. AN ENGINEERING ANALYSIS OF THE FLOW FOR BOTH THE CULVERTS AND THE LOW WATER CROSSINGS WILL ALSO BE INCLUDED IN 90% DESIGN.				HARDIN III SOLAR			
KEY MAP					S S	£	
					ORIGIN		SUE
Seattle seat	States.		-H-	∟	01/2	1/20	22
-	- mail	ощо		Ľ	HA PR 168	0JEC 75404	
	-	Utilities P		Γ	SHEET	NUM	BER
0110.0	100		SERVICE p Before You Dig	1	C	30	7
and the second second		1-800-3			0	00	r E





LEGEND:

	PROJECT BOUNDARY
~ ~	ADJ. / INTERIOR PROPERTY LINE
	EX. RIGHT OF WAY
	EX, EASEMENT
	SETBACK
ACCESS & ADDRESS & ADDRESS & ADDRESS	APPROXIMATE EX. ROAD CENTERLINE
	EX. OVERHEAD ELECTRIC
	EX GAS
	EX. STREAM
and the second s	EX. TREE LINE
	EX. WETLAND EX. WETLAND/STREAM BUFFER
Second Second	EX. CULTURAL EXCLUSION AREA
	EX. CULTURAL BUFFER
	EX. CONTOURS
	EX. FLOW (DIRECTION AND SLOPE)
XX	PR. CONTOURS
x x %	PR. FLOW (DIRECTION AND SLOPE)
ADDER DEFENSE	PR GRADING AREA
	PR. GRAVEL ACCESS ROAD
	PR. INVERTER
x x	PR. FENCE
	LIMITS OF DISTURBANCE
	WRE BACKED SILT FENCE
	SUPER SILT FENCE
	SILT FENCE ROCK OUTLET
	PR LAYDOWN AREA
FXXXXXXX	CONSTRUCTION ENTRANCE
·	PR. STORWWATER PIPE
F\$	PR, FILTER SOCK
	PR EARTH BERM
,	TEMPORARY DIVERSION DITCH
	PR. LOW WATER CROSSING SEE DETAIL 4 ON C-803
EROSION CONTROL	
A SILT FENCE WITH WIRE	SUPPORT, SEE DETAIL 4, SHEET C-800
	CONSTRUCTION ENTRANCE, C-800.
	ET, SEE DETAIL 1, SHEET C-800
() FILTER SOCK, SEE DET	AIL 3, SHEET C-800.
ODCUMULTER LOCATION	


PREUMINARY LOCATION OF LAYDOWN AREAS. (E) LAYDOWN AREAS UP TO CONTRACTOR DISCRETION BASED ON SHEE CONDITIONS, SEE DETAIL 3, SHEET C-803.

(F) TEMPORARY SEDIMENTATION BASIN, SEE DETAIL 3, SHEET C-801


C TEMPORARY DIVERSION DITCH, SEE DETAIL 7, SHEET C+801


H SUPER SILT FENCE, SEE DETAIL 4. SHEET C-801


GENERAL NOTES
















LEGEND:			
	PROJECT BOUNDARY		SNOISIN
	ADJ. / INTERIOR PROPERTY LINE		REVISI
R/W R/W	EX RIGHT OF WAY		
	EX. EASEMENT		DE SICH
	SETBACK		20% 0
NAME OF A DESCRIPTION O	APPROXIMATE EX. ROAD CENTERLINE		NO
	EX. OVERHEAD ELECTRIC		
GAS GAS	EX GAS		E ta
	EX. STREAM		
F	EX. TREE LINE EX. WETLAND		
	EX. WETLAND/STREAM		
07777777777777777	BUFFER EX. CULTURAL EXCLUSION	AREA	e
	EX. CULTURAL BUFFER		E
	EX. CONTOURS		
	EX. FLOW		OTED ERS ALH CPC
	(DIRECTION AND SLOPE)		N N N
	PR. CONTOURS PR. FLOW		
XXX	(DIRECTION AND SLOPE)		SCALE DESIGNED
	PR. GRADING AREA		
	PR. GRAVEL ACCESS ROAD		PRELIMINARY
	PR, INVERTER		NOT FOR CONSTRUCTION
x x	PR. FENCE		
	LIMITS OF DISTURBANCE		
aa	WIRE BACKED SILT FENCE		
	SUPER SILT FENCE		
	SILT FENCE ROCK OUTLET		
	PR LAYDOWN AREA		or Be
	CONSTRUCTION ENTRANCE		
	PR. STORMWATER PIPE		8 – ²
f5	PR, FILTER SOCK		PREPARED FOR
<u>_</u>	PR EARTH BERM		EPA
	TEMPORARY DIVERSION DIT	CH	8
	PR: LOW WATER CROSSING SEE DETAIL 4 ON C-803		Z
EROSION CONTROL	NOTES		_, ≤
A SILT FENCE WITH WIRE	UPPORT, SEE DETAIL 4, SHI	EET C-800	
A TEMPORARY STABILIZED	CONSTRUCTION ENTRANCE.	1.5	% -
SEE DETAIL 2, SHEET C	-800. IT. SEE DETAIL 1. SHEET C-	-800.	
D FILTER SOCK, SEE DETA		1000	
PRELIMINARY LOCATION			U U N
(E) LAYDOWN AREAS UP TO SITE CONDITIONS, SEE 0	CONTRACTOR DISCRETION E	BASED ON	
F TEMPORARY SEDIMENTA		SHEET C-801	
C TEMPORARY DIVERSION	DITCH, SEE DETAIL 7. SHEET	C-801.	
H SUPER SILT FENCE, SEE		251	~
0	BEIME 4, SHEET G-001		Ľ ¥ -
GENERAL NOTES			RDIN III SOL
1 60% PLANS SHOW LOW W HIGH FLOW IN 90% DESIG	ATER CROSSINGS AT ALL RO N. SOME LOW WATER CROSS ROADS WITH CULVERTS. THIS D OF WATER PONDING ON TO IN TO BACKUP INTO THE AF THE FLOW FOR BOTH THE IS WILL ALSO BE INCLUDED	IAD AREAS WITH	S I N
BASED ON THE LIKELIHOO POTENTIAL FOR INUNDAT	D OF WATER PONDING ON THE	HE ROAD AND	
ENGINEERING ANALYSIS OF THE LOW WATER CROSSIN	THE FLOW FOR BOTH THE	IN 90% DESIGN	
KEY MAP			HARDIN III SOLAR Hardin county, oh
1	State of the local division of the local div		l
CE228 00.0			
Deal 2			ORIGINAL ISSUE
	(Centering		01/21/2022 KHA PROJECT NO
	OHIO		168754044 SHEET NUMBER
	Utilities !	Protection SERVICE	
A State of State		Tap Before You Dig	C-310
		362-2764	









LEGEND:							
	PROJECT BON	INDARY		SNS.			
	ADJ. / INTER PROPERTY LI			REVISIONS			
P/W P/W	EX. RIGHT OF			R			
	EX. EASEMEN			ŝ	DESICH		
	SETBACK			30% DESIGN	90% DC		
	APPROXIMATE ROAD CENTER	EX. RLINE			-++	┝-┼-	
	EX. OVERHEA			- N	~		
GAS GAS	EX GAS				E	¥	-
	EX STREAM	_			ō	NU ASSOCANS. PEET, SUNE 200 OH 43235	8.8
	EX. TREE LIN	E			Ĕ	8 ASSO ET, SU 4 322	HONE 630-487-555 Newshang£7-4408N CO
Contration of the second secon	EX WETLAND EX WETLAND	/STREAM			ŝ.	1 K K K K K K K K K K K K K K K K K K K	1
Concernanti	BUFFER FX CULTURA	L EXCLUSION AREA			ē.	NOTI HANLY++HORM AND ASSIDDA 7965 N. HECH STREET, SUNT COLUMBUS, OH 43235	THOME I'M
Dest test stational	EX. CULTURA		n		E	5967	o
	EX. CONTOUR				Z		
	EX_FLOW	-		8	in.	I	0
	(DIRECTION A			NOTED	BY: ERS	ЧЧ	BY CPC
	PR. CONTOUR	!S		E. AS	CSOMED	WW BY	CHECKED B
	(DIRECTION A	NO SLOPE)		SCAL	Š.	NY KO	Ŭ
ACLESCO II INVERSION	PR, GRADING	AREA					
hanne see an start	PR. GRAVEL	ACCESS ROAD		Р	RELIN	AINA	γγ
	PR. INVERTER	1			FOR CO		
x x	PR. FENCE						
	LIMITS OF DIS	STURBANCE					
<u> </u>	WRE BACKED	SILT FENCE					
	SUPER SILT	FENCE					
	SILT FENCE F	OCK OUTLET					good
<i>\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\</i>	PR. LAYDOWN	AREA					
	CONSTRUCTIO	N ENTRANCE				9	ower for
	PR. STORMW	TER PIPE		ĕ			<u>×</u>
FS	PR FILTER S	OCK		PREPARED FOR			
-0	PR EARTH B			REP			
		DIVERSION DITCH ER CROSSING I ON C-803				z	
EROSION CONTROL	NOTES				_	- PLAN	
A SILT FENCE WITH WIRE	SUPPORT, SEE	DETAIL 4. SHEET	C-800.		NOISC	٦	
B TEMPORARY STABILIZED	CONSTRUCTION	ENTRANCE.			×.	귄	
© SEE DETAIL 2, SHEET C		1. SHEET C-800			õ	Ľ	
D FILTER SOCK, SEE DETA					Ř	Ĕ	
PRELIMINARY LOCATION	OF LAYDOWN	AREAS. DISCRETION BASE	DON		ш	No	
SITE CONDITIONS, SEE (T C-801			O	
0							
G TEMPORARY DIVERSION			801				
H SUPER SILT FENCE, SEE	DETAIL 4, SH	EET C-801			AR		
GENERAL NOTES					Ъ	Ч.	
1 60% PLANS SHOW LOW W MIGH FLOW IN 90% DESIG UPCRADED TO ELEVATED BASED ON THE LIKEUHOO POTENTIAL FOR HUNDATT ENGINEERING ANALYSIS O THE LOW WATER CROSSIN	ATER CROSSING IN, SOME LOW ROADS WITH C ID OF WATER F ON TO BACKUP F THE FLOW FO GS WILL ALSO	35 AT ALL ROAD . WATER CROSSINGS ULVERTS. THIS WH ONDING ON THE F INTO THE ARRAY DR BOTH THE CUL BE INCLUDED IN S	AREAS WITH 5 WILL BE ROAD AND 7 AREA, AN VERTS AND 90% DESIGN.		HARDIN III SOLAR	HARDIN COUNTY, OF	
KEY MAP					AH		
	STORE STORE				_		
G-300 40141	and and						
			_ال		RGINA 01/21		
24	Contraction of	0000	5		A PR0	UECT	ND.
<u>eu eu</u> ,	24	OHIO Utilities Pro	tection	SI	HEET		
anone	the state	SI	ERVICE		\sim	24	4
and the state of the second	1	Click, Call or Tap B 1-800-362			C-:	31	1
	- 2%		19.24				







SOILS LEGEND	
BLOUNT SILT LOAM, END MORAINE, O TO 2 PERCENT SLOPES	Ble1A1
BLOUNT SILT LOAM, END MORAINE, 2 TO 4 PERCENT SLOPES	Ble1B1
BLOUNT SILT LOAM, GROUND MORAINE, O TO 2 PERCENT SLOPES,	Blg1A1
BLOUNT SILT LOAM. GROUND MORAINE, 2 TO 4 PERCENT SLOPES.	Blg1B1
GLYNWOOD SILT LOAM, 6 TO 12 PERCENT SLOPES,	Gwd5C2
GLYNWOOD SILT LOAM END MORAINE, 2 TO 5 PERCENT SLOPES	Gwe1B1
GLYNWOOD CLAY LOAM END MORAINE, 2 TO 6 PERCENT SLOPES	Gwe5B2
GLYNWOOD SILT LOAM GROUND MORAINE, 2 TO 6 PERCENT SLOPES	Gwg181
CLYNWOOD CLAY LOAM GROUND MORAINE, 2 TO 6 PERCENT SLOPES	Gwg5B2
GLYNWOOD CLAY LOAM, GROUND MORAINE, 6 TO 12 PERCENT SLOPES	Gwg5C2
LINWOD MUCK	ln
MCGUFFEY MUCK, MILFORD SILTY CLAY LOAM, O TO 2 PERCENT SLOPES	Mc
MILFORD SILTY CLAY LOAM. 0 TO 2 PERCENT SLOPES	Mf
MINSTER SILTY CLAY LOAM, 0 TO 1 PERCENT SLOPES	Mnl3A
MINSTER SILTY CLAY LOAM, 0 TO 1 PERCENT SLOPES	Mns3A
MORLEY CLAY LOAM, 12 TO 18 PERCENT SLOPES	MrD2
PEWAMO SILTY CLAY LOAM, 0 TO 1 PERCENT SLOPES	PkA
ROUNDHEAD MUCK	Po Ro



LEGEND:

	PROJECT BOUNDARY
10000 C To	ADJ. / IN TERIOR PROPERTY LINE
$\cdots \cdots \in \mathfrak{f} \longrightarrow \mathfrak{f} $	EX. RIGHT OF WAY
	EX. EASENENT
··· ··································	EX. TREE LINE
	SETBACK
	APPROXIMATE EX. ROAD CENTERLINE
P 34 P 34	EX. OVERHEAD ELECT
10	EX. UTILITY POLE
	EX. STREAM
The second second	EX. WETLAND
	EX. WETLAND/STREAM BUFFER
<u></u>	EX. CULTURAL EXCLU AREA
	EX. CULTURAL BUFFE
	EX. CONTOURS
	AREAS TO BE CLEARE AND GRUGGED
*********	LIMITS OF DISTURBAN
	PANEL LIMITS
	EX. DRAIN THE
	(APPROXIMATE LOCAT EX. DITCH
	LIMITS OF SOIL TYPES
	CIMITS OF SOLUTIFES

EX, TREE LINE
SETBACK
APPROXIMATE EX. ROAD CENTERLINE
EX. OVERHEAD ELECTRIC
EX. UTLITY POLE
EX. STREAM
EX. WETLAND
EX. WETLAND/STREAM BUFFER
EX. CULTURAL EXCLUSION AREA
EX. CULTURAL BUFFER
EX. CONTOURS
AREAS TO BE CLEARED AND GRUBBED
LIMITS OF DISTURBANCE
PANEL LIMITS
EX. DRAIN TILE
(APPROXIMATE LOCATION) EX. DITCH
LIMITS OF SOIL TYPES


PROTECTION/DEMOLITION NOTES


- A PROTECT IN PLACE B DEMOUSH OR REMOVE **GENERAL NOTES**
- 1. ALL EXISTING FEATURES NOT SHOWN ON THIS PLAN AND NOT SHOWN TO BE REMOVED ARE TO REMAIN.
- 2. ALL EXISTING VEGETATION WITHIN THE AREAS TO BE CLEARED AND GRUBBED SHALL BE REMOVED AS FOLLOWS:
- ALL EXISTING SHRUBS SHALL BE CUT FLUSH WITH THE GROUND, EXCEPT IN AREAS WHERE ROOT STRUCTURES WILL INTERFERE WITH INSTALLATION OF STRUCTURAL FOUNDATIONS: IN SUCH CASES, REMOVE ALL ROOTS. 2.1.
- 2.2 ALL EXISTING GRASSES SHALL BE MOWED AS SHORT AS POSSIBLE.
- 2.3. IN AREAS OF GRADING, ALL VECETATION SHALL BE CLEARED AND GRUBBED PER THE RECOMMENDATIONS PROVIDED IN THE PROJECT GEOTECHNICAL REPORT.
- 2.4. IN AREAS OF EXISTING ACRICULTURAL LAND, ALL CROPS SHALL BE REMOVED AND SOLIS, SHALL BE OFSKED, CULIVATED AND ROLLED, AS NEEDED, TO AND IN ESTABLISHMENT OF PERMANENT VEGETATION. REFER TO LANDSCAPE PLAN.
- DAMAGE TO ANY EXISTING UTILITIES AND SERVICES TO REMAIN SHALL BE REPARED AND/OR REPLACED IN KIND AT CONTRACTOR'S OWN EXPENSE.
- 4 DUST CONTROL MEASURES SHALL BE IMPLEMENTED DURING DEMOLITION INCLUDING BUT NOT LIMITED TO WATERING DIRT ACCESS ROADS.
- DRAIN TITLE/DITCH LOCATIONS SHOWN ARE APPROXIMATE AND BASED ON INFORMATION PROVIDED BY THE OWNER. TO THE EXTENT POSSIBLE, DRAINTILE SHALL REMAIN IN PLACE DURING CONSTRUCTION
- 6. TREE REMOVAL SHALL BE LIMITED DURING PROJECT CONSTRUCTION AND BASED ON ENGINEER'S APPROVAL. TREE RPOTECTION FENCING SHOULD BE INSTALLED AS NECESSARY.


R

1-800-362-2764

OHIO









LEGEND	
	PROJECT BOUNDARY
	ADJ / INTERIOR PROPERTY LINE
	EX. RIGHT OF WAY
	EX. EASEMENT
$= (1 - 1)^{-1} ($	EX. TREE LINE
	SETBACK
	APPROXIMATE EX.
	EX. OVERHEAD ELECTRIC
197	EX UTILITY POLE
(and 1) ((and 1) ((and 1)) ((a))	EX. STREAM
	EX WETLAND
	EX WETLAND/STREAM BUFFER
[272252222]	EX. CULTURAL EXCLUSION AREA
	EX. CULTURAL BUFFER
	EX. CONTOURS
	AREAS TO BE CLEARED AND GRUBBED
	LIMITS OF DISTURBANCE
	PANEL LIMITS
	EX. DRAIN TILE (APPROXIMATE LOCATION)
\rightarrow \rightarrow $-$	EX, DITCH
	LIMITS OF SOIL TYPES


PROTECTION/DEMOLITION NOTES

- A PROTECT IN PLACE
- B DEMOLISH OR REMOVE
- GENERAL NOTES
- ALL EXISTING FEATURES NOT SHOWN ON THIS PLAN AND NOT SHOWN TO BE REMOVED ARE TO REMAIN
- 2. ALL EXISTING VEGETATION WITHIN THE AREAS TO BE CLEARED AND GRUBBED SHALL BE REMOVED AS FOLLOWS:
- ALL EXISTING SHRUBS SHALL BE CUT FLUSH WITH THE GROUND, EXCEPT IN AREAS WHERE ROOT STRUCTURES WILL INTERFERE WITH INSTALLATION OF STRUCTURAL FOUNDATIONS; IN SUCH CASES, REMOVE ALL ROOTS.
- 2.2. ALL EXISTING GRASSES SHALL BE MOWED AS SHORT AS POSSIBLE.
- 2 3. IN AREAS OF GRADING, ALL VEGETATION SHALL BE CLEARED AND GRUBBED PER THE RECOMMENDATIONS PROVIDED IN THE PROJECT GEOTECHNICAL REPORT.
- 2.4. IN AREAS OF EXISTING AGRICULTURAL LAND, ALL CROPS SHALL BE REMOVED AND SOLL SHALL BE DISKED, CULTWATED AND FOLLED, AS NEEDED. TO AND IN ESTABLISHMENT OF PERMANENT VEGETATION REFER TO LANDSCAPE PLAN.
- 3. DAMAGE TO ANY EXISTING UTILITIES AND SERVICES TO REMAIN SHALL BE REPAIRED AND/OR REPLACED IN KIND AT CONTRACTOR'S OWN EXPENSE.
- DUST CONTROL MEASURES SHALL BE INPLEMENTED DURING DEMOLITION INCLUDING BUT NOT LIMITED TO WATERING DIRT ACCESS R DADS.
- DRAIN TITLE/DITCH LOCATIONS SHOWN ARE APPROXIMATE AND BASED ON INFORMATION PROVIDED BY THE OWNER. TO THE EXTENT POSSIBLE, DRAINTLE SHALL REMAIN IN PLACE DURING CONSTRUCTION
- 6. TREE REMOVAL SHALL BE LIMITED DURING PROJECT CONSTRUCTION AND BASED ON ENGINEER'S APPROVAL. TREE RPOTECTION FENCING SHOULD BE INSTALLED AS NECESSARY.











	PROJECT BOUNDARY
	ADJ. / INTERIOR PROPERTY LINE
	EX. RIGHT OF WAY
	EX, EASEMENT
	EX. TREE LINE
	SETBACK
	APPROXIMATE EX.
	EX. OVERHEAD ELECTRIC
10,741	EX. UTUTY POLE
	EX. STREAM
	EX. WETLAND
	EX. WETLAND/STREAM BUFFER
1.	EX. CULTURAL EXCLUSIO AREA
	EX. CULTURAL BUFFER
	EX. CONTOURS
	AREAS TO BE CLEARED AND GRUBBED
	LINITS OF DISTURBANCE
	PANEL LIMITS
	EX. ORAIN TILE
	 (APPROXIMATE LOCATION EX. DITCH
	LIMITS OF SOIL TYPES
	0.000 0.000 0.000

Α

- B DEMOLISH OR REMOVE.
- GENERAL NOTES
- ALL EXISTING FEATURES NOT SHOWN ON THIS PLAN AND NOT SHOWN TO BE REMOVED ARE TO REMAIN.
- 2. ALL EXISTING VECETATION WITHIN THE AREAS TO BE CLEARED AND GRUBBED SHALL BE REMOVED AS FOLLOWS:
- 2.1. ALL EXISTING SHRUBS SHALL BE CUT FLUSH WITH THE GROUND, EXCEPT IN AREAS WHERE ROOT STRUCTURES WILL INTERFERE WITH INSTALLATION OF STRUCTURE FOUNDATIONS, IN SUCH CASES, REMOVE ALL ROOTS.
- 2.2. ALL EXISTING GRASSES SHALL BE MOWED AS SHORT AS POSSIBLE.
- 2.3. IN AREAS OF GRADING, ALL VECETATION SHALL BE CLEARED AND GRUBBED PER THE RECOMMENDATIONS PROVIDED IN THE PROJECT GEOTECHNICAL REPORT.
- 2.4. IN AREAS OF EXISTING AGRICULTURAL LAND, ALL CROPS SHALL BE REMOVED AND SOIL SHALL BE DISKED, CULTIVATED AND ROLLED, AS NEEDED, TO AD IN ESTABLISHMENT OF PERMANENT VEGETATION. REFER TO LANDSCAPE PLAN.
- 3. DAMAGE TO ANY EXISTING UTILITIES AND SERVICES TO REMAIN SHALL BE REPAIRED AND/OR REPLACED IN KIND AT CONTRACTOR'S OWN EXPENSE.
- DUST CONTROL MEASURES SHALL BE IMPLEMENTED DURING DEMOLITION INCLUDING BUT NOT LIMITED TO WATERING DIRT ACCESS ROADS;
- DRAIN TITLE/DITCH LOCATIONS SHOWN ARE APPROXIMATE AND BASED ON INFORMATION PROVIDED BY THE OWNER TO THE EXTENT POSSIBLE, DRAINTILE SHALL REMAIN IN PLACE DURING CONSTRUCTION.
- 6. TREE REMOVAL SHALL BE LIMITED DURING PROJECT CONSTRUCTION AND BASED ON ENCINEER'S APPROVAL. TREE RPDTECTION FENCING SHOULD BE INSTALLED AS NECESSARY.










	ADJ. / IN TERIOR
	PROPERTY LINE
	EX. RIGHT OF WAY
	EX. EASEMENT
	EX. TREE LINE
- 503	- SETBACK
	ROAD CENTERLINE
9.36	EX. UTILITY POLE
	EX STREAM
	EX, WETLAND
	EX. WETLAND/STREAM BUFFER
	EX. CULTURAL EXCLUSIO
	EX. CULTURAL BUFFER
	EX. CONTOURS
	AREAS TO BE CLEARED AND GRUBBED
	LIMITS OF DISTURBANCE
	- PANEL LIMITS
	EX. DRAIN TILE (APPROXIMATE LOCATION EX. DITCH
	UNITS OF SOIL TYPES
PROTECTION/DE	
	E. GVE
A PROTECT IN PLACE B DEMOLISH OR REM GENERAL NOTES	e. Gve S
A PROTECT IN PLACE B DEMOLISH OR REM GENERAL NOTES ALL EXISTING FEATURES INT SHOWN TO BE REMO MLL EXISTING VECETATION LEARED AND GRUBBED	E OVE S NOT SHOWN ON THIS PLAN AND VED ARE TO REMAIN L WITHIN THE AREAS TO BE SHALL BE REMOVED AS FOLLOW
A PROTECT IN PLACE B DEMOLISH OR REM GENERAL NOTES GENERAL NOTES SHOWN TO BE REMO ALL EXISTING VECETATION LEARED AND GRUBBED ALL EXISTING SHRUBS GROUND, EXCEPT IN MUL INTERFERE WITH FOUNDATIONS, IN SUM	ENDT SHOWN ON THIS PLAN AND S NOT SHOWN ON THIS PLAN AND VED ARE TO REMAIN. IN WITHIN THE AREAS TO BE SHALL BE CREADED AS FOLLOW S SHALL BE CREADED AS FOLLOW AREAS WHERE ROOT STRUCTURI INSTALLATION OF STRUCTURI INSTALLATION OF STRUCTURI INSTALLATION OF STRUCTURI INSTALLATION OF STRUCTURI H CASES. REMOVE ALL ROOTS.
A PROTECT IN PLACE B DEMOLISH OR REM GENERAL NOTES ALL EXISTING FEATURES I NOT SHOWN TO BE REMO ALL EXISTING VECETATION CLARED AND GRUBBED ALL EXISTING SHRUBS GROUND, EXCEPT IN MUL INTERFER MUL INTERFER	E OVE S NOT SHOWN ON THIS PLAN AND VED ARE TO REMAIN. I WITHIN THE AREAS TO BE SHALL BE CUT FLUSH WITH IT AREAS WHERE ROOT STRUCTURAL SHALL BE CUT FLUSH WITH IT NOTALATION OF STRUCTURAL CH CASES, REMOVE ALL ROOTS. IS SHALL BE MOWED AS SHORT
A PROTECT IN PLACE B DEMOLISH OR REM GENERAL NOTES ALL EXISTING FEATURES I NOT SHOWN TO BE REMO ALL EXISTING FEATURES GROUND, EXCEPT IN I MLL INTERFERE WITH FOUNDATIONS; IN SUR ALL EXISTING GRASSE POSSIBLE, IN AREAS OF GRADIN CLEARED AND GRUBB PROVIDED IN THE PRE-	E OVE. S NOT SHOWN ON THIS PLAN AND VED ARE TO REMAIN. IN WITHIN THE AREAS TO BE SHALL BE CHUT FLUSH WITH TI AREAS WHERE ROOT STRUCTURAL CH CASES. REMOVE ALL ROOTS. IS SHALL BE MOWED AS SHORT G. ALL VEGETATION SHALL BE ED PER THE RECOMMENDATIONS DACT GEOTECHINICAL REPORT.
A PROTECT IN PLACE DEMOLISH OR REM GENERAL NOTES ALL EXISTING FEATURES I NOT SHOWN TO BE REMO ALL EXISTING VECETATION ALL EXISTING CHECETATION ALL EXISTING CHECETATION WILL INTERFERE WITH FOUNDATIONS; IN SUI 2. ALL EXISTING GRASSE POSSIBLE. 3. IN AREAS OF GRADIN CLEARED AND GRUBB PROVIDED IN THE PRICE	E OVE. S NOT SHOWN ON THIS PLAN AND VED ARE TO REMAIN. IN WITHIN THE AREAS TO BE SHALL BE CHUT FLUSH WITH TI AREAS WHERE ROOT STRUCTURAL CH CASES. REMOVE ALL ROOTS. IS SHALL BE MOWED AS SHORT G. ALL VEGETATION SHALL BE ED PER THE RECOMMENDATIONS DACT GEOTECHINICAL REPORT.
A PROTECT IN PLACE B DEMOLISH OR REM GENERAL NOTES GENERAL NOTES GENERAL NOTES SHOWN TO BE REMO ALL EXISTING FEATURES IN ALL EXISTING VECETATION CLEARED AND GRUBBED FOUNDATIONS; IN SUR ALL EXISTING GRASSE POSSIBLE. IN AREAS OF CRADIN CLEARED AND GRUBB PROVIDED IN THE PRE IN AREAS OF EXISTING IN AREAS OF EXISTING	E OVE S NOT SHOWN ON THIS PLAN AND VED ARE TO REMAIN I WITHIN THE AREAS TO BE SHALL BE CREAVED AS FOLLOW S SHALL BE CREATED AS FOLLOW INSTALLATION OF STRUCTURI INSTALLATION OF STRUCTURI INSTALLATION OF STRUCTURI INSTALLATION OF STRUCTURI C CASES. REMOVE ALL ROOTS. IS SHALL BE MOWED AS SHORT G. ALL VEGETATION SHALL BE ED PER THE RECOMMENDATIONS OMECT GEOTECHNICAL REPORT. G AGRICULTURAL LAND. ALL CR AND SOL SHALL BE DISKED. ED ASIL SHALL BE ONSKED. IED ASIL SHALL BE ONSKED. IED ASIL SHALL BE ON SHALL OF INTERNATION. REMANENT VEGETATION. REFER
A PROTECT IN PLACE B DEMOLISH OR REM GENERAL NOTES ALL EXISTING FEATURES I NOT SHOWN TO BE REMO ALL EXISTING VEGETATION CLEARED AND GRUBBED ALL EXISTING VEGETATION CLEARED AND GRUBBED ALL EXISTING GRADEN FOUNDATIONS, IN SUR 2. ALL EXISTING GRASSE POSSIBLE. 3. IN AREAS OF GRADIN CLEARED AND GRUBB PROVIDED IN THE PRI SHALL BE REMOVED J ULTIVATED AND ROU ESTABLISHIGHT OF PLANOSCAPE PLAN. DAMAGE TD ANY EXISTINI REMAIN SHALL BE REMOVED J CONTRACTOR'S OWN EXPI DUST CONTROL MEASURE DEMOLTION INCLUDING BI ACCESS ROADS.	CVE. S NOT SHOWN ON THIS PLAN AND VED ARE TO REMAIN. I WITHIN THE AREAS TO BE. SHALL BE REMOVED AS FOLLOW S SHALL BE CUT FLUSH WITH TI REASS WHERE ROOT STRUCTURAL INSTALLATION OF STRUCTURAL ROOTS. INSTALLATION OF STRUCTURAL INSTALLATION OF STRUCTURAL INSTALLATION OF STRUCTURAL INSTALLATION OF STRUCTURAL CASES, REMOVE ALL ROOTS. INSTALL BE WOWED AS SHORT G. ALL VEGETATION SHALL BE ED FER THE RECOMMENDATIONS OLECT GEOTECHNICAL REPORT. INSTALLATION ALL CR AND SOIL SHALL BE OSKED. INSTALLATION. REFER G. UTILITIES AND SERVICES TO RED AND/OR REPLACED IN KING INST. S SHALL BE INPLEMENTED DURAL
A PROTECT IN PLACE B DEMOLISH OR REM GENERAL NOTES ALL EXISTING FEATURES I NOT SHOWN TO BE REMO ALL EXISTING VEGETATION CLEARED AND GRUBBED ALL EXISTING VEGETATION CLEARED AND GRUBBED ALL EXISTING GRADEN FOUNDATIONS, IN SUR 2. ALL EXISTING GRASSE POSSIBLE. 3. IN AREAS OF GRADIN CLEARED AND GRUBB PROVIDED IN THE PRI SHALL BE REMOVED J ULTIVATED AND ROU ESTABLISHIGHT OF PLANOSCAPE PLAN. DAMAGE TD ANY EXISTINI REMAIN SHALL BE REMOVED J CONTRACTOR'S OWN EXPI DUST CONTROL MEASURE DEMOLTION INCLUDING BI ACCESS ROADS.	COVE S NOT SHOWN ON THIS PLAN AND VED ARE TO REMAIN I WITHIN THE AREAS TO BE SHALL BE REMOVED AS FOLLOW S SHALL BE CUIFILISH WITH T REASS WHERE ROOT STRUCTURAL INSTALLATION OF STRUCTURAL INSTALLATION OF STRUCTURAL INSTALLATION OF STRUCTURAL C ASSE. REMOVE ALL ROOTS S SHALL BE MOWED AS SHORT G. ALL VEGETATION SHALL BE ED PER THE RECOMMENDATION G. CARGULUTURAL LAND, ALL OF AND SOL SHALL BE ONSKED LED. AS NEEDED, TO AD IN REMANENT VEGETATION, REFER G UTILITIES AND SERVICES TO EED AND/OR REPLACED IN KINE INSE.



2

6









•	0.253
	ADJ / INTERIOR PROPERTY LINE
	EX. RIGHT OF WAY
	EX EASEMENT
and the second second second	EX, TREE LINE
	SETBACK
	APPROXIMATE EX. ROAD CENTERLINE
	EX. OVERHEAD ELECTRIC
10-	EX. UTILITY POLE
	- EX STREAM
	EX. WETLAND
	EX WETLAND/STREAM
	EX_ CULTURAL EXCLUSION
	EX. CONTOURS
	AREAS TO BE CLEARED AND GRUBBED
	LIMITS OF DISTURBANCE
	- PANEL LIMITS
	EX. DRAIN TILE (APPROXIMATE LOCATION)
	EX. DITCH
	LIMITS OF SOIL TYPES
PROTECTION/DE	MOLITION NOTES
A PROTECT IN PLAC	
B DEMOLISH OR REA	IOVE.
GENERAL NOTE	S
ALL EXISTING FEATURES NOT SHOWN TO BE REMO	NOT SHOWN ON THIS PLAN AND
ALL EXISTING VEGETATION	N WITHIN THE AREAS TO BE SHALL BE REMOVED AS FOLLOWS
1. ALL EXISTING SHRUB GROUND, EXCEPT IN WILL INTERFERE WITH FOUNDATIONS: IN SU	S SHALL BE CUT FLUSH WITH TH AREAS WHERE ROOT STRUCTURE INSTALLATION OF STRUCTURAL CH CASES, REMOVE ALL ROOTS.
2. ALL EXISTING GRASS	ES SHALL BE MOWED AS SHORT
	IC, ALL VEGETATION SHALL BE BED PER THE RECOMMENDATIONS OJECT GEOTECHNICAL REPORT.
4. IN AREAS OF EXISTIN SHALL BE REMOVED CULTIVATED AND ROI ESTABLISHMENT OF F LANDSCAPE PLAN.	IG AGRICULTURAL LAND, ALL CRO AND SOIL SHALL BE DISKED, LLED, AS NEEDED, TO AID IN PERMANENT VEGETATION. REFER
	IG UTILITIES AND SERVICES TO

- 3. REMAIN SHALL BE REPARED AND/OR REPLACED IN KIND AT CONTRACTOR'S OWN EXPENSE.
- DUST CONTROL MEASURES SHALL BE IMPLEMENTED DURING DEMOLITION INCLUDING BUT NOT LIMITED TO WATERING DIRT ACCESS ROADS.
- DRAIN TITLE/DITCH LOCATIONS SHOWN ARE APPROXIMATE AND BASED ON INFORMATION PROVIDED BY THE OWNER TO THE EXTENT POSSIBLE, DRAINTILE SHALL REMAIN IN PLACE DURING CONSTRUCTION.
- TREE REMOVAL SHALL BE LIMITED DURING PROJECT CONSTRUCTION AND BASED ON ENGINEER'S APPROVAL. TREE RPOTECTION FENCING SHOULD BE INSTALLED AS NECESSARY.











LEGEND	
	PROJECT BOUNDARY ADJ / INTERIOR PROPERTY LINE
	EX. RIGHT OF WAY
	EX. EASEMENT
1000000000000000000000	EX. TREE LINE
	SETBACK
	APPROXIMATE EX. ROAD CENTERLINE
	EX. OVERHEAD ELECTRIC
20	EX. UTILITY POLE
	EX. STREAM
Et al a ser a s	EX, WETLAND
	EX. WETLAND/STREAM BUFFER
[27/2002/2013]	EX. CULTURAL EXCLUSION AREA
	EX CULTURAL BUFFER
	EX CONTOURS
	AREAS TO BE CLEARED AND GRUBBED
	UNITS OF DISTURBANCE
	PANEL LIMITS
	EX. ORAIN TILE (APPROXIMATE LOCATION)
	EX. DITCH
	LIMITS OF SOIL TYPES
PROTECTION/DEMO	LITION NOTES
I DEMOLISH OR REMOVE.	

- B DEMOLISH OR REMOVE
- GENERAL NOTES
- ALL EXISTING FEATURES NOT SHOWN ON THIS PLAN AND NOT SHOWN TO BE REMOVED ARE TO REMAIN
- 2. ALL EXISTING VEGETATION WITHIN THE AREAS TO BE CLEARED AND GRUBBED SHALL BE REMOVED AS FOLLOWS:
- 21. ALL EXISTING SHRUBS SHALL BE CUT FLUSH WITH THE GROUND, EXCEPT IN AREAS WHERE ROOT STRUCTURES WILL INTERFERE WITH INSTALLATION OF STRUCTURAL FOUNDATIONS; IN SUCH CASES, REMOVE ALL ROOTS.
- 2.2. ALL EXISTING GRASSES SHALL BE MOWED AS SHORT AS POSSIBLE.
- 2.3. IN AREAS OF GRADING, ALL VEGETATION SHALL BE CLEARED AND GRUBBED PER THE RECOMMENDATIONS PROVIDED IN THE PROJECT GEOTECHNICAL REPORT.
- 2.4. IN AREAS OF EXISTING AGRICULTURAL LAND, ALL CROPS SHALL BE REMOVED AND SOIL SHALL BE DISKED, CULTIVATED AND ROLLED, AS NEEDED, TO AID IN ESTABLISHMENT OF PERMANENT VEGETATION. REFER TO LANDSCAPE PLAN.
- DAMAGE TO ANY EXISTING UTILITIES AND SERVICES TO REMAIN SHALL BE REPAIRED AND/OR REPLACED IN KIND AT CONTRACTOR'S OWN EXPENSE.
- DUST CONTROL MEASURES SHALL BE IMPLEMENTED DURING DEMOLITION INCLUDING BUT NOT LIMITED TO WATERING DIRT ACCESS ROADS.
- DRAIN TITLE/DITCH LOCATIONS SHOWN ARE APPROXIMATE AND BASED ON INFORMATION PROVIDED BY THE OWNER TO THE EXTENT POSSIBLE, DRAINTILE SHALL REMAIN IN PLACE DURING CONSTRUCTION.
- TREE REMOVAL SHALL BE LIMITED DURING PROJECT CONSTRUCTION AND BASED ON ENGINEER'S APPROVAL. TREE RPOTECTION FENCING SHOULD BE INSTALLED AS NECESSARY.

╷┌╀










	PROJECT BOUNDARY
	ADJ. / INTERIOR PROPERTY LINE
	EX. RIGHT OF WAY
~	EX EASEMENT
(1+1) = (1+1) + (1+1) = (1+1) + (1+1	EX. TREE LINE
	SETBACK
and a support of the support	APPROXIMATE EX
	EX. OVERHEAD ELECTRIC
101	EX. UTILITY POLE
	EX: STREAM
State and	EX. WETLAND
	EX. WETLAND/STREAM OUFFER
1999 - 1997 (1997)	EX. CULTURAL EXCLUSION AREA
	EX CULTURAL BUFFER
	EX, CONTOURS
	AREAS TO BE CLEARED AND GRUBBED
	LIMITS OF DISTURBANCE
	PANEL LIMITS
	EX. ORAIN TILE (APPROXIMATE LOCATION)
	EX. DITCH
	LIMITS OF SOIL TYPES


PROTECTION/DEMOLITION NOTES

- A PROTECT IN PLACE.
- B DEMOLISH OR REMOVE
- GENERAL NOTES
- 1. ALL EXISTING FEATURES NOT SHOWN ON THIS PLAN AND NOT SHOWN TO BE REMOVED ARE TO REMAIN
- 2. ALL EXISTING VEGETATION WITHIN THE AREAS TO BE CLEARED AND GRUBBED SHALL BE REMOVED AS FOLLOWS:
- ALL EXISTING SHRUBS SHALL BE CUT FLUSH WITH THE CROUND, EXCEPT IN AREAS WHERE ROOT STRUCTURES WILL INTERFERE WITH INSTALLATION OF STRUCTURAL FOUNDATIONS; IN SUCH CASES, REMOVE ALL ROOTS. 21.
- 2.2. ALL EXISTING GRASSES SHALL BE MOWED AS SHORT AS POSSIBLE.
- 2.3. IN AREAS OF GRADING, ALL VEGETATION SHALL BE CLEARED AND GRUBBED PER THE RECOMMENDATIONS PROVIDED IN THE PROJECT GEOTECHNICAL REPORT.
- 2.4. IN AREAS OF EXISTING AGRICULTURAL LAND, ALL CROPS SHALL BE REMOVED AND SOL SHALL BE DISKED, CULTIVATED AND ROLLED, AS NEEDED, TO AID IN ESTABLISHMENT OF PERMANENT VEGETATION. REFER TO LANDSCAPE PLAN.
- DAMAGE TO ANY EXISTING UTILITIES AND SERVICES TO REMAIN SHALL BE REPAIRED AND/OR REPLACED IN KIND AT CONTRACTOR'S OWN EXPENSE.
- DUST CONTROL MEASURES SHALL BE IMPLEMENTED DURING DEMOLITION INCLUDING BUT NOT UMITED TO WATERING DIRT ACCESS ROADS.
- DRAIN TITLE/DITCH LOCATIONS SHOWN ARE APPROXIMATE AND BASED ON INFORMATION PROVIDED BY THE OWNER. TO THE EXTENT POSSIBLE, DRAINTILE SHALL REMAIN IN PLACE DURING CONSTRUCTION.
- 6 TREE REMOVAL SHALL BE UMITED DURING PROJECT CONSTRUCTION AND BASED ON ENGINEER'S APPROVAL. TREE RPOTECTION FENCING SHOULD BE INSTALLED AS NECESSARY.

t t









	PROJECT BOUNDARY
	ADJ. / INTERIOR PROPERTY LINE
$(-1) = (1, 2, 2, \cdots, 2, 2, \cdots,$	EX RIGHT OF WAY
And many many page 1988 many	EX. EASEMENT
NO DATE OF A DESCRIPTION OF A	EX. TREE LINE
	SETBACK
	APPROXIMATE EX. ROAD CENTERUNE
10 M 10 M	EX. OVERHEAD ELECTRIC
-525	EX. UTILITY POLE
	EX. STREAM
1.	EX. WETLAND
	EX. WETLAND/STREAM BUFFER
[01022322220]	EX. CULTURAL EXCLUSION
	EX. CULTURAL BUFFER
	EX. CONTOURS
	AREAS TO BE CLEARED AND GRUBBED
	LIMITS OF DISTURBANCE
	PANEL LIMITS
name solute elevant detries deland triate	EX, DRAIN TILE
	(APPROXIMATE LOCATION)
	EX. DITCH
	UMITS OF SOIL TYPES

PROTECTION/DEMOLITION NOTES

A PROTECT IN PLACE. B DEMOLISH OR REMOVE.

GENERAL NOTES

- 1. ALL EXISTING FEATURES NOT SHOWN ON THIS PLAN AND NOT SHOWN TO BE REMOVED ARE TO REMAIN...
- 2. ALL EXISTING VEGETATION WITHIN THE AREAS TO BE CLEARED AND GRUBBED SHALL BE REMOVED AS FOLLOWS:
- 2.1. ALL EXISTING SHRUBS SHALL BE CUT FLUSH WITH THE GROUND, EXCEPT IN AREAS WHERE ROOT STRUCTURES WILL INTERFERE WITH INSTALLATION OF STRUCTURAL FOUNDATIONS; IN SUCH CASES, REMOVE ALL ROOTS.
- 2.2. ALL EXISTING GRASSES SHALL BE MOWED AS SHORT AS POSSIBLE
- 2.3. IN AREAS OF GRADING, ALL VEGETATION SHALL BE CLEARED AND GRUBBED PER THE RECOMMENDATIONS PROVIDED IN THE PROJECT GEOTECHNICAL REPORT.
- 2.4. IN AREAS OF EXISTING AGRICULTURAL LAND, ALL CROPS SHALL BE REMOVED AND SOIL SHALL BE DISKED, CULTIVATED AND ROLLED, AS NEEDED, TO AID IN ESTABUSHIENT OF PERMANENT VEGETATION REFER TO LANDSCAPE PLAN.
- 3 DAMAGE TO ANY EXISTING UTILITIES AND SERVICES TO REMAIN SHALL BE REPAIRED AND/OR REPLACED IN KIND AT CONTRACTOR'S OWN EXPENSE.
- 4. DUST CONTROL MEASURES SHALL BE IMPLEMENTED DURING DEMOLITION INCLUDING BUT NOT LIMITED TO WATERING DIRT ACCESS ROADS.
- DRAIN THE/DITCH LOCATIONS SHOWN ARE APPROXIMATE AND BASED ON INFORMATION PROVIDED BY THE OWNER TO THE EXTENT POSSIBLE, DRAINTILE SHALL REMAIN IN PLACE DURING CONSTRUCTION.
- 6. TREE REMOVAL SHALL BE LIMITED DURING PROJECT CONSTRUCTION AND BASED ON ENGINEER'S APPROVAL. TREE INPOTECTION FENCING SHOULD BE INSTALLED AS NECESSARY


ОШО






JOX DESICH

- ~ ·





	PROJECT BOUNDARY
	ADJ. / INTERIOR PROPERTY LINE
	EX. RIGHT OF WAY
	EX, EASEMENT
$(1,2)_{ij}(2$	EX, TREE LINE
	SETBACK
	APPROXIMATE EX. ROAD CENTERLINE
	EX OVERHEAD ELECTRIC
-O+	EX. UTILITY POLE
	EX, STREAM
	EX. WETLAND
	EX: WETLAND/STREAM BUFFER
0.000000000	EX. CULTURAL EXCLUSION AREA
	EX. CULTURAL BUFFER
	EX CONTOURS
	AREAS TO BE CLEARED AND GRUBBED
	UNITS OF DISTURBANCE
	PANEL LIMITS
	EX. DRAIN THE (APPROXIMATE LOCATION)
	EX. DITCH
	LIMITS OF SOIL TYPES


PROTECTION/DEMOLITION NOTES


A PROTECT IN PLACE. B DEMOLISH OR REMOVE GENERAL NOTES

- 1. ALL EXISTING FEATURES NOT SHOWN ON THIS PLAN AND NOT SHOWN TO BE REMOVED ARE TO REMAIN
- 2. ALL EXISTING VEGETATION WITHIN THE AREAS TO BE CLEARED AND GRUBBED SHALL BE REMOVED AS FOLLOWS:
- 2.1. ALL EXISTING SHRUBS SHALL BE CUT FLUSH WITH THE GROUND, EXCEPT IN AREAS WHERE ROOT STRUCTURES WILL INTERFERE WITH INSTALLATION OF STRUCTURAL FOUNDATIONS: IN SUCH CASES, REMOVE ALL ROOTS.
- 2.2. ALL EXISTING GRASSES SHALL BE MOWED AS SHORT AS POSSIBLE.
- IN AREAS OF GRADING, ALL VEGETATION SHALL BE CLEARED AND GRUBBED PER THE RECOMMENDATIONS PROVIDED IN THE PROJECT GEOTECHNICAL REPORT 2.3.
- IN AREAS OF EXISTING AGRICULTURAL LAND, ALL CROPS SMALL BE REMOVED AND SOLL SMALL BE DISKED, OULTWATED AND ROLED, AS NEEDD, TO AND IN ESTABLISHMENT OF PERMANENT VEGETATION. REFER TO LANDSCAPE PLAN. 24.
- 3. DAMAGE TO ANY EXISTING UTILITIES AND SERVICES TO REMAIN SHALL BE REPAIRED AND/OR REPLACED IN KIND AT CONTRACTOR'S OWN EXPENSE.
- DUST CONTROL MEASURES SHALL BE IMPLEMENTED DURING DEMOLITION INCLUDING BUT NOT LIMITED TO WATERING DIRT ACCESS ROADS.
- 5. DRAIN TITLE/DITCH LOCATIONS SHOWN ARE APPROXIMATE AND BASED ON INFORMATION PROVIDED BY THE OWNER. TO THE EXTENT POSSIBLE, DRAINTLE SHALL REMAIN IN PLACE DURING CONSTRUCTION
- 6. TREE REMOVAL SHALL BE LIMITED DURING PROJECT CONSTRUCTION AND BASED ON ENGINEER'S APPROVAL. TREE RPOTECTION FENCING SHOULD BE INSTALLED AS NECESSARY.

0











	PROJECT BOUNDARY
	AD J. / IN TERIOR
	PROPERTY LINE
	EX. RIGHT OF WAY
	EX. EASEMENT
Address and the solution of the	EX. TREE LINE
	SETBACK
	APPROXIMATE EX. ROAD CENTERLINE
Is at Is at	EX. OVERHEAD ELECTRIC
0	EX UTILITY POLE
	EX. STREAM
[maximum marked]	EX WETLAND
	EX. WETLAND /STREAM
210000000	EX. CULTURAL EXCLUSION AREA
	EX. CULTURAL BUFFER
	EX. CONTOURS
	AREAS TO BE CLEARED AND GRUBBED
	LIMITS OF DISTURBANCE
	PANEL LIMITS
and the local set of the	EX. DRAIN TILE
	(APPROXIMATE LOCATION)
	EX. DITCH
	LIMITS OF SOL TYPES

PROTECTION/DEMOLITION NOTES


- A PROTECT IN PLACE
- B DEMOLISH OR REMOVE


GENERAL NOTES


- ALL EXISTING FEATURES NOT SHOWN ON THIS PLAN AND NOT SHOWN TO BE REMOVED ARE TO REMAIN.
- 2 ALL EXISTING VEGETATION WITHIN THE AREAS TO BE CLEARED AND GRUBBED SHALL BE REMOVED AS FOLLOWS:
- ALL EXISTING SHRUBS SHALL BE CUT FLUSH WITH THE CROUND, EXCEPT IN AREAS WHERE ROOT STRUCTURES WILL INTERFERE WITH INSTALLATION OF STRUCTURAL FOUNDATIONS, IN SUCH CASES, REMOVE ALL ROOTS 21.
- 2.2. ALL EXISTING GRASSES SHALL BE MOWED AS BHORT AS POSSIBLE
- IN AREAS OF GRADING, ALL VEGETATION SHALL BE CLEARED AND GRUBBED PER THE RECOMMENDATIONS PROVIDED IN THE PROJECT GEOTECHNICAL REPORT. 2.3.
- IN AREAS OF EXISTING AGRICULTURAL LAND. ALL CROPS SHALL BE REMOVED AND SOIL SHALL BE DISKED. OLITIVATED AND ROLEO, AS NEEDED, TO AID IN ESTADLISHMENT OF PERMANENT VEGETATION. REFER TO LANDSCAPE PLAN. 24
- 3 DAMAGE TO ANY EXISTING UTILITIES AND SERVICES TO REMAIN SHALL BE REPAIRED AND/OR REPLACED IN KIND AT CONTRACTOR'S OWN EXPENSE.
- DUST CONTROL MEASURES SHALL BE IMPLEMENTED DURING DEMOLITION INCLUDING BUT NOT UMITED TO WATERING DIRT ACCESS ROADS.
- ORAIN TITLE/DITCH LOCATIONS SHOWN ARE APPROXIMATE AND BASED ON INFORMATION PROVIDED BY THE OWNER TO THE EXTENT POSSIBLE, DRAINTILE SHALL REMAIN IN PLACE DURING CONSTRUCTION.
- 6 TREE REMOVAL SHALL BE LIMITED DURING PROJECT CONSTRUCTION AND BASED ON ENGINEER'S APPROVAL TREE RPOTECTION FENCING SHOULD BE INSTALLED AS NECESSARY.


ОШО

























LEGEND:	L	E	GE	ΞN	D:
---------	---	---	----	----	----

	PROJECT BOUNDARY
	ADJ. / INTERIOR PROPERTY LINE
- R/A R/W	EX. RIGHT OF WAY
	EX. EASEMENT
	SETBACK
	APPROXIMATE EX. ROAD CENTERLINE
EX CHE	EX. OVERHEAD ELECTRIC
— 645 —— 645 ——	EX, GAS
·· · ·	EX. STREAM
n in state of the	EX. TREE LINE
	EX. WETLAND
	EX. WETLAND/STREAM BUFFER
	EX. CULTURAL EXCLUSION AREA
	EX. CULTURAL BUFFER
	EX, CONTOURS
· · ·	EX. FLOW (DIRECTION AND SLOPE)
×x	PR. CONTOURS
	PR. FLOW (DIRECTION AND SLOPE)
	PR. GRADING AREA (LESS THAN 6" FROM EG)
	PR, GRADING AREA (CUT)
No. of Concession, Name	PR. GRADING AREA (FILL)
	PR. GRAVEL ACCESS ROAD
	PR. INVERTER
x x	PR. FENCE
	PR. CULVERT
ONSTRUCTION NO	TES
) 7' CHAIN LINK FENCE. S	EE DETAIL 1. SHEET C-802


<u>c</u> 102

- (2) 20' SWING ACCESS GATE, SEE DETAIL 3, SHEET C-802,
- 3 16' SITE GRAVEL ACCESS ROAD, SEE DETAILS 1 AND 2, SHEET C-B03.
- EQUIPMENT PAD. REFER TO ELECTRICAL AND STRUCTURAL PLANS, SEE DETAIL 4, SHEET C-804.
- 5 TYPICAL ROAD ENTRANCE, SEE DETAIL 2, SHEET C-804.
- 6 12" RCP CULVERT.
- TYPICAL TURN AROUND, SEE DETAIL 3. SHEET C-804.

₹7


1-800-362-2764







C. Physical Differences
F/2 R/A
states a builded & second a science
and a second sec
GAS GAS
V-2 01.2
the second secon
provide table inclusion in a second second second
and a second second and
17.70 C C C C C C C C C C C C C C C C C C C
the second of the second s
~~
18.75
-
and the second sec



PROJECT BOUNDARY
ADJ. / INTERIOR PROPERTY LINE
EX. RIGHT OF WAY
EX. EASEMENT
SETBACK
APPROXIMATE EX. ROAD CENTERLINE
EX. OVERHEAD ELECTRIC
ÉX, GAS
ÉX, STREAM
EX. TREE LINE
EX, WETLAND
EX WETLAND/STREAM BUFFER
EX. CULTURAL EXCLUSION AREA
EX. CULTURAL BUFFER
EX. CONTOURS
EX FLOW (DIRECTION AND SLOPE)
PR CONTOURS
PR FLOW (DIRECTION AND SLOPE)
PR GRADING AREA (LESS THAN 6" FROM EG)
PR. GRADING AREA (CUT)
PR GRADING AREA (FILL)
PR. GRAVEL ACCESS ROAD
PR. INVERTER
PR FENCE
PR CULVERT


CONSTRUCTION NOTES

- 1 7' CHAIN UNK FENCE, SEE DETAIL 1, SHEET C-802.
- 2 20 SWNG ACCESS GATE, SEE DETAIL 3, SHEET C-802.
- 3 16' SHTE GRAVEL ACCESS ROAD, SEE DETAILS I AND 2. SHEET C-803.
- EQUIPMENT PAD. REFER TO ELECTRICAL AND STRUCTURAL PLANS, SEE DETAIL 4, SHEET C-804.
- 5 TYPICAL RUAD ENTRANCE, SEE DETAIL 2, SHEET C-804.
- 6 12" RCP CULVERT
- TYPICAL TURN AROUND, SEE DETAIL 3, SHEET C-804





					,	SCALE		No. REVISIONS	DATE	ΒY
	(H)				P tot	AS NOTED		1 30% DESIGN	11/18/2021	30
0	161 161 161				RE	DESIGNED BY ERS	Kimlev»Horn	2 60% DESIGN	01/21/2022	с»С
)-	21 R0	HARDIN III SOLAR			LI.				_	
-6	/20 JE0 540	HARDIN COUNTY, OH	I AND URAINAGE		AIN IST	DRAWN BY: ALM	2021 IMMLY-HOTM AND ASSOCIATES. INC. 7965 H. HIGH STREET, SLATE 200			
0)22 ;T 44			and the second	IAR Ruc		COLIMABUS, ON 43235			
1	NŌ		PLAN	nong uni	ξ¥ :ħοi	CHECKED BY, CPC	MANN KING L-MODEL COL			
					7	24	4			





Contra d'Anna d'Anna d'Anna
GAS
processing.
[22]222222[2]
2 11 75
-
7

PROJECT BOUNDARY
ADJ. / INTERIOR PROPERTY LINE
EX. RIGHT OF WAY
EX. EASEMENT
SETBACK
APPROXIMATE EX. ROAD CENTERLINE
EX. OVERHEAD ELECTRIC
EX. GAS
EX, STREAM
EX. TREE LINE
EX, WETLAND
EX, WETLAND/STREAM BUFFER
EX. CULTURAL EXCLUSION AREA
EX. CULTURAL BUFFER
EX, CONTOURS
EX FLOW (DIRECTION AND SLOPE)
PR. CONTOURS
PR. FLOW (DIRECTION AND SLOPE)
PR. GRADING AREA (LESS THAN 6" FROM EG)
PR. GRADING AREA (CUT)
PR. GRADING AREA (FILL)
PR GRAVEL ACCESS ROAD
PR INVERTER
PR FENCE
PR. CULVERT

CONSTRUCTION NOTES

- 1) 7' CHAIN LINK FENCE, SEE DETAIL 1, SHEET C-802.
- 2 20' SWING ACCESS GATE, SEE DETAIL 3, SHEET C-BO2
- (3) 16' SITE GRAVEL ACCESS ROAD, SEE DETAILS 1 AND 2, SHEET C-803.
- EQUIPMENT PAD. REFER TO ELECTRICAL AND STRUCTURAL PLANS, SEE DETAIL 4, SHEET C-804.
- 5 TYPICAL ROAD ENTRANCE, SEE DETAIL 2, SHEET C-804.
- 6 12" RCP CULVERT
- (7) TYPICAL TURN AROUND, SEE DETAIL 3, SHEET C-804,






C-602

REVISIONS DATE BY	DESIGN DESIGN 11/19/2021 CPC	DESIGN 01/21/2022 CPC					
No	1 30% DESCN	2 60% DESIGN					
		Kimlev» Hom		12062	COLUMBUS, OH 43235 PROVE A VIL 487-4400	NWW KENLEY - HORN COM	
SCALE:	AS NOTED	DESIGNED BY: ERS		DRAWN BY: ALM		CHECKED BY: CPC	
		RE			RUC	Those and the second	2
			AND DPAINAGE		DIAN		
			HARDIN III SOLAR	HARDIN COUNTY, OH			
-	OR	IGII 01/	IA.	15	550	E:	





and a single a stress a second
GAS GAS
and the second sec
er de la constante
XX
XX74



ADJ. / INTERIOR PROPERTY LINE EX. RIGHT OF WAY EX. EASEMENT SETBACK APPROXIMATE EX. ROAD CENTERLINE EX. OVERHEAD ELECTRIC EX. GAS EX. STREAM EX. TREE LINE EX. WETLAND EX. WETLAND EX. WETLAND EX. CULTURAL EXCLUSION AREA EX. CULTURAL BUFFER EX. CONTOURS EX. FLOW (DIRECTION AND SLOPE)	
PROPERTY LINE EX. RIGHT OF WAY EX. EASEMENT SETBACK APPROXIMATE EX. ROAD CENTERLINE EX. OVERHEAD ELECTRIC EX. GAS EX. STREAM EX. TREE LINE EX. WETLAND EX. WETLAND/STREAM BUFFER EX. CULTURAL EXCLUSION AREA EX. CULTURAL BUFFER EX. CULTURAL BUFFER EX. CONTOURS EX. FLOW (ORECTION AND SLOPE) PR. CONTOURS PR. FLOW (ORECTION AND SLOPE) PR. CONDING AREA (ESS THAN 6° FROM EG) PR. GRADING AREA (FILL) PR. GRADING AREA (FILL) PR. GRAVEL ACCESS ROAD PR. INVERTER PR. FENCE	PROJECT BOUNDARY
EX. EASEMENT SETBACK APPROXIMATE EX. ROAD CENTERLINE EX. OVERHEAD ELECTRIC EX. GAS EX. STREAM EX. TREE LINE EX. WETLAND EX. WETLAND EX. WETLAND EX. WETLAND EX. WETLAND EX. WETLAND EX. CULTURAL EXCLUSION AREA BUFFER EX. CONTOURS EX. FLOW (DIRECTION AND SLOPE) PR. FLOW (DIRECTION AND SLOPE) PR. FLOW (DIRECTION AND SLOPE) PR. GRADING AREA (LESS THAN 6° FROM EG) PR. GRAVEL ACCESS ROAD PR. INVERTER PR. FENCE	ADJ. / INTERIOR PROPERTY LINE
SETBACK APPROXIMATE EX ROAD CENTERLINE EX, OVERHEAD ELECTRIC EX, GAS EX, STREAM EX, TREE LINE EX, WEILAND EX, WEILAND EX, WEILAND EX, WEILAND EX, WEILAND EX, ULTURAL EXCLUSION AREA BUIFER EX, COLTURAL EXCLUSION AREA EX, CONTOURS EX, FLOW (DIRECTION AND SLOPE) PR, CONTOURS PR, FLOW (DIRECTION AND SLOPE) PR, GRADING AREA (LESS THAN 6° FROM EG) PR, GRADING AREA (LESS ROAD PR, INVERTER PR, FLOE	EX. RIGHT OF WAY
APPROXIMATE EX ROAD CENTERLINE EX. OVERHEAD ELECTRIC EX. GAS EX. STREAM EX. TREE LINE EX. WETLAND EX. WETLAND/STREAM BUFFER EX. CULTURAL EXCLUSION AREA EX. CULTURAL EXCLUSION AREA EX. CULTURAL BUFFER EX. CONTOURS EX. FLOW (DIRECTION AND SLOPE) PR. GRADING AREA (LESS THAN 6" FROM EG) PR. GRADING AREA (LESS THAN 6" FROM EG) PR. GRADING AREA (LESS THAN 6" FROM EG) PR. GRAVEL ACCESS ROAD PR. INVERTER PR. FENCE	EX, EASEMENT
ROAD CENTERLINE EX. OVERHEAD ELECTRIC EX. GAS EX. STREAM EX. TREE LINE EX. WETLAND EX. WETLAND/STREAM BUFFER EX. CULTURAL EXCLUSION AREA EX. CULTURAL BUFFER EX. CONTOURS EX. FLOW (DIRECTION AND SLOPE) PR. CONTOURS PR. FLOW (DIRECTION AND SLOPE) PR. CONTOURS PR. FLOW (DIRECTION AND SLOPE) PR. CONTOURS PR. FLOW (CONTOURS PR. FLOW (CONTOURS PR. GRADING AREA (CLESS THAN 6" FROM EG) PR. GRADING AREA (CLESS ROAD PR. GRAVEL ACCESS ROAD PR. INVERTER PR. FENCE	SETBACK
EX. GAS EX. STREAM EX. TREE LINE EX. WETLAND/STREAM BUFFER EX. CULTURAL EXCLUSION AREA EX. CULTURAL BUFFER EX. CULTURAL BUFFER EX. CONTOURS EX. FLOW (DIRECTION AND SLOPE) PR. CONTOURS PR. FLOW (DIRECTION AND SLOPE) PR. CADING AREA (LESS THAN 6" FROM EG) PR. GRADING AREA (LESS THAN 6" FROM EG) PR. GRADING AREA (FILL) PR. GRAVEL ACCESS ROAD PR. INVERTER PR. FENCE	
EX. STREAM EX. STREAM EX. TREE LINE EX. WETLAND/STREAM BUFFER EX. CULTURAL EXCLUSION AREA EX. CULTURAL BUFFER EX. CONTOURS EX. FLOW (DIRECTION AND SLOPE) PR. CONTOURS PR. FLOW (DIRECTION AND SLOPE) PR. CONTOURS PR. FLOW (DIRECTION AND SLOPE) PR. CONTOURS PR. FLOW (LESS THAN 6" FROM EG) PR. GRADING AREA (LESS THAN 6" FROM EG) PR. GRADING AREA (FILL) PR. GRAVEL ACCESS ROAD PR. INVERTER PR. FENCE	EX. OVERHEAD ELECTRIC
EX, TREE LINE EX. WETLAND EX. WETLAND/STREAM BUFFER EX. CULTURAL EXCLUSION AREA EX. CULTURAL BUFFER EX. CONTOURS EX. FLOW (DIRECTION AND SLOPE) PR. CONTOURS PR. FLOW (DIRECTION AND SLOPE) PR. CONTOURS PR. FLOW (DIRECTION AND SLOPE) PR. CONTOURS PR. FLOW (LESS THAN 6" FROM EG) PR. GRADING AREA (LESS THAN 6" FROM EG) PR. GRADING AREA (FUL) PR. GRAVEL ACCESS ROAD PR. INVERTER PR. FENCE	EX. GAS
EX. WETLAND EX. WETLAND/STREAM BUFFER EX. CULTURAL EXCLUSION AREA EX. CULTURAL BUFFER EX. CONTOURS EX. FLOW (DIRECTION AND SLOPE) PR. FLOW (DIRECTION AND SLOPE) PR. GRADING AREA (LESS THAN 6" FROM EG) PR. GRADING AREA (FILL) PR. GRAVEL ACCESS ROAD PR. INVERTER PR. FENCE	EX. STREAM
EX. WETLAND/STREAM BUFFER EX. CULTURAL EXCLUSION AREA EX. CULTURAL BUFFER EX. CONTOURS EX. FLOW (DIRECTION AND SLOPE) PR. CONTOURS PR. FLOW (DIRECTION AND SLOPE) PR. CONTOURS PR. GRADING AREA (LESS THAN 6° FROM EG) PR. GRADING AREA (FUL) PR. GRADING AREA (FUL) PR. GRAVEL ACCESS ROAD PR. INVERTER PR. FENCE	EX. TREE LINE
BUFFER EX. CULTURAL EXCLUSION AREA EX. CULTURAL BUFFER EX. CONTOURS EX. FLOW (DIRECTION AND SLOPE) PR. CONTOURS PR. GRADING AND SLOPE) PR. GRAVEL ACCESS ROAD PR. INVERTER PR. FENCE	EX. WETLAND
EX. CULTURAL BUFFER EX. CONTOURS EX. FLOW (DIRECTION AND SLOPE) PR. CONTOURS PR. FLOW (DIRECTION AND SLOPE) PR. GRADING AREA (LESS THAN 6" FROM EG) PR. GRADING AREA (CUT) PR. GRADING AREA (FILL) PR. GRAVEL ACCESS ROAD PR. INVERTER PR. FENCE	EX. WETLAND/STREAM BUFFER
EX. CONTOURS EX. FLOW (ORECTION AND SLOPE) PR. CONTOURS PR. FLOW (DIRECTION AND SLOPE) PR. GRADING AREA (LESS THAN 6° FROM EG) PR. GRADING AREA (CUT) PR. GRADING AREA (FILL) PR. GRAVEL ACCESS ROAD PR. INVERTER PR. FENCE	EX. CULTURAL EXCLUSION AREA
EX. FLOW (DIRECTION AND SLOPE) PR, CONTOURS PR, FLOW (DIRECTION AND SLOPE) PR, GRADING AREA (LESS THAN 6" FROM EG) PR. GRADING AREA (FULL) PR. GRADING AREA (FULL) PR. GRAVEL ACCESS ROAD PR, INVERTER PR. FENCE	EX. CULTURAL BUFFER
(DIRECTION AND SLOPE) PR. CONTOURS PR. FLOW (DIRECTION AND SLOPE) PR. GRADING AREA (LESS THAN 5" FROM EG) PR. GRADING AREA (FLL) PR. GRADING AREA (FLL) PR. GRAVEL ACCESS ROAD PR. INVERTER PR. FENCE	EX. CONTOURS
PR. FLOW (DIRECTION AND SLOPE) PR. GRADING AREA (LESS THAN 6" FROM EG) PR. GRADING AREA (CUT) PR. GRADING AREA (FILL) PR. GRAVEL ACCESS ROAD PR. INVERTER PR. FENCE	
(DIRECTION AND SLOPE) PR. GRADING AREA (LESS THAN 6" FROM EG) PR. GRADING AREA (CUT) PR. GRADING AREA (FILL) PR. GRAVEL ACCESS ROAD PR. INVERTER PR. FENCE	PR. CONTOURS
(LESS THAN 6" FROM EG) PR. GRADING AREA (CUIT) PR. GRADING AREA (FILL) PR. GRAVEL ACCESS ROAD PR. INVERTER PR. FENCE	
PR. GRADING AREA (FILL) PR. GRAVEL ACCESS ROAD PR. INVERTER PR. FENCE	
PR GRAVEL ACCESS ROAD PR. INVERTER PR. FENCE	PR. GRADING AREA (CUT)
PR. INVERTER PR. FENCE	PR. GRADING AREA (FILL)
PR. FENCE	PR GRAVEL ACCESS ROAD
	PR. INVERTER
PR. CULVERT	PR. FENCE
	PR. CULVERT

CONSTRUCTION NOTES

- () 7' CHAIN LINK FENCE, SEE DETAIL 1, SHEET C-802,
- 2 20' SWING ACCESS GATE, SEE DETAIL 3, SHEET C-BO2.
- (3) 16' SITE GRAVEL ACCESS ROAD, SEE DETAILS 1 AND 2, SHEET C-803.
- EQUIPMENT PAD. REFER TO ELECTRICAL AND STRUCTURAL PLANS, SEE DETAIL 4, SHEET C-804.
- 5 TYPICAL ROAD ENTRANCE, SEE DETAIL 2, SHEET C-804
- 6 12" RCP CULVERT.
- 7 TYPICAL TURN AROUND, SEE DETAIL 3, SHEET C-804





έ	ð		
DATE /19/2021	01/21/2022		
TI SUCION SICKS	60% DESIGN		
ő, -	~		
•	Kimley»Horn	2009 NUMELY-HORM AND ASSOCIATES, WC 7005 N. HICH STREET, SUIT 200 DOLLANDAS, CH. 437975	PHIDINE 620-489-5550 WWW KIAKET-HORN COM
SCALE: AS NOTED	DESIGNED BY: ERS	DRAWN BY ALH	CHECKED BY. CPC
PREPARED FOR	PRELI		Pool and Among
			PLAN
1	AR		
	HARDIN III SOI AF	HARDIN COUNTY, OH	





	J
	i
······································	1
	1
	:
annua a haine a manua a manua	
E+ O+E	1
	Ì
$= \sum_{i=1}^{n} \sum_{j=1}^{n} \sum_$	I
	1
10000000000	
	Ì
Concerning the second	
3	1
	1
xx	
	1
	1
	I
	I
	1
	1
x x	

PROJECT BOUNDARY ADJ. / INTERIOR PROPERTY LINE EX. RIGHT OF WAY EX. EASEMENT SETBACK APPROXIMATE EX. ROAD CENTERLINE EX. OVERHEAD ELECTRIC EX. GAS EX. STREAM EX. TREE LINE EX. WETLAND EX. WETLAND/STREAM BUFFER EX. CULTURAL EXCLUSION AREA EX. CULTURAL EXCLUSION AREA EX. CULTURAL EXCLUSION AREA EX. CULTURAL EXCLUSION AREA EX. CULTURAL BUFFER EX. CONTOURS EX. FLOW (DIRECTION AND SLOPE) PR. CONTOURS PR. FLOW (DIRECTION AND SLOPE) PR. GRADING AREA (LESS THAN 6" FROM EG) PR. GRADING AREA (CUT) PR. GRAVEL ACCESS ROAD PR. INVERTER PR. FENCE PR. CULTURE	
PROPERTY LINE EX. RIGHT OF WAY EX. EASEMENT SETBACK APPROXIMATE EX. ROAD CENTERLINE EX. OVERHEAD ELECTRIC EX. GAS EX. STREAM EX. TREE LINE EX. WETLAND/STREAM BUFFER EX. CULTURAL EXCLUSION AREA EX. CULTURAL BUFFER EX. CUNTOURS EX. FLOW (DIRECTION AND SLOPE) PR. FLOW (DIRECTION AND SLOPE) PR. FLOW (DIRECTION AND SLOPE) PR. GRADING AREA (LESS THAN 6° FROM EG) PR. GRADING AREA (FILL) PR. GRAVEL ACCESS ROAD PR. INVERTER PR. FENCE	PROJECT BOUNDARY
EX: EASEMENT SETBACK APPROXIMATE EX: ROAD CENTERLINE EX: OVERHEAD ELECTRIC EX: GAS EX: STREAM EX: TREE LINE EX: WETLAND EX: WETLAND EX: WETLAND/STREAM BUFFER EX: CULTURAL EXCLUSION AREA EX: CULTURAL EXCLUSION AREA (DIRECTION AND SLOPE) PR: GRADING AREA (FILL) PR: GRADING AREA (FILL) PR: FENCE	ADJ. / INTERIOR PROPERTY LINE
SETBACK APPROXIMATE EX ROAD CENTERLINE EX. OVERHEAD ELECTRIC EX. GAS EX. STREAM EX. TREE LINE EX. WETLAND EX. WETLAND EX. WETLAND EX. WETLAND/STREAM BUFFER EX. CULTURAL EXCLUSION AREA EX. CULTURAL EXCLUSION AREA EX. CULTURAL BUFFER EX. CONTOURS EX. FLOW (DIRECTION AND SLOPE) PR. CONTOURS PR. FLOW (DIRECTION AND SLOPE) PR. GRADING AREA (LESS THAN 6" FROM EG) PR. GRADING AREA (CUT) PR. GRADING AREA (FILL) PR. INVERTER PR. FENCE	EX. RIGHT OF WAY
APPROXIMATE EX ROAD CENTERLINE EX. OVERHEAD ELECTRIC EX. GAS EX. STREAM EX. TREE LINE EX. WETLAND EX. WETLAND/STREAM BUFFER EX. CULTURAL EXCLUSION AREA EX. CONTOURS PR. FLOW (DIRECTION AND SLOPE) PR. GRADING AREA (LESS THAN 6" FROM EG) PR. GRADING AREA (FILL) PR. GRAVEL ACCESS ROAD PR. INVERTER PR. FENCE	EX. EASEMENT
ROAD CENTERLINE EX. OVERHEAD ELECTRIC EX. GAS EX. STREAM EX. TREE LINE EX. WETLAND EX. WETLAND/STREAM BUFFER EX. CULTURAL EXCLUSION AREA EX. CULTURAL BUFFER EX. CONTOURS EX. FLOW (DIRECTION AND SLOPE) PR. FLOW (DIRECTION AND SLOPE) PR. FLOW (DIRECTION AND SLOPE) PR. FLOW (DIRECTION AND SLOPE) PR. GRADING AREA (LESS THAN 6° FROM EG) PR. GRADING AREA (FILL) PR. GRAVEL ACCESS ROAD PR. INVERTER PR. FENCE	SETBACK
EX. GAS EX. STREAM EX. TREE LINE EX. WETLAND EX. WETLAND/STREAM BUFFER EX. CULTURAL EXCLUSION AREA EX. CULTURAL BUFFER EX. CONTOURS EX. FLOW (DIRECTION AND SLOPE) PR. CONTOURS PR. FLOW (DIRECTION AND SLOPE) PR. GRADING AREA (LESS THAN 6° FROM EG) PR. GRADING AREA (CUT) PR. GRADING AREA (FILL) PR. GRAVEL ACCESS ROAD PR INVERTER PR. FENCE	
EX. STREAM EX. TREE LINE EX. WETLAND EX. WETLAND/STREAM BUFFER EX. CULTURAL EXCLUSION AREA EX. CULTURAL BUFFER EX. CONTOURS EX. FLOW (DIRECTION AND SLOPE) PR. CONTOURS PR. FLOW (DIRECTION AND SLOPE) PR. GRADING AREA (LESS THAN 6" FROM EG) PR. GRADING AREA (CUT) PR. GRADING AREA (FILL) PR. GRAVEL ACCESS ROAD PR. INVERTER PR. FENCE	EX. OVERHEAD ELECTRIC
EX. TREE LINE EX. WETLAND EX. WETLAND/STREAM BUFFER EX. CULTURAL EXCLUSION AREA EX. CULTURAL BUFFER EX. CONTOURS EX. FLOW (DIRECTION AND SLOPE) PR. CONTOURS PR. FLOW (DIRECTION AND SLOPE) PR. GRADING AREA (LESS THAN 6" FROM EG) PR. GRADING AREA (CUT) PR. GRADING AREA (CUT) PR. GRADING AREA (FILL) PR. GRAVEL ACCESS ROAD PR. INVERTER PR. FENCE	EX. GAS
EX. WETLAND EX. WETLAND/STREAM BUFFER EX. CULTURAL EXCLUSION AREA EX. CULTURAL BUFFER EX. CONTOURS EX. FLOW (DIRECTION AND SLOPE) PR. CONTOURS PR. FLOW (DIRECTION AND SLOPE) PR. GRADING AREA (LESS THAN 6" FROM EG) PR. GRADING AREA (CUT) PR. GRADING AREA (FILL) PR. GRAVEL ACCESS ROAD PR INVERTER PR. FENCE	EX. STREAM
EX. WETLAND/STREAM BUFFER EX. CULTURAL EXCLUSION AREA EX. CULTURAL BUFFER EX. CONTOURS EX. FLOW (DIRECTION AND SLOPE) PR. CONTOURS PR. FLOW (DIRECTION AND SLOPE) PR. GRADING AREA (LESS THAN 6" FROM EG) PR. GRADING AREA (CUT) PR. GRADING AREA (FILL) PR. GRAVEL ACCESS ROAD PR INVERTER PR. FENCE	EX. TREE LINE
BUFFER EX. CULTURAL EXCLUSION AREA EX. CULTURAL BUFFER EX. CONTOURS EX. FLOW (DIRECTION AND SLOPE) PR. CONTOURS PR. FLOW (DIRECTION AND SLOPE) PR. GRADING AREA (LESS THAN 6" FROM EG) PR. GRADING AREA (CUT) PR. GRAVEL ACCESS ROAD PR. INVERTER PR. FENCE	EX. WETLAND
EX. CULTURAL BUFFER EX. CONTOURS EX. FLOW (DIRECTION AND SLOPE) PR. CONTOURS PR. FLOW (DIRECTION AND SLOPE) PR. GRADING AREA (LESS THAN 6" FROM EG) PR. GRADING AREA (FILL) PR. GRADING AREA (FILL) PR. GRAVEL ACCESS ROAD PR INVERTER PR. FENCE	EX. WETLAND/STREAM BUFFER
EX. CONTOURS EX. FLOW (URECTION AND SLOPE) PR. CONTOURS PR. FLOW (DRECTION AND SLOPE) PR. GRADING AREA (LESS THAN 6" FROM EG) PR. GRADING AREA (CUT) PR. GRADING AREA (FILL) PR. GRAVEL ACCESS ROAD PR INVERTER PR. FENCE	EX. CULTURAL EXCLUSION AREA
EX. FLOW (DIRECTION AND SLOPE) PR. CONTOURS PR. FLOW (DIRECTION AND SLOPE) PR. GRADING AREA (LESS THAN 6" FROM EG) PR. GRADING AREA (CUT) PR. GRADING AREA (FILL) PR. GRAVEL ACCESS ROAD PR INVERTER PR. FENCE	EX. CULTURAL BUFFER
(DIRECTION AND SLOPE) PR. CONTOURS PR. FLOW (DIRECTION AND SLOPE) PR. GRADING AREA (LESS THAN 6" FROM EG) PR. GRADING AREA (CUT) PR. GRADING AREA (FILL) PR. GRAVEL ACCESS ROAD PR INVERTER PR. FENCE	EX. CONTOURS
PR. FLOW (DIRECTION AND SLOPE) PR. GRADING AREA (LESS THAN 6" FROM EG) PR. GRADING AREA (CUT) PR. GRADING AREA (FILL) PR. GRAVEL ACCESS ROAD PR INVERTER PR. FENCE	
(DIRECTION AND SLOPE) PR. GRADING AREA (LESS THAN 6" FROM EG) PR. GRADING AREA (CUT) PR. GRADING AREA (FILL) PR. GRAVEL ACCESS ROAD PR INVERTER PR. FENCE	PR. CONTOURS
(LESS THAN 6" FROM EG) PR. GRADING AREA (CUT) PR. GRADING AREA (FILL) PR. GRAVEL ACCESS ROAD PR. INVERTER PR. FENCE	
PR. GRADING AREA (CUT) PR. GRADING AREA (FILL) PR. GRAVEL ACCESS ROAD PR INVERTER PR. FENCE	
PR. GRADING AREA (FILL) PR. GRAVEL ACCESS ROAD PR INVERTER PR: FENCE	PR GRADING AREA (CUT)
PR. GRAVEL ACCESS ROAD PR. INVERTER PR. FENCE	
PR. INVERTER PR. FENCE	
PR. FENCE	PR. GRAVEL ACCESS ROAD
	PR. INVERTER
PR. CULVERT	PR. FENCE
	PR. CULVERT

CONSTRUCTION NOTES


1 7' CHAIN LINK FENCE, SEE DETAIL 1, SHEET C-802

- 2 20' SWING ACCESS GATE, SEE DETAIL 3, SHEET C-BO2.

- 3 16' SITE GRAVEL ACCESS ROAD, SEE DETAILS 1 AND 2, SHEET C-803.
 4 EQUIPMENT PAD. REFER TO ELECTRICAL AND STRUCTURAL PLANS, SEE DETAIL 4, SHEET C-804.
 (3) TYPICAL ROAD ENTRANCE, SEE DETAIL 2, SHEET C-804.
- 6 12" RCP CULVERT
- TYPICAL TURN AROUND, SEE DETAIL 3, SHEET C-804.









B
EX CHE
GAS GAS
and the second s
· · · · · · · · · · · · · · · · · · ·
('
and the second se
,
20
-
115
11.72
And a second
4
and the second s
the second se
1212423-36464232473-464646424242
·

PROJECT BOUNDARY
ADJ. / INTERIOR PROPERTY LINE
EX. RIGHT OF WAY
EX. EASEMENT
SETBACK
APPROXIMATE EX. ROAD CENTERUNE
EX. OVERHEAD ELECTRIC
EX. GAS
EX. STREAM
EX. TREE LINE
EX. WETLAND
EX. WETLAND/STREAM BUFFER
EX. CULTURAL EXCLUSION AREA
EX. CULTURAL BUFFER
EX. CONTOURS
EX. FLOW (DIRECTION AND SLOPE)
PR. CONTOURS
PR. FLOW (DIRECTION AND SLOPE)
PR. GRADING AREA (LESS THAN 6" FROM EG)
PR. GRADING AREA (CUT)
PR. GRADING AREA (FILL)
PR. GRAVEL ACCESS ROAD
PR. INVERTER
PR. FENCE
PR CULVERT

CONSTRUCTION NOTES

x ----- x -

- 1) 7' CHAIN LINK FENCE, SEE DETAIL 1, SHEET C-802.
- 2 20' SWING ACCESS GATE, SEE DETAIL 3, SHEET C-802
- 3 16 SHEE GRAVEL ACCESS ROAD, SEE DETAILS 1 AND 2, SHEET C-803.
- EQUIPMENT PAD. REFER TO ELECTRICAL AND STRUCTURAL PLANS, SEE DETAIL 4, SHEET C-804.
- 5 TYPICAL ROAD ENTRANCE, SEE DETAIL 2, SHEET C-804.
- 6 12" RCP CULVERT
- TYPICAL TURN AROUND, SEE DETAIL 3, SHEET C-804.





No. REVISIONS DATE BY	1 JOT DESIGN 11/19/2021 CPC	2 60% DESIGN 01/21/2022 CPC					· · · ·
N					COLUMBUS, DH 43235	ALLOW THE ALLOW COM	
SCALE:	AS NOTED	DESIGNED BY: ERS		DRAWN BY: ALK		DHECKED BY: OPC	
	P	RE		MIN NST	IAR	Y	-
		(for sead		
	SITE GRADING		AND DPAINAGE				
					ā	-	
						-	





	PROJECT
	ADJ. / I PROPERT
	EX. RIGH
	EX, EAS
	SETBACK
Califor & Brings & California & Stateme	APPROXI ROAD CE
E < C+E	EX. OVE
GAS GAS	EX GAS
	EX STR
and a strange with a second second	EX_ TREE
	EX WET
	EX WETO BUFFER
10000000000000000000000000000000000000	EX. CUL
	EX: CUL
	EX CON
-115 -	EX. FLOW
XX	PR CON
714	PR. FLO
	PR. GRA
	PR GRA
	PR. CRA
	PR. GRA
	PR. INVE
—— x —— x ——	PR. FEN

PROJECT BOUNDARY
ADJ. / INTERIOR PROPERTY LINE
X. RIGHT OF WAY
X, EASEMENT
SETBACK
APPROXIMATE EX. ROAD CENTERLINE
X. OVERHEAD ELECTRIC
X GAS
X. STREAM
X TREE LINE
X WETLAND
EX. WETLAND/STREAM BUFFER
EX CULTURAL EXCLUSION AREA
X. CULTURAL BUFFER
CONTOURS
X. FLOW DIRECTION AND SLOPE)
R CONTOURS
PR. FLOW DIRECTION AND SLOPE)
PR. GRADING AREA LESS THAN 6" FROM EG)
PR GRADING AREA (CUT)
PR: GRADING AREA (FILL)
PR. GRAVEL ACCESS ROAD
PR. INVERTER
PR, FENCE
PR, CULVERT

CONSTRUCTION NOTES

- 1 7' CHAIN LINK FENCE, SEE DETAIL 1, SHEET C-802.
- 2 20' SWING ACCESS GATE, SEE DETAIL 3. SHEET C-802.
- 3 16' SITE GRAVEL ACCESS ROAD, SEE DETAILS 1 AND 2, SHEET C-803.
 COUIPMENT PAD. REFER TO ELECTRICAL AND STRUCTURAL PLANS, SEE DETAIL 4, SHEET C-804.

- 5 TYPICAL ROAD ENTRANCE, SEE DETAIL 2, SHEET C-804. 6 12" RCP CULVERT
- () TYPICAL TURN AROUND, SEE DETAIL 3, SHEET C-804.









	PROJECT BOUNDARY
	ADJ. / INTERIOR PROPERTY LINE
	EX_ RIGHT OF WAY
	EX. EASEMENT
	SETBACK
	APPROXIMATE EX.
EX CHE	EX. OVERHEAD ELECTRIC
GAS GAS	EX. GAS
Alexandra (1999)	EX. STRÉAM
and the second s	EX. TREE LINE
	EX WETLAND
	EX. WETLAND/STREAM BUFFER
[2222/j.j2222]	EX. CULTURAL EXCLUSION AREA
	EX. CULTURAL BUFFER
	EX CONTOURS
	EX. FLOW (DIRECTION AND SLOPE)
xx	PR. CONTOURS
**3	PR. FLOW (DIRECTION AND SLOPE)
	PR. GRADING AREA (LESS THAN 6" FROM EG)
Concerning of the local division of the	PR. GRADING AREA (CUT)
	PR GRADING AREA (FILL)
	PR. GRAVEL ACCESS ROAD
	PR. INVERTER
x x	PR. FENCE
	PR. CULVERT

CONSTRUCTION NOTES

1 7' CHAIN LINK FENCE, SEE DETAIL 1. SHEET C-802.


- 2 20' SWING ACCESS GATE, SEE DETAIL 3, SHEET C-802.


- 3 15' SITE GRAVEL ACCESS ROAD, SEE DETAILS 1 AND 2, SHEET C=803...
 ④ EOUIPMENT PAD, REFER TO ELECTRICAL AND STRUCTURAL PLANS, SEE DETAIL 4, SHEET C-804.
 ⑤ TYPICAL ROAD ENTRANCE, SEE DETAIL 2, SHEET C-804. 6 12" RCP CULVERT
- TYPICAL TURN AROUND, SEE DETAIL 3, SHEET C-804.



N







EC	26	м	n-
 E(76		υ.

	ρ
	A P
R/W R/W	E
	E
	s
	A R
	E
G45	E
	£
and the second s	Ę
	£
	E: Bi
[700/02/02/02/0]	E
	E
	E
	E (0
	P
*×5	Р) (С
	P
Contraction of the second second	()
2	P
	P
	P
	P
x x	P
└────→	p

PROJECT BOUNDARY
ADJ. / INTERIOR PROPERTY LINE
EX RIGHT OF WAY
EX_ EASEMENT
SETBACK
APPROXIMATÉ EX. ROAD CENTERLINE
EX OVERHEAD ELECTRIC
EX_ GAS
EX_ STREAM
EX TREE LINE
EX: WETLAND
EX WETLAND/STREAM BUFFER
EX CULTURAL EXCLUSION AREA
EX CULTURAL BUFFER
EX. CONTOURS
EX FLOW (DIRECTION AND SLOPE)
PR. CONTOURS
PR. FLOW (DIRECTION AND SLOPE)
PR. GRADING AREA (LESS THAN 6" FROM EC)
PR. GRADING AREA (CUT)
PR. GRADING AREA (FILL)
PR GRAVEL ACCESS ROAD
PR
PR. FENCE
PR. CULVERT

2

OTED ERS

12

PRELIMINARY NOT FOR CONSTRUCTION

CONSTRUCTION NOTES

1) 7' CHAIN LINK FENCE, SEE DETAIL 1, SHEET C-802


- 2 20' SWING ACCESS GATE, SEE DETAIL 3, SHEET C-802.

- 3 I6' SITE GRAVEL ACCESS ROAD, SEE DETAILS 1 AND 2, SHEET C-803.
 4 EQUIPMENT PAD. REFER TO ELECTRICAL AND STRUCTURAL PLANS, SEE DETAIL 4, SHEET C-804.
 5 TYPICAL ROAD ENTRANCE, SEE DETAIL 2, SHEET C-804.
- 6 12" RCP CULVERT
- (7) TYPICAL TURN AROUND, SEE DETAIL 3, SHEET C-804.












PROJECT BOUNDARY
ADJ. / INTERIOR PROPERTY LINE
X RIGHT OF WAY
EX EASEMENT
SETBACK
APPROXIMATE EX. ROAD CENTERLINE
EX. OVERHEAD ÉLÉCTRIC
EX GAS
EX. STREAM
EX. TREE LINE
EX. WETLAND
EX, WETLAND/STREAM BUFFER
EX. CULTURAL EXCLUSION AREA
EX. CULTURAL BUFFER
EX. CONTOURS
EX.: FLOW (DIRECTION AND SLOPE)
PR. CONTOURS
PR. FLOW (DIRECTION AND SLOPE)
PR. GRADING AREA
(LESS THAN 6" FROM EG)
PR. GRADING AREA (CUT)
PR. GRADING AREA (FILL)
PR. GRAVEL ACCESS ROAD
PR INVERTER
PR. FENCE
PR. CULVERT


CONSTRUCTION NOTES

- 1 7' CHAIN LINK FENCE, SEE DETAIL 1, SHEET C-802,
- (2) 20' SWING ACCESS GATE, SEE DETAIL 3. SHEET C-802.
- 16' SITE GRAVEL ACCESS ROAD, SEE DETAILS 1 AND 2, SHEET C-803.
 COMPLENT PAD, REFER TO ELECTRICAL AND STRUCTURAL PLANS, SEE DETAIL 4, SHEET C-804.
- 5 TYPICAL ROAD ENTRANCE, SEE DETAIL 2, SHEET C-804.
- 6 12" RCP CULVERT,
- TYPICAL TURN AROUND. SEE DETAIL 3. SHEET C-804.









|--|

	PROJECT BOU
	ADJ / INTER
	EX. RIGHT OF
	EX. EASEMENT
	SETBACK
AND A COLUMN A ASSOCIATION (APPROXIMATE ROAD CENTER
	EX. OVERHEAD
CAS	EX. GAS
	EX. STREAM
$e^{-i\omega_{1}}e^{-i\omega_{1}}e^{-i\omega_{2$	EX TREE LINE
	EX. WETLAND
	EX. WETLAND/ BUFFER
[37200000]	EX CULTURAL
	EX. CULTURAL
	EX. CONTOURS
	EX. FLOW (DIRECTION AN
	PR. CONTOUR
3×5	PR. FLOW (DIRECTION AN
	PR. GRADING
	PR. GRADING
-	PR. GRADING
	PR. GRAVEL A
	PR: INVERTER
x x	PR. FENCE
<u> </u>	PR CULVERT

BOUNDARY TERIOR OF WAY **JENT** ATÉ EX HEAD ELECTRIC M. LINE ND ND/STREAM RAL EXCLUSION AREA RAL BUFFER URS AND SLOPE) DURS AND SLOPE) ING AREA AN 6" FROM EG) ING AREA (CUT) ING AREA (FILL) VEL ACCESS ROAD TER

CONSTRUCTION NOTES


1) 7' CHAIN LINK FENCE, SEE DETAIL 1, SHEET C-802

- 2 20' SWING ACCESS GATE, SEE DETAIL 3, SHEET C-BO2
- 3 16 SITE GRAVEL ACCESS ROAD, SEE DETAILS 1 AND 2. SHEET C-803.
- EQUIPMENT PAD. REFER TO ELECTRICAL AND
 STRUCTURAL PLANS, SEE DETAIL 4, SHEET C-804.
- 5 TYPICAL ROAD ENTRANCE, SEE DETAIL 2, SHEET C-804. 6 12" RCP CULVERT.
- TYPICAL TURN AROUND, SEE DETAIL 3, SHEET C-804





	BY CPC	CPC		
	021		\parallel	
	0ATE 11/19/2	01/21/2		
	30% DESIGN	60% DCSCN		
	°N °	Ē	1 1	
BILE CRADING SITE CRADING BILE CRADING SITE CRADING BILE CRADING BI	-	Kimley »Ho	2001 UMALY-HOMI AND ASSOCIATE 2965 N. NUCH STREET, SUITE 2 COLUMBUS, ON 43225	PHORE: 630-487-550 WWW FRAEEY=HORE COM
NOT FOR CONSTRUCTION SITE GRADING SITE GRADING SITE GRADING AND DRAINAGE AND DRAINAGE AND DRAINAGE AND DRAINAGE AND DRAINAGE AND DRAINAGE AND DRAINAGE AND DRAINAGE AND DRAINAGE AND AND DRAINAGE AND AND DRAINAGE AND AND AND AND AND AND AND AND AND AND		DESIGNED BY ERS	DRAWH BY ALH	CHECKED BY, CPC
BITE GRADING SITE GRADING HARDIN III SOLAR AND DRAINAGE AND DRAINAGE PLAN PLAN	Р NOT	RELI		₹Y STION
ORIGINAL ISSUE: 01/21/2022 KHA PROJECT NO. 168754044	PREPARED FOR	E	<u></u>	power tor good
ORIGINAL ISSUE: 01/21/2022 KHA PROJECT NO. 168754044				
01/21/2022 KHA PROJECT NO. 168754044	_			
C-610		HARDIN III SOLAR	HARDIN COUNTY, OH	





9/2-	f	R (A
-		
	I CHE	
- 643		045
	1	
-		-
	-11-3	

	EX BU
[20202002630]	EX
	EX
	EX
	EX (Di
	PR
- 105	PR (Di
	PR (Li
	PŔ
	PR
	PR
	PR
x x	PA

PROJECT BOUNDARY ADJ / INTERIOR EX. RIGHT OF WAY EX. EASEMENT SETBACK APPROXIMATE EX. ROAD CENTERLINE EX OVERHEAD ELECTRIC EX GAS EX_STREAM EX TREE LINE EX. WETLAND X. WETLAND/STREAM SUFFER CULTURAL EXCLUSION AREA X CULTURAL BUFFER X. CONTOURS X. FLOW DIRECTION AND SLOPE) PR. CONTOURS PR. FLOW (DIRECTION AND SLOPE) PR: GRADING AREA (LESS THAN 6" FROM EG) PR. GRADING AREA (CUT) PR. GRADING AREA (FILL) PR. GRAVEL ACCESS ROAD PR PR. FENCE PR. CULVERT

CONSTRUCTION NOTES


1) 7' CHAIN LINK FENCE, SEE DETAIL 1, SHEET C-802


- 2) 20' SWING ACCESS GATE, SEE DETAIL 3, SHEET C-802
- 3 16' SITE GRAVEL ACCESS ROAD, SEE DETAILS 1 AND 2, SHEET C-803.
 4 EQUIPMENT PAD, REFER TO ELECTRICAL AND STRUCTURAL PLANS, SEE DETAIL 4, SHEET C-804.

- (5) TYPICAL ROAD ENTRANCE, SEE DETAIL 2, SHEET C-804
- (6) 12" RCP CULVERT.
- (7) TYPICAL TURN AROUND, SEE DETAIL 3, SHEET C-804.



L







	Ρ
	AP
	Ε
	E
	s
enters a locale a deline a status	A R
E7 . UHE	E
CAC CAS	£
	Ε
	E
COLUMN STREET	E
	6 8
17777777777	ε
	ε
	ε
	E ((
xx	P
	P ()
1	P (1
	Ρ
	P
	P
	P
x x	P

ROJECT BOUNDARY
ADJ. / INTERIOR PROPERTY LINÉ
X, RIGHT OF WAY
X. EASEMENT
SETBACK
APPROXIMATE EX
X. OVERHEAD ELECTRIC
X GAS
X, STREAM
X. TREE LINE
X WETLAND
X WETLAND/STREAM BUFFER
CULTURAL EXCLUSION AREA
X. CULTURAL BUFFER
EX. CONTOURS
EX FLOW DIRECTION AND SLOPE)
PRICONTOURS
PR. FLOW (DIRECTION AND SLOPE)
PR GRADING AREA (LESS THAN 6" FROM EG)
PR GRADING AREA (CUT)
PR GRADING AREA (FILL)
PR GRAVEL ACCESS ROAD
PR. INVERTER
PR FENCE
PR. CULVERT

No. 1 30% 0 2 50% 0

Kimley Horn

AS NOTED DESIGNED BY, ENS

PRELIMINARY NOT FOR CONSTRUCTION

N

CONSTRUCTION NOTES


1 7' CHAIN LINK FENCE, SEE DETAIL 1, SHEET C-802


- (2) 20' SWING ACCESS GATE, SEE DETAIL 3, SHEET C-802.
- 16' SITE CRAVEL ACCESS ROAD, SEE DETAILS 1 AND 2. SHEET C-803.
 EQUIPMENT PAD. REFER TO ELECTRICAL AND STRUCTURAL PLANS, SEE DETAIL 4. SHEET C-804

- (5) TYPICAL ROAD ENTRANCE, SEE DETAIL 2. SHEET C-804.
- 6 12" RCP CULVERT
- 7 TYPICAL TURN AROUND, SEE DETAIL 3, SHEET C-804









=
Ex CrE
G45
0200000000
1.2 m
xx
<u></u>


PROJECT BOUNDARY
ADJ. / INTERIOR PROPERTY LINE
EX. RIGHT OF WAY
EX. EASEMENT
SETBACK
APPROXIMATE EX. ROAD CENTERLINE
EX. OVERHEAD ELECTRIC
EX. GAS
EX STREAM
EX TREE LINE
EX. WETLAND
EX. WETLAND/STREAM BUFFER
EX. CULTURAL EXCLUSION AREA
EX CULTURAL BUFFER
EX. CONTOURS
EX. FLOW (DIRECTION AND SLOPE)
PR. CONTOURS
PR FLOW (DIRECTION AND SLOPE)
PR. GRAVEL ACCESS ROAD
PR. INVERTER
PR. FENCE
PR. DRAIN TILE











C-620













SKIMMER DISCHARGE SYSTEM 5 SCALE: NTS C-801





STRIPS OF THE BLANKET SHALL BE INSTALLED PARALLEL TO THE DIRECTION OF FLOW OVER THE SURFACE WHICH IS TO BE PROTECTED.

The UP-SLOPE END OF THE BLANKET SHALL BE BURED IN A TRENCH WEASHING & INCHES DEEP AND & INCHES THE UNIT OF THE END. THE SOL SHALL BE BACKFLED INTO THE TRENCH AND BACKFLED INTO THE TRENCH AND END. THE TRENCH AND END INTO THE TRENCH AND END.

EDGES OF ADJACENT STRIPS OF THE BLANKET SHALL BE OVERLAPPED A WHITHAN OF 4 INCHES AND SHALL BE STAPLED EVERY 3 FEET ALONG THE OVERLAP...


NHG STRAPS OF THE BLANKET END TO END, A TRENCH SUNLAR TO THE ONE DUG AT THE BEGNINNN NIGNAL STRAP SHALL BE DUG AT THE UP-SLOPE END OF THE NEW STRIP. THE END OF THE NEW ULB E FOLDED UNDER AT LEAST IT MONES MIT THE FOLD BENE FRACED HA LAKE MANNER IN OH AS THE BEGNINNN END OF THE ORIGINAL STRIP. STAPLES SHALL BE HISTALLED AT 12 INCH AQUIG THE FRENCH.

STARTES FOR ANYMONING SON STABLIDHER MATERIALS SUMAL BE MADE OF 10 FUNCE WHIT OF MEANER THEY SHALL BE TO 10 ANYMES H LIDER. HA WITH THE LIDERE BENGE USED IN LIDES OF UNSTRAET SOLS THEY SHALL BE ONE START FOR EACH & SQUARE FEET OF THE BLAWET TO ASSURE PROPER BOHONG BETWEN THE SOL MAD DE VAN MATERAL



INSPECTION AND MAINTENANCE T MISPECT BMP ON A WEEKLY BAUS AND AFTER STORM EVENTS OF > 0.5" OF PRCOPILITATION. 2 IMMEDIATELY REPAIR OR REPLACE THE BLANKET DUE TO ANY DAMAGE


3.00 NOT NOW WHEN THE BLANKETED AREA IS WET 4. COMPOSTABLE OR PHOTODEGRADABLE BLANKETS DO NOT NEED TO BE REWOVED FROM THE STE.




3

7


C-801






OHIO

THESE CONSTRUCTION DETAILS HAVE BEEN PROVIDED FOR REFERENCE ONLY WITH THE 30% CIVIL DESIGN. THE DETAILS ARE BASED ON SIMILAR PROJECTS IN OHIO, BUT HAVE NOT BEEN FINALIZED AND ARE SUBJECT TO CHANGE BASED ON FINAL ENGINEERING.





ARRAY AREA SEED MIX

PERMANENT SOLAR FARM SEED MIX
34.0% Festuca rubra
33.0% Festuca ovina
10.0% Festuca Brevipila 'Beacon'
5.0% Festuca Ovina Var, Dunuscula 'Rhino'
5.0% Festuca Ovina Var, Glauca 'Blue Ray'
5.0% Poa Pratensis 'Argyle'
5.0% Poa Pratensis 'Shamrock'
3.0% Agrostis Perennans,
Albany Pine Bush - NY Ecotype

Creeping Red Fescue Sheep fescue Hard Fescue 'Beacon' Hard Fescue 'Rhino' Blue Fescue 'Blue Ray Kentucky Bluegrass 'Argyle' Kentucky Blugrass 'Shamrock

Autumn Bengrass, Albany Pine Bush-NY Ecotype

POLLINATOR SEED MIX

SEEDING RATE: 200 LB PER ACRE

NATIVE DETENTION AREA SEED MIX 40% Schizachyrium scoparium 23.40% Bouteloua Curtipendula 7.30% Cosmos Bipinnalus 3.5% Coreopsis lanceolata 3.5% Echinacea purpurea 3.0% Elymus virginicus 2.50% Sorghastrum nutans 2.20% Lupinus Polyphyllus 2.0% Chamaecrista (asc 2.0% Rudbeckia hirta 1.50% Gaillardia Artistata 1.0% Senna hebacarpa 1.0% Penstemon digitalis 0.60% Papaver Rhoeas 0.50% Andropogon Gerardi 0.50% Elymus Canadensi 0.50% Coreopsis Tincloria 0.40% Liatris Spicata 0.40% Asclepias syriaca 0.40% Ascleoias luberosa 0.30% Zizia aurea 0.30% Asclepias incarnata 0.20% Monarda fistulosa 0.20% Penstemon laevigatus 0 20% Senna manlandic 0.10% Solidago nemoralis 0.10% Tradescantia ohiensis 0.10% Aster laevis 0.10% Aster novae-angliae 0.10% Aster prenanthoides 0.10% Heliopsis helianthoide

Little Bluestern 'Prairie View' IN Ecotype Sideoats Grama Cosmos Lanceleaf Coreopsis Purple Coneflower Virginia Wildrye, Madison-NY Ecotype Indiangrass, WI Ecotype **Bigleaf Lupine** Partridge Pea, PA Ecotype Blackeyed Susan Blanket Flower Mild Senna, VA & WV Ecotype Tall White Beardtonour Shirley Mix (Com Poppy, Shirley Mix) **Big Bluestem** Canada Wildrye Plains Coreopsis Blazing Star Common Milkweed **Butterfly Milkweed** Golden Alexander Swamp Milkweed, PA Ecotype Wild Bergamot, Fort Indian Appalachian Beartongue vn Gap-PA Ecotype Maryland Senna Gray Goldenrod, PA Ecotype Ohio Spiderwort, PA Ecotype Smooth Blue Aster New England Aster, PA Ecotype Zigzag Aster Oxeve Sunflower PA Ecotype

SEEDING RATE: 20 LB PER ACRE

NOTE: APPLY AT INDICATED RATE FOLLOWED BY ANNUAL RYE COVER CROP AT 30 LB PER ACRE.

PRODUCT; ERNST SEED ITEM NUMBER ERNMX-105 OR EQUAL

VEGETATION MANAGEMENT NOTES

- SOIL PH IS TO BE TESTED PRIOR TO AMENDMENT AND FINAL GRADING, LIME OR SULFUR IS TO BE ADDED IN APPROPRIATE QUANTITY TO BRING PH TO ACCEPTABLE LEVELS FOR SEED
- APPLICATION AS NEEDED.
- IN AREAS OF SOIL AMENDMENT OR EXISTING AGRICULTURAL LAND, SOIL IS RECOMMENDED TO BE DISKED, CULTIVATED, AND ROLLED AS NEEDED.
- 3
 - SEED TO BE HYDRO APPLICATION WITH 2 TONS OF STRAW MULCH PER ACRE. SITE MANAGER TO OBSERVE SITE IN THE SPRING, TWICE IN THE SUMMER, AND ONCE IN

PROBLEMS. 6

- ACTON SHOULD BE TAKEN. THE INITIAL THREE YEARS WILL REQUIRE MORE FREQUENT MAINTENANCE AND MONITORING TO PROVIDE NATIVE PLANT ESTABLISHMENT INSTEAD OF INVASIVE WEEDS. WITHIN FIRST TWO YEARS OF COMPLETION, SITE MANAGER TO VISIT THE SITE ONCE PER MONTH THROUGHOUT THE GROWING SEASON TO CONTROL INVASIVE WEEDS. ALSO DURING THIS TIME, MOWING SHOULD OCCUR AT LEAST TWICE PER YEAR TO ELIMINATE
- 8
- SHADING FROM AGRONOMIC, ANNUAL WEEDS, SITE MANAGER SHOULD PERFORM YEARLY INSPECTIONS WITH A LANDSCAPE
- MAINTENANCE PROFESSIONAL TO IDENTIFY WEED PROBLEMS AND TO DISCUSS A STRATEGY FOR MAINTENANCE FOR THE YEAR

AND APPLY HERBICIDE.

LANDSCAPE NOTES

THE LANDSCAPE CONTRACTOR SHALL BE RESPONSIBLE FOR INSTALLING MATERIALS AND PLANTS SHOWN ON THE LANDSCAPE PLAN. THE CONTRACTOR IS RESPONSIBLE FOR THE COST TO REPAIR UTILITIES, ADJACENT LANDSCAPE, PUBLIC AND PRIVATE PROPERTY THAT IS DAMAGED BY THE CONTRACTOR OR THEIR SUBCONTRACTOR'S OPERATIONS DURING INSTALLATION OR DURING THE SPECIFIED MAINTENANCE PERIOD. CALL FOR UTILITY LOCATIONS PRIOR TO ANY EXCAVATION.


2. WORK. 3.

EXCAVATIONS THAT SETTLE.


- 4.
- DO NOT DISTURB THE EXISTING PAVING, LIGHTING, OR LANDSCAPING THAT EXISTS ADJACENT TO THE SITE UNLESS OTHERWISE NOTED ON PLAN.
 PLANT QUANTITIES SHOWN ARE FOR THE CONVENIENCE OF THE OWNER AND JURISDICTIONAL
- AS DRAWN. THE CONTINUED MAINTENANCE OF ALL REQUIRED LANDSCAPING SHALL BE THE RESPONSIBILITY OF THE OWNER OF THE PROPERTY ON WHICH SAID MATERIALS ARE REQUIRED, ALL PLANT MATERIALS REQUIRED BY THIS SECTION SHALL BE MAINTAINED AS LIVING VEGETATION AND SHALL BE PROMPTLY REPLACED IF THE PLANT MATERIAL HAS DIED PRIOR TO FINAL
- ACCEPTANCE, PLANTING AREAS SHALL BE KEPT FREE OF TRASH, LITTER, AND WEEDS AT ALL TIMES.
- 8. IT IS THE CONTRACTORS RESPONSIBILITY TO KEEP PLANT MATERIAL WATERED AND IN GOOD HEALTHY CONDITION THROUGHOUT THE WARRANTY PERIOD.

- IN AREAS OF SATURATED SOILS WITH POOR DRAINAGE, AERIFICATION SHOULD BE PERFORMED WITH MECHANICAL AERATORS OR SPIKE ROLLERS.
- THE FALL, TO IDENTIFY GROWTH RATES, NOXIOUS WEEDS AND ESTABLISHMENT
- MOWING AND WEEDING MAY NEED TO OCCUR AT EACH OBSERVATION. IF PROBLEMS ARE NOT IDENTIFIED WITH EITHER HEIGHT OF VEGETATION OR QUANTITY OF WEEDS, NO
- 10. ANNUALLY, AT THE START OF SPRING, SITE SHOULD BE MOWED WITH A ROTARY MOWER AT A HEIGHT BETWEEN 4 AND 6 INCHES TO KNOCKDOWN STANDING VEGETATION FROM
- THE PREVIOUS SEASONS. 11. IF SITE MANAGER DETERMINES THE NEED TO REMOVE INVASIVE WEEDS WITH A HERBICIDE. THE MOST EFFECTIVE METHOD IS DURING THE FALL WITH A DIRECT APPLICATION SITE MANAGER SHOULD CONDUCT A THOROUGH WALK-THROUGH OF THE SITE TO FIND WEEDS

- THE CONTRACTOR SHALL REPORT ANY DISCREPANCY IN PLAN VS. FIELD CONDITIONS IMMEDIATELY TO THE LANDSCAPE ARCHITECT, PRIOR TO CONTINUING WITH THAT PORTION OF
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE REPAIR OF ANY OF THEIR TRENCHES OR
- SEED LIMIT LINES ARE APPROXIMATE. CONTRACTOR SHALL SEED ALL AREAS WHICH ARE DISTURBED BY GRADING WITH THE SPECIFIED SEED MIXES.
- REVIEW AGENCIES. THE CONTRACTOR IS RESPONSIBLE FOR VERIFYING ALL PLANT QUANTITIES



3




				SCALE.		No. REVISIONS	DATE	ΒY
(H) Sł			P	AS NOTED		1 202 DESCH	11/19/2021	CPC
01/ 161 162			RE	DESIGNED BY ERS		2 60% DC3/CM	01/21/2022	СРС
21 R0 B75	HARDIN III SOLAR							
/20 JEC	HARDIN COUNTY, OH		AUN	ORAWN BY: ALM	2027 MARTY-MORN AND ASSOCIATE, MC 7965 H NGN SPRET, SUIT 200			
5SU)22 (T 44 400		and the second	AR		COLUMBUS, Dr. 43233 PANNE A YOL ANT-AND		_	
NO R			Y TION	ONECKED BY: OPC	WWW K RALE T - HORN COM			
10		618 	'					

NORTH GRAPHIC SCALE IN FEET 0 1000 2000 4000











PLANT SCHEDULE


GROUND COVERS	CODE	<u>911</u>	BOTANICAL/COMMON/NAME	INPE
	X1	105.572.045 \$F	ARRAY AREA SEED MIX	-
	x3	16,575,866 SF	POLUNATOR SEED MIK	











)	
GRAPHIC S	SCALE 200)N	0

BOTANICAL / COMMON NAME TYPE


POLLINATOR SEED MX

PLANT SCHEDULE

105,572,045 SF

No. 2 60% Kimley Horn SCALL AS NOTED OCSICATO BY: ERS PRELIMINARY LANDSCAPE PLAN HARDIN III SOLAR HARDIN COUNTY, OH ORIGINAL ISSUE 01/21/2022 KHA PROJECT NO. 168754044 SHEET NUMBER L-303






NC	RTH	┝
GRAPHIC SC 0 100 2	ALE IP	FEET 400

	BΥ	CPC	CPC					
LE IN FEET 400	DATE	1202/61/11	01/21/2022	_	-			
400								
	REVISIONS							
	REV	30% DESIGN	60% DESIGN					:
	No.	- 202	2 60%					_
			HOT H		C. SUIT 290	43233	IN COM	
OR SEED MAX			Kimlev»Horn		2001 HAND VIOLAN AND ASSOCIATE THE	COLUMBUS, OH 43235 PHONE 6 YOL 417 4540	WWW KIMALE =- HORN COM	
			_		_		U	
	SCALE.	AS NOTED	DE SIGNEO BY: ERS		ORAWN BY: ALH	10 - 2004 10 - 2004	CHECKED BY: CPC	
			RE		AIN		Y	
						and the second se	and the second	
					DI AN			
				HARDIN III SOLAR	HARDIN COUNTY, OH			
OHIO Utilities Protection SERVICE Citk; Call or Tap Before You Dig 1-800-362-2764		SI	01/ 161	21 R0 375	115 120 140 140	44	NÖ.	
				_		_	_	

PLANT SCHEDULE

GROUND COVERS	CODE	<u> 110</u>	BOTANICAL / COMMON NAME	TYPE
1995	Х1	105 \$72.045 SF	ARRAY AREA SEED MIX	
	x3	16.575.886 SF	POLUMITOR SEED MIX	-







No. 1 30% 0550H 2 60% 0550H Kimley Horn AS NOTED DESIGNED BY: ERS DRAWN BY, ALM PRELIMINARY NOT FOR CONSTRUCTION **N** E LANDSCAPE PLAN HARDIN III SOLAR HARDIN COUNTY, OH ORIGINAL ISSUE; 01/21/2022 KHA PROJECT NO: 168754044 SHEET NUMBER

PLANT SCHEDULE


GROUND COVERS	<u>2002</u>	<u>979</u>	BOTARICAL / COMMON NAME	TYPE
100	X 1	1 05 ,572.045 SF	ARRAY AREA SEED MIX	
	23	16,575,086 SP	POLUMNTOR SEED MAK	






L-305










1-800-362-2764




3VPGYYQ8MW




PLANT SCHEDULE

GROUND COVERS	CODE	OTY	BOTANICAL / COMMON NAME	IVPE
	XI	105.572.045 SF	ARRAY AREA SEED MIX	-
	×3	16.575.886 \$F	POLUNATOR SEED MIX	-









NORTH
GRAPHIC SCALE IN FEET 0 100 200 400

	_	_			_	_	_	_
	βγ	CPC	S					
E IN FEET	DATE	11/19/2021	01/21/2022					
400		-					:	
	REVISIONS							
		JOX DESIGN	60X OESCH					
	ÖN	1 30%	2 60X					
CONMON NAME TYPE					DATES. POC		2 31	
EA SEED MX -			L≪N	-	TOTH MALEY-HORN AND ASSOCIATES, MC	COLUMBUS, OH 43235	WWW KINGET - HORH COM	
R SEED MAX —			Kimlev»Horn		-ADD MINUTAL	COLUM	A WAY	
		AS MOTED	DESIGNED BY: ERS				CHECKED BY, CPC	
	SCALE		DESIGNE		DRAWN BY		CHECKE	
			RE					ł
					•		8	
							Ower for god	
		ARED FOR					۵.	
	_	A REPA						
			Ц	1				
	}		IDSCAPE		IVVI	Ś		
			ANF	ζ	0	L		
				Ŋ				
				SOL	THE ALL	5,110		
				HARDIN III SOLAR	THE ALL OF THE ALL OF			
				HAR		2		
4		0	RIGI 01/	NA /21	L 1	S\$1	UE:	
OHIO Utilities Protection SERVICE Club, Cull or Tup Before You Dig			A P	R(54(CT)44	NO	
SFRVICE								
Click, Call or Tap Before You Dig 1-800-362-2764			Ŀ	-3	3()8	3	

UNIVER WITCHS	<u>cope</u>	911	DOLLARDY COMMONTANCE	1110
	X.	105 572.045 SF	ARRAY AREA SEED MX	9
	хз	16.575.886 SF	POLUNATOR SEED MIX	9








NOF	TH	-
GRAPHIC SC.	ALE IN	FEE1
0 100 20	10	400

GROUND COVERS	CODE	<u>017</u>	BOTANICAL (COMMON NAME	DPE
	X1	105,572,046 SF	ARRAY AREA SEED MIK	():
	k3	16.575.888 SF	POLINATOR SEED MIK	









GROUND COVERS	CODE	212	BOTANICAL/COMMONINAME	TYPE
	X1	105.572.045 SF	ARRAY AREA SEED MX	2
	кì	18,575,886 SF	POLUNATOR SEED MIX	1





Click, Call or Tay Before You Dig

1-800-362-2764





GROUND COVERS	CODE	210	BOTANICAL / COMMON NAME	TYPE
	X1	105.572.045.5F	ARRAY AREA SEED MX	×.
	x3	18,575,588 SF	POLLINATOR SEED MIX	







Attachment 5 Example Cable Cut Sheet

EmPowr

October 10, 2018





Drawing / Data Sheet

Single Conductor EmPowr® Link CL[™] BIFILL® Concentric Neutral (Flat Strap) Power Cable 35kV



Representative drawing not to scale

Thio	Thickness (inches)			Diameter (inches)		
Min.	Nom.*	Max.	Min.	Nom.*	Max.	
			1 160	1 184	1.208	
			1.100	1.104	1.200	
0.024	0.030			1 244		
0.024	0.030			1.244		
0.330	0.345	0.375	1 800	1 03/	1.995	
0.330	0.345	0.375	1.690	1.934	1.995	
0.024	0.030	0.060	1.040	1 00/	2.085	
0.024	0.050	0.000	1.940	1.994	2.085	
	0.025			2 0 4 4		
	0.025			2.044		
0.070	0.000	0.120		2 204		
0.070	0.080	0.120		2.204		
		Min. Nom.* 0.024 0.030 0.330 0.345 0.024 0.030 0.025	Min. Nom.* Max. 0.024 0.030 0.330 0.345 0.375 0.024 0.030 0.060 0.025	Min. Nom.* Max. Min. 1.160 0.024 0.030 0.330 0.345 0.375 1.890 0.024 0.030 0.060 1.940 0.025	Min. Nom.* Max. Min. Nom.* 1.160 1.184 0.024 0.030 1.244 0.330 0.345 0.375 1.890 1.934 0.024 0.030 0.060 1.940 1.994 0.025 2.044	

* - Nominal Values are Subject to Manufacturing Tolerances; Bold Font Indicates Minimum Average Values

Customer:	RENEWABLE ENERGY	Customer P/N:	EA/PC Number:
		NONE	253647 Rev. 4
Specification /	AEIC CS8-13, ICEA S-94-649, UL 1072 TYPE MV-105	Prepared By:	Date:
Standard:		HQQUTYO	10/10/2018

Dimensions and weights not designated minimum or maximum are nominal and subject to manufacturing tolerances.

The information contained in this document is the exclusive and proprietary intellectual property of General Cable Corporation, and any reproduction or disclosure, in whole or in part, is prohibited without the express written consent of an officer of General Cable Corporation.

©General Cable Corporation 2018, all rights reserved.



Electrical Characteristics

Single Conductor EmPowr® Link CL™ BIFILL® Concentric Neutral (Flat Strap) Power Cable 35kV

Cable Description:	1250 kcmil Al, 0.345'' TRXLPE, 15 x 0.193'' x 0.025'' Cu, XLPE						
Input Parameters:	Electrical Characteristics Based on Normal Operating Temperature: 105 °C IR Constant @ 60°F: 20000 Dielectric Constant: 2.35 Conductor Earth Resistivity: 100 Ω-m	Dissipation Factor: Voltage (line to ground): Center to Center Spacing (S):	0.01 % 20.21 kV 7.5 in Flat	$3 \rightarrow 4$ $3 \rightarrow 4$ $23 \rightarrow 4$ Arrangement			
Conductor Resistance:	Rdc @ 25°C: Rac @ 25°C: Rac @ 105°C:	0.0141 Ω/kft 0.0149 Ω/kft 0.0202 Ω/kft	0.0463 Ω/km 0.0489 Ω/km 0.0663 Ω/km				
Shield Resistance:	Rac @ 25°C: Rac @ 95°C:	0.124 Ω/kft 0.158 Ω/kft	0.407 Ω/km 0.517 Ω/km				
Capacitance:		0.090 µF/kft	0.296 µF/km				
Shunt Capacitive Reactance/Susceptance:	Shunt Capacitive Reactance: Shunt Capacitive Susceptance:	29390 Ω-kft 34.03 μS/kft	8958 Ω-km 111.64 μS/km				
Charging Current:		687.6 mA/kft	2256.2 mA/km				
Single Dhose	Inductive Reactance:	0.018 Ω/kft	0.060 Ω/km				
Single Phase Reactance/Impedance:	Real Imag. Pos. & Neg. Seq. Impedance (Met. Shield): 0.020 0.018 Zero Seq. Impedance (Earth & Met. Shield): 0.339 0.223	<u>Impedance</u> 0.027 Ω/kft 0.406 Ω/kft	Real Imag. 0.066 0.060 1.113 0.733	<u>Impedance</u> 0.090 Ω/km 1.333 Ω/km			
	Inductive Reactance:	0.070 Ω/kft	0.229 Ω/km				
3-Phase Reactance/Impedance:	Real Imag. Pos. & Neg. Seq. Impedance (Met. Shield): 0.035 0.065 Zero Seq. Impedance (Earth & Met. Shield): 0.165 0.054 Zero Seq. Impedance (Earth Only): 0.074 0.633 Zero Seq. Impedance (Met. Shield Only): 0.178 0.018	Impedance 0.074 Ω/kft 0.174 Ω/kft 0.638 Ω/kft 0.179 Ω/kft	Real Imag. 0.116 0.213 0.543 0.179 0.244 2.078 0.583 0.060	Impedance 0.242 Ω/km 0.571 Ω/km 2.093 Ω/km 0.587 Ω/km			
Dielectric Losses: (Per Phase)		1.38 W/kft	4.54 W/km				
Electrical Stress:	Insulation Average: Conductor Shield - Insulation Interface Maximum: Insulation - Insulation Shield Interface Minimum:	58.58 V/mil 73.58 V/mil 47.33 V/mil	2.31 kV/mm 2.90 kV/mm 1.86 kV/mm				
Insulation Resistance:		3832.72 MΩ-kft	1168.16 MΩ-km				
Velocity of Propagation		477.33 ft/µs	145.49 m/µs				

Customer:	RENEWABLE ENERGY	Customer P/N:	EA/PC Number:			
		NONE	253647 Rev. 4			
Specification / Standard:	AEIC CS8-13, ICEA S-94-649, UL 1072 TYPE MV-105	Prepared by:	Date:			
		HQQUTYO	10/10/2018			
Dimensions and weights not designated minimum or maximum are nominal and subject to manufacturing tolerances. The information contained in this document is the exclusive and proprietary intellectual property of General Cable Corporation, and any reproduction or disclosure, in whole or in part, is prohibited without the express written consent of an officer of General Cable Corporation.						
©General Cable Corporation 2018, all rights reserve	u.					



Electrical Characteristics

Single Conductor EmPowr® Link CL™ BIFILL® Concentric Neutral (Flat Strap) Power Cable 35kV

Cable Description:	1250 kcmil Al, 0.345'' TRXLPE, 15 x 0.193'' x 0.025'' Cu, XLPE						
Input Parameters:	Electrical Characteristics Based on Normal Operating Temperature: 105 °C IR Constant @ 60°F: 20000 Dielectric Constant: 2.35 Conductor of Earth Resistivity: 100 Ω-m	Dissipation Factor: Voltage (line to ground): Center to Center Spacing (S):	0.01 % 20.21 kV 2.204 in	Flat Adjacent Arrangement			
Conductor Resistance:	Rdc @ 25°C: Rac @ 25°C: Rac @ 105°C:	0.0141 Ω/kft 0.0149 Ω/kft 0.0202 Ω/kft	0.0463 Ω/km 0.0489 Ω/km 0.0663 Ω/km				
Shield Resistance:	Rac @ 25°C: Rac @ 95°C:	0.124 Ω/kft 0.158 Ω/kft	0.407 Ω/km 0.517 Ω/km				
Capacitance:		0.090 µF/kft	0.296 µF/km				
Shunt Capacitive Reactance/Susceptance:	Shunt Capacitive Reactance: Shunt Capacitive Susceptance:	29390 Ω-kft 34.03 μS/kft	8958 Ω-km 111.64 μS/km				
Charging Current:		687.6 mA/kft	2256.2 mA/km				
Single Phase	Inductive Reactance:	0.018 Ω/kft	0.060 Ω/km				
Reactance/Impedance:	Real Imag. Pos. & Neg. Seq. Impedance (Met. Shield): 0.020 0.018 Zero Seq. Impedance (Earth & Met. Shield): 0.339 0.223	<u>Impedance</u> 0.027 Ω/kft 0.406 Ω/kft	Real Imag. 0.066 0.060 1.113 0.733	<u>Impedance</u> 0.090 Ω/km 1.333 Ω/km			
	Inductive Reactance:	0.042 Ω/kft	0.136 Ω/km				
3-Phase Reactance/Impedance:	Real Imag. Pos. & Neg. Seq. Impedance (Met. Shield): 0.024 0.041 Zero Seq. Impedance (Earth & Met. Shield): 0.167 0.052 Zero Seq. Impedance (Earth Only): 0.074 0.690 Zero Seq. Impedance (Met. Shield Only): 0.178 0.018	Impedance 0.047 Ω/kft 0.175 Ω/kft 0.694 Ω/kft 0.179 Ω/kft	Real Imag. 0.077 0.135 0.549 0.171 0.244 2.263 0.583 0.060	Impedance 0.155 Ω/km 0.575 Ω/km 2.276 Ω/km 0.587 Ω/km			
Dielectric Losses: (Per Phase)		1.38 W/kft	4.54 W/km				
Electrical Stress:	Insulation Average: Conductor Shield - Insulation Interface Maximum: Insulation - Insulation Shield Interface Minimum:	58.58 V/mil 73.58 V/mil 47.33 V/mil	2.31 kV/mm 2.90 kV/mm 1.86 kV/mm				
Insulation Resistance:		3832.72 MΩ-kft	1168.16 MΩ-km				
Velocity of Propagation		477.33 ft/µs	145.49 m/µs				

Customer:	RENEWABLE ENERGY	Customer P/N:	EA/PC Number:			
		NONE	253647 Rev. 4			
Specification / Standard:	AEIC CS8-13, ICEA S-94-649, UL 1072 TYPE MV-105	Prepared by:	Date:			
		HQQUTYO	10/10/2018			
HQUTYO 10/10/2018 Dimensions and weights not designated minimum or maximum are nominal and subject to manufacturing tolerances. The information contained in this document is the exclusive and proprietary intellectual property of General Cable Corporation, and any reproduction or disclosure, in whole or in part, is prohibited without the express written consent of an officer of General Cable Corporation.						
©General Cable Corporation 2018, all rights reserved.						



Electrical Characteristics

Single Conductor EmPowr® Link CL™ BIFILL® Concentric Neutral (Flat Strap) Power Cable 35kV

Cable Description:	1250 kcmil Al, 0.345'' TRXLPE, 15 x 0.193'' x 0.025'' Cu, XLPE					
Input Parameters:	Electrical Characteristics Based on Normal Operating Temperature: 105 °C IR Constant @ 60°F: 20000 Dielectric Constant: 2.35 Conductor of Earth Resistivity: 100 Ω·m	Dissipation Factor: Voltage (line to ground): Center to Center Spacing (S):	0.01 % 20.21 kV 2.204 in	Trifoll Arrangement		
Conductor Resistance:	Rdc @ 25°C: Rac @ 25°C: Rac @ 105°C:	0.0141 Ω/kft 0.0149 Ω/kft 0.0202 Ω/kft	0.0463 Ω/km 0.0489 Ω/km 0.0663 Ω/km			
Shield Resistance:	Rac @ 25°C: Rac @ 95°C:	0.124 Ω/kft 0.158 Ω/kft	0.407 Ω/km 0.517 Ω/km			
Capacitance:		0.090 µF/kft	0.296 µF/km			
Shunt Capacitive Reactance/Susceptance:	Shunt Capacitive Reactance: Shunt Capacitive Susceptance:	29390 Ω-kft 34.03 μS/kft	8958 Ω-km 111.64 μS/km			
Charging Current:		687.6 mA/kft	2256.2 mA/km			
Single Dhose	Inductive Reactance:	0.018 Ω/kft	0.060 Ω/km			
Single Phase Reactance/Impedance:	Real Imag. Pos. & Neg. Seq. Impedance (Met. Shield): 0.020 0.018 Zero Seq. Impedance (Earth & Met. Shield): 0.339 0.223	<u>Impedance</u> 0.027 Ω/kft 0.406 Ω/kft	Real Imag. 0.066 0.060 1.113 0.733	<u>Impedance</u> 0.090 Ω/km 1.333 Ω/km		
	Inductive Reactance:	0.036 Ω/kft	0.119 Ω/km			
3-Phase Reactance/Impedance:	Real Imag. Pos. & Neg. Seq. Impedance (Met. Shield): 0.022 0.036 Zero Seq. Impedance (Earth & Met. Shield): 0.168 0.052 Zero Seq. Impedance (Earth Only): 0.074 0.700 Zero Seq. Impedance (Met. Shield Only): 0.178 0.018	Impedance 0.042 Ω/kft 0.175 Ω/kft 0.704 Ω/kft 0.179 Ω/kft	Real Imag. 0.073 0.118 0.550 0.169 0.244 2.298 0.583 0.060	Impedance 0.139 Ω/km 0.575 Ω/km 2.311 Ω/km 0.587 Ω/km		
Dielectric Losses: (Per Phase)		1.38 W/kft	4.54 W/km			
Electrical Stress:	Insulation Average: Conductor Shield - Insulation Interface Maximum: Insulation - Insulation Shield Interface Minimum:	58.58 V/mil 73.58 V/mil 47.33 V/mil	2.31 kV/mm 2.90 kV/mm 1.86 kV/mm			
Insulation Resistance:		3832.72 MΩ-kft	1168.16 MΩ-km			
Velocity of Propagation		477.33 ft/µs	145.49 m/µs			


Customer:	RENEWABLE ENERGY	Customer P/N:	EA/PC Number:
		NONE	253647 Rev. 4
Specification / Standard:	AEIC CS8-13, ICEA S-94-649, UL 1072 TYPE MV-105	Prepared by:	Date:
		HQQUTYO	10/10/2018
0 0		y reproduction or disclosure, in whole or in part, is	prohibited without the express

CGeneral Cable *Em***Powr**°



Conductor Fault Current 1250 kcmil Al, 0.345" TRXLPE, 15 x 0.193" x 0.025" Cu, XLPE

MAXIMUM FAULT CURRENT OPERATING LIMITS FOR AN 1250 INSULATED ALUMINUM CONDUCTOR AT 60 Hz



1250 Insulated Aluminum Conductor

Number of Cycles	Time (s)	Current (amps)
8	0.13	151600
16	0.27	107200
24	0.40	87600

Notes -

The calculations are as per ICEA P-32-382. The calculations assume that all heat generated remains in the metal. The duration of a short circuit is considered to be up to approximately 2 seconds. The indicated short circuit value shown on this graph for durations longer than 2 seconds should be used with caution. The time shown is calculated for a given RMS fault current to bring the conductor to a temperature that will not cause damage to the conductor shield or the insulation. The calculations are based on a cross-sectional area of 1250000 cmil of Aluminum starting at an initial temperature of 105 C, and a final temperature of 250 C. The calculations utilize an absolute temperature of resisitvity of 228 and an ICEA calculation factor of 0.0125 The system frequency is 60 Hz

Customer:	RENEWABLE ENERGY	Customer P/N:	EA/PC Number:
		NONE	253647 Rev. 4
Specification / Standard:	cification / Standard: AEIC CS8-13, ICEA S-94-649, UL 1072		Date:
	TYPE MV-105	HQQUTYO	10/10/2018

Dimensions and weights not designated minimum or maximum are nominal and subject to manufacturing tolerances.

The information contained in this document is the exclusive and proprietary intellectual property of General Cable Corporation, and any reproduction or disclosure, in whole or in part, is prohibited without the express written consent of an officer of General Cable Corporation.

©General Cable Corporation 2018, all rights reserved


Utility Engineering Center Tel: 859-572-8000

Contraction Cable EmPowr®



Shield Fault Current

1250 kcmil Al, 0.345" TRXLPE, 15 x 0.193" x 0.025" Cu, XLPE



15 x [25mil x 193mil] Copper Flat Strap Neutral

Number of Cycles	Time (s)	Current (amps)
8	0.13	21700
16	0.27	15300
24	0.40	12500

Notes -

The curves assume that all heat generated remains in the metal. The time shown is that calculated for a given RMS fault current to bring the metallic shield to a temperature that will not cause damage to the insulation shield or cable jacket. The calculations are as per ICEA P-45-482 using an "M factor" of 0.086 corresponding to a 35-46 kV rated cable, with a conductor temperature of 105 and a metallic shield starting temperature of 95 C and a

metallic shield ending temperature of 350

Customer:	RENEWABLE ENERGY	Customer P/N:	EA/PC Number:
		NONE	253647 Rev. 4
pecification / Standard: AEIC CS8-13, ICEA S-94-649, UL 1072			-
Specification / Standard:	AEIC CS8-13, ICEA S-94-649, UL 10/2	Prepared by:	Date:
Specification / Standard:	AEIC CS8-13, ICEA S-94-649, UL 1072 TYPE MV-105	Prepared by: HQQUTYO	Date: 10/10/2018

The information contained in this document is the exclusive and proprietary intellectual property of General Cable Corporation, and any reproduction or disclosure, in whole or in part, is prohibited without the express written consent of an officer of General Cable Corporation.

©General Cable Corporation 2018, all rights reserved.

Utility Engineering Center Tel: 859-572-8000

Cable Installation

Single Conductor EmPowr® Link CL[™] BIFILL® Concentric Neutral (Flat Strap) Power Cable 35kV

Cable Description:	1250 kcmil Al, 0.345'' TRXLPE, 15 x 0.193'' x 0.025'' Cu, XLPE									
Maximum Pulling Tension:	NOTE: When	Basket Grip:	10000 10000	lb vith basket gri	44.5 44.5 ps, proceed w	kN	on. Pulling grips mu	20000 20000	lb	llel 89.0 kN 89.0 kN 3 grips, 1 per cable /ith grip manufacturer's
Maximum Sidewall Bearing Pressure:	2000 lb/foot of bend radius 29 kN/meter of bend radius					dius				
Minimum Bending Radius for Permanent Training Purposes:		Non-NEC A	suitable for con	8 x O.D.	18	inches inches er curved	surfaces around wl	457	mm mm may be pulled	l under tension while being installed d
Conduit Information (EPEC-40/SCH 40):		Metric Size (mm) 91 78 Conduit Dim Metric Size (mm) 203 155 *Jam Ratio be **Jam Ratio be	Imperial Size (in.) 8 6 etween 2.8 ar	Image: constraint of the system Image: constraint of the system 3.522 3.042 3.042 10 (in.) 7.981 6.031 6.031	(mm) 89.46 77.27 3x1/C Pa (mm) 202.72 153.19 ming Prob	% Fill 39 53 arallel % Fill 23 40	Jam Ratio N/A N/A Jam Ratio 3.80 2.87	Clea (in.) 1.318 0.838 Clearanc (in.) 4.936 2.558	rance (mm) 33.48 21.29 e (mm) 125.38 64.97	

Customer:	RENEWABLE ENERGY	Customer P/N:	EA/PC Number:			
		NONE	253647 Rev. 4			
Specification / Standard:	AEIC CS8-13, ICEA S-94-649, UL 1072 TYPE MV-105	Prepared by:	Date:			
		HQQUTYO	10/10/2018			
Dimensions and weights not designated minimum or maximum are nominal and subject to manufacturing tolerances.						

The information contained in this document is the exclusive and proprietary intellectual property of General Cable Corporation, and any reproduction or disclosure, in whole or in part, is prohibited without the express written consent of an officer of General Cable Corporation.


©General Cable Corporation 2018, all rights reserved.

Attachment 6 Example Trench Detail Drawing Hardin Solar Energy, LLC. Case No. 17-773-EL-BGN

RRC Power & Energy, LLC

January 22, 2021





5

SOIL INFORMATION

SOIL AMBIENT TEMPERATURE

SOIL COMPACTION DRYOUT REGION THERMAL RESISTIVITY AT 0% MOISTURE IMPORTED FILL THERMAL RESISTIVITY AT 0% MOISTURE BACKFILL THERMAL RESISTIVITY AT 3% MOISTURE IN SITU THERMAL RESISTIVITY AT 5% MOISTURE LOAD FACTOR

NOTES

1. SUPPLY, PLACE, AND COMPACT NATIVE BACKFILL. THE NATIVE BACKFILL SHALL BE INSTALLED IN A APPROVED METHOD THAT WILL ACHIEVE AN EFFECTIVE COMPACTION FOR THE ENTIRE DEPTH OF THE TRENCH. THE MATERIAL SHALL ACHIEVE A MINIMUM COMPACTION OF 90% SPD, 5% SPD WHERE APPROVED" AFTER "90% SPD" AND BEFORE "95% SPD IN VEHICULAR AREASAND 95% SPD IN VEHICULAR AREAS. ORGANIC SOIL (SOIL WITH 5% OR MORE ORGANICS) SHALL NOT BE USED AS BACKFILL MATERIAL.

= 27.2 °C

= 75%

= 90% SPD

= 235 °C - cm/W

=185 °C - cm/W

= 160 °C - cm/W

= 135 °C - cm/W

- 2. PRIOR TO INSTALLATION OF NATIVE SOIL BACKFILL, ROCKS LARGER THAN $\frac{3}{8}$ " AND ANY HINDERING ORGANICS SHOULD BE REMOVED.
- 3. MINIMUM BENDING RADIUS FOR FIBER OPTIC CABLE SHALL BE 20 TIMES THE OUTSIDE DIAMETER OF THE CABLE, OR PER MANUFACTURER'S RECOMMENDATION, WHICHEVER IS GREATER.
- 4. MINIMUM BENDING RADIUS FOR MV AC CABLE SHALL BE 12 TIMES THE OUTSIDE DIAMETER OF THE CABLE, OR PER MANUFACTURER'S RECOMMENDATION, WHICHEVER IS GREATER.
- 5. FOR MV CABLE RUNS FROM SUBSTATION TO THE FIRST SKID ON EACH CIRCUIT, CABLE DEPTH MAY BE UP TO SIX FEET TO MINIMIZE DRAIN TILE DAMAGE AND REPAIR.
- #9 GRADATION IMPORTED THERMAL BACKFILL MAY BE USED AS FIRST LIFT TO ALLOW FOR REQUIRED COMPACTION IN OVERSATURATED AREAS.

LEGEND

NATIVE SOIL BACKFILL

UNDISTURBED NATIVE SOIL

SELECT NATIVE SOIL BACKFILL (NOTE 2)

STANDARD PROCTOR DENSITY

SPD

9# GRADATION IMPORTED THERMAL BACKFILL (NOTE 6)



RRC POWER & ENERGY, LLC 7591 SW MOHAWK ST, TUALATIN, OR 97062 PHONE: (503) 342-4064 www.RRCcompanies.com

CONFIDENTIAL

THIS DRAWING IS THE PROPERTY OF RRC POWER & ENERGY, LLC, INVENERGY LLC, AND RES AMERICAS. NO REPRODUCTION MAY BE MADE IN WHOLE OR IN PART WITHOUT WRITTEN CONSENT.

PREPARED FOR:





RECORD DRAWING

THIS AS-RECORDED DRAWING WAS PRODUCED BASED ON FIELD CHANGES MADE AND RECORDED BY THE CONTRACTOR. THIS DRAWING RELIES ON THE INFORMATION PROVIDED BY THE CONTRACTOR AND IT HAS NOT BEEN VERIFIED BY THE ENGINEER- OF-RECORD.

3	01/22/2021	AS RECO		
2	02/04/2020	-	DIM UPD	
1	01/09/2020			STRUCTION
0	10/29/2019			TRUCTION
REV			E DESCRI	PTION
	ROVED BY:	-		
-	CKED BY:	T. CARR		
	SIGNED BY:	J. TAYLO		
	WN BY:	J. TAYLO	JR	
SCA	LE: N.T.S.			
	0	1"		2"
	BAR MUST	SCALE 2"	FOR FULL	SIZE
	OR 1" FC	OR HALF SI	ZE DRAWII	NG
PRC	DJECT NUM	BER: EE19	05015	
DRA	WING NAM	E:		
		HARD	IIN	
	SU1 /			די
	SULF)
	AC	CTRE	NCH	
	-			
		DETAI	LS	
DB V	WING No.		SHEET:	REVISION
	WING NU.		SHEET.	
ЦП	SP-E-450-	.01	1 of 2	3
שהן	0F-L-400	-01	1012	
CAE	FILE: HDSP	-E-450-00		

This foregoing document was electronically filed with the Public Utilities

Commission of Ohio Docketing Information System on

6/3/2022 4:47:35 PM

in

Case No(s). 21-1231-EL-BGN

Summary: Response - Response to Fourth Data Request from Staff of the Ohio Power Siting Board electronically filed by Christine M.T. Pirik on behalf of Fountain Point Solar Energy LLC